CORE_APP_FILES.md 1/9 2025-08-15

Core App Files - Complete Source Code & Documentation

Table of Contents

- 1. Root Layout
- 2. Home Page
- 3. Providers
- 4. Theme Provider
- 5. Global Styles
- 6. Middleware

Root Layout

app/layout.tsx

Purpose: Main application wrapper and metadata configuration Location: /app/layout.tsx

```
import type { Metadata } from "next";
import { Inter } from "next/font/google";
import "./globals.css";
import { ClerkProvider } from "@clerk/nextjs";
import { ThemeProvider } from "./theme-provider";
import { Providers } from "./providers";
import Navbar from "@/components/navbar/Navbar";
import { Toaster } from "sonner";
const inter = Inter({ subsets: ["latin"] });
export const metadata: Metadata = {
 title: "Wine Store",
  description: "Premium wines from around the world",
  keywords: ["wine", "premium", "store", "ecommerce"],
  authors: [{ name: "Wine Store Team" }],
  creator: "Wine Store",
  publisher: "Wine Store",
  formatDetection: {
    email: false,
    address: false,
   telephone: false,
  },
  metadataBase: new URL("https://wine-store.com"),
  alternates: {
    canonical: "/",
  openGraph: {
    title: "Wine Store",
    description: "Premium wines from around the world",
    url: "https://wine-store.com",
    siteName: "Wine Store",
    images: [
        url: "https://wine-store.com/og-image.jpg",
        width: 1200,
        height: 630,
        alt: "Wine Store",
      },
    locale: "en US",
    type: "website",
  },
  twitter: {
    card: "summary_large_image",
```

CORE_APP_FILES.md 2/9 2025-08-15

```
title: "Wine Store",
    description: "Premium wines from around the world",
    images: ["https://wine-store.com/twitter-image.jpg"],
  },
  robots: {
    index: true,
    follow: true,
    googleBot: {
      index: true,
      follow: true,
      "max-video-preview": -1,
      "max-image-preview": "large",
      "max-snippet": -1,
    },
  },
  verification: {
   google: "google-site-verification-code",
  },
};
export default function RootLayout({
  children,
}: {
 children: React.ReactNode;
}) {
  return (
    <ClerkProvider>
      <html lang="en" suppressHydrationWarning>
        <body className={inter.className}>
          <ThemeProvider
            attribute="class"
            defaultTheme="system"
            enableSystem
            disableTransitionOnChange
            <Providers>
              <div className="min-h-screen bg-background">
                <Navbar />
                <main className="flex-1">{children}</main>
                <Toaster />
              </div>
            </Providers>
          </ThemeProvider>
        </body>
      </html>
    </ClerkProvider>
  );
}
```

Layout Structure Explained:

- ClerkProvider: Wraps the entire app for authentication
- ThemeProvider: Enables dark/light mode switching
- **Providers**: Context providers for state management
- Navbar: Global navigation component
- **Toaster**: Notification system for user feedback
- Metadata: Comprehensive SEO and social media optimization

Key Features:

- SEO Optimized: Rich metadata for search engines
- Social Media Ready: OpenGraph and Twitter card support
- Accessibility: Proper lang attribute and semantic structure
- Responsive: Mobile-first design approach

CORE_APP_FILES.md 3/9 2025-08-15

Home Page

app/page.tsx

Purpose: Main landing page of the application Location: /app/page.tsx

Page Structure Explained:

- Hero: Main banner section with call-to-action
- HeroCarousel: Rotating featured content
- FeaturedProducts: Showcase of premium wines
- **Spacing**: Consistent vertical rhythm with space-y-16

Providers

app/providers.tsx

Purpose: Context providers for global state management Location: /app/providers.tsx

```
"use client";
import { QueryClient, QueryClientProvider } from "@tanstack/react-query";
import { ReactQueryDevtools } from "@tanstack/react-query-devtools";
import { useState } from "react";
export function Providers({ children }: { children: React.ReactNode }) {
 const [queryClient] = useState(
     new QueryClient({
        defaultOptions: {
          queries: {
            staleTime: 60 * 1000, // 1 minute
            refetchOnWindowFocus: false,
          },
       },
     })
 );
  return (
   <QueryClientProvider client={queryClient}>
      {children}
      <ReactQueryDevtools initialIsOpen={false} />
    </QueryClientProvider>
 );
}
```

CORE_APP_FILES.md 4/9 2025-08-15

- QueryClient: React Query for server state management
- Stale Time: Data considered fresh for 1 minute
- DevTools: Development-only query inspector
- Client-Side: Marked as client component for browser APIs

Theme Provider

app/theme-provider.tsx

Purpose: Dark/light mode theme switching Location: /app/theme-provider.tsx

```
"use client";
import { ThemeProvider as NextThemesProvider } from "next-themes";
import { type ThemeProviderProps } from "next-themes/dist/types";

export function ThemeProvider({ children, ...props }: ThemeProviderProps) {
   return <NextThemesProvider {...props}>{children}</NextThemesProvider>;
}
```

Theme Provider Explained:

- next-themes: Popular theme switching library
- Client Component: Requires browser APIs for theme detection
- System Default: Automatically detects user's system preference
- Persistent: Remembers user's theme choice

Global Styles

app/globals.css

Purpose: Global CSS styles and Tailwind directives Location: /app/globals.css

```
@import "tailwindcss";
@layer base {
  :root {
    --background: 0 0% 100%;
    --foreground: 222.2 84% 4.9%;
    --card: 0 0% 100%;
    --card-foreground: 222.2 84% 4.9%;
    --popover: 0 0% 100%;
    --popover-foreground: 222.2 84% 4.9%;
    --primary: 222.2 47.4% 11.2%;
    --primary-foreground: 210 40% 98%;
    --secondary: 210 40% 96%;
    --secondary-foreground: 222.2 84% 4.9%;
    --muted: 210 40% 96%;
    --muted-foreground: 215.4 16.3% 46.9%;
    --accent: 210 40% 96%;
    --accent-foreground: 222.2 84% 4.9%;
    --destructive: 0 84.2% 60.2%;
    --destructive-foreground: 210 40% 98%;
    --border: 214.3 31.8% 91.4%;
    --input: 214.3 31.8% 91.4%;
    --ring: 222.2 84% 4.9%;
     --radius: 0.5rem;
  .dark {
    --background: 222.2 84% 4.9%;
    --foreground: 210 40% 98%;
```

CORE_APP_FILES.md 5/9 2025-08-15

```
--card: 222.2 84% 4.9%;
    --card-foreground: 210 40% 98%;
    --popover: 222.2 84% 4.9%;
    --popover-foreground: 210 40% 98%;
    --primary: 210 40% 98%;
    --primary-foreground: 222.2 47.4% 11.2%;
    --secondary: 217.2 32.6% 17.5%;
    --secondary-foreground: 210 40% 98%;
    --muted: 217.2 32.6% 17.5%;
    --muted-foreground: 215 20.2% 65.1%;
    --accent: 217.2 32.6% 17.5%;
    --accent-foreground: 210 40% 98%;
    --destructive: 0 62.8% 30.6%;
    --destructive-foreground: 210 40% 98%;
    --border: 217.2 32.6% 17.5%;
    --input: 217.2 32.6% 17.5%;
    --ring: 212.7 26.8% 83.9%;
  }
}
@layer base {
  * {
   @apply border-border;
 body {
    @apply bg-background text-foreground;
}
/* Custom scrollbar */
::-webkit-scrollbar {
 width: 8px;
::-webkit-scrollbar-track {
 @apply bg-muted;
::-webkit-scrollbar-thumb {
 @apply bg-muted-foreground/50 rounded-full;
::-webkit-scrollbar-thumb:hover {
 @apply bg-muted-foreground;
}
/* Custom focus styles */
.focus-ring {
 @apply focus:outline-none focus:ring-2 focus:ring-primary focus:ring-offset-
2;
}
/* Custom animations */
@keyframes fade-in {
  from {
    opacity: 0;
    transform: translateY(10px);
  }
  to {
    opacity: 1;
    transform: translateY(0);
  }
}
.fade-in {
  animation: fade-in 0.3s ease-out;
```

CORE_APP_FILES.md 6/9 2025-08-15

```
}
/* Wine-specific styles */
.wine-gradient {
  background: linear-gradient(135deg, #8b5cf6 0%, #ec4899 100%);
.wine-text {
  @apply text-wine-600 dark:text-wine-400;
.wine-border {
  @apply border-wine-200 dark:border-wine-700;
/* Responsive utilities */
.container-responsive {
  @apply mx-auto max-w-7xl px-4 sm:px-6 lg:px-8;
}
/* Loading states */
.skeleton {
 @apply animate-pulse bg-muted rounded;
.skeleton-text {
 @apply skeleton h-4 w-full;
.skeleton-image {
  @apply skeleton aspect-square w-full;
/* Button variants */
.btn-primary {
 @apply bg-primary text-primary-foreground hover:bg-primary/90 focus-ring px-4
py-2 rounded-md font-medium transition-colors;
.btn-secondary {
 @apply bg-secondary text-secondary-foreground hover:bg-secondary/80 focus-
ring px-4 py-2 rounded-md font-medium transition-colors;
}
.btn-outline {
  @apply border border-input bg-background hover:bg-accent hover:text-accent-
foreground focus-ring px-4 py-2 rounded-md font-medium transition-colors;
/* Form styles */
.form-input {
 @apply flex h-10 w-full rounded-md border border-input bg-background px-3 py-
2 text-sm ring-offset-background file:border-0 file:bg-transparent file:text-sm
file:font-medium placeholder:text-muted-foreground focus-visible:outline-none
focus-visible:ring-2 focus-visible:ring-ring focus-visible:ring-offset-2
disabled:cursor-not-allowed disabled:opacity-50;
.form-label {
  @apply text-sm font-medium leading-none peer-disabled:cursor-not-allowed
peer-disabled:opacity-70;
}
.form-error {
  @apply text-sm text-destructive;
```

CORE_APP_FILES.md 7/9 2025-08-15

```
/* Card styles */
.card-hover {
 @apply transition-all duration-200 hover:shadow-lg hover:-translate-y-1;
.card-border {
 @apply border border-border bg-card text-card-foreground shadow-sm;
/* Grid layouts */
.grid-responsive {
  @apply grid grid-cols-1 gap-6 sm:grid-cols-2 lg:grid-cols-3 xl:grid-cols-4;
.grid-featured {
 @apply grid grid-cols-1 gap-8 lg:grid-cols-2;
/* Typography */
.heading-1 {
  @apply scroll-m-20 text-4xl font-extrabold tracking-tight lg:text-5xl;
.heading-2 {
 @apply scroll-m-20 border-b pb-2 text-3xl font-semibold tracking-tight
}
.heading-3 {
  @apply scroll-m-20 text-2xl font-semibold tracking-tight;
.heading-4 {
 @apply scroll-m-20 text-xl font-semibold tracking-tight;
.paragraph {
  @apply leading-7 [&:not(:first-child)]:mt-6;
.lead {
  @apply text-xl text-muted-foreground;
}
.large {
 @apply text-lg font-semibold;
.small {
 @apply text-sm font-medium leading-none;
.muted {
 @apply text-sm text-muted-foreground;
/* Interactive elements */
.interactive {
  @apply cursor-pointer transition-all duration-200 hover:scale-105
active:scale-95;
}
.interactive-text {
  @apply transition-colors hover:text-primary;
```

CORE_APP_FILES.md 8/9 2025-08-15

```
/* Status indicators */
.status-success {
 @apply text-green-600 dark:text-green-400;
.status-warning {
 @apply text-yellow-600 dark:text-yellow-400;
.status-error {
  @apply text-red-600 dark:text-red-400;
.status-info {
  @apply text-blue-600 dark:text-blue-400;
/* Loading spinners */
.spinner {
  @apply animate-spin rounded-full border-2 border-current border-t-
transparent;
.spinner-sm {
  @apply spinner h-4 w-4;
.spinner-md {
  @apply spinner h-6 w-6;
.spinner-lg {
 @apply spinner h-8 w-8;
```

Global Styles Explained:

- CSS Variables: Light/dark theme color schemes
- Tailwind Directives: Base, components, and utilities layers
- Custom Utilities: Wine-specific styling classes
- Responsive Design: Mobile-first approach
- Accessibility: Focus states and keyboard navigation
- Performance: Optimized animations and transitions

Middleware

middleware.ts

Purpose: Request/response processing and authentication **Location**: /middleware.ts

```
import { authMiddleware } from "@clerk/nextjs";

export default authMiddleware({
  publicRoutes: [
    "/",
    "/products",
    "/products",
    "/about",
    "/api/products",
    "/api/carousel",
  ],
  ignoredRoutes: ["/api/webhook", "/_next", "/favicon.ico"],
```

CORE_APP_FILES.md 9/9 2025-08-15

```
});
export const config = {
  matcher: ["/((?!.+\\.[\\w]+$|_next).*)", "/", "/(api|trpc)(.*)"],
};
```

Middleware Explained:

- Public Routes: Pages accessible without authentication
- Ignored Routes: Routes that bypass middleware completely
- Matcher Pattern: Regex pattern for route matching
- Authentication: Clerk handles user verification

middleware0.ts (Alternative)

Purpose: Alternative middleware configuration **Location**: /middleware0.ts

```
import { authMiddleware } from "@clerk/nextjs";
export default authMiddleware({
  publicRoutes: [
    "/",
    "/products",
    "/products/(.*)",
    "/about",
    "/api/products",
    "/api/carousel",
    "/api/webhook",
  ],
  ignoredRoutes: ["/_next", "/favicon.ico", "/api/webhook"],
});
export const config = {
  matcher: ["/((?!.+\\.[\\w]+$|_next).*)", "/", "/(api|trpc)(.*)"],
};
```

Alternative Configuration:

- Webhook Public: Allows Stripe webhook access
- Flexible Routing: More permissive public access
- **Development Friendly**: Easier testing and development

These core app files provide the foundation for the Wine Store application. They handle:

- Application Structure: Layout and routing
- Global State: Context providers and state management
- **Styling**: CSS variables and utility classes
- Authentication: Route protection and user management
- SEO: Metadata and social media optimization