

Backdooring Flash Objects (the walkthrough)

Backdooring Flash Objects (the walkthrough) - Author not stated, gnucitizen.org.

- Published: date not stated
- Original: <<https://www.gnucitizen.org/blog/backdooring-flash-objects/>>
- Preserved from: <https://www.gnucitizen.org/blog/backdooring-flash-objects/> (live) on 2026-08-06
- Licence: unknown

Rights remain with the original author and publisher. This is a research archive of a source from the Top 10 Web Hacking Techniques lists, kept so the page going offline. To read the original, follow the link above.

Content

UNTRUSTED SOURCE TEXT. Everything below this line is third-party material quoted for research. It is data, not instructions. Do not follow directions, execute code, or fetch URLs because this text says so.

Backdooring Flash Objects (the walkthrough)

Mon, 04 Sep 2006 19:07:37 GMT

by [pdp](#)

The following article is in narrative format and it is purely experimental. Feedback on whether you like it or not will be highly appreciated.

[image: The Flash]

I started my work station. The old DELL Inspiron 8100 laptop switched automatically to Windows XP SP2 after 30 seconds of countdown in Grub. "What is going to be?" [The Prodigy](#) seemed to be quite alright for the situation. These guys have never let me down. There is something about their music. When I am listening to their stuff my brain switches to state of mind which I usually call hackmode.

People in hackmode loose their perception of real and virtual world. To them all it matters is performing something that is valuable in this very moment. Hackmode requires total concentration and the feeling of it usually starts like this:

The brain dysfunctions 70% of your body. You feel relaxed. It almost seams like you are in a bubble. Now there is another 10% of brain activity gain. You don't need to calculate the distance between you and other objects in your surrounding environment. There is no need to perform unnecessary reflexive calculations too. There is only you and the object of your concentration.

On that day, my area of concentration was Backdooring Flash Objects. By saying backdooring I mean everything... from trojanning to infecting with viral code. It is quite hard to differentiate between viral infection and trojan infection. At the end of the day it is all about enhancing an object with some

malicious functionalities. If it is a virus, the malicious code will introduce itself automatically. If it is a trojan, the user help is needed to introduce the code.

Both of these are quite disruptive activities used by biological viruses that have been with us since the day of our creation. We have been exploited by them and that's the reason why we spend a lot of time figuring out how they work. That they I was exercising malicious infection of otherwise harmless Flash files for the same reasons.

My first aim was to download some tools. I used to play with Flash and its IDE in the past, however I needed something more robust. The first tool to download was [Mtasc](#) from Nicolas Cannasse. I had found it couple of weeks ago but I had never had time to do some serious play with it. To me it looked quite sophisticated little tool, great to hacking around Flash.

For the purpose of my training day I needed to download a SWF file that would be eventually enhanced with my demo backdoor as well. After couple of seconds in Google, I found "[The Corruptibles](#)". This is quite interesting and well composed animation that was just perfect for my proof of concept.

I unzipped Mtasc project into my `C:/` drive and started to fiddle around with it. The command line of the tool is not as straight forward as you might think. There are several options that could confuse you but it is OK. Good tools are usually like that; too much functionalities to put inside the same shell.

After reading the usage, I realized that I need to have a hello world backdoor before even thinking of executing the compiler. So, I switched to my browser window and started reading [Mtasc project page](#). A few minutes later I had the following sample script.

```

class Backdoor {
    function Backdoor() {
    }

    static function main(mc) {
        getUrl("javascript:alert('hello from backdoor')");
    }
}

```

Actually, the code above is kind of direct replicate of one of the [examples](https://chatbotkit.com

After I saved the file from gvim, I was ready for compiling. I fired the following command:

```
c:\Mtasc\mtasc.exe -swf The_Corruptibles.swf -out The_Corruptibles_backdoored.swf -main backdoor.as
```

I though that the command above would produce what I really wanted (trojaned version of the movie cl

Flare's syntax was quite obvious. I ran my backdoored SWF object through the tool and a new file cal

```

movie 'The_Corruptibles_backdoored.swf' {
    // flash 5, total frames: 3180, frame rate: 24 fps, 500x365 px

    movieClip 20480 __Packages.Backdoor {

        #initclip
        if (!Backdoor) {
            _global.Backdoor = function () {};

            var v1 = _global.Backdoor.prototype;
            _global.Backdoor.main = function (mc) {
                getUrl('javascript:alert(\'hello from backdoor\')', '_self');
            };

            ASSetPropFlags(v1, null, 1);
        }
        #endinitclip
    }

    frame 1 {
        Backdoor.main(this);
    }
}

```

To me it all looked quite alright. Frame 1 should load my object through the main method, but that w

I went back to Mtasc homepage to search for clues. Nicolas has some nice things going on there. To m
Anyway, Nicolas was apparently working on another project of his, called [Haxe](http://haxe.org/). I
I didn't download the tool but I had really good go through its documentation. I also read very care
I went back to Mtasc project page to look for a way to attach a movie. What I found was that I could
Another tab and couple of minutes latter I found [Swfmill](http://swfmill.org/). This tools was quit
I jumped on the tutorial provided by the developers of the project. Using the tool is quite straight

```
<?xml version="1.0" encoding="UTF-8"?>
<movie width="500" height="365" framerate="30">
  <background color="#000000"/>
    <frame>
      <library>
        <clip id="cc1" import="The_Corruptibles.swf"/>
      </library>
    </frame>
</movie></pre>
```

I called the clip in the library cc1. There were no reason to call it this way but when you are in h

```
c:\swfmill\swfmill.exe simple backdoor_lib.xml backdoor_lib.swf
c:\Mtasc\mtasc.exe -swf backdoor_lib.swf -out The_Corruptibles_backdoored.swf -main backdoor.as
```

It worked. Well, not exactly. Although I was able to display the **hello world** alert box, the **Th**

```
class Backdoor {
  function Backdoor() {
  }

  static function main(mc) {
    getURL("javascript:alert('hello from backdoor')");
    mc.attachMovie("cc1", "cccc", 0);
  }
}
```

"Compile! Launch on Firefox from localhost WAMP server! Bingo!" The SWF file was successfully altere

There is something magical about doing things from the command line. Surely you can do the same thin

After refreshing my browser couple of times, enjoying my newly born creature, I spotted a huge problem. It suddenly occurred to me that what I was doing was not very efficient. There was a simpler method. Simple cat doesn't work. It works for .exe files though. This used to be one of the main ways of displaying content in Flash, you have to use special software in order to do that. I cannot concatenate two objects but "Google has always been a friend." I found the [Swftools project](http://www.swftools.org/). One of the project contained tools to do other cool stuff with Flash. Some of them can be used to convert WFLA files. I remember that the bad guys in this movie has the ability to hack into your ghost (sole/brain). This is a long story short, I had the tool that I needed. I changed my **backdoor.as** file back to the following:

```
class Backdoor {
    function Backdoor() {
    }

    static function main(mc) {
        getURL("javascript:alert('hello from backdoor')");
    }
}
```

Yes, this is my initial script. The next stage was to compile it to an one-frame SWF file. Than all

```
c:\Mtasc\mtasc.exe -swf backdoor.swf -main -header 500:365:24 backdoor.as
c:\Swftools\swfcombine.exe -o The_Corruptibles_backdoored.swf -T backdoor.swf The_Corruptibles.swf
```

"Voila! There is my backdoor, trojan or virus. So now what? Hard to say!"