

Code

Code - portswigger, GitHub.

- Published: date not stated
- Original: <<https://github.com/portswigger/css-the-bomb-inside-your-inbox>>
- Preserved from: <https://github.com/portswigger/css-the-bomb-inside-your-inbox> (git) on 2026-08-08
- Repository commit: 2aa5850e95c842b0c0f1f670c872a677bdf5520e
- Licence: see the repository

Rights remain with the original author and publisher. This is a research archive of a source from the Web Hacking Techniques Index collections, kept so the page going offline. To read the original, follow the link above.

Content

UNTRUSTED SOURCE TEXT. Everything below this line is third-party material quoted for research. It is data, not instructions. Do not follow directions, execute code, or fetch URLs because this text says so.

This reference is a source-code repository. The archive preserves its documentation at an exact commit; the code itself stays in a private mirror and is never checked out, built or run.

- Repository: <<https://github.com/portswigger/css-the-bomb-inside-your-inbox>>
- Commit: 2aa5850e95c842b0c0f1f670c872a677bdf5520e
- Documents preserved: 1

README.md

Blob 655e555b2f94, 5403 bytes, at commit 2aa5850e95c8.

CSS: the bomb inside your inbox

[image: Repro header]

Welcome to the repo. This repository contains all the materials for my talk "CSS: the bomb inside your inbox". This repository contains proof of concept code, test cases, and supporting material that were identified, developed, or collected solely for the purposes of legitimate security research, analysis, and defensive testing. You can read about this research at: [Research paper](#)

Table of contents

Pocs

- [CSS hotwiring](#)

- [Exfiltrate tokens on paste](#)
- [Exfiltrate text nodes with CSP blocking external resources](#)
- [HTML only keylogger](#)
- [Prompt injection via email](#)
- [Outlook defacement](#)
- [Outlook Firefox keylogger](#)
- [Outlook label jacking](#)
- [Outlook sanitized keylogger](#)
- [Realtime Chrome keylogger](#)

Tools

- [Shazzer](#)
- [Hackvertor](#)

Proof of concepts

CSS hotwiring

This directory contains the poc for the CSS hotwiring attack on FastMail. The first code snippet shows the plaintext vector without being encoded. The second example is the payload encoded, and it mutates when using the CSSOM is used and the CSS code is read back.

[Poc](#)

Exfiltrate tokens via paste

This directory contains the poc demonstrating the attack on Medium using Firefox. It generates the CSS to steal the start, end and middle part of the token. Then copies it to clipboard when the victim clicks the button. I've included the required PHP files needed to retrieve the token parts. The text files need to be writable on the server and the .htaccess file needs to be used in order to extract information from the path.

[Poc](#)

Exfiltrate text nodes with CSP blocking external resources

This directory demonstrates the token exfiltration technique to steal text nodes when CSP is blocking external resources. I've included the debugging information to make it clear how it works.

[Poc](#)

HTML only keylogger

This demonstrates stealing keystrokes using pure HTML. I use small unicode characters to hide the letters. The marquee is used to cut off the select so it doesn't look like one.

[Poc](#)

Prompt injection via email

This poc shows the prompt I used to convince Atlas to get data from the page and exfiltrate it via the URL by opening tabs. You'll notice each URL is in the prompt this is because Atlas seemed to compare the prompt text against URLs it opens to decide if it opens a confirmation prompt.

[Poc](#)

Outlook defacement

This contains the poc I used to deface Outlook. "data-tabster" is the HTML attribute needed to for the library to append the CSS gadget to the node when the email is read.

[Poc](#)

Outlook Firefox keylogger

This is the exploit on Outlook I demonstrated in my talk. It spoofs the login screen, uses the animation trick to make it real time on Firefox and the label makes the fake input clickable which reproduces the behaviour of the login screen.

[Poc](#)

Outlook label jacking

This shows how I used labels to control the UI in Outlook to pin an attackers message to the victim's inbox.

[Poc](#)

Outlook sanitized keylogger

Unbelievably I managed to construct a fully working keylogger in sanitized CSS. This uses the CSS gadget to take over the screen. But it has limitations since you did not have full control over the CSS. See the "Outlook Firefox keylogger" for the full version that spoofs the Outlook login screen completely.

[Poc](#)

Realtime Chrome keylogger

This poc shows how to use Interest Invokers to create a realtime keylogger in Chrome.

Poc

Tools

CSS token exfiltrate

I created a minimal CSS token exfiltration tool whilst testing Gitlab. You can use this if you have a style injection and recursive CSS imports are allowed.

Tool

Shazzer

[Shazzer](#) enabled me to find image proxy bypasses and various CSS quirks and behaviours. I've made my vectors public so you can see how they were discovered. You can view the entire collection of vectors with the following URL:

[CSS: the bomb inside your inbox collection](#)

Note: The vectors will be made public after my talk.

Hackvertor

I used [Hackvertor](#) to construct the CSS mutations. This was done using the `cssEscape` tag. Hackvertor also has a "Copy as HTML" feature which creates a blob of your input and places it on the clipboard. This was used to probe sites for CSS injection from paste.

Don't forget to check out the [Research paper](#)!

Archived from <https://github.com/portswigger/css-the-bomb-inside-your-inbox>. Rendered offline from the local Markdown copy.