```
In [20]: import numpy as np
          import pandas as pd
          import scipy as sp
In [21]: %matplotlib inline
          import matplotlib.pyplot as plt
          plt.style.use('ggplot')
In [22]: | %%file hw_data.csv
          id, sex, weight, height
          1,M,190,77
          2,F,120,70
          3,F,110,68
          4,M,150,72
          5,0,120,66
          6,M,120,60
          7, F, 140, 70
         Overwriting hw data.csv
```

#### **Python**

## 1. Finish creating the following function that takes a list and returns the average value.

Add each element in the list to total and return total

#### DO NOT use a library function nor sum()

```
In [23]: def average(my_list):
    total = 0
    for item in my_list:
        #do something with item!
        ## print(item)
        total = total + item

    return total/len(my_list)

average([1,2,1,4,3,2,5,9])

Out[23]: 3.375
```

## 2. Using a Dictionary keep track of the count of numbers (or items) from a list

```
In [24]:
    def counts(my_list):
        counts = dict()
        for item in my_list:
            if item in counts:
```

3. Using the counts() function you created above and the .split() function, return a dictionary of most occuring words from the following paragraph. Bonus, remove punctuation from words.

```
paragraph_text = '''
In [25]:
          For a minute or two she stood looking at the house, and wondering what to do next, who
          The Fish-Footman began by producing from under his arm a great letter, nearly as large
          Then they both bowed low, and their curls got entangled together.
          Alice laughed so much at this, that she had to run back into the wood for fear of thei
          Alice went timidly up to the door, and knocked.
          'There's no sort of use in knocking,' said the Footman, 'and that for two reasons. Fir
          'Please, then,' said Alice, 'how am I to get in?'
          'There might be some sense in your knocking,' the Footman went on without attending to
          'I shall sit here,' the Footman remarked, 'till tomorrow-'
          At this moment the door of the house opened, and a large plate came skimming out, stra
          import string # Need String Punctuation
          pgph clean = paragraph text.translate(str.maketrans("","",string.punctuation))
          pgph_clean_1 = pgph_clean.replace("'", "")
          pgph_clean_2 = pgph_clean_1.replace(",", "")
pgph_clean_3 = pgph_clean_2.replace("-", "")
          word_list = pgph_clean_3.split()
          word list 2 = counts(word list)
          print(word_list_2)
```

{'For': 3, 'a': 15, 'minute': 1, 'or': 2, 'two': 2, 'she': 6, 'stood': 1, 'looking': 2, 'at': 6, 'the': 32, 'house': 2, 'and': 17, 'wondering': 1, 'what': 2, 'to': 15, 'd o': 1, 'next': 2, 'when': 2, 'suddenly': 1, 'footman': 3, 'in': 9, 'livery': 3, 'cam e': 2, 'running': 1, 'out': 5, 'of': 9, 'woodshe': 1, 'considered': 1, 'him': 3, 'b e': 2, 'because': 3, 'he': 5, 'was': 8, 'otherwise': 1, 'judging': 1, 'by': 3, 'his': 6, 'face': 2, 'only': 2, 'would': 1, 'have': 1, 'called': 1, 'fishand': 1, 'rapped': 1, 'loudly': 1, 'door': 6, 'with': 2, 'knuckles': 1, 'It': 1, 'opened': 2, 'another': 1, 'round': 1, 'large': 3, 'eyes': 2, 'like': 1, 'frog': 1, 'both': 2, 'footmen': 1, 'Alice': 5, 'noticed': 1, 'had': 4, 'powdered': 1, 'hair': 1, 'that': 3, 'curled': 1, 'all': 3, 'over': 2, 'their': 3, 'heads': 1, 'She': 1, 'felt': 1, 'very': 2, 'curiou s': 1, 'know': 2, 'it': 3, 'about': 1, 'crept': 1, 'little': 2, 'way': 1, 'wood': 2, 'listen': 1, 'The': 2, 'FishFootman': 2, 'began': 1, 'producing': 1, 'from': 2, 'unde r': 1, 'arm': 1, 'great': 2, 'letter': 1, 'nearly': 2, 'as': 4, 'himself': 1, 'this': 4, 'handed': 1, 'other': 2, 'saying': 1, 'solemn': 2, 'tone': 2, 'Duchess': 2, 'An': 2, 'invitation': 2, 'Queen': 2, 'play': 2, 'croquet': 2, 'FrogFootman': 1, 'repeate d': 2, 'same': 2, 'changing': 1, 'order': 1, 'words': 1, 'From': 1, 'for': 3, 'Then': 1, 'they': 1, 'bowed': 1, 'low': 1, 'curls': 1, 'got': 1, 'entangled': 1, 'together': 1, 'laughed': 1, 'so': 2, 'much': 1, 'run': 1, 'back': 1, 'into': 3, 'fear': 1, 'hear ing': 1, 'her': 2, 'peeped': 1, 'gone': 1, 'sitting': 1, 'on': 4, 'ground': 1, 'nea r': 1, 'staring': 1, 'stupidly': 1, 'up': 3, 'sky': 2, 'went': 2, 'timidly': 1, 'knoc ked': 1, 'Theres': 1, 'no': 2, 'sort': 1, 'use': 1, 'knocking': 2, 'said': 3, 'Footma n': 3, 'reasons': 1, 'First': 1, 'Im': 1, 'side': 1, 'you': 6, 'are': 2, 'secondly': 1, 'theyre': 1, 'making': 1, 'such': 1, 'noise': 2, 'inside': 2, 'one': 2, 'could': 2, 'possibly': 1, 'hear': 1, 'And': 1, 'certainly': 1, 'there': 1, 'most': 1, 'extrao rdinary': 1, 'going': 1, 'withina': 1, 'constant': 1, 'howling': 1, 'sneezing': 1, 'e very': 1, 'now': 1, 'then': 2, 'crash': 1, 'if': 3, 'dish': 1, 'kettle': 1, 'been': 1, 'broken': 1, 'pieces': 2, 'Please': 1, 'how': 1, 'am': 2, 'I': 4, 'get': 2, 'Ther e': 1, 'might': 3, 'some': 1, 'sense': 1, 'your': 1, 'without': 1, 'attending': 1, 'w e': 1, 'between': 1, 'us': 1, 'instance': 1, 'were': 1, 'knock': 1, 'let': 1, 'He': 1, 'time': 1, 'speaking': 1, 'thought': 1, 'decidedly': 1, 'uncivil': 1, 'But': 2, 'p erhaps': 1, 'cant': 1, 'help': 1, 'herself': 1, 'top': 1, 'head': 2, 'any': 1, 'rat e': 1, 'answer': 1, 'questionsHow': 1, 'aloud': 1, 'shall': 1, 'sit': 1, 'here': 1, 'remarked': 1, 'till': 1, 'tomorrow': 1, 'At': 1, 'moment': 1, 'plate': 1, 'skimmin g': 1, 'straight': 1, 'Footmans': 1, 'just': 1, 'grazed': 1, 'nose': 1, 'broke': 1, 'against': 1, 'trees': 1, 'behind': 1}

# 4. Read in a file using open() and iterated through the file line-by-line write each line from the file to a new file in a title() -ized. Create your own file for input

This is the first line -> This Is The First Line

Hint: There's a function to do this

```
In [26]: jab = open("C:/Users/Brett/Desktop/JHU_AAP/ML/mlnn-main-personal/mlnn-main/02/jabberwo
# jab = open(r"C:\Users\Brett\Downloads\demofile.txt",'r')

jab_string = jab.read()
#print(jab_string)

new_jab = []
for line in jab_string.splitlines():
    line = str.title(line)
```

```
new jab.append(line)
    print(line)
'Twas Brillig, And The Slithy Toves
      Did Gyre And Gimble In The Wabe:
All Mimsy Were The Borogoves,
      And The Mome Raths Outgrabe.
"Beware The Jabberwock, My Son!
      The Jaws That Bite, The Claws That Catch!
Beware The Jubjub Bird, And Shun
      The Frumious Bandersnatch!"
He Took His Vorpal Sword In Hand;
      Long Time The Manxome Foe He Sought-
So Rested He By The Tumtum Tree
      And Stood Awhile In Thought.
And, As In Uffish Thought He Stood,
      The Jabberwock, With Eyes Of Flame,
Came Whiffling Through The Tulgey Wood,
      And Burbled As It Came!
One, Two! One, Two! And Through And Through
      The Vorpal Blade Went Snicker-Snack!
He Left It Dead, And With Its Head
      He Went Galumphing Back.
"And Hast Thou Slain The Jabberwock?
      Come To My Arms, My Beamish Boy!
O Frabjous Day! Callooh! Callay!"
      He Chortled In His Joy.
'Twas Brillig, And The Slithy Toves
      Did Gyre And Gimble In The Wabe:
All Mimsy Were The Borogoves,
      And The Mome Raths Outgrabe.
```

#### Numpy

### 1. Given a list, find the average using a numpy function.

2. Given two lists of Heights and Weights of individual, calculate the BMI of those individuals, without writing a for-loop

```
In [28]: heights = [174, 173, 173, 175, 171]
    weights = [88, 83, 92, 74, 77]


    np_heights = np.array(heights)
    np_weights = np.array(weights)

bmis = np_weights / (np_heights/100)**2
    print(bmis)
```

[29.06592681 27.73229978 30.73941662 24.16326531 26.33288875]

## 3. Create an array of length 20 filled with random values (between 0 to 1)

## 4. Create an array with at least 1000 random numbers from normal distributions (normal). Then, plot a histogram of these values (plt.hist).



#### **Pandas**

## 1. Read in a CSV () and display all the columns and their respective data types

In [31]: hw = pd.read\_csv('C:/Users/Brett/Desktop/JHU\_AAP/ML/mlnn-main-personal/mlnn-main/02/hw
hw.head(20)

Out[31]:		sex	weight	height
	id			
	1	М	190	77
	2	F	120	70
	3	F	110	68
	4	М	150	72
	5	0	120	66
	6	М	120	60
	7	F	140	70

#### 2. Find the average weight


```
In [32]: hw.weight.mean()
Out[32]: 135.71428571428572
```

#### 3. Find the Value Counts on column sex

#### 4. Plot Height vs. Weight

```
In [34]: hw.plot.scatter(
    x = 'height',
    y = 'weight')
```

Out[34]: <Axes: xlabel='height', ylabel='weight'>



#### 5. Calculate BMI and save as a new column

```
In [35]: hw['weight']
hw['height']
bmi = (703*hw['weight'])/(hw['height']**2) # These appear to be imperial units
```

```
hw['bmi'] = bmi
hw
```

Out[35]:	sex	weight	heiaht	bmi
000[]].	507			

id				
1	М	190	77	22.528251
2	F	120	70	17.216327
3	F	110	68	16.723616
4	М	150	72	20.341435
5	Ο	120	66	19.366391
6	М	120	60	23.433333
7	F	140	70	20.085714

#### 6. Save sheet as a new CSV file hw\_dataB.csv

```
In [36]: hw.to_csv('hw_dataB.csv')
```

#### Run the following (Mac)

```
In [37]: !cat hw_dataB.csv

'cat' is not recognized as an internal or external command,
    operable program or batch file.
```

#### Run the following (Windows)

```
In [38]: !type hw_dataB.csv
```

```
id,sex,weight,height,bmi
1,M,190,77,22.528250969809413
2,F,120,70,17.216326530612246
3,F,110,68,16.723615916955016
4,M,150,72,20.341435185185187
5,0,120,66,19.366391184573004
6,M,120,60,23.433333333333334
7,F,140,70,20.085714285714285
```