



THE UNIVERSITY
of EDINBURGH

Usher
institute

HDS Tutorial 4

| Brittany Blankinship | 9 & 10 November 2021 |



THE UNIVERSITY
of EDINBURGH



Audio check


Open to
the world

Can you hear the presenter talking?

Please type **yes** or **no** in the “Text chat area”

If you can't hear:

- Check your Audio/Visual settings in the Collaborate Panel
- Try signing out and signing back into the session
- Type into the chat box and a moderator will try to assist you



ddi.hsc.talent@ed.ac.uk

Supported by



THE UNIVERSITY
of EDINBURGH




Recording

Open to
the world

This session will now be recorded. Any further information that you provide during a session is optional and in doing so you give us consent to process this information.

These sessions will be stored by the University of Edinburgh for one year and published for 30 days after the event. Schools or Services may use the recordings for up to a year on relevant websites.

By taking part in a session, you give us your consent to process any information you provide during it.

 Start Recording




THE UNIVERSITY
of EDINBURGH

Usher
institute

HDS Tutorial 4

| Brittany Blankinship | 9 & 10 November 2021 |

Agenda



- Interactive overview of key functions discussed in the course
- R Markdown knit to PDF demo
- Q&A

Have you managed to successfully
knit an R Markdown document?

Summary of key functions



Brittany's computer

R hex stickers are so fun!





Importing Data

★ read_csv()



```
#from a webpage
activity_raw <- read_csv("https://www.opendata.nhs.scot/dataset/0e17f3fc-9429-48aa-b1ba-2b7e55688253
/resource/748e2065-b447-4b75-99bd-f17f26f3eaeef/download/hd_activitybyhbr.csv")

#from a saved file on your computer in a folder called data
mortality_raw <- read_csv(here::here("./data/heartdiseaseMortalitybyHB.csv"))

#or without the here package
mortality_raw <- read_csv("./data/heartdiseaseMortalitybyHB.csv")
```



Variable naming conventions


☀️ `clean_names()`

Default to snake case, but there are 18 options you can choose from



Artwork by Allison Horst

Wrangling



Artwork by Allison Horst

Logical Operators

< Less than

> Greater than

== Equal to

<= Less than equal to

>= Greater than equal to

!= Not equal to

%in% Group membership




Figure 5.1: Complete set of boolean operations. x is the left-hand circle, y is the right-hand circle, and the shaded region show which parts each operator selects.

Source: R for Data Science book, Figure 5.1



Subsetting Data (observations)

★ `filter()`

Extract rows of existing data
that meeting logical
conditions

`data.frame` `logical test`
`filter(surveys, year >= 1985)`

`data.frame` `logical test`
`surveys %>% filter(year >= 1985)`

Credit: [Coding TogetherR](https://www.youtube.com/watch?v=Zc_ufg4uW4U)

For more check out this RStudio Data Manipulation video from Garrett Grolemund https://www.youtube.com/watch?v=Zc_ufg4uW4U



Subsetting Data (variables)

★ `select()`

Select columns by name or helper functions

Helper functions for `select` - `?select`

```
select(iris, contains("."))  
Select columns whose name contains a character string.  
select(iris, ends_with("Length"))  
Select columns whose name ends with a character string.  
select(iris, everything())  
Select every column.  
select(iris, matches(".t."))  
Select columns whose name matches a regular expression.  
select(iris, num_range("x", 1:5))  
Select columns named x1, x2, x3, x4, x5.  
select(iris, one_of(c("Species", "Genus")))  
Select columns whose names are in a group of names.  
select(iris, starts_with("Sepal"))  
Select columns whose name starts with a character string.  
select(iris, Sepal.Length:Petal.Width)  
Select all columns between Sepal.Length and Petal.Width (inclusive).  
select(iris, -Species)  
Select all columns except Species.
```

data.frame

column
variables

```
select(surveys, year, plot_type)
```

data.frame

column
variables

```
surveys %>% select(year, plot_type)
```

Credit: [Coding TogetherR](#)



New Variables

★ mutate()

Compute and append one or more new columns – changes an existing column or adds a new one

Works with grouped data or the whole dataset

Original columns remain after being passed to mutate

data.frame

new column
variable

expression

```
mutate(surveys, weight_kg = weight/1000)
```

data.frame

new column
variable

expression

```
surveys %>% mutate(weight_kg = weight/1000)
```

Credit: [Coding TogetherR](https://www.youtube.com/watch?v=Zc_ufg4uW4U)

For more check out this RStudio Data Manipulation video from Garrett Golemund https://www.youtube.com/watch?v=Zc_ufg4uW4U



Summarise

★ `summarise()`

Summarise data into single row of values

Drops variables not listed in `group_by()` or created inside it, drops columns after calculating the new one



Credit: [Coding TogetherR](https://www.youtube.com/watch?v=Zc_ufg4uW4U)

For more check out this RStudio Data Manipulation video from Garrett Golemund https://www.youtube.com/watch?v=Zc_ufg4uW4U



Group Data

★ `group_by()`

Group data into rows according to column variables

★ `ungroup()`

Remove grouping information from the data frame

```
data.frame      column
variables

group_by(surveys, species_id, rodent_type) %>%
  summarise(mean_weight = mean(weight, na.rm = TRUE))

data.frame      column
variables

surveys %>% group_by(species_id, rodent_type) %>%
  summarise(mean_weight = mean(weight, na.rm = TRUE))
```

Credit: [Coding TogetherR](#)

For more check out this RStudio Data Manipulation video from Garrett Golemund https://www.youtube.com/watch?v=Zc_ufg4uW4U

Data formats & Tidy Data

“**TIDY DATA** is a standard way of mapping the meaning of a dataset to its structure.”

—HADLEY WICKHAM

In tidy data:

- each variable forms a column
- each observation forms a row
- each cell is a single measurement

each column a variable

| id | name | color |
|----|--------|--------|
| 1 | floof | gray |
| 2 | max | black |
| 3 | cat | orange |
| 4 | donut | gray |
| 5 | merlin | black |
| 6 | panda | calico |

each row an observation

Wickham, H. (2014). Tidy Data. *Journal of Statistical Software* 59 (10). DOI: 10.18637/jss.v059.i10

Ways data can become untidy:

- Column headers contain values, rather than names
- Multiple variables are stored in a single column
- Variables are stored in both rows and columns
- Multiple observational types are stored in a single table
- A single observational unit is stored in multiple tables

Wickham, H. (2014). Tidy data. *Journal of statistical software*, 59(1), 1-23.

For more on tidy data see the above paper & Chapter 12 of the R for Data Science Book

Data formats & Tidy Data

| wide | | | | long | | |
|------|---|---|---|------|-----|-----|
| id | x | y | z | id | key | val |
| 1 | a | c | e | 1 | x | a |
| 2 | b | d | f | 2 | x | b |
| | | | | 1 | y | c |
| | | | | 2 | y | d |
| | | | | 1 | z | e |
| | | | | 2 | z | f |

| "Long" format | | | "Wide" format | | | |
|---------------|------|--------|---------------|--------|--------|--------|
| country | year | metric | country | yr1960 | yr1970 | yr2010 |
| x | 1960 | 10 | x | 10 | 13 | 15 |
| x | 1970 | 13 | y | 20 | 23 | 25 |
| x | 2010 | 15 | z | 30 | 33 | 35 |
| y | 1960 | 20 | | | | |
| y | 1970 | 23 | | | | |
| y | 2010 | 25 | | | | |
| z | 1960 | 30 | | | | |
| z | 1970 | 33 | | | | |
| z | 2010 | 35 | | | | |

Wide format = generally untidy, but found in many datasets




Transforming Data (wide to long)

★ `pivot_longer()`

Requires:

1. `data` = data you want to pivot
2. `names_to` = name of the column you want to create to capture condition, requires a character string
3. `values_to` = name of column you want to contain data values, requires a character string
4. `column X:column Y` = range of columns that you have and want to pivot longer, or that you do not want to pivot



Credit: Alistair Bailey's [Coding TogetherR](#)



Transforming Data

★ `pivot_longer()` = wide to long

| country | 1999 | 2000 | 2001 | 2002 |
|----------|-------|-------|-------|-------|
| Angola | 800 | 750 | 925 | 1020 |
| India | 20100 | 25650 | 26800 | 27255 |
| Mongolia | 450 | 512 | 510 | 586 |

Pivot data longer

```
data %>%  
  pivot_longer(  
    cols = 1999:2002,  
    names_to = "year",  
    values_to = "cases"  
  )
```



| country | year | cases |
|----------|------|-------|
| Angola | 1999 | 800 |
| Angola | 2000 | 750 |
| Angola | 2001 | 925 |
| Angola | 2002 | 1020 |
| India | 1999 | 20100 |
| India | 2000 | 25650 |
| India | 2001 | 26800 |
| India | 2002 | 27255 |
| Mongolia | 1999 | 450 |
| Mongolia | 2000 | 512 |
| Mongolia | 2001 | 510 |
| Mongolia | 2002 | 586 |

Credit: [Epidemiologist R Handbook](#)




Transforming Data (long to wide)

★ `pivot_wider()`

Requires:

1. `data` = data you want to pivot
2. `names_from` = name of column you want to end up in several columns
3. `values_from` = name of column that currently contains data values



Credit: Alistair Bailey's [Coding Together](#)

For more check out this RStudio Data Wrangling video from Garrett Grolemund

<https://www.youtube.com/watch?v=1ELALQIO-yM> - however includes the now superseded functions `gather()` & `spread()`



Transforming Data

★ `pivot_wider()` = long to wide

| country | year | cases |
|----------|------|-------|
| Angola | 1999 | 800 |
| Angola | 2000 | 750 |
| Angola | 2001 | 925 |
| Angola | 2002 | 1020 |
| India | 1999 | 20100 |
| India | 2000 | 25650 |
| India | 2001 | 26800 |
| India | 2002 | 27255 |
| Mongolia | 1999 | 450 |
| Mongolia | 2000 | 512 |
| Mongolia | 2001 | 510 |
| Mongolia | 2002 | 586 |

| country | 1999 | 2000 | 2001 | 2002 |
|----------|-------|-------|-------|-------|
| Angola | 800 | 750 | 925 | 1020 |
| India | 20100 | 25650 | 26800 | 27255 |
| Mongolia | 450 | 512 | 510 | 586 |

Pivot data wider

```
data %>%  
  pivot_wider(  
    names_from = "year",  
    values_from = "cases"  
  )
```

Credit: [Epidemiologist R Handbook](#)



| wide | | | |
|------|---|---|---|
| id | x | y | z |
| 1 | a | c | e |
| 2 | b | d | f |

Credit: [Garrick Aden-Buie](#)
& [Mara Averick](#)



Joins

★ left_join()
★ inner_join()
★ full_join()

left_join(x, y)

| | | | |
|---|----|---|----|
| 1 | x1 | 1 | y1 |
| 2 | x2 | 2 | y2 |
| 3 | x3 | 4 | y4 |
| | | 2 | y5 |

inner_join(x, y)

| | | | |
|---|----|---|----|
| 1 | x1 | 1 | y1 |
| 2 | x2 | 2 | y2 |
| 3 | x3 | 4 | y4 |

full_join(x, y)

| | | | |
|---|----|---|----|
| 1 | x1 | 1 | y1 |
| 2 | x2 | 2 | y2 |
| 3 | x3 | 4 | y4 |

For a fun explanation using The Beatles & Rolling Stones see Nic Crane's tweet:

<https://bit.ly/3qfhBb9>

Credit: Garrick Aden-Buie

<https://www.garrickadenbuie.com/project/tidyexplain/>



Dates

★ `separate()` turns a character column into multiple columns

| Order of elements in date-time | Parse function |
|--|------------------------|
| year, month, day | ★ <code>ymd()</code> |
| year, day, month | <code>ydm()</code> |
| month, day, year | <code>mdy()</code> |
| day, month, year | <code>dmy()</code> |
| hour, minute | <code>hm()</code> |
| hour, minute, second | <code>hms()</code> |
| year, month, day, hour, minute, second | <code>ymd_hms()</code> |

*adapted from *Dates and Times Made Easy with lubridate* (Grolemund & Wickham, 2011)



```
#where col = name of column to separate
# into = vector of names for column to be separated into
# sep = value to separate column at
separate(data, col, into, sep)

#example we have seen before
separate(financial_year, into = c("year", NA), sep = "/")
```



Factors & Strings

★ `levels()` to see the set of levels in the factor

★ `fct_relevel()` to manually reorder factor levels

★ `fct_recode()` to manually change the levels labels

★ `fct_collapse()` to collapse levels into manually defined groups

★ `str_replace()` to change the labels of a string

★ `str_wrap()` to wrap the text of a string if it is too long into 2+ lines

Plotting




Artwork by Allison Horst






Grammar of Graphics

Theme
Coordinates
Statistics
Facets
Geometries
Aesthetics
Data



- ★ + theme_bw()
+ theme_classic() etc.
- ★ + coord_flip()
 - Example: + stat_summary()
- ★ + facet_wrap()
+ facet_grid(x~y)
- ★ + geom_line() + geom_bar()
+ geom_jitter() etc.
- ★ ggplot(data, aes(x, y,
color, shape, fill))
- ★ ggplot(data)

| | | |
|-------------|---|--|
| | Numerical | Categorical |
| Numerical |  <ul style="list-style-type: none"> Scatter plot (point) 2D binning (bin2d, hex) Contour plot (density2d) Quantiles (quantile, qq) Lines (line, smooth) Ribbons (ribbon, area) |  <ul style="list-style-type: none"> Boxplot (boxplot, violin) Counts (count, tile) Error bars (errorbar) Columns (col) |
| Categorical | <p>Which ggplot2 data viz is right for your data? (geoms in parentheses)</p> |  <ul style="list-style-type: none"> Mosaic (ggmosaic::geom_mosaic) Counts (count, tile) |

From Dr Sam Tyner's guest lecture in Week 4

Importance of variable class

ggplot2 Cheatsheet

Data Visualization with ggplot2 :: CHEAT SHEET



Basics

ggplot2 is based on the **grammar of graphics**, the idea that you can build every graph from the same components: a **data set**, a **coordinate system**, and **geoms**—visual marks that represent data points.



To display values, map variables in the data to visual properties of the geom (**aesthetics**) like **size**, **color**, and **x** and **y** locations.



Complete the template below to build a graph.

```
ggplot (data = <DATA>) +  
  <GEOM_FUNCTION> (mapping = aes (<MAPPINGS>),  
  stat = <STAT>, position = <POSITION>) +  
  <COORDINATE_FUNCTION> +  
  <FACET_FUNCTION> +  
  <SCALE_FUNCTION> +  
  <THEME_FUNCTION>
```

required
Not required, sensible defaults supplied

ggplot(data = mpg, aes(x = cty, y = hwy)) Begins a plot that you finish by adding layers to. Add one geom function per layer.

last_plot() Returns the last plot.

ggsave("plot.png", width = 5, height = 5) Saves last plot as 5" x 5" file named "plot.png" in working directory. Matches file type to file extension.

Aes

Common aesthetic values.

color and fill - string ("red", "#RRGGBB")
linetype - integer or string (0 = "blank", 1 = "solid", 2 = "dashed", 3 = "dotted", 4 = "dotdash", 5 = "longdash", 6 = "twodash")

lineend - string ("round", "butt", or "square")

linejoin - string ("round", "mitre", or "bevel")

size - integer (line width in mm)

shape - integer/shape name or a single character ("a")



Geoms

Use a geom function to represent data points, use the geom's aesthetic properties to represent variables. Each function returns a layer.

GRAPHICAL PRIMITIVES

a <- ggplot(economics, aes(date, unemploy))
b <- ggplot(seals, aes(x = long, y = lat))

a + geom_blank() and **a + expand_limits()**
Ensure limits include values across all plots.

b + geom_curve(aes(yend = lat + 1, xend = long + 1, curvature = 1) - x, yend, y, alpha, angle, color, curvature, linetype, size)

a + geom_path(lineend = "butt", linejoin = "round", linemitre = 1)
x, y, alpha, color, group, linetype, size

a + geom_polygon(aes(alpha = 50)) - x, y, alpha, color, fill, group, subgroup, linetype, size

b + geom_rect(aes(xmin = long, ymin = lat, xmax = long + 1, ymax = lat + 1)) - xmax, xmin, ymax, ymin, alpha, color, fill, linetype, size

a + geom_ribbon(aes(ymin = unemploy - 900, ymax = unemploy + 900)) - x, y, alpha, color, fill, group, linetype, size

LINE SEGMENTS

common aesthetics: x, y, alpha, color, linetype, size

b + geom_abline(aes(intercept = 0, slope = 1))
b + geom_hline(aes(yintercept = lat))
b + geom_vline(aes(xintercept = long))

b + geom_segment(aes(yend = lat + 1, xend = long + 1))
b + geom_spoke(aes(angle = 1:1155, radius = 1))

ONE VARIABLE continuous

c <- ggplot(mpg, aes(hwy)); c2 <- ggplot(mpg)

c + geom_area(stat = "bin")
x, y, alpha, color, fill, linetype, size

c + geom_density(kernel = "gaussian")
x, y, alpha, color, fill, group, linetype, size, weight

c + geom_dotplot()
x, y, alpha, color, fill

c + geom_freqpoly()
x, y, alpha, color, group, linetype, size

c + geom_histogram(binwidth = 5)
x, y, alpha, color, fill, linetype, size, weight

c2 + geom_qq(aes(sample = hwy))
x, y, alpha, color, fill, linetype, size, weight

c2 + geom_qq(aes(sample = hwy))
x, y, alpha, color, fill, linetype, size, weight

discrete

d <- ggplot(mpg, aes(f1))

d + geom_bar()
x, alpha, color, fill, linetype, size, weight

TWO VARIABLES

both continuous

e <- ggplot(mpg, aes(cty, hwy))

e + geom_label(aes(label = cty), nudge_x = 1, nudge_y = 1) - x, y, label, alpha, angle, color, family, fontface, hjust, lineheight, size, vjust

e + geom_point()
x, y, alpha, color, fill, shape, size, stroke

e + geom_quantile()
x, y, alpha, color, group, linetype, size, weight

e + geom_rug(sides = "bl")
x, y, alpha, color, linetype, size

e + geom_smooth(method = lm)
x, y, alpha, color, fill, group, linetype, size, weight

e + geom_text(aes(label = cty), nudge_x = 1, nudge_y = 1) - x, y, label, alpha, angle, color, family, fontface, hjust, lineheight, size, vjust

one discrete, one continuous

f <- ggplot(mpg, aes(class, hwy))

f + geom_col()
x, y, alpha, color, fill, group, linetype, size

f + geom_boxplot()
x, y, lower, middle, upper, ymax, ymin, alpha, color, fill, group, linetype, shape, size, weight

f + geom_dotplot(binaxis = "y", stackdir = "center")
x, y, alpha, color, fill, group

f + geom_violin(scale = "area")
x, y, alpha, color, fill, group, linetype, size, weight

both discrete

g <- ggplot(diamonds, aes(cut, color))

g + geom_count()
x, y, alpha, color, fill, shape, size, stroke

e + geom_jitter(height = 2, width = 2)
x, y, alpha, color, fill, shape, size

THREE VARIABLES

seals\$z <- with(seals, sqrt(delta_long^2 + delta_lat^2)); l <- ggplot(seals, aes(long, lat))

l + geom_contour(aes(z = z))
x, y, z, alpha, color, group, linetype, size, weight

l + geom_contour_filled(aes(fill = z))
x, y, alpha, color, fill, linetype, size, subgroup

continuous bivariate distribution

h <- ggplot(diamonds, aes(carat, price))

h + geom_bin2d(binwidth = c(0.25, 500))
x, y, alpha, color, fill, linetype, size, weight

h + geom_density_2d()
x, y, alpha, color, group, linetype, size

h + geom_hex()
x, y, alpha, color, fill, size

continuous function

i <- ggplot(economics, aes(date, unemploy))

i + geom_area()
x, y, alpha, color, fill, linetype, size

i + geom_line()
x, y, alpha, color, group, linetype, size

i + geom_step(direction = "hv")
x, y, alpha, color, group, linetype, size

visualizing error

df <- data.frame(grp = c("A", "B"), fit = 4:5, se = 1:2)
j <- ggplot(df, aes(grp, fit, ymin = fit - se, ymax = fit + se))

j + geom_crossbar(fatten = 2) - x, y, ymax, ymin, alpha, color, fill, group, linetype, size

j + geom_errorbar() - x, ymax, ymin, alpha, color, group, linetype, size, width
Also **geom_errorbarh**()

j + geom_linerange()
x, ymin, ymax, alpha, color, group, linetype, size

j + geom_pointrange() - x, y, ymin, ymax, alpha, color, fill, group, linetype, shape, size

maps

data <- data.frame(murder = USArrests\$Murder, state = tolower(rownames(USArrests)))

map <- map_data("state")

k <- ggplot(data, aes(fill = murder))

k + geom_map(aes(map_id = state), map = map) + **expand_limits**(x = map\$long, y = map\$lat)
map_id, alpha, color, fill, linetype, size

maps

l + geom_raster(aes(fill = z), hjust = 0.5, vjust = 0.5, interpolate = FALSE)
x, y, alpha, fill

l + geom_tile(aes(fill = z))
x, y, alpha, color, fill, linetype, size, width

Color palettes

Emil Hvitfeldt has created a “one stop destination for anyone looking for a color palette to use in r.”

<https://github.com/EmilHvitfeldt/r-color-palettes>

Including an interactive color selector!

<https://emilhvitfeldt.github.io/r-color-palettes/discrete.html>



introverse package

https://spielmanlab.github.io/introverse/articles/introverse_online.html

introverse 0.0.1 Home Get help here Get help in RStudio RStudio reference Resources and tutorials

Get help online

Source: vignettes/introverse_online.Rmd

Get help with the example datasets

- carnivores
- msleep

Get help with operators and magrittr pipes

- [Assignment operators in R](#)
- [Mathematical operators in R](#)
- [Logical operators in R](#)
- [magrittr pipe](#)
- [magrittr assignment pipe](#)

Get help with Base R

Contents

- Get help with the example datasets
- Get help with operators and magrittr pipes
- Get help with Base R
- Get help with ggplot2
- Get help with dplyr
- Get help with tidyselect helpers
- Get help with forcats
- Get help with readr
- Get help with tibble
- Get help with tidyr
- Get help with stringr
- Get help with glue

Report generation



Artwork by Allison Horst




★ `kable()` for nice tables

★ `kable_styling()` for more formatting/styling options

Note: `kableExtra` is *not* a generating package, but an *extra* which can add features to a `kable()` output

R Markdown



A bit more on knitting to PDFs



Questions?

R Programming Assignment

Due: Monday, 29th November at 12 noon GMT

See Learn pages or [the repository here](#) for more info

Q&A around the assignment Wednesday 10 November 6pm!