

RESEARCH

Incorporating Periodic Variability in Hidden Markov Models for Animal Movement

Michael Li^{1*} and Benjamin M. Bolker^{1,2}

Sample of title note

* Correspondence:

lim88@mcmaster.ca

¹ Department of Biology,
McMaster University, 1280 Main
St. West, L8S 4K1, Hamilton,
Ontario, Canada

Full list of author information is
available at the end of the article

[†]Equal contributor

Abstract

Clustering time-series data into discrete groups can improve prediction and provide insight into the nature of underlying, unobservable states of the system. However, temporal variation in the rates at which individuals move between groups can obscure such signals. We use finite mixture and hidden Markov models (HMMs), two standard clustering techniques, to model high-resolution hourly movement data from Florida panthers (*Puma concolor coryi*). Allowing for temporal heterogeneity in transition probabilities, a straightforward but little-used extension of the standard HMM framework, resolves some shortcomings of current models and clarifies the behavioural patterns of panthers. More generally, we point out that model misspecification (omitting important sources of variation) can lead to overfitting, and as a corollary that incorporating previously neglected structure in statistical models can allow more accurate assessment of appropriate model complexity.

Background: Text for this section.

Results: Text for this section.

Conclusion: Text for this section.

Keywords: Hidden Markov Model; Animal Movement; Temporal Autocorrelation; Temporal Heterogeneity; Florida Panther

Background

Given a sequence of animal movements, movement models aim to find a parsimonious description that can be used to understand past movements and predict future movements. Ecologists have long considered the effects of individual-level covariates (sex, age, nutritional status) and environmental covariates (habitat type, location of predators or prey) on movement [1, 2, 3]. More recently, modelers have developed *hidden Markov models* (HMMs) [4, 5, 6] — used in animal ecology under the rubric of the “multiphasic movement framework” [7] — that consider the effects of organisms’ *internal* states; in particular, HMMs model animal movement as though individual animals’ movement behaviour at particular times is determined by which of a discrete set of unobserved movement states (e.g. “foraging”, “traveling”, “resting”) they currently occupy. Conditional on the state occupied by an individual, HMMs typically assume that animals follow a standard correlated walk model [8, 9].

Ever-increasing capabilities of remote sensors are making movement data available over an ever-wider range of time scales, at both higher resolution (e.g. hourly data from GPS collars vs. daily or weekly fixes for radio or VHF collars) and longer extent (e.g. from a few days to significant fractions of a year, or longer). When analyzing such long-term data, ecologists will more often have to account for temporal variability in movement behaviour at diurnal and seasonal scales that were previously not captured in the data.

HMMs have typically been used to model movements over short time scales, where the probability of transitioning between movement states is approximately constant. Changes in latent/hidden behavioural state/mode transition probabilities based on the local environment can be accounted for incorporating environmental covariates in the HMM [10], or by more direct comparisons between inferred states and environmental conditions [7]. Schliehe-Diecks et al. [11] consider temporal trends in behavioural transitions over the time scales of a six-hour observation period, but in general ecologists have turned to other tools to describe behavioural changes over longer (diurnal, seasonal, or ontogenetic) time scales [12].

For movement behaviours that change on a fast time scale, such that movement behaviours recorded at successive observations are effectively independent, *finite mixture models* (FMMs) — which can be considered a special case of HMMs where the probability of state occupancy is independent of the previous state — can adequately describe movement [13]. When movement varies over long time scales (relative to the time between observations) with little short-term persistence or correlation, movement could be well represented by FMMs where the occupancy probabilities change deterministically over time. Thus FMMs and HMMs, with or without temporal variation in the occupancy or transition probabilities, form a useful family of models for capturing changes in movement behaviour over a range of time scales.

Our primary goal in this paper is to introduce the use of HMMs with temporally varying transition probabilities – in particular, transition probabilities that follow a diurnal cycle – for modeling animal movement recorded over long time scales. In addition to simulation-based examples, we also re-analyze data from van de Kerk et al. [14], who used temporally homogeneous hidden semi-Markov models (HSMMs: an extension of HMMs that allow flexible modelling of the distribution of *dwell times*, the lengths of consecutive occupancy of a behavioural state) to describe the movement and putative underlying behavioural states of Florida panthers (*Puma concolor coryi*).

van de Kerk et al. [14] found that the best-fitting HSMMs incorporated a surprisingly large number of hidden behavioural states (as many as six for individuals with a large amount of available data); for reasons of computational practicality and biological interpretability, they restricted their detailed analysis to models with only three underlying states. In contrast, most studies using HMM have chosen the number of underlying states *a priori*, typically using either two [11, 15, 6, 7], or three states [16, 17, 18]. In contrast, [19] evaluated models with up to 10 states, but like

[14] they chose to consider only models with three states. As van de Kerk et al. [14] comment, and as we discuss further below, behavioural repertoires with more than three distinct states are difficult to interpret — one possible reason that other authors have not adopted van de Kerk et al.’s model-based approach to identifying the number of latent states.

Our second goal, therefore, is to explore whether van de Kerk et al.’s results on optimal model complexity might be driven at least in part by structural problems with their statistical model, i.e. the assumption of temporally homogeneous behaviour. For large data sets, information-theoretic model selection methods will typically choose complex, highly parameterized models; when there is only one way in which models can become more complex (e.g. by increasing the number of latent states), complexity that is present in the data but not accounted for in the model (e.g. spatial or temporal heterogeneity) can be misidentified as other forms of complexity. We predict that increasing volumes of data will increasingly lead researchers who are accustomed to fitting small models to sparse data into such traps. We examine whether allowing for diurnal variation in the Florida panther data leads to selection of models with smaller numbers of latent states; we also fit models to simulated data with varying numbers of latent states and degrees of temporal heterogeneity to test our conjecture that heterogeneity can be misidentified as behavioural complexity.

Methods

Data and previous analyses

GPS collars were fitted to 18 Florida panthers in 2005–2012 by Florida Fish and Wildlife and Conservation Commission staff using trained hounds and houndsmen. Of these animals, 13 had sufficient data to be used by van de Kerk et al. [14]. Here we focus on the four cats with the most data (all with approximately 10,000–15,000 observations: see Table 1 in Supplementary Material), in part because our goal is to understand the issues that arise when simple models are fitted to large data sets, and in part because the general trend in telemetry studies is toward larger data sets. As is typical in studies of animal movement, we took first differences of the data by decomposing contiguous sequences of hourly GPS coordinates into successive step lengths (in meters) and turning angles (in radians) [9, 14].

van de Kerk et al. [14] used hidden semi-Markov models (HSMM), an extension of HMM that permits explicit modelling of dwell times [6], considering both Poisson and negative binomial distributions for dwell times. As shown by van de Kerk et al. [14] (Figure S3b, top row, middle panel), the estimated shape parameter of the negative binomial dwell time distribution was typically close to 1 ($\approx 0.4 - 1.6$; confidence intervals were not given), implying that a geometric distribution (i.e., negative binomial with shape=1) might be adequate. In turn, this suggests that we might not lose much accuracy by reverting to a simpler HMM framework, which corresponds to making precisely this assumption.

van de Kerk et al.[14] considered time-homogeneous models with a variety of candidate distributions — log-Normal, Gamma, and Weibull distributions for step lengths and von Mises and wrapped Cauchy distributions for the turning angle — concluding on the basis of the Akaike information criterion (AIC) that Weibull step length and wrapped Cauchy turning angle distributions were best. Since our analysis aims for simplicity and qualitative conclusions rather than for picking the very best predictive model, we focus on models that treat each step as a univariate, log-Normally distributed observation, glossing over both the differences in shape between the three candidate step-length distributions and the effects of considering multivariate (i.e., step length plus turning angle) observations. However, we do briefly compare log-Normal and Weibull step-length distributions, with and without a von Mises-distributed turning angle included in the model (Figure ??). (Note that most movement analyses, including van de Kerk et al. [14], are only partially multivariate, treating step length and turning angle at a particular time as multivariate observations for the purpose of HMM analysis but neglecting possible correlations between the two measures.)

van de Kerk et al.[14] used the Bayesian (Schwarz) information criterion (BIC) to test the relative penalized goodness of fit for models ranging from 2 to 6 latent states. In general, BIC values decreased as the number of states increased from three to six states, suggesting that the six-state model was favoured statistically; however, the authors used three-state models in most of their analyses for ease of biological interpretation. We follow van de Kerk et al.[14] in using BIC-optimality (i.e., minimum BIC across a family of models) as the criterion for identifying the best model, because we are interested in explaining the data generation process by identifying the “true” number of underlying movement states. Using BIC also simplifies evaluation of model selection procedures; it is easier to test whether our model selection procedure has selected the model used to simulate the data, rather than testing whether it has selected the model with the minimal Kullback-Leibler distance [20]. We recognize that ecologists will often be interested in maximizing predictive accuracy rather than selecting a true model, and that as usual in ecological systems the true model will be far more complicated than any candidate model [21]; we believe that the qualitative conclusions stated here for BIC-optimality will carry over to analyses using AIC instead.

Model description

In a HMM, the joint likelihood of *emissions* (i.e., direct observations) $\mathbf{Y} = \mathbf{y}_1, \dots, \mathbf{y}_T$ and a hidden state sequence $\mathbf{Z}, z_t \in \{1, \dots, n\}, t = 1, \dots, T$, given model parameters $\boldsymbol{\theta}$ and covariates $\mathbf{X}_{1:T} = \mathbf{x}_1, \dots, \mathbf{x}_T$, can be written as:

$$P(\mathbf{Y}_{1:T}, \mathbf{Z}_{1:T} | \boldsymbol{\theta}, \mathbf{X}_{1:T}) = P(z_1 | \mathbf{x}_1) P(\mathbf{y}_1 | z_1, \mathbf{x}_1) \cdot \prod_{k=2}^T P(z_k | z_{k-1}, \mathbf{x}_k) P(\mathbf{y}_k | z_k, \mathbf{x}_k) \quad (1)$$

The emissions \mathbf{y}_i are boldfaced to denote that we may have a vector of observations at each time point (e.g., step length and turning angle). The model contains three distinct components:

Initial probability $P(z_1 = i | \mathbf{x}_1)P(\mathbf{y}_1 | z_1, \mathbf{x}_1)$: the probability of state i at time $t = 1$ where the covariate is \mathbf{x}_1 , times the vector of observations \mathbf{y}_1 conditioned on covariates \mathbf{x}_1 and state z_1 .

Transition probability $P(z_k = j | z_{k-1} = i, \mathbf{x}_k)$: the probability of a transition from state i at time $t = k - 1$ to state j with covariate \mathbf{x}_k at time $t = k$.

Emission probability $P(\mathbf{y}_k | z_k, \mathbf{x}_k)$: a vector of observations \mathbf{y}_k conditioned on covariates \mathbf{x}_k at state z_k at time $t = k$.

Eq. 1 gives the likelihood of the observed sequence given (conditional on) a particular hidden sequence. In order to calculate the overall, unconditional (or marginal) likelihood of the observed sequence, we need to average over all possible hidden sequences. There are several efficient algorithms for computing the marginal likelihood and numerically estimating parameters [22]; we used those implemented in the `depmixS4` package for R [23, 24].

For any n -state HMM, we need to define a $n \times n$ matrix that specifies the probabilities π_{ij} of being in movement states j at time $t+1$ given that the individual is in state i . The FMM is a special case of HMM where the probabilities of *entering* a given state are identical across all states — i.e., the probability of occupying a state at the next time step is independent of the current state occupancy. It can be modelled in the HMM framework by setting the transition probabilities $\pi_{ij} = \pi_{i*}$.

In any case, the transition matrix π_{ij} must respect the constraints that (1) all probabilities are between 0 and 1 and (2) transition probabilities out of a given state sum to 1. As is standard for HMMs with covariates [23], we define this multinomial logistic model in terms of a linear predictor η_{ij} , where η_{i1} is set to 1 without loss of generality (i.e. we have only $n \times (n - 1)$ distinct parameters; we index j from 2 to n for notational clarity):

$$\pi_{ij} = \exp(\eta_{ij}(t)) / \left(1 + \sum_{j=2}^n \exp(\eta_{ij}(t)) \right), \text{ for } j = 2, \dots, n$$

$$\pi_{i1} = 1 - \sum_{j=2}^n \pi_{ij}$$
(2)

We considered four different transition models for diurnal variation in behaviour, incorporating hour-of-day as a covariate following the general approach of Morales et al.[17] of incorporating covariate dependence in the transition matrix.

Multiple block transition Here we assume piecewise-constant transition probabilities. The transition probability π_{ij} is a function of time (hour of day), where it is assigned to one of M different time blocks:

$$\eta_{ij}(t) = \sum_{m=1}^M a_{ijm} \delta_{m=t}$$

where a_{ijm} are parameters, and $\delta_{m=t}$ is a Kronecker delta ($\delta_{m=t} = 1$ for the time block at the corresponding time t , and 0 otherwise).

Quadratic transition model We assume the elements of the linear predictor are quadratic functions of hour. The quadratic model is not diurnally continuous, i.e. there is no constraint that forces $\eta_{ij}(0) = \eta_{ij}(24)$; imposing a diurnal continuity constraint would collapse the model to a constant.

$$\eta_{ij}(t) = b_{ij1} + b_{ij2} \left(\frac{t}{24} \right) + b_{ij3} \left(\frac{t}{24} \right)^2$$

Sinusoidal transition model A sinusoidal model with a period of 24 hours is identical in complexity to the quadratic model, but automatically satisfies the diurnal continuity constraint.

$$\eta_{ij}(t) = b_{ij1} + b_{ij2} \cos \left(\frac{2\pi t}{24} \right) + b_{ij3} \sin \left(\frac{2\pi t}{24} \right)$$

Hourly model Lastly, we extended the multi-block approach and assign a different transition matrix for every hour of the day. This model is included for comparative purposes due to the large number of parameters in the model which makes it not really practical. We only fitted up to four states using the hourly model.

Other periodic functions, such as Fourier series (the sinusoidal transition model augmented by additional sinusoidal components at higher frequencies) or periodic splines, could be useful directions for future exploration.

0.1 Model evaluation

We used the `depmixS4` package to fit covariate-dependent transition HMMs, simulate states and step lengths using the estimated parameters, and estimate the most likely states with the Viterbi algorithm.

We used three approaches to assess the fit of both time-homogeneous and time-inhomogeneous HMMs with 3 to 6 states to step-length data from the four of the thirteen Florida panthers with the most data (> 9000 observations). (1) Comparing BICs to the optimal-BIC model within each type of transition complexity ($\Delta\text{BIC} = \text{BIC} - \min(\text{BIC})$) assesses the overall goodness of fit of each model type. (2)

Comparing average step-length by hour of day for the observed data and for data simulated from the models shows how well a particular class of models can capture the diurnal variation in behaviour. (3) Comparing temporal autocorrelations for the observed data and for data simulated from the models shows how well a particular class of models captures serial correlation at both short and long scales.

Model complexity and the number of parameters increase as the number of latent states increase, FMM to HMM, and lastly, FMM and HMM incorporating temporal heterogeneity. The number of free parameters in an HMM can be generalized by summing up the number of free parameters of the three distinct components. Let n be the number of hidden states and k_i, k_t, k_e be the number of parameters describing the covariate-dependence of the prior distribution, transition function and emission distributions; that is, for a homogeneous model, $k = 1$, while a single numeric covariate or a categorical predictor with two levels would give $k = 2$. Then the number of free parameters of an HMM is:

$$\underbrace{k_i \cdot (n - 1)}_{\text{Initial}} + \underbrace{k_t \cdot n \cdot (n - 1)}_{\text{Transition}} + \underbrace{k_e \cdot n}_{\text{Emission}} \quad (3)$$

As the number of states increases, the number of free parameters in time-homogeneous FMMs and HMMs and FMMs with temporal heterogeneity will increase linearly, whereas HMMs with temporal heterogeneity will increase quadratically (Eq. 3). When comparing BICs, it is important to account for the tradeoff between log-likelihood and number of states, but also log-likelihood and number of free parameters.

We used simulations to predict hourly step length and ACF because, while the computation is reasonably straightforward for FMMs, and manageable for homogeneous HMMs, the interaction between the geometric dwell time within each state and the temporally varying interaction probabilities makes it unreasonably complex. We used this approach to validate our models and comparing these models with the observed movements instead of the standard Viterbi predictions by the Viterbi algorithm because Viterbi predictions, which use the most probable sequence of movement states based on the observations [22, 6], double-count the observed data. It is useful to predict missing data in the observation sequence, but because it is conditional on the observed values, it can not reliably evaluate goodness of fit for the different structural complexities of HMM models.

1 Results

We simulated a two-state HMM with sinusoidal temporal transitions 100 times and fitted it with two to five state HMMs and without temporal transition. Fig. ?? shows heterogeneous transition models can always predict the correct number of states, whereas, can overestimate the number of states via BIC-optimal approach.

Fig. ?? shows that the BIC-optimal number of states for time homogenous models is consistent with van de Kerk et al.'s [14] results (Weibull wrapped-Cauchy to Weibull von Mises, and Weibull von Mises to log Normal without turning angles)

As a complement, we also fitted FMM and FMM with sinusoidal variation in state occupancy probabilities to compare the temporal effects in goodness of fit (dashed lines). As a reminder, FMMs assume that the latent state in each time step is *independent* of the latent state at the previous time step; time-varying FMMs can accurately describe movement when behaviour can change on a short time scale, but the average propensity for different behaviours changes over time.

Figure ?? shows that models with temporal heterogeneity are better (lower BIC) than homogeneous models in both FMM and HMM frameworks, but time-homogenous HMMs are better than FMMs with sinusoidal temporal heterogeneity. Turning to the temporally heterogeneous HMMs (right panel), we see that the model with different transition probabilities for each hour of the day (HMM + THhourly) is overparameterized; it underperforms homogeneous HMM with even 3 states, and gets much worse with 4 states. The multiple-block model approximately matches the homogeneous HMM, although it gives the BIC-optimal number of states as 4, in contrast to 6 for the homogeneous HMM. Finally, the quadratic and sinusoidal models are considerably better than any other models tested; they both give the BIC-optimal number of states as 5, and they have similar goodness of fit. However, this similarity is somewhat overstated due to the very large variation in BIC (over thousands of units) across the full range of models; there is a difference of approximately 80 BIC units, which would normally be interpreted as an enormous difference in goodness of fit, between the sinusoidal and quadratic models (both of which have 90 parameters).

Fig. ?? shows a clear diurnal pattern from the average hourly step lengths from the observed data. As expected, temporally homogeneous models (whether FMM or HMM) predict the same mean step length regardless of time of day, failing to capture the diurnal activity cycle. All of the models incorporating temporal heterogeneity, including the temporally heterogeneous FMM, can capture the observed patterns. However, the block model does markedly worse than the other temporal models (changing the block definitions might help), and the (overparameterized) hourly model does better than any other model at capturing the early-evening peak (but worse at capturing the mid-day trough). We also included average hourly step lengths from three-state temporally homogeneous HMM Viterbi prediction (v points).

Like the diurnal pattern shown in Fig. ??, the strong autocorrelation of the observed step lengths at a 24-hour lag (Fig. ??) shows the need to incorporate temporal heterogeneity in the model — we could have reached this conclusion even without developing any of the temporal-heterogeneity machinery. Because there are a huge number of potential complexities that can be added to movement models

(e.g. spatial/temporal/among-individual heterogeneity; effects of conspecific attraction or avoidance; memory or cognitive effects), each with associated costs in researcher and computational effort, such diagnostic plots are invaluable. In contrast to the hourly averages, the autocorrelation (ACF) captures both short- and long-term temporal effects. HMM without temporal heterogeneity captures the short-term autocorrelation, but misses the long-term autocorrelation beyond a 7-hour lag. Temporally homogeneous FMM, by definition, produces neither short- nor long-term autocorrelation. FMM without temporal heterogeneity, although it captures the diurnal pattern well, underpredicts the degree of short-term autocorrelation.

The hardest problem with multiple latent states is interpreting them biologically. We have no way of knowing what panthers are actually thinking (it is certainly more complex than being in one of a small number of discrete latent states); we don't know the "true" number of latent states, nor are we able to observe them directly, although incorporating additional direct observations of behaviour (if available) can at least partially address this problem [7]. Three distinct movement states seem biologically interpretable for Florida panthers according to van de Kerk et al.[14]: Short step length suggests resting states, intermediate step length a foraging state, and long step length a traveling state. Figure ?? compares the estimated parameter values for several cats (mean and standard deviation of the step length in each state) between the time-homogeneous and time-heterogeneous models. In general, the states with longer mean step lengths are relatively similar between model classes. For cats 14 and 15, the states with the longest or next-longest mean step lengths have similar means and standard deviations; for cats 1 and 2, three long-step states in the homogeneous HMM appear to divide two long-step states in the heterogeneous HMM. For short-step states, the heterogeneous HMM tends to identify a high-variance state, while the homogeneous HMM picks up states with very short step lengths (questionable in any case because we have not taken any special efforts to account for GPS error).

Competing interests

The authors declare that they have no competing interests.

Author's contributions

Text for this section ...

Acknowledgements

Text for this section ...

Author details

¹ Department of Biology, McMaster University, 1280 Main St. West, L8S 4K1, Hamilton, Ontario, Canada. ² Department of Mathematics and Statistics, McMaster University, 1280 Main St. West, L8S 4K1, Hamilton, Ontario, Canada.

References

1. Patterson, T.A., Thomas, L., Wilcox, C., Ovaskainen, O., Matthiopoulos, J.: State-space models of individual animal movement. *Trends in Ecology & Evolution* **23**(2), 87–94 (2008)
2. McKenzie, H.W., Lewis, M.A., Merrill, E.H.: First passage time analysis of animal movement and insights into the functional response. *Bulletin of Mathematical Biology* **71**(1), 107–129 (2009)
3. Pal, S., Ghosh, B., Roy, S.: Dispersal behaviour of free-ranging dogs (*Canis familiaris*) in relation to age, sex, season and dispersal distance. *Applied Animal Behaviour Science* **61**(2), 123–132 (1998)
4. Firle, S., Bommarco, R., Ekbo, B., Natiello, M.: The influence of movement and resting behavior on the range of three carabid beetles. *Ecology* **79**(6), 2113–2122 (1998). doi:10.1890/0012-9658(1998)079[2113:TIOMAR]2.0.CO;2. Accessed 2015-04-14

5. Nathan, R., Getz, W.M., Revilla, E., Holyoak, M., Kadmon, R., Saltz, D., Smouse, P.E.: A movement ecology paradigm for unifying organismal movement research. *Proceedings of the National Academy of Sciences* **105**(49), 19052–19059 (2008). doi:10.1073/pnas.0800375105. Accessed 2015-04-29
6. Langrock, R., King, R., Matthiopoulos, J., Thomas, L., Fortin, D., Morales, J.M.: Flexible and practical modeling of animal telemetry data: hidden Markov models and extensions. *Ecology* **93**(11), 2336–2342 (2012). doi:10.1890/11-2241.1. Accessed 2013-10-24
7. Fryxell, J.M., Hazell, M., Börger, L., Dalziel, B.D., Haydon, D.T., Morales, J.M., McIntosh, T., Rosatte, R.C.: Multiple movement modes by large herbivores at multiple spatiotemporal scales. *Proceedings of the National Academy of Sciences* **105**(49), 19114–19119 (2008). doi:10.1073/pnas.0801737105. Accessed 2013-04-09
8. Okubo, A.: *Diffusion and Ecological Problems: Mathematical Models* (1980)
9. Turchin, P.: *Quantitative Analysis of Movement: Measuring and Modeling Population Redistribution in Animals and Plants*. Sinauer Associates, Sunderland, MA, USA (1998)
10. Patterson, T.A., Basson, M., Bravington, M.V., Gunn, J.S.: Classifying movement behaviour in relation to environmental conditions using hidden Markov models. *Journal of Animal Ecology* **78**(6), 1113–1123 (2009)
11. Schliehe-Diecks, S., Kappeler, P.M., Langrock, R.: On the application of mixed hidden Markov models to multiple behavioural time series. *Interface Focus* **2**(2), 180–189 (2012). doi:10.1098/rsfs.2011.0077. Accessed 2014-05-02
12. Gurarie, E., Andrews, R.D., Laidre, K.L.: A novel method for identifying behavioural changes in animal movement data. *Ecology Letters* **12**(5), 395–408 (2009)
13. Tracey, J.A., Zhu, J., Boydston, E., Lyren, L., Fisher, R.N., Crooks, K.R.: Mapping behavioral landscapes for animal movement: a finite mixture modeling approach. *Ecological Applications* **23**(3), 654–669 (2012). doi:10.1890/12-0687.1. Accessed 2015-04-20
14. van de Kerk, M., Onorato, D.P., Criffield, M.A., Bolker, B.M., Augustine, B.C., McKinley, S.A., Oli, M.K.: Hidden semi-Markov models reveal multiphasic movement of the endangered Florida panther. *Journal of Animal Ecology* **84**(2), 576–585 (2015)
15. McKellar, A.E., Langrock, R., Walters, J.R., Kesler, D.C.: Using mixed hidden Markov models to examine behavioral states in a cooperatively breeding bird. *Behavioral Ecology*, 171 (2014). doi:10.1093/beheco/aru171. Accessed 2015-04-21
16. Dean, B., Freeman, R., Kirk, H., Leonard, K., Phillips, R.A., Perrins, C.M., Guilford, T.: Behavioural mapping of a pelagic seabird: combining multiple sensors and a hidden Markov model reveals the distribution of at-sea behaviour. *Journal of the Royal Society Interface*, 20120570 (2012)
17. Morales, J.M., Haydon, D.T., Frair, J., Holsinger, K.E., Fryxell, J.M.: Extracting more out of relocation data: building movement models as mixtures of random walks. *Ecology* **85**(9), 2436–2445 (2004)
18. Franke, A., Caelli, T., Kuzyk, G., Hudson, R.J.: Prediction of wolf (*Canis lupus*) kill-sites using hidden Markov models. *Ecological Modelling* **197**(1–2), 237–246 (2006). doi:10.1016/j.ecolmodel.2006.02.043. Accessed 2015-04-29
19. Dean, B., Freeman, R., Kirk, H., Leonard, K., Phillips, R.A., Perrins, C.M., Guilford, T.: Behavioural mapping of a pelagic seabird: combining multiple sensors and a hidden Markov model reveals the distribution of at-sea behaviour. *Journal of The Royal Society Interface* **10**(78), 20120570 (2013). doi:10.1098/rsif.2012.0570. Accessed 2016-06-07
20. Richards, S.A.: Testing ecological theory using the information-theoretic approach: examples and cautionary results. *Ecology* **86**(10), 2805–2814 (2005)
21. Burnham, K.P., Anderson, D.R.: *Model Selection and Inference: A Practical Information-Theoretic Approach*. Springer, New York (1998)
22. Zucchini, W., MacDonald, I.L.: *Hidden Markov Models for Time Series: An Introduction Using R*. CRC Press, ??? (2009)
23. Visser, I., Speekenbrink, M.: depmixS4: An R package for hidden Markov models. *Journal of Statistical Software* **36**(7), 1–21 (2010)
24. R Core Team: *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing, Vienna, Austria (2015). R Foundation for Statistical Computing. <https://www.R-project.org/>

Figures

Figure 1 Sample figure title. A short description of the figure content should go here.

Figure 2 Sample figure title. Figure legend text.

Tables

Table 1 Sample table title. This is where the description of the table should go.

	B1	B2	B3
A1	0.1	0.2	0.3
A2
A3

Additional Files

Additional file 1 — Sample additional file title

Additional file descriptions text (including details of how to view the file, if it is in a non-standard format or the file extension). This might refer to a multi-page table or a figure.

Additional file 2 — Sample additional file title

Additional file descriptions text.