

Title

biggertab — Displays cross-tabs of variables and allows more than 3 variables

Syntax

biggertab *varList* [*if*] [*in*] [, *options*]

| <i>options</i> | Description |
|----------------------------------|--|
| <hr/> | |
| Options | |
| stats (<i>string</i>) | select which statistics to be displayed |
| sepby (<i>varList2</i>) | draw a separator line whenever <i>varList2</i> values change |
| title (<i>string</i>) | specifies an optional custom title |
| divider | draw divider lines between columns |
| noLabel | display numeric codes rather than label values |
| zero | include combinations with frequency zero |
| nomiss | drop observations with missing values |

Description

biggertab displays cross-tabs of variables with frequencies and percentages. Biggertab can display more than 3 variables, but with many variables users may need to use the option **noLabel** to avoid line overflow.

Options

| |
|---------|
| Options |
|---------|

stats(*string*) allows users to choose from the following statistics:

| | |
|----------------|--|
| freq | frequency |
| pct | percent |
| cumfreq | cumulative frequency |
| cumpct | cumulative percent |
| rowfreq | row frequency (within the sepby <i>varList</i>) |
| rowpct | row percent (within the sepby <i>varList</i>) |
| none | displays no statistics |

sepby(*varList2*) draws a separator line whenever *varList2* values change. The default behavior is to draw a separator every 9,999 lines.

title(*string*) specifies an optional custom title. The default behavior is to display no title.

divider draws divider lines between each column.

noLabel specifies that the numeric codes be displayed rather than label values.

zero specifies that combinations with frequency zero be included.

nomiss specifies that observations with missing values on any variable in *varList* be dropped. If **nomiss** is not specified, all observations possible are used.