

Title

biggertab — Displays cross-tabs of variables and allows more than 3 variables

Syntax

biggertab *varList* [*if*] [*in*] [, *options*]

<i>options</i>	Description
<hr/>	
Options	
stats (<i>string</i>)	select which statistics to be displayed
sepby (<i>varList2</i>)	draw a separator line whenever <i>varList2</i> values change
title (<i>string</i>)	specifies an optional custom title
divider	draw divider lines between columns
noLabel	display numeric codes rather than label values
zero	include combinations with frequency zero
nomiss	drop observations with missing values

Description

biggertab displays cross-tabs of variables with frequencies and percentages. Biggertab can display more than 3 variables, but with many variables users may need to use the option **noLabel** to avoid line overflow.

Options

Options

stats(*string*) allows users to choose from the following statistics:

freq	frequency
pct	percent
cumfreq	cumulative frequency
cumpct	cumulative percent
rowfreq	row frequency (within the sepby <i>varList</i>)
rowpct	row percent (within the sepby <i>varList</i>)

sepby(*varList2*) draws a separator line whenever *varList2* values change. The default behavior is to draw a separator every 9,999 lines.

title(*string*) specifies an optional custom title. The default behavior is to display no title.

divider draws divider lines between each column.

noLabel specifies that the numeric codes be displayed rather than label values.

zero specifies that combinations with frequency zero be included.

nomiss specifies that observations with missing values on any variable in *varList* be dropped. If **nomiss** is not specified, all observations possible are used.