

Title

bradmean — Computes multiple independent means in a single table

Syntax

bradmean [*varlist*] [*if*] [*in*] [, *options*]

<i>options</i>	Description
Weight	
svy	statistics will be survey weighted
subpop (<i>varname</i>)	subpopulation estimation by <i>varname</i> ; <i>varname</i> must be 0/1
Over	
over (<i>varlist</i>)	estimation over groups defined by <i>varlist</i>
overopt (<i>string</i>)	options for over variables
test (<i>string</i>)	options for significance testing
Output	
display (<i>string</i>)	general display options
title (<i>string</i>)	optional custom title or "none" to display no title
sort (<i>string</i>)	sorting results within a series
stats (<i>string</i>)	select which statistics to be displayed
format (<i>string</i>)	formatting options for displayed statistics
excel (<i>string</i>)	Excel output options

weights are allowed; see [svyset](#).

Description

bradmean computes multiple independent means of *varlist*. Estimations can be run by groups and

Options

_____ Weight _____	
svy specifies that statistics will be survey weighted.	
subpop (<i>varname</i>) specifies that estimates be computed using subpopulation <i>varname</i> . <i>varname</i> must	
_____ Over _____	
over (<i>varlist</i>) specifies that estimates be computed for multiple groups, which are identified b	
overopt (<i>string</i>) has the following options:	
nolabels	do not display over labels
nolegend	do not display legend for over groups
nomiss	do not display groups with no non-missing values
total	display overall statistics
group	display each group size below name (wide only)
test (<i>string</i>) has the following options:	
chi2	display Chi2 p-values for categorical variables. When data is svyset , a
ttest (<i>string</i>)	display t-test p-values for overall comparisons (only applies when there
ftest (<i>string</i>)	display adjusted Wald F-test p-values for overall comparisons, individua
	multiple comparisons using bonferroni , holm , or sidak
stars (<i>numlist</i>)	creates up to 3 significance stars for overall p-values less than <i>numlis</i>
scripts (<i>numlist</i>)	creates up to 18 significance scripts for individual p-values less than
stat	display test statistics with p-values
force	display p-values even with stars or scripts enabled
nofooter	do not display footer explaining significance stars and scripts

display(string) has the following options:

xi	enable both xi value and xi variable labels
xivals	enable xi value labels (default is ON)
xivars	enable xi variable labels (default is ON)
series	enable both series value and series variable labels
seriesvals	enable series value labels (default is OFF)
seriesvars	enable series variable labels (default is OFF)
wide	print table in a wide format
align(string)	choose left , center , or right alignment of statistics
nostat	do not display statistic names (wide only & single statistic only)
noprint	do not display table (can be used with Excel output)

title(string) specifies an optional custom title or "**none**" to display no title.

sort(string) allows sorting within series by choosing direction (+ for ascending, - for descending)

stats(string) allows users to choose from the following statistics:

obs	observations
nyes	number of "yes" answers (only for binary variables)
mean	mean
se	standard error
sd	standard deviation
var	variance
ci	confidence interval
min	minimum
max	maximum
all	all of the above

format(string) sets the formatting for statistics. Individual statistics can be formatted using (se/sd/var), or minmax (min/max). The following options are allowed:

round(#)	round for both binary and continuous variables. Default is 7
roundi(#)	round for binary variables. Default is 7
roundc(#)	round for continuous variables. Default is 7
pct	format binary variables as a percentage
percent	format binary variables as a percentage
nosymbol	do not display % after percentage
notation(string)	choose to surround statistic with parentheses or brackets
stars	display significance stars on this statistic. Default is mean
scripts	display significance scripts on this statistic. Default is ci
lvl(#)	(ci only) choose level for confidence interval
level(#)	(ci only) choose level for confidence interval
proportion	(ci only) logit transform the confidence interval (similar to <u>proportion</u>)
combined	(ci only) put lower CI and upper CI in 1 column
separator(string)	(ci only) use "-" or "," to separate a combined CI
nocomma	(count only) do not display thousands separators

excel(string) has the following options:

file(string)	location of output file. Default is a file named bradmean_output.xlsx in the
sheet(string)	name of sheet to be used. Default is the first file in the sheet or Sheet1
replace	replace the workbook
sheetreplace	replace the sheet
modify	append table to the end of the sheet
font(string)	choose the font face from Arial , Calibri , Garamond , Helvetica , TNR (Times N
size(#)	choose the font size between 9 and 12. Default is 11
color(string)	choose the color styles from bradmean , monochrome , rti , material_red , mater