Ruby Test Suite@ButterflyMX

Zoran.Majstorovic@ButterflyMX.com Senior Ruby Developer




The First Principle of the Agile Manifesto

Our highest priority is to satisfy the customer

through early and continuous delivery


of valuable software.

Traditional Waterfall vs. Continuous Integration



Continuous Integration @ButterflyMX






Continuous Integration & Deployment CI Server



Continuous Integration & Deployment






Continuous Code Quality Check



Continuous Code Quality Check








Behaviour Driven Development for Ruby



(example | expectation | spec) expresses desired behaviour





```
# in spec/calculator_spec.rb
RSpec.describe Calculator do
   describe '#add' do
    it 'returns the sum of its arguments' do
        expect(Calculator.new.add(1, 2)).to eq(3)
    end
   end
end
```



RSpec Nested Structures (describe/context)

```
RSpec.describe Order do
  context "with no items" do
    it "behaves one way" do
    end
  end
  context "with one item" do
    it "behaves another way" do
    end
  end
end
```



- **rspec-core:** the spec runner, a command line program
- **rspec-expectations:** express expected outcomes of a code example
- rspec-mocks: test double framework
 (fake objects to to control the environment in which specs run)
- rspec-rails: support for testing Ruby on Rails applications

Capybara



Acceptance test framework for web applications simulates how a user interacts with your application

Capybara Acceptance Tests (features)

```
feature "Signing in" do
  background do
    User.make(email: 'user@example.com', password: 'caplin')
  end
  scenario "Signing in with correct credentials" do
    visit '/sessions/new'
   within("#session") do
      fill_in 'Email', with: 'user@example.com'
      fill in 'Password', with: 'caplin'
    end
    click_button 'Sign in'
    expect(page).to have_content 'Success'
  end
end
```



Capybara with RSpec

```
describe "the signin process", :type => :feature do
  before :each do
    User.make(email: 'user@example.com', password: 'password')
  end
  it "signs me in" do
    visit '/sessions/new'
   within("#session") do
      fill_in 'Email', with: 'user@example.com'
      fill_in 'Password', with: 'password'
    end
    click_button 'Sign in'
    expect(page).to have_content 'Success'
  end
end
```



Capybara Navigating and Clicking

- visit('/projects')
- click_link('id-of-link')
- click_link('Link Text')
- click_button('Save')
- click_on('Link Text') # clicks on either links or buttons
- click_on('Button Value')



Capybara Interacting with Forms

- **fill_in**('First Name', with: 'John')
- **fill_in**('Password', with: 'Seekrit')
- fill_in('Description', with: 'Really Long Text...')
- choose('A Radio Button')
- check('A Checkbox')
- uncheck('A Checkbox')
- attach_file('Image', '/path/to/image.jpg')
- select('Option', from: 'Select Box')



Capybara Matchers

querying the page for the existence of certain elements

- page.has_selector?('table tr')
- page.has_selector?(:xpath, './/table/tr')
- page.has_xpath?('.//table/tr')
- page.has_css?('table tr.foo')
- page.has_content?('foo')



Capybara with RSpec's matchers

- expect(page).to have_selector('table tr')
- expect(page).to have_selector(:xpath, './/table/tr')
- expect(page).to have_xpath('.//table/tr')
- expect(page).to have_css('table tr.foo')
- expect(page).to have_content('foo')



Capybara Finders and Actions

- find_field('First Name').value
- find_field(id: 'my_field').value
- find_link('Hello').visible?

- find_button('Send').click
- find_button(value: '1234').click



SimpleCov

code coverage analysis tool

app/controllers/app/sessions_controller.rb

86.67 % covered


15 relevant lines. 13 lines covered and 2 lines missed.

```
class App::SessionsController < App::ApplicationController</pre>
 2.
       skip_after_action :verify_authorized
       skip_before_filter :authenticate_user!
 3.
 5.
       # GET /sessions/new
       def new
         redirect_to current_user_index if current_user.present?
 7.
 8.
         @session = User.new
9.
       end
10.
11.
       # POST /sessions
12.
       def create
13.
         @session = User.new params_user
         login! params_user[:email], params_user[:password]
14.
15.
       end
16.
17.
       def logout
18.
         session[:current_user_id] = nil
19.
         redirect_to new_session_path
20.
       end
21.
22.
       private
23.
24.
       def params_user
25.
         params.require(:user).permit(:email, :password)
26.
       end
     end
```

TEST WITH US



info@6lix.com



TEST WITH US



info@6lix.com

Responsibilities

- Test web, mobile and desktop (windows)
- Design test protocols
- Liaison with developers
- Automate tests

Thank You

