

1 Lecture 2: Data processing in Pandas library

Data Visualization · 1-DAV-105

Lecture by Broňa Brejová

1.1 Tabular data

- We will often work with data in the form of tables.
- Columns represent different features / variables (príznamy, atribúty, veličiny, premenné).
- Rows represent different items / data points / observations (countries, people, dates of measurement,...).
- A small example:

Country	Region	Population	Area (km2)	Landlocked
Slovakia	Europe	5450421	49035	yes
Czech Republic	Europe	10649800	78866	yes
Hungary	Europe	9772756	93030	yes
Poland	Europe	38386000	312696	no

1.2 Pandas library

- <https://pandas.pydata.org/>, [documentation](#), [overview](#), [tutorial](#)
- Pandas is a Python library for data manipulation and analysis.
- It is fast and has many functions for data import and export in various formats

Basic data structures

- **Series**: 1D table, all elements of the same type.
- **DataFrame**: 2D table, elements within each column of the same type.

NumPy library

- <https://numpy.org/>, [tutorial](#), [reference](#)
- NumPy is a library of efficient multi-dimensional arrays used for numerical computations.
- We will mostly use Pandas, but some NumPy functions will be useful.

```
[1]: import numpy as np
import pandas as pd
from IPython.display import Markdown
```

1.2.1 Creating Series and DataFrame

```
[2]: countries = pd.Series(['Slovakia', 'Czech Republic', 'Hungary', 'Poland'])
regions = pd.Series(['Europe', 'Europe', 'Europe', 'Europe'])
populations = pd.Series([5450421, 10649800, 9772756, 38386000])
areas = pd.Series([49035, 78866, 93030, 312696])
landlocked = pd.Series([True, True, True, False])
table = pd.DataFrame({'country':countries,
                      'region':regions,
```

```

        'population':populations,
        'area':areas,
        'landlocked':landlocked})
# display: special notebook command for pretty-printing data
display(table)

```

	country	region	population	area	landlocked
0	Slovakia	Europe	5450421	49035	True
1	Czech Republic	Europe	10649800	78866	True
2	Hungary	Europe	9772756	93030	True
3	Poland	Europe	38386000	312696	False

1.2.2 Accessing elements of Series and DataFrame by position

- Attribute `ndim` is the number of dimensions. E.g. `areas.ndim` is 1, `table.ndim` is 2.
- Attribute `shape` is a tuple holding the size in each dimension. E.g. `areas.shape` is (4,), `table.shape` is (4,5).
- Rows and columns are numbered 0, 1, ...
- To access a particular column / row, use `some_series.iloc[row]` or `some_table.iloc[row, column]`.
- Rows and columns can be
 - a single number e.g. 0,
 - a slice (range) e.g. 0:2 or : for everything,
 - a list of positions e.g. [0, 2, 3]
 - a list of boolean values [True, False, True, True].
- The result is a single element or a Series / DataFrame of a smaller size.

```

[3]: display(Markdown("**Table:**"), table)
display(Markdown("**table.iloc[1, 2]**"), table.iloc[1, 2])
display(Markdown("**table.iloc[[0, 2, 3], 0:2]**"), table.iloc[[0, 2, 3], 0:2])
display(Markdown("**table.iloc[[True, False, True, True], :]**"),
        table.iloc[[True, False, True, True], :])

```

Table:

	country	region	population	area	landlocked
0	Slovakia	Europe	5450421	49035	True
1	Czech Republic	Europe	10649800	78866	True
2	Hungary	Europe	9772756	93030	True
3	Poland	Europe	38386000	312696	False

`table.iloc[1, 2]:`

10649800

`table.iloc[[0, 2, 3], 0:2]`

	country	region
0	Slovakia	Europe
2	Hungary	Europe
3	Poland	Europe

```
table.iloc[[True, False, True, True], :]
```

	country	region	population	area	landlocked
0	Slovakia	Europe	5450421	49035	True
2	Hungary	Europe	9772756	93030	True
3	Poland	Europe	38386000	312696	False

1.2.3 Views vs. copies

- Accessing parts of tables by `iloc` may return a partial copy or simply a ‘view’.
- If we later modify this result, it is not clear if the original table is modified.
- Direct assignment of new values to part of the table works: `some_table.iloc[row, column] = new_value` modifies `some_table`.
- To copy a table, use `other_table = some_table.copy(deep=True)`.

```
[4]: table2 = table.copy(deep=True)
# create a copy of the original table

table2.iloc[0,0] = 'Slovensko'
display(table2)
# table2 now has Slovensko instead of Slovakia

countries2 = table2.iloc[:, 0]
countries2.iloc[2] = 'Maďarsko'
display(table2)
# table2 now can have Hungary or Maďarsko
# we get a warning
```

	country	region	population	area	landlocked
0	Slovensko	Europe	5450421	49035	True
1	Czech Republic	Europe	10649800	78866	True
2	Hungary	Europe	9772756	93030	True
3	Poland	Europe	38386000	312696	False

```
/tmp/ipykernel_982246/1022731433.py:9: SettingWithCopyWarning:
A value is trying to be set on a copy of a slice from a DataFrame
```

See the caveats in the documentation: https://pandas.pydata.org/pandas-docs/stable/user_guide/indexing.html#returning-a-view-versus-a-copy

```
countries2.iloc[2] = 'Maďarsko'
```

	country	region	population	area	landlocked
0	Slovensko	Europe	5450421	49035	True
1	Czech Republic	Europe	10649800	78866	True
2	Maďarsko	Europe	9772756	93030	True
3	Poland	Europe	38386000	312696	False

1.2.4 Inplace operations

- Many operations return a new table.

- If you do not need the original table, you can specify option `inplace=True`.
- The example below sorts a table by a specified column, returning a new table or replacing the old one.

```
[5]: # copy original table to table2
table2 = table.copy(deep=True)

# table3 is a copy of table2 sorted by population size
table3 = table2.sort_values(by="population")

# display both table2 and table3
display(Markdown("**Original table2:**"), table2)
display(Markdown("**Sorted table3:**"), table3)

# now change table2 to be sorted by name of the country
table2.sort_values(by="country", inplace=True)
display(Markdown("**Sorted table2:**"), table2)
```

Original table2:

	country	region	population	area	landlocked
0	Slovakia	Europe	5450421	49035	True
1	Czech Republic	Europe	10649800	78866	True
2	Hungary	Europe	9772756	93030	True
3	Poland	Europe	38386000	312696	False

Sorted table3:

	country	region	population	area	landlocked
0	Slovakia	Europe	5450421	49035	True
2	Hungary	Europe	9772756	93030	True
1	Czech Republic	Europe	10649800	78866	True
3	Poland	Europe	38386000	312696	False

Sorted table2:

	country	region	population	area	landlocked
1	Czech Republic	Europe	10649800	78866	True
2	Hungary	Europe	9772756	93030	True
3	Poland	Europe	38386000	312696	False
0	Slovakia	Europe	5450421	49035	True

1.2.5 Indexes

- Rows and columns have both an integer location (0,1,2,...) and an index (name).
- In our table, column names are 'country', 'region' etc.
- We have not named rows, so a default location-based index was constructed.
 - See the sorted tables above—their index labels are kept from the original.
- Indexes can be obtained by attributes `index` and `columns`.
- We can set the country name as an index using `set_index`, the opposite is `reset_index` (in Series, use `set_axis` and `reset_index`).

- Index can be more complex (multiindex), we will see later.

```
[6]: display(Markdown("**`table.columns` is an object of class `Index`:**"), table.
      ↪columns)
display(Markdown("**`table.columns.values` is an array of column names:**"),
      table.columns.values)

display(Markdown("**`table.index.values` is an array of row names, here equal_
      ↪to location:**"),
      table.index.values)
display(Markdown("**`index` for Series `areas`:**"), areas.index.values)

display(Markdown("**`table` after setting country name as index:**"))
table2 = table.set_index('country')
display(table2)

display(Markdown("**`reset_index` will put the index back as a column:**"))
table3 = table2.reset_index()
display(table3)
```

`table.columns` is an object of class `Index`:

```
Index(['country', 'region', 'population', 'area', 'landlocked'], dtype='object')
```

`table.columns.values` is an array of column names:

```
array(['country', 'region', 'population', 'area', 'landlocked'],
      dtype=object)
```

`table.index.values` is an array of row names, here equal to location:

```
array([0, 1, 2, 3])
```

index for Series `areas`:

```
array([0, 1, 2, 3])
```

table after setting country name as index:

	region	population	area	landlocked
country				
Slovakia	Europe	5450421	49035	True
Czech Republic	Europe	10649800	78866	True
Hungary	Europe	9772756	93030	True
Poland	Europe	38386000	312696	False

`reset_index` will put the index back as a column:

	country	region	population	area	landlocked
0	Slovakia	Europe	5450421	49035	True
1	Czech Republic	Europe	10649800	78866	True
2	Hungary	Europe	9772756	93030	True
3	Poland	Europe	38386000	312696	False

1.2.6 Accessing elements by index

- Method `some_table.loc[row, column]` is an analog of `iloc`, but using indexes rather than locations.
- You can also use `[]`, and pandas will try to guess whether it is an index or location.
- Some examples for Series:

```
[7]: populations2 = populations.set_axis(countries)
display(Markdown("**`populations2` series with index:**"), populations2)
display(Markdown("**`populations2.loc['Slovakia']`**:"), populations2.
        ↪loc['Slovakia'])
display(Markdown("**`populations2.loc[['Slovakia','Poland']]`**:"),
        ↪populations2.loc[['Slovakia','Poland']])

display(Markdown("**`populations2[1]` and `populations2['Czech Republic']`**:"))
display(populations2[1], populations2['Czech Republic'])
```

populations2 series with index:

```
Slovakia      5450421
Czech Republic 10649800
Hungary       9772756
Poland        38386000
dtype: int64
```

populations2.loc['Slovakia']:

```
5450421
```

populations2.loc[['Slovakia','Poland']]:

```
Slovakia      5450421
Poland        38386000
dtype: int64
```

populations2[1] and populations2['Czech Republic']:

```
10649800
10649800
```

1.2.7 Operations and functions on Series

- Operations such as `+`, `*` can be applied on two Series, causing them to be used on each corresponding pair of elements.
- For example, `populations/areas` will compute population density for each country.
- You can also use a single number (scalar) as an operand, e.g. `populations/1e6` will get population in millions.
- NumPy also contains functions that can be applied to each element of a series, e.g. `np.log(populations)`.
- Relational operators such as `populations < 10e6` produce Series of boolean values.
 - Those can be then used in `[]` or `loc`.

```
[8]: # creating two Series with country as index
populations2 = populations.set_axis(countries)
areas2 = areas.set_axis(countries)
display(Markdown("**`populations2 / areas2`:**"), populations2 / areas2)
display(Markdown("**`populations2 / 1e6`:**"), populations2 / 1e6)
display(Markdown("**`populations2 > 10e6`:**"), populations2 > 10e6)
display(Markdown("**`areas2[populations2 > 10e6]`:**"), areas2.loc[populations2_
↳ 10e6])
display(Markdown("**`np.log10(populations2)`:**"), np.log10(populations2))
```

populations2 / areas2:

Slovakia	111.153686
Czech Republic	135.036644
Hungary	105.049511
Poland	122.758206

dtype: float64

populations2 / 1e6:

Slovakia	5.450421
Czech Republic	10.649800
Hungary	9.772756
Poland	38.386000

dtype: float64

populations2 > 10e6:

Slovakia	False
Czech Republic	True
Hungary	False
Poland	True

dtype: bool

areas2[populations2 > 10e6]:

Czech Republic	78866
Poland	312696

dtype: int64

np.log10(populations2):

Slovakia	6.736430
Czech Republic	7.027341
Hungary	6.990017
Poland	7.584173

dtype: float64

Beware: when we combine two Series, e.g. by +, Pandas will use index, not position.

```
[9]: a = pd.Series([1, 2, 3, 4], index=['a', 'b', 'c', 'd'])
b = pd.Series([10, 20, 30], index=['c', 'a', 'e'])
```

```

c = pd.Series([100, 200])
display(Markdown("**Series a:**"), a)
display(Markdown("**Series b:**"), b)
display(Markdown("**Series c:**"), c)
display(Markdown("**Series a+b:**"), a + b)
display(Markdown("**Series a+c:**"), a + c)

```

Series a:

```

a    1
b    2
c    3
d    4
dtype: int64

```

Series b:

```

c    10
a    20
e    30
dtype: int64

```

Series c:

```

0    100
1    200
dtype: int64

```

Series a+b:

```

a    21.0
b     NaN
c    13.0
d     NaN
e     NaN
dtype: float64

```

Series a+c:

```

a    NaN
b    NaN
c    NaN
d    NaN
0    NaN
1    NaN
dtype: float64

```

1.2.8 Working with DataFrame columns

- `DataFrame` is similar to a dictionary of `Series` objects (columns).
- For example, `table['area']` or `table.area` is the **column** of country areas.
- Columns can be added `table['density'] = table['population'] / table['area']`

- But `table[0:2]` are the first 2 **rows** of the table.
 - To be save, use `loc[]` / `iloc[]` rather than just `[]`.
- By `table[table['population'] > 1e7]` we get countries with more that 10 million people (CZ, PL).

```
[10]: display(Markdown("**`table['area']`:**"), table['area'])
display(Markdown("**`table.area`:**"), table.area)
display(Markdown("**Adding density:**"))
display(Markdown("`table['density'] = table['population'] / table['area']`"))
table['density'] = table['population'] / table['area']
display(Markdown("**`table[0:2]`:**"), table[0:2])
display(Markdown("**`table[table['population'] > 1e7]`:**"),
↪table[table['population'] > 1e7])
```

`table['area']:`

```
0    49035
1    78866
2    93030
3   312696
```

Name: area, dtype: int64

`table.area:`

```
0    49035
1    78866
2    93030
3   312696
```

Name: area, dtype: int64

Adding density:

```
table['density'] = table['population'] / table['area']
```

`table[0:2]:`

	country	region	population	area	landlocked	density
0	Slovakia	Europe	5450421	49035	True	111.153686
1	Czech Republic	Europe	10649800	78866	True	135.036644

`table[table['population'] > 1e7]:`

	country	region	population	area	landlocked	density
1	Czech Republic	Europe	10649800	78866	True	135.036644
3	Poland	Europe	38386000	312696	False	122.758206

1.2.9 Query

- Method `query` is very useful for selecting `DataFrame` rows satisfying some properties.
- In examples below, `@` substitutes variable value.
- While `loc[]` and `iloc[]` raise an exception if the requested value is not found, `query` can return an empty table.

```
[11]: display(Markdown("**`table.query(\"country=='Slovakia'\")`:**"),
            table.query("country=='Slovakia'"))

def get_country(table, country):
    """Get a given country from the table"""
    return table.query("country == @country")
display(Markdown("**The same but for Hungary and using a function:**"),
        get_country(table, 'Hungary'))

display(Markdown("**Query with an empty result:**"))
display(Markdown("`table.query(\"population < 10e6 and not landlocked\")`:"))
display(table.query("population < 10e6 and not landlocked"))
```

```
table.query("country=='Slovakia'"):
```

	country	region	population	area	landlocked	density
0	Slovakia	Europe	5450421	49035	True	111.153686

The same but for Hungary and using a function:

	country	region	population	area	landlocked	density
2	Hungary	Europe	9772756	93030	True	105.049511

Query with an empty result:

```
table.query("population < 10e6 and not landlocked"):
```

Empty DataFrame

Columns: [country, region, population, area, landlocked, density]

Index: []

1.2.10 Importing and exporting data

- Import and export is possible using many [file formats](#) (text-based CSV, JSON, HTML; binary Excel, HDF5 etc.).
- We will mostly use CSV (=comma separated values) format.
 - Each row is one line of the file.
 - Columns are separated by commas.
 - Columns containing commas or end-of-line characters may be enclosed in quotation marks.
 - Sometimes a different column separator is used, e.g. tab "\t".
- Writing our table to a csv file: `table.to_csv("countries.csv")`.
 - If run in Colab, this will create a temporary file, which you can save on your computer (see the right panel, tab Files).
- Conversely, `table2 = pd.read_csv("countries.csv", index_col=0)` will read data from the file to a new DataFrame called `table2`.
- Input and output functions allow you to set many optional arguments to tweak the format.

1.3 Example: a table of country populations from the United Nations

- Obtained from the UN webpage <https://data.un.org/>

- We will read the table in CSV format directly from a URL.
- We need to play a bit with settings:
 - We skip the top two lines.
 - We supply our own (simpler) column names.
 - We specify character encoding (default is UTF8) and that thousands are separated by a comma in numerical values, such as 1,000,000.
 - Note that empty fields (missing values) are imported as `np.NaN`.

```
[12]: # original source:
# url = 'https://data.un.org/_Docs/SYB/CSV/
#       ↪SYB65_1_202209_Population,%20Surface%20Area%20and%20Density.csv'
# our local copy:
url = 'https://bbrejova.github.io/viz/data/Un_population.csv'
column_names = ['Region ID', 'Region', 'Year',
                'Series', 'Value', 'Footnotes', 'Source']
un_table = pd.read_csv(url, encoding='latin-1', names=column_names, skiprows=2,
#       ↪thousands=",")
# print the first 5 rows to check the result
un_table.head()
```

```
[12]:
```

	Region ID	Region	Year	\
0	1	Total, all countries or areas	2010	
1	1	Total, all countries or areas	2010	
2	1	Total, all countries or areas	2010	
3	1	Total, all countries or areas	2010	
4	1	Total, all countries or areas	2010	

		Series	Value	Footnotes	\
0		Population mid-year estimates (millions)	6985.60	NaN	
1		Population mid-year estimates for males (milli...	3514.41	NaN	
2		Population mid-year estimates for females (mil...	3471.20	NaN	
3		Sex ratio (males per 100 females)	101.20	NaN	
4		Population aged 0 to 14 years old (percentage)	27.10	NaN	

		Source
0		United Nations Population Division, New York, ...
1		United Nations Population Division, New York, ...
2		United Nations Population Division, New York, ...
3		United Nations Population Division, New York, ...
4		United Nations Population Division, New York, ...

```
[13]: # print the last 5 rows, to see if the bottom looks ok
un_table.tail()
```

```
[13]:
```

	Region ID	Region	Year	\
7868	716	Zimbabwe	2022	
7869	716	Zimbabwe	2022	

```

7870      716  Zimbabwe  2022
7871      716  Zimbabwe  2022
7872      716  Zimbabwe  2022

```

```

                                Series  Value  \
7868  Population mid-year estimates for females (mil...  8.61
7869                                Sex ratio (males per 100 females)  89.40
7870      Population aged 0 to 14 years old (percentage)  40.60
7871      Population aged 60+ years old (percentage)    4.80
7872                                Population density  42.20

```

```

                                Footnotes  \
7868  Projected estimate (medium fertility variant).
7869  Projected estimate (medium fertility variant).
7870  Projected estimate (medium fertility variant).
7871  Projected estimate (medium fertility variant).
7872  Projected estimate (medium fertility variant).

```

```

                                Source
7868  United Nations Population Division, New York, ...
7869  United Nations Population Division, New York, ...
7870  United Nations Population Division, New York, ...
7871  United Nations Population Division, New York, ...
7872  United Nations Population Division, New York, ...

```

```
[14]: # check types of columns; strings are imported as object, which is expected
un_table.dtypes
```

```
[14]: Region ID      int64
      Region      object
      Year        int64
      Series      object
      Value       float64
      Footnotes   object
      Source      object
      dtype: object
```

- Each country has data for several years.
- There are several values per country and year, e.g. total population, the number of men and women, sizes of three age groups.
- The first part of the table contains various continents and regions, later individual countries arranged alphabetically from 'Afghanistan' to 'Zimbabwe'.

1.3.1 A simple table with total population across years

We will create a simpler table `country_pop`.

- It will contain only countries, not regions.

- It will contain only rows with total population, all available years.
- It will contain columns Country (originally Region) ,Year, and Population (originally Value).

```
[24]: # get all rows for Afghanistan, choose the label for the first of them
first_country = un_table.query('Region == "Afghanistan").index[0]
# get all rows from the first Afghanistan onwards and all columns
un_countries = un_table.iloc[first_country:, :]
# get only rows with total population and select only some columns using loc
country_pop = (un_countries
               .query('Series=="Population mid-year estimates (millions)"')
               .loc[:, ['Region', 'Year', 'Value']]
               .rename(columns={'Value': 'Population', 'Region': 'Country'}))
# print the start of the result
country_pop.head()
```

```
[24]:      Country  Year  Population
930  Afghanistan  2010      28.19
937  Afghanistan  2015      33.75
945  Afghanistan  2020      38.97
953  Afghanistan  2022      41.13
960    Albania  2010       2.91
```

1.4 Tidy data, wide and long tables

- The original UN table has in column Value various values, including population size, sex ratio, population density, etc.
- In general, one column of a table should contain values of the same type.
- This is true in our country_pop table with columns Country,Year, and Population.
- This type of table is called **long** and is usually preferable.
- For some analysis, we may want to have countries as rows and years as columns; this is called a **wide table**.
- Pandas has methods to convert between the two formats, e.g. `wide_to_long`, `melt`, `pivot`, `unstack` etc.
- See the article [Tidy data](#) by Hadley Wickham for a longer discussion.

1.5 Back to example: comparing populations in 2010 and 2022

- We select only two years from country_pop.
- Function `pivot` will use the column Country as the row index, values from column Year as new column names and values from column Population as values to populate the table itself.
- Finally we rename the columns so that they are strings starting with a letter; otherwise they are harder to be used in query.

```
[26]: display(Markdown("**Original `country_pop` table:**"), country_pop.head())

pop = (country_pop.query("Year==2010 or Year==2022")
      .pivot(index='Country', columns=['Year'], values='Population')
      .rename(columns={2010:'pop2010', 2022:'pop2022'}))

display(Markdown("**New `pop` table:**"), pop.head())
```

Original country_pop table:

	Country	Year	Population
930	Afghanistan	2010	28.19
937	Afghanistan	2015	33.75
945	Afghanistan	2020	38.97
953	Afghanistan	2022	41.13
960	Albania	2010	2.91

New pop table:

Year	pop2010	pop2022
Country		
Afghanistan	28.19	41.13
Albania	2.91	2.84
Algeria	35.86	44.90
American Samoa	0.05	0.04
Andorra	0.07	0.08

```
[17]: # compute the difference between years for each country (positive = increase)
pop['difference'] = pop['pop2022'] - pop['pop2010']
# relative difference, percentual increase compared to 2010
pop['relDifference'] = pop['difference'] / pop['pop2010']
pop.head()
```

```
[17]: Year          pop2010  pop2022  difference  relDifference
Country
Afghanistan      28.19     41.13         12.94         0.459028
Albania           2.91      2.84          -0.07        -0.024055
Algeria          35.86     44.90          9.04         0.252091
American Samoa    0.05      0.04          -0.01        -0.200000
Andorra           0.07      0.08           0.01         0.142857
```

Now we will use this table to create some plots and tables.

- What can you observe from these data displays?
- Are some of these visualizations more useful than others or are they complementary? How could we improve them?
- What other questions you could ask about this table and how would you answer them using plots or tables?

```
[18]: import matplotlib.pyplot as plt
figure, axes = plt.subplots()
axes.plot(pop.pop2010, pop.pop2022, '.')
axes.set_aspect('equal')
axes.set_xlabel('Population in 2010')
axes.set_ylabel('Population in 2022')
pass
```

```
[19]: figure, axes = plt.subplots()
axes.plot(pop.pop2010, pop.difference, '.')
axes.set_xlabel('Population in 2010')
axes.set_ylabel('Change from 2010 to 2022')
pass
```

```
[20]: figure, axes = plt.subplots()
axes.plot(pop.pop2010, pop.relDifference, '.')
axes.set_xlabel('Population in 2010')
axes.set_ylabel('Rel. change from 2010 to 2022')
pass
```

```
[21]: pop.sort_values('relDifference').head(10)
```

```
[21]: Year
Country
Saint Martin (French part)    0.04    0.03    -0.01    -0.250000
American Samoa                0.05    0.04    -0.01    -0.200000
Marshall Islands              0.05    0.04    -0.01    -0.200000
Bosnia and Herzegovina        3.81    3.23    -0.58    -0.152231
Ukraine                       45.68   39.70    -5.98    -0.130911
Puerto Rico                   3.72    3.25    -0.47    -0.126344
Lithuania                     3.14    2.75    -0.39    -0.124204
Latvia                         2.10    1.85    -0.25    -0.119048
Republic of Moldova           3.68    3.27    -0.41    -0.111413
Bulgaria                       7.59    6.78    -0.81    -0.106719
```

```
[22]: pop.sort_values('relDifference', ascending=False).head(10)
```

```
[22]: Year          pop2010  pop2022  difference  relDifference
Country
Anguilla          0.01     0.02         0.01      1.000000
Turks and Caicos Islands  0.03     0.05         0.02      0.666667
Jordan            6.93    11.29         4.36      0.629149
Oman              2.88     4.58         1.70      0.590278
Qatar             1.71     2.70         0.99      0.578947
Niger            16.65    26.21         9.56      0.574174
Mayotte           0.21     0.33         0.12      0.571429
Equatorial Guinea   1.09     1.67         0.58      0.532110
Angola            23.36    35.59        12.23      0.523545
Bonaire, St. Eustatius & Saba 0.02     0.03         0.01      0.500000
```

```
[23]: pop.loc[['Slovakia', 'Czechia', 'Hungary', 'Poland', 'Austria', 'Ukraine'], : ]
```

```
[23]: Year          pop2010  pop2022  difference  relDifference
Country
Slovakia         5.40     5.64         0.24      0.044444
Czechia          10.46    10.49         0.03      0.002868
Hungary           9.99     9.97        -0.02     -0.002002
Poland           38.60    39.86         1.26      0.032642
Austria           8.36     8.94         0.58      0.069378
Ukraine          45.68    39.70        -5.98     -0.130911
```

1.6 Summary and outlook

- We will work mostly with tabular data.
- We will store them in `DataFrame` from Pandas library.
- This is more convenient and more efficient than regular Python lists.
- We have seen several functions for basic manipulation:
 - `iloc[]`, `loc[]`, `query`, `head`, `set_index`, `reset_index`, `rename`, `pivot`, `copy`, `sort_values`, operations and functions on `Series`.
- Next lecture will be focused on examples of different chart types.
- More Pandas later.