

UCS Driver Installation for Common Operating Systems

Contents

[Introduction](#)

[Prerequisites](#)

[Requirements](#)

[Components Used](#)

[Background Information](#)

[Driver Definition](#)

[Devices that Require a Driver](#)

[Drivers Versus Firmware](#)

[Driver Dependence on Firmware](#)

[When Drivers Must be Installed and Updated](#)

[Driver Versions Required](#)

[Download the Driver Bundle](#)

[Identify Server Hardware](#)

[UCS B Series](#)

[UCS C Series](#)

[Identify the UCS Firmware Release](#)

[UCS B Series](#)

[UCS C Series](#)

[OS Specifics](#)

[VMware ESXi](#)

[Install the Driver](#)

[ESXi 5.x/6.x](#)

[ESXi 4.x](#)

[Finish the Installation](#)

[Useful VMware CLI Commands](#)

[Microsoft Windows Server](#)

[Check Current Driver Version](#)

[Check Current Driver Version CLI](#)

[Missing Drivers](#)

[Install the Driver](#)

[Install the Driver from CLI](#)

[Useful Windows CLI Commands](#)

[Red Hat and SUSE Linux](#)

[SUSE Background Information](#)

[Verify current driver versions and OS Release](#)

[Install the Driver](#)

[Appendix](#)

[Driver Name Reference Table](#)

[Related Information](#)

Introduction

This document describes how to install device drivers on the Cisco Unified Computing System (UCS) for common operating systems.

Prerequisites

Requirements

Cisco recommends that you have knowledge of these topics:

- Cisco UCS Manager
- Cisco Integrated Management Controller (CIMC)
- Virtual Machine-ware (VMware), Windows Server, or Linux Operating Systems (OS)

Components Used

The information in this document is based on these hardware platforms:

- UCS B Series
- UCS C Series

"The information in this document was created from the devices in a specific lab environment. All of the devices used in this document started with a cleared (default) configuration. If your network is live, ensure that you understand the potential impact of any command."

Background Information

Driver Definition

A device driver is software that is the interface between the OS and the hardware. The device driver translates general OS commands into specialized commands for a particular device, which allows the OS to communicate with hardware devices.

Devices that Require a Driver

Here is a list of hardware devices that require device drivers:

- Ethernet Network Interface Card (ENIC)
- Fibre Channel Network Interface Card (FNIC)
- Redundant Array of Independent Disks (RAID) Controller
- Motherboard Chipset
- Video Card
- Trusted Platform Module (TPM)

Drivers Versus Firmware

Device drivers are different from firmware. Device driver software is installed on the OS, whereas firmware is lower-level code that is installed on hardware devices. Firmware is stored in non-volatile memory, such as ROM, Erasable Programmable ROM (EPROM), or flash memory.

Driver Dependence on Firmware

Device drivers have a strong dependence on the device firmware. Device drivers must be compatible with the firmware level of a hardware device, so that they properly communicate with each other; driver and firmware functionality must match for correct operation to take place.

When Drivers Must be Installed and Updated

Device drivers come pre-installed with operating systems (such as Cisco OEM VMware ESXi images), or they can be manually installed post-OS setup.

Device drivers generally need to be updated after these procedures:


- UCS firmware upgrades
- Major OS upgrades/patches

Driver Versions Required

The [UCS Hardware and Software Interoperability matrix](#) outlines the driver versions that are required for a particular OS, device, and firmware combination.

Warning: The driver versions listed on the matrix have been tested and verified by the Cisco Engineering Quality Assurance team, and it is crucial to install the correct driver; otherwise, unexpected behavior which could lead to network outages.

This example shows that an FNIC driver version of 1.6.0.36 is required for a B200 M4 with a Virtual Interface Card (VIC) 1240 that runs ESXi 6.0 U3, on UCS Release 3.2.2.



Download the Driver Bundle

Complete these steps in order to download the driver bundle:

1. In a web browser, navigate to <https://www.cisco.com>
2. Under **Support**, click **Download Software**.
3. Click **Unified Computing and Servers**.
4. Choose your server. Cisco UCS drivers are available for both **Cisco UCS B-Series Blade servers** and **Cisco UCS C-Series Rack-Mount**.
5. Click **Unified Computing System (UCS) Drivers**.
6. Select the bundle you want to download, and click **Download Now**.

Tip: When you choose which driver bundle to download, it is important to select the driver bundle version that is most similar to the server firmware release. For example, if you run a UCS-B Release 3.2(2b), then VMware driver bundle **ucs-bxxx-drivers-vmware.3.2.2.iso** is required.


Tip: Most VMware ESXi drivers are downloaded directly from www.vmware.com/download, with a search for the driver version. This is often quicker than if you were to download the entire driver bundle.

Identify Server Hardware

Before you select the correct driver, you must identify what hardware devices are installed on the server. This section describes how to find the devices located on the UCS Manager and in the CIMC.

UCS B Series


This example shows how to find the server inventory in UCS Manager. Server 1/1 has two adapter models installed: the **VIC 1240**.



Name	vNIC	Vendor	PID	Model
NIC 1	eth0	Cisco Systems Inc	UCSB-MLOM-40G-01	Cisco UCS VIC 1240
NIC 2	eth1	Cisco Systems Inc	UCSB-MLOM-40G-01	Cisco UCS VIC 1240
NIC 3	eth3	Cisco Systems Inc	UCSB-MLOM-40G-01	Cisco UCS VIC 1240
NIC 4	eth2	Cisco Systems Inc	UCSB-MLOM-40G-01	Cisco UCS VIC 1240

UCS C Series

This example shows how to find the server hardware devices in the CIMC. The server has a Cisco12G ModularSAS HBA RAID controller installed.



Slot ID	Product Name	Option ROM Status	Firmware Version	Vendor ID	Sub Vendor ID	Device ID	Sub Device ID
L	Intel X550 LOM	Loaded	0x8000ECB-1.819.0	0x8086	0x1137	0x1563	0x01a4
MLOM	Cisco UCS VIC 1457 MLOM	Not Loaded	5.1(2f)	0x1137	0x1137	0x0042	0x0218
MRAID	Cisco 12G Modular SAS HBA (max 16 drives)	Loaded	N/A	0x1000	0x1137	0x00ab	0x020f

Identify the UCS Firmware Release

Before the correct driver version is selected, the UCS release must be identified. This section describes how to identify the current UCS release installed on the servers.

UCS B Series

In this example, the UCS B Series runs UCS Release 4.1(3h)

Equipment

Chassis

Chassis 2

Fans

IO Modules

PSUs

Servers

Server 3

Server 4

Server 5

Server 6

Server 7

Server 8

Rack-Mounts

Enclosures

FEX

Servers

Fabric Interconnects

Fabric Interconnect A (subordinate)

Fabric Interconnect B (primary)

Main Topology View

Fabric Interconnects

Servers

Thermal

Decommissioned

Firmware Management

Installed Firmware

Firmware Auto Install

Catalog Package

Download Tasks

Packages

Images

Upgrades

Advanced Filter

Export

Print

Download Firmware

Update Firmware

Activate Firmware

Capabilities

Name

Model

Package Version

Running Version

UCS Manager

UCS Manager Service Processor

UCS Manager System

4.1(3h)A

Chassis

Chassis 2

Cisco UCS 5108 AC2 Chassis

IO Modules

PSUs

Servers

Server 3

Cisco UCS B200 M5 2 Socket...

Adapters

Adapter 1

Cisco UCS VIC 1340

4.0(4e)B

4.3(3b)

BIOS

Cisco UCS B200 M5 2 Socket...

4.1(1a)B

B200M5.4.1.1b.0.012

Board Controller

Cisco UCS B200 M5 2 Socket...

4.1(1a)B

14.0

Persistent Configuration

CIMC Controller

Cisco UCS B200 M5 2 Socket...

4.0(4e)B

4.1(30c)

UCS C Series

In this example, the UCS C Series runs UCS Release 4.1(2f).

Cisco Integrated Management Controller	
/ Chassis / Summary	
<div> <div> Server Properties </div> <div> Product Name: HX 240C M5SD Serial Number: WZP24150FQQ PID: HX240C-M5SD UUID: 3897B490-F3E4-4297-AC0E-E080A587632C BIOS Version: C240M5.4.1.2f.0.0110210243 Description: Asset Tag: Unknown </div> </div>	
<div> <div> Cisco Integrated Management Controller (Cisco IMC) Information </div> <div> Hostname: HX-20-CIMC-1 IP Address: MAC Address: Firmware Version: 4.1(2f) Current Time (UTC): Fri Jul 15 20:58:52 2022 Local Time: Fri Jul 15 20:58:52 2022 UTC +0000 Timezone: UTC </div> </div>	

OS Specifics

This section describes how to check driver versions and how to install drivers on common OSs.

VMware ESXi

Use these commands in order to check the current driver versions and VMware build:

Tip: These commands are executed from the ESXi CLI. Secure Shell (SSH) must be enabled before an SSH session is initiated.

Command	Description
---------	-------------

vmware -vl	Displays the VMware build and patch level
esxcli software profile get	Displays flavor of install ISO
esxcfg-scsidevs -a	Lists the hosts HBAs and the associated driver name
esxcfg-nics -l	Lists the host vmnics and network interface card (NIC) models
ethtool -i vmnicX	Displays the Ethernet driver used by the specified vmnic
esxcli network nic get -n vmnicX	Displays the Ethernet driver used by the specified vmnic on ESXi 6.5
vmkload_mod -s fnic	Displays the host bus adapter (HBA) driver version for the Cisco VIC
vmkload_mod -s enic	Displays the Ethernet driver version for the Cisco VIC
vmkload_mod -s nenic	Displays the Ethernet driver version for the Cisco VIC for ESXi 6.5 and later releases
vmkload_mod -s megaraid_sas	Displays the LSI MegaRAID driver version
vmkload_mod -s lsi_mr3	Displays the LSI lsi_mr3 driver version (Native driver on ESXi 6.7)
vmkload_mod -s driver_name	Displays the driver version for a specified driver

These examples show that **vmnic2** uses a **Cisco VIC** and a driver version of 1.4.2.15a.

```
~ # esxcfg-nics -l
Name PCI Driver Link Speed Duplex MAC Address MTU Description
vmnic2 0000:0b:00.00 enic Up 1000Mbps Full 00:22:bd:d6:65:e7 1500 Cisco Systems Inc Cisco VIC Ethernet NIC
vmnic4 0000:0c:00.00 enic Up 1000Mbps Full 00:22:bd:d6:65:e8 1500 Cisco Systems Inc Cisco VIC Ethernet NIC
vmnic5 0000:16:00.00 igb Up 1000Mbps Full c4:71:fe:b0:ef:68 1500 Intel Corporation 82576 Gigabit Network Connection
vmnic6 0000:16:00.01 igb Up 1000Mbps Full c4:71:fe:b0:ef:69 1500 Intel Corporation 82576 Gigabit Network Connection
~ #

~ # ethtool -i vmnic2
driver: enic
version: 1.4.2.15a
firmware-version: 2.0(2i)
bus-info: 0000:0b:00.0
```


These examples show that the **Qlogic Host Bus Adapter (HBA)** uses driver **qla2xxx** Version 901.1k.1-14vmw.

```
~ # esxcfg-scsidevs -a
vmhba2 mptsas link-n/a sas.5002651086b44000 (0:1:0:0) LSI Logic / Symbios Logic LSI064E
vmhba3 qla2xxx link-up fc.20000025b5a00505:20000025b500051f (0:4:0:0) QLogic Corp ISP2432-based 4Gb Fibre Channel to PCI Express HBA
vmhba4 qla2xxx link-up fc.20000025b5a00505:20000025b500050f (0:4:0:1) QLogic Corp ISP2432-based 4Gb Fibre Channel to PCI Express HBA
~ # vmkload_mod -s qla2xxx
vmkload_mod module information
input file: /usr/lib/vmware/vmkmod/qla2xxx
Version: Version 901.1k.1-14vmw, Build: 469512, Interface: 9.2 Built on: Aug 18 2011
License: GPL
Required name-spaces:
com.vmware.driverAPI#9.2.0.0
com.vmware.vmkapi#v2_0_0_0
```

Install the Driver

Complete these steps in order to install the driver:

1. Extract the contents of the driver zip file, and identify the ***.vib** file.
2. Use the Datastore Browser in order to upload the ***.vib** file to an ESXi host datastore.



3. Enter the host into **Maintenance** mode.

4. Install the driver.

ESXi 5.x/6.x

Use this command in order to install the driver on ESXi Release 5.x/6.x:

```
esxcli software vib install -v /path/async-driver.vib
```

```
# esxcli software vib install -v /tmp/scsi-fnic-1.5.0.20-10EM.500.0.0.472560.x86_64.vib
Installation Result
  Message: The update completed successfully, but the system needs to be rebooted for the changes to be effective.
  Reboot Required: true
  VIBs Installed: Cisco_bootbank_scsi-fnic_1.5.0.20-10EM.500.0.0.472560
  VIBs Removed: Cisco_bootbank_scsi-fnic_1.5.0.8-10EM.500.0.0.472560
  VIBs Skipped:
#
```

Note: If the drivers require a signature verification, run this command with the **--no-sig-check** switch. Ensure that you use the full path to the file.

ESXi 4.x

Use this command in order to install the driver on ESXi Release 4.x:

```
esxupdate --bundle=offline-bundle.zip update
```

Finish the Installation

After you install the driver with one of the previously mentioned commands, exit **Maintenance** mode and reboot the host. For more information on how to install drivers, reference the Related Information section at the end of this document.

Useful VMware CLI Commands

Here are some other useful VMware commands that you can use when you install a driver:

Check Maintenance Mode Status

```
vim-cmd hostsvc/hostsummary | grep -i maintenace
```

Check for Powered-On VMs

```
vim-cmd vmsvc/getallvms
```

Power-Off VMs

```
vim-cmd vmsvc/power.off <vm id>
```

Enter Maintenance Mode

```
vim-cmd hostsvc/maintenace_mode_enter
```

Exit Maintenance Mode


```
vim-cmd hostsvc/maintenace_mode_exit
```

Microsoft Windows Server

This section describes how to install a driver on a Microsoft Windows server.

Check Current Driver Version

In order to check the device drivers in Microsoft Windows, use the **Device Manager** located in the Control Panel.



Check Current Driver Version CLI

For Windows Server Core the Plug-and-Play (PnP) Utility (**PNPUtil.exe**) is used to check driver versions.

```
Administrator: Windows PowerShell
PS F:\windows\storage\Cisco\mlom\w2k12r2\x64> PnPUtil.exe -e
Microsoft PnP Utility

Published name : oem2.inf
Driver package provider : Cisco Systems, Inc.
Class : Storage controllers
Driver date and version : 10/30/2013 2.4.0.8
Signer name : Microsoft Windows Hardware Compatibility Publisher

Published name : oem1.inf
Driver package provider : Cisco Systems, Inc.
Class : Network adapters
Driver date and version : 11/20/2013 2.4.0.15
Signer name : Microsoft Windows Hardware Compatibility Publisher
```


Missing Drivers

Hardware devices with missing drivers are displayed in the Device Manager with a yellow question mark. These devices must be updated with the correct driver in order to prevent unexpected behavior.



Install the Driver

In order to install or update a driver in Microsoft Windows, right-click on the device, and choose **Install/Update Driver** in order to start the Installation Wizard.



Install the Driver from CLI

The PNPUtil tool can also be used to install drivers from the CLI. The driver ISO bundle can be mounted via the UCS KVM Console Virtual Media.

```

Administrator: Windows PowerShell

PS F:\windows\storage\Cisco\m1om\w2k12r2\x64> PnPutil.exe -i -a .\fnic2k12.inf
Microsoft PnP Utility

Processing inf :          fnic2k12.inf
Successfully installed the driver on a device on the system.
Driver package added successfully.
Published name :          oem2.inf

Total attempted:          1
Number successfully imported: 1
  
```

Useful Windows CLI Commands

Command	Description
<code>pnputil.exe -e</code>	List all installed 3rd party drivers
<code>pnputil.exe -a <INF name></code>	Install driver
<code>pnputil.exe -d <INF name></code>	Delete driver

pnputil.exe -f -d <INF name> Force delete driver

Red Hat and SUSE Linux

This section describes how to install and validate a driver on Red Hat Enterprise Linux (RHEL) and SUSE Linux Enterprise Server (SLES).

SUSE Background Information

Starting with SLES 12 SP1, the Cisco eNIC and usNIC drivers are bundled together into a single RPM (vs. being packaged in separate RPMs, as they are for other Linux distributions). Bundling both drivers into a single RPM is required because of how kernel module dependencies are managed in SLES 12 SP1 and later. If you are not using Cisco usNIC functionality (For example, if you have not provisioned any usNIC devices in UCSM / CIMC), the usNIC driver is effectively be ignored.

The eNIC and usNIC drivers have their own distinct version numbers. If you install the cisco-enic-usnic RPM on SLES 12 SP 1 or later, once those drivers are loaded into the running kernel (For example, via rebooting), use **cat /sys/module/enic/version** and **cat /sys/module/usnic_verbs/version** to view their respective version numbers. The cisco-enic-usnic RPM has its own distinct version number as well. Because it represents the *packaging* of the eNIC and usNIC drivers, the RPM version number look similar, but does not reflect the specific version of either driver.

For additional information on the exact driver versions query and review the RPM description section. The query looks similar to the example below:

```
# rpm -qip cisco-enic-usnic-kmp-default-<RPM_VERSION>.x86_64.rpm
Name      : cisco-enic-usnic-kmp-default  Relocations: (not relocatable)
...
Summary   : Cisco VIC Ethernet NIC drivers
Description :
This RPM contains both the Cisco VIC Linux Ethernet driver (enic.ko, version <ENIC_VERSION>) and
the Cisco Userspace NIC (usNIC) Linux Ethernet driver (usnic_verbs.ko, version <USNIC_VERSION>).
Some Linux distros require both kernel modules to be in the same RPM in order to properly test
for
symbol compatibility (because usnic_verbs.ko depends on enic.ko) when installing into post-GA
upgrade kernels.
```

Verify current driver versions and OS Release

Here is a list of commands used in order to check the current driver version and OS release:

Command	Description
<code>modinfo driver_name</code>	Displays driver version for the specified driver that is loaded (by default) at next reboot
<code>modinfo /path/to/driver_name.ko</code>	Displays driver version for the specified driver kernel object file
<code>cat /sys/module/enic/version</code>	Displays the Ethernet driver version currently loaded in the running Linux kernel for the Cisco VIC adapter
<code>cat /sys/module/fnic/version</code>	Displays the FC NIC driver version currently loaded in the running Linux kernel for the Cisco VIC adapter
<code>cat</code>	Displays the LSI MegaRAID driver version currently loaded in the

<code>/sys/module/megaraid_sas/version</code>	running Linux kernel
<code>lsmod -l</code>	Lists currently-loaded drivers in the kernel
<code>cat /etc/redhat-release</code>	Shows the RHEL release (for RHEL 6.x and earlier)
<code>cat /etc/SuSE-release</code>	Shows the SUSE release (for SLES 11 SP3 and earlier)
<code>cat /etc/os-release</code>	Shows the RHEL release (for RHEL 7.x and later, and SLES 11 SP4 and later)
<code>uname -a</code>	Shows kernel related information

Note: Be aware of the command **modinfo [driver name]** shows the module information about the driver that is loaded upon next reboot. This is not necessarily the same driver version currently loaded in the running kernel. Review **cat/sys/module/DRIVER_NAME/version** to validate the driver version loaded in the currently running kernel, and/or use the command **modinfo [/path/to/driver.ko]** to validate the module info for a specific driver kernel object file.

Tip: Refer to the Driver Name Reference Table located in the Appendix for examples of other common driver names.

This example shows that an ENIC driver version of 3.2.210.18-738.12 bundled in the cisco-enic-usnic RPM package 3.2.272.23 is installed on SLES 15 GA.

```
# cat /etc/os-release
NAME="SLES"
VERSION="15"
VERSION_ID="15"
PRETTY_NAME="SUSE Linux Enterprise Server 15"
ID="sles"
ID_LIKE="suse"
ANSI_COLOR="0;32"
CPE_NAME="cpe:/o:suse:sles:15"

# rpm -qa | grep enic
cisco-enic-usnic-kmp-default-3.2.272.23_k4.12.14_23-738.12.x86_64

# modinfo enic | grep ^version
version: 3.2.210.18-738.12

# cat /sys/module/enic/version
3.2.210.18-738.12
```

Install the Driver

Drivers in RHEL and SLES are installed using the Redhat Package Manager (RPM). Use this command in order to install the driver:

```
# rpm -ihv RPM filename.x86_64.rpm
[root@localhost tmp]#
[root@localhost tmp]# rpm -ihv kmod-enic-2.1.1.41-rhel6u2.el6.x86_64.rpm
Preparing... ##### [100%]
 1:kmod-enic ##### [100%]
[root@localhost tmp]#
```

Tip: When you install drivers in Linux ensure that you review the README files associated

with the driver if available. You can look at the contents of the RPM to see where its associated README file was installed (**rpm -qp kmod-enic**). Some RPM driver packages have dependencies on other modules, and require installation of additional RPM packages. The README files contain full instructions on how to install the driver file.

Appendix

Driver Name Reference Table

This table shows the driver names or prefixes for common drivers.

Command	Description
enic	Cisco VIC Ethernet NIC
fnic	Cisco VIC FC NIC
qlc or qla	Qlogic adapter
lpfc	Emulex HBA (light pulse)
be2net	Emulex Ethernet NIC
igb or ixgbe	Intel NICs
bnx	Broadcom adapter
megaraid	LSI MegaRAID
megasr	Embedded SW RAID
nenic	Cisco VIC Ethernet NIC for ESXi 6.5

Related Information

- [VMware KB: How to download and install async drivers in ESXi 5.x/6.x \(2005205\)](#)
- [VMware KB: Determining Network/Storage firmware and driver version in ESXi/ESX 4.x and 5.x \(1027206\)](#)
- [VMware KB: Installing async drivers on ESXi 5.x \(2005205\)](#)
- [VMware KB: Installing async drivers on ESXi 4.x \(1032936\)](#)
- [VMware KB: Identifying a PCI device in ESX/ESXi 4.x or ESXi 5.x and comparing it with the VMware HCL \(1031534\)](#)
- [Technical Support & Documentation - Cisco Systems](#)