深圳市宝安区沙井兴永达铜铝绝缘材料行

Shenzhen Bao'an District Shajing Xing Yongda Copper Aluminum Insulation Material Co., Ltd.

检 验 证 明 书

INSPECTION CERTIFICATE

ADD：深圳市宝安区沙井

TEL：086-755-27230881

客户名称 CUSTOMER		订单编号 ORDER NO		证明书编号 CERTIFICATE NO	CYL202409050001
钢种 STEEL GRADE	C11000	产品名称 COMMODITY	紫铜	日期 DATE	2024-9-5

项目 ITEM	规格 SIZE (MM)	数量 QTY	轧制批号	炉号 HEAT NO	区分 CONDITION	机械性能 MECHANICAL PROPERTIES				化学成份 CHEMICAL COMPOSITION %							
						断面收缩率 Z (%)	抗拉强度 T/S (kfg/m2)	硬度 Hv	断后伸长率 A (%)	CU	PB	Bi	Fe	Sb	As	S	Zn
1	45*35*55	1			CD		255	70	25	99.9	0.005	0.001	0.005	0.002	0.002	0.005	0.003

区分(Condition)：FC:炉冷(Furnace Coole) S:固溶化(Solution Treaied) HF:热煅(Hot Forged) B:黑皮(Black) SR:应力消除(Stress Relived) A:退火(Anmealed) R 压光(Reeled) QT:淬火及回火(Quenched & Tempered) AC:空冷(Air Cooled) HR:热扎(Hot Rolled) T:车削(Turned or Peeled) N:正常化（Normalized） FA:完全退火(Pull Anmealed) P:抛光(Polished) WQ:水淬(Water Quenched) SA:球化退火(Spheroidized Annealed) CD:冷抽(Cold Drawn) CG:研磨(Centerless Grinding) RS 矫直(Re Straight)

兹证明本表所列产品，均依材料规格制造及试验，并符合规格之要求。

We hereby certify that the material described herein has been manufactured and testen with satisfactory results in accordance with the requirement of the above material specification.

Surveyor to.

备 注：1、化学成份引自原质保书.
Remark:2、按 ASTM

Company Manager