广东韶钢松山股份有限公司
SGIS SONGSHAN CO.,LTD.

宝武集团中南钢铁有限公司
BAOWU Group Zhongnan Iron&Steel Co.,ltd.

产品质量证明书
INSPECTION CERTIFICATE

广东省韶关市曲江区马坝 邮编 512123
Maba,QUJIANG DISTRICT 512123
SHAOGUAN,GUANGDONG
PROVINCE,P.R.CHINA
售后服务电话（TEL）：0751- 8788929
售后服务传真（FAX）：0751- 8788929

订货单位 CUSTOMER	广东华亿工业用钢供应链服务有限公司	产品名称 PRODUCT	碳素结构钢板 carbon structural steel		
收货单位 PURCHASER	广东华亿工业用钢供应链服务有限公司	牌号 STEEL GRADE	Q235B	证书号 CERTIFICATE NO.	KB2301070039
标准 SPECIFICATION	GB/T 3274-2017	签发日期 DATE OF ISSUE	1/7/2023	码单号 DELIVERY No.	P303107028
		许可证号 LICENSE NO.		合同号 CONTRACT NO.	J2C0081024

序号 NO.	钢板号 PLATE NO.	检验批号 BATCH NO.	炉号 HEAT NO.	规格及重量 MATERIAL DESCRIPTION 单位(mm) 厚度Thickness 16 宽度 Width	长度 Length	数量 QTY	重量 MASS (t)	化学成分 CHEMICAL COMPOSITION % 分析区分*1	C	Si	Mn	P	S	Cu	Cr	Als		硬度*7	拉伸试验 TENSILE TEST 位置方向*3	屈服 Y.S. ReH	抗拉 T.S. Rm	伸长 EL	Z *4	YR *5	冲击试验 IMPACT TEST 位置方向*3	温度 TEMP	冲击吸收能量: KV2 冲击功(J) ABSORBED ENERGY J 1	2	3	AVG	厚度方向性能 THROUGH THICKNESS PROPERTIES 位置方向*3	断面收缩率% *4 1	2	3	AVG	交货状态*6
									2	2	2	3	3	2	2	3																			
									2=×0.01 3=×0.001 4=×0.0001											MPa		%			℃										
1		Z3800530R	3Z300148	2000	12000	6	18.084	L	16	13	44	21	10	2	2	9		/	C	293	455	33.0			L	20	130.0	133.0	122.0	128	/	/	/	/	/	AR
2		Z3800530R	3Z300148	2000	12100	1	3.04	L	16	13	44	21	10	2	2	9		/	C	293	455	33.0			L	20	130.0	133.0	122.0	128	/	/	/	/	/	AR
3		Z3800530R	3Z300148	2000	12200	1	3.065	L	16	13	44	21	10	2	2	9		/	C	293	455	33.0			L	20	130.0	133.0	122.0	128	/	/	/	/	/	AR
4		Z3800531R	3Z100136	2000	12000	3	9.042	L	14	16	43	21	19	2	2	5		/	C	287	452	32.5			L	20	106.0	90.9	93.8	97	/	/	/	/	/	AR

超声 U.T.	弯曲试验 BEND TEST 弯曲d=1.5a 180° 合格	外观及尺寸ACCEPTABLE VISUAL AND DIMENSIONS 合格	*2 试样热处理:TEST PIECE STRESS RELIEVED: /		车船号: 粤F58680

合计 Total:	PIECES	11	33.231	t	当前页小计 Current Page Subtotal:	PIECES:	11	33.231	t		

备注 REMARKS:
1.冲击试样尺寸（Impact Sample Size）：冲击试样尺寸按执行标准的规定(Impact Sample Size in accordance with the requirements of the Delivery Standard);
2.弯曲试验（Bending Test）：试样宽度b、弯曲压头直径d、弯曲角度按执行标准的规定（Bend tested in accordance with the requirements of the Delivery Standard）
3.交货状态(CONDITION OF SUPPLY)：AR （热轧）；N （正火）；CR （控轧）；NT （正火加回火）；TMCP （热机械控轧轧制）
4.注明探伤合格的检验批表示该检验批在质量证明书中列出的产品逐张合格.(Testing indicated that the product lot number of qualified inspection by one of the tests listed in the batch of qualified quality certificate).

注释 NOTES: *1分析区分ANALYSIS:L=熔炼成分LADLEANALYSIS,P=成品分析PRODUCT ANALYSIS *2试样热处理HEAT TREATMENT OF TEST PIECE*3位置方向LOCATION AND ORIENTATION:B=尾部BOTTOM,T=头部TOP.,C=横向TRANS.,L=纵向LONGI.,Z=板厚方向THROUGH-THICK.1=近表面NEAR THE SURFACE,2=1/2厚度THICKNESS,3=1/3厚度THICKNESS.4=1/4厚度THICKNESS.*4断面收缩率PERCENTAGE REDUCTION OF AREA *5YR=屈强比 YIELD RATIO Y.S/T.S(TR=强屈比 T.S/Y.S) *6交货状态CONDITION OF SUPPLY*7硬度HARDNESS:布氏硬度Brinell Hardness=HB,洛氏硬度Rockwell Hardness=HR

Chen Xing

质量负责人 QUALITY MANAGER

本产品已按照上述要求进行制造和检验，其结果符合要求，特此证明。
WE HEREBY CERTIFY THAT MATERIAL DESCRIBED HEREIN HAS MANUFACTURED AND TESTED WITH SATISFACTORY RESULTS IN ACCORDACE WITH THE REQUIREMENTS OF THE ABOVE MATERIAL SPECIFICATION.