BAOSTEEL
宝钢特钢

宝钢特钢长材有限公司
Baosteel Speclal Metals Long Product Co.,Ltd.

产品质量说明书
INSPECTION CERTIFICATE

上海宝山区水产路1269号
No.1269 Shuichan Road, Baoshan District
200940 Shangha,P.R.China
TEL (021)26032097
FAX (021)26032097

订货单位 Customer	上海宝钢浦东国际贸易有限公司			订货单位代号 Customer No.	001779
收货单位 Purchaser	上海宝钢浦东国际贸易有限公司			合同号 Contract No.	B9IT003665
品种名称 Designation	圆棒 Round bar			证书号 Certificate No.	BGAPB2502260002713
产品标准 Specification	EN 10083-3-2006		牌号 Steel Grade	42CrMo4	
规格(mm) Size	Φ75		制造商及许可证号 License No.	……	
支（吊盘件）数 Piece(Bundie)Number	3	重量 Weight(kg)	6328.0	签发日期 Date of Issue	2025年02月26日
生产编号 Production NO.	9Y01017	热处理编号 Heat Treatment No.	……	冶炼炉号 Heat No.	972-0634
加工用途 Designated Further	……	交货状态 Condition of Delivery	……	制造命令号 PONO	9A00709
地区订货用户 IntermEdiate User			最终用户 Final User		

一、化学成分（%）Chemical Composition(%)

C |0.41 Si |0.23 Mn |0.76 P |0.017 S |0.003 Mo |0.21 Cr |1.01

二、宏观检测Macrostructure Examination

1、尺寸、外形、表面质量Dimension, Contourand, Surface Quality 合格
accept

2、低倍组织Macro-structure

锭型偏析(级) Pattern Segregation (grdae)	0.5	0.5
一般疏松(级) Ordinary Porosi ty (grade)	0.0	0.0
中心疏松(级) Centre Porosi ty (grade)	0.5	0.5

三、力学性能Mechanical Property

1、硬度 Hardness
布氏硬度（HBW）
2、拉伸 Tensile

实验温度℃ Test temperature	室温	室温
抗拉强度Rm (MPa) Tensile Strength	879	885
断后伸长率(A)% Elogation	18.5	19.0
断面收缩率(Z)% Reduction of Area		
屈服强度Rp0.2 (MPa) Yield Strength	601	605

本证书符合EN10204 3.1

备注: Note:		
声明：Statement	兹证明本表所列产品，均依标准规定制造，取样、实验和检验，并符合标准及合同要求。 WE HERE CERTIFY THAT THE MATERLAL HEREIN DESCRIBED HAS BEEN MANUFACTURED, SAMPLED, TESTED AND INSPECTED IN ACCORDANCE WITH THE REQUIREMENTS OF ABOVE SPECIFICATIONS AND PURCHASE ORDER, AND MET THE REQUIREMENTS.	Ji Ren Feng 质量负责人 QUALITY MANAGER 纪仁峰