may.be

Design System

A quiet mobile interface for exploring decisions

Clear	Calm	Continuous
One purpose per screen	Space is part of the experience	Every choice grows from the same tree

Platform iPhone first. Responsive web and Android use the same semantic system.

Standard Apple Human Interface Guidelines for hierarchy, motion, accessibility, safe areas, and touch behavior.

Brand Warm cream, deep brown, restrained language, and one cinematic focal point.

Version 1.0 October 2026

Principles

Apple familiar. may.be distinct.

One focus Each scene has one primary action and one visual centre.

Direct manipulation The object a person chooses is the object that moves and grows.

Agency Undo is immediate. Exploration never feels like commitment.

Restraint No dashboard cards, decorative gradients, or unnecessary copy.

Adaptation Safe areas, Dynamic Type, appearance modes, and input methods shape the layout.

Trust Plausible paths are never presented as predictions.

Screen rhythm

Tell	Understand	Transform	Explore
Speak or type	Keywords emerge	Dot becomes decision	Branches grow

Keep

- Native behavior for keyboard, microphone, focus, permissions, and safe areas.
- may.be styling in the content layer: color, graph, pacing, and language.

Color

Warm neutrals carry the story. Brown marks the active decision.

Swatch	Token	Light	Use
	Canvas	#F5F0E7	Atmosphere
	Surface	#FFFAF2	Nodes and sheets
	Primary text	#332119	Essential content
	Secondary text	#6F625A	Supporting content
	Primary action	#3A241B	One active control
	Separator	#D8CEC5	Borders and paths
	Success	#3F6B4F	Confirmed state
	Warning	#8A5A18	Recoverable issue
	Destructive	#B3261E	Destructive action

Rules

- Use semantic color names in Figma and code. Do not name tokens by hex value.
- Reserve deep brown for the decision seed, selected path, or one primary action.
- Provide dark and Increased Contrast variants. Prefer system semantic colors for standard controls.
- Never use color alone. Pair state with text, icon, line weight, or motion.

Contrast 4.5 to 1 for normal text. 3 to 1 for large text and essential geometry.

Type and layout

Use the system font. Let content breathe.

Style	Size	Weight	Use
Large title	**34 pt**	Semibold	Rare cinematic statement
Title	**28 pt**	Semibold	Decision framing
Title 3	**20 pt**	Semibold	Decision seed
Body	**17 pt**	Regular	Input and explanations
Callout	**16 pt**	Medium	Branch labels
Subheadline	**15 pt**	Regular	Secondary instruction
Caption	**12 pt**	Regular	Noncritical hint

Font SF Pro through the Apple system font. Web stack: -apple-system, BlinkMacSystemFont, Segoe UI, sans-serif.

Case Sentence case. Short labels. No all caps in the product interface.

Scaling Support Dynamic Type. Wrap before shrinking. At accessibility sizes, switch the graph to a list presentation.

Spacing

4	8	12	16	20	24	32	48
Micro	Inside	Compact	Default	Margin	Group	Section	Pause

Frame 390 by 844 points. 20 point side margin. 44 by 44 point minimum targets.

Insets Respect the system safe area and keyboard inset.

Components

Few components. Complete states.

Component	Default	States
Microphone orb	104 pt circle	Idle, pressed, listening, unavailable
Text composer	50 pt minimum height	Empty, focused, submitting, error
Keyword bubble	Content-sized capsule	Enter, settle, dissolve
Decision seed	120 pt circle	Growing, current, loading, error
Branch node	96 pt circle	Resting, focused, selected, rejected
Branch path	1.5 pt line	Drawing, active, historical
Detail caption	Three lines maximum	Hint, summary, loading, error
Undo	Symbol and label	Hidden, available, pressed

Shape

Corners 12 pt controls. 18 pt fields. 24 pt sheets. Full circle for bubbles and nodes.

Depth Use borders and tonal contrast first. Use one restrained shadow only on the active seed.

Material Use platform material for floating navigation only. Keep the graph surface warm and opaque.

Logo rule

- Keep the cinematic dot mathematically centred.
- Position may and be around it; word width must never move the dot.
- Keep the header logo conventional while the cinematic logo transforms.

Motion

Motion shows cause and continuity.

Moment	Timing	Behavior
Press	100 to 160 ms	Scale or tone responds immediately
Caption	180 to 260 ms	Short crossfade
Keyword	420 to 700 ms	Rise, settle, pause, dissolve
Branch	500 to 800 ms	Path draws before node arrives
Camera	600 to 900 ms	Pan and scale one world
Logo to seed	900 to 1400 ms	Words fade; pinned dot grows

Easing Authored motion: cubic-bezier(.22, 1, .36, 1). Direct touch: a tight spring with minimal overshoot.

Branch sequence

1	2	3	4
Draw path	Reveal node	Enable touch	Prefetch nearby paths

Reduced Motion

- Replace zoom, large travel, parallax, and blur with short fades.
- Keep the same order, labels, focus, and final state.
- Do not remove feedback or meaning.

Accessibility and handoff

The system is complete only when every path remains usable.

Setting	Required response
VoiceOver	Decision is a heading. Branches are buttons with label and summary.
Dynamic Type	Containers grow. Graph can become a structured list.
Increase Contrast	Strengthen text, paths, borders, and focus rings.
Reduce Transparency	Use opaque warm surfaces instead of blur.
Switch or keyboard	Logical focus order. Enter and Space activate.
Touch	44 point minimum targets with clear pressed feedback.

Shared naming

Figma Color, Type, Spacing, Radius, Motion, and Components collections.

States idle, focused, pressed, listening, processing, current, selected, rejected, loading, error, disabled.

Code Use the same semantic names in SwiftUI and CSS. Each motion token includes a reduced-motion alternative.

Release check

- Test light, dark, Increased Contrast, Reduce Transparency, and Reduce Motion.
- Test smallest iPhone width and one accessibility text size.
- Confirm every branch stays inside the viewport and Undo restores the exact previous fork.

Apple references Design Principles / Color / Layout / Motion / Accessibility / Typography