may.be User Story Specification

End to end mobile decision exploration journey

Purpose Define the intended user experience, functional behavior, acceptance criteria, and product boundaries for the first complete may.be journey.

Audience Product design, frontend engineering, backend engineering, AI integration, quality assurance, and accessibility review.

Product promise Help a person see plausible paths through a difficult decision without pretending to predict the future or compressing the experience into a dashboard.

Input	Interpretation	Transformation	Exploration	Recovery
Speak or type	Keywords and factors	Story to decision seed	Living branch graph	Undo or restart

Document status Product and engineering handoff

1 Product intent

may.be is a mobile first decision exploration experience. A person describes where they are stuck, the system extracts grounded meaning, distils the central decision, and reveals a spatial tree of credible alternatives. The graph remains exploratory: choosing a branch means following it to understand what it could lead to, not committing to it.

The primary product requirement is continuity. The user should feel that one story becomes one decision seed and then grows into one persistent tree. Screens may change, but the experience must not feel like a sequence of unrelated cards, reports, or dashboard panels.

1.1 Core principles

- Voice is the primary input; typing is a quiet and fully functional fallback.
- AI interpretation stays visibly connected to the words the person supplied.
- The graph represents plausible paths, not predicted or guaranteed outcomes.
- Motion explains transformation and continuity, so interface copy remains minimal.
- The number of branches is determined by distinct credible options, not a fixed layout quota.
- Every exploration action is reversible without refreshing or rebuilding the page.
- Human unknowns and assumptions remain distinguishable from user facts and evidence.

1.2 Primary persona

Person An adult facing a meaningful personal, career, financial, relationship, or product choice who feels overwhelmed by competing consequences.

Need A calm way to externalise the decision, see distinct alternatives, and follow consequences without reading a long AI answer.

Success The person can articulate the decision more clearly, understand the credible paths, inspect why each path exists, and return to earlier forks safely.

1.3 Scope of the first complete journey

Included	Deferred
Voice and text capture	Accounts and cross device sync
Local AI analysis and branch expansion	Evidence retrieval with citations
Cinematic keyword and logo transition	Probability or outcome scoring
Variable branch graph with details	Autonomous multi agent planning
Selection, expansion, undo, restart	Saved Your paths constellation

2 End to end journey

The journey below is the canonical product flow. Each stage owns the screen and advances only when its completion condition is satisfied.

Stage	User goal	Experience response
1 Invitation	See a calm entry point and understand that speech or text can be used.	Large microphone, short greeting, compact text field.
2 Capture	Speak or type the situation in natural language.	Interim transcript or typed text remains visible and editable.
3 Listening	Know the system received the story and is working.	Breathing sound orb with minimal listening copy.
4 Meaning	Recognise the important ideas extracted from the story.	Grounded keyword bubbles rise from the bowl and dissolve rhythmically.
5 Passage	Move emotionally from telling the story to seeing paths.	Short transition sentence fades, followed by a deliberate empty pause.
6 Transformation	See may.be become the decision itself.	Wordmark appears; may and be fade outward; the centred dot remains.
7 Decision seed	Confirm the distilled question before branching.	The dot expands in place and then reveals the decision label.
8 Branching	See all distinct credible first level choices.	Organic paths grow from the seed; branch nodes arrive as paths reach them.
9 Exploration	Understand and follow one path.	Tap or focus reveals concise detail; selection grows the same continuous tree.
10 Recovery	Return to an earlier fork or start again.	Undo restores the previous branch state; brand action resets the journey.

2.1 Journey completion criteria

- The first decision graph appears only after valid structured analysis has been received.
- The user can inspect every visible branch without selecting it.
- Selecting a branch preserves spatial continuity and loads the next level without replacing the scene.
- Undo restores the exact previous fork, alternatives, and camera position.

- The user can always restart from the brand control without reloading the browser page.

3 Epic A Capture the situation

US 01 Start with voice

User story As a person who is unsure how to frame my problem, I want to speak naturally so that I can begin without composing a formal prompt.

Acceptance criteria

- Given the invitation screen, when I tap the microphone, then recording starts and the microphone visibly enters a listening state.
- Given speech recognition is available, when I speak, then interim and final transcript text appears in the text field.
- When recording ends with a non-empty final transcript, then the journey starts automatically using that transcript.
- When I tap the microphone while recording, then recording stops cleanly.

Implementation note The initial speech locale is en-IN. A native app may replace browser speech recognition with platform ASR without changing the story contract.

US 02 Use text instead

User story As a person who cannot or does not want to speak, I want a compact text input so that I can use the complete experience privately.

Acceptance criteria

- Given the invitation screen, when I type, then the field preserves the full text while visually truncating only when space requires it.
- When I press Enter or tap Send with valid input, then analysis starts once.
- The text path provides the same interpretation and graph journey as voice input.
- The input remains editable until analysis begins.

US 03 Recover from capture problems

User story As a person whose browser or permissions prevent voice capture, I want a clear fallback so that I am never trapped at the first screen.

Acceptance criteria

- Given speech recognition is unsupported, when I tap the microphone, then the app explains that I can use Chrome or Edge or type below.
- Given microphone access is denied, when the browser reports not allowed, then the app explains how to enable access and keeps text input usable.
- Given speech cannot be understood, then the app offers a calm retry message without discarding typed content.
- Error messages are announced to assistive technology and do not cover the primary controls.

US 04 Restart the journey

User story As a returning explorer, I want to reset from the may.be brand so that I can describe a different decision without refreshing the page.

Acceptance criteria

- When I activate the brand control, then active timers, animations, analysis state, branch history, captions, and errors are cleared.
- The invitation scene returns with the input available for a new situation.
- No stale branch nodes or keyword bubbles remain after reset.

4 Epic B Turn the story into meaning

US 05 See that analysis is active

User story As a person waiting for interpretation, I want calm feedback so that processing time feels intentional rather than broken.

Acceptance criteria

- After valid submission, the invitation screen transitions to one breathing orb and minimal listening copy.
- The listening state remains visible for at least the minimum cinematic hold while analysis runs.
- If analysis completes early, the experience does not flash abruptly to the next scene.
- If analysis fails, the app returns to the invitation and shows a retryable error.

US 06 Recognise my own words

User story As a person who shared a nuanced situation, I want the extracted words to reflect what I said so that I can trust the interpretation.

Acceptance criteria

- The analysis returns between one and eight concise keywords.
- Keywords prioritise explicit options, people, places, constraints, values, and stakes present in the input.
- Generic filler such as values, change, risk, or timing is not used when more specific user language is available.
- For a direct alternative such as Android or iOS, the displayed keywords are Android and iOS.

US 07 Experience the keyword rhythm

User story As a person watching the app make sense of my story, I want keywords to emerge and disappear naturally so that the transition feels alive rather than mechanical.

Acceptance criteria

- Each keyword rises individually from the bowl with a slight stagger.
- Each bubble enlarges, overshoots, settles, pauses, and then dissolves with lift and blur.
- The sequence is rhythmic and readable; bubbles do not overlap important content or leave the viewport.
- The scene advances only after all keyword dissolving is complete.

Implementation note Target cadence is approximately 430 ms between arrivals with a breathing ease curve of cubic-bezier(.22, 1, .36, 1).

US 08 Receive a structured decision

User story As the experience renderer, I need validated structured analysis so that the interface can create meaning without parsing prose.

Acceptance criteria

- The response contains keywords, framing, factors, a root decision node, decision nodes, and edges.
- Every node has a short label, concise summary, grounding kind, factor references, and a human-input flag.
- Labels remain compact enough for circular nodes and summaries remain concise enough for the fixed caption area.
- Malformed provider output is rejected before it reaches the frontend.

US 09 Respect direct either or questions

User story As a person comparing two named options, I want those exact options to become the first branches so that the AI does not replace my decision with generic advice.

Acceptance criteria

- Given input matching A or B, A vs B, or A versus B, the root label is A or B.
- The first branches use the two named alternatives in the same order.
- Known product names preserve expected casing, including iOS and iPhone.
- The AI may add detail beneath each branch but does not introduce unrelated root alternatives.

5 Epic C Transform meaning into a decision

US 10 Cross the passage

User story As a person who has finished telling the story, I want a short acknowledgement before paths appear so that the experience has emotional pacing.

Acceptance criteria

- After keywords dissolve, the app shows a short acknowledgement and path-finding sentence.
- The copy fades with blur and slight upward movement rather than disappearing instantly.
- A brief blank pause separates the passage from the logo appearance.
- No additional instructions or analysis text crowd the scene.

US 11 See the centred logo transformation

User story As a person entering the decision space, I want the may.be mark to transform into the decision seed so that the brand and interaction feel like one continuous idea.

Acceptance criteria

- The cinematic may.be wordmark appears with the dot fixed at the mathematical centre of the screen.
- The may and be text align around the centred dot and do not move the dot because of unequal word widths.
- The may and be text fade outward while the same dot stays in place.
- The small header logo remains conventional and is not changed by the cinematic wordmark treatment.

US 12 Understand the decision seed

User story As a person, I want the final decision question to appear inside the enlarged dot so that I know what the tree is branching from.

Acceptance criteria

- The dot visibly grows from its original position into the current decision node.
- The dot does not juggle or translate while growing.
- Decision text appears only after the node reaches a usable size.
- The decision label is concise, readable, and derived from the validated root node.

6 Epic D Explore the living decision tree

US 13 See every credible first path

User story As a person considering a decision, I want all distinct credible alternatives to grow from the decision seed so that I can see more than a forced binary choice.

Acceptance criteria

- The renderer supports two to six branches returned by the analysis contract.
- The trunk and curved branch paths grow before their destination nodes appear.
- Choice nodes arrive with a slight stagger as their paths reach them.
- No extra branches are invented merely to fill visual space.
- The root, paths, and choices share one world coordinate system.

US 14 Inspect a path before following it

User story As a cautious explorer, I want a concise explanation for each branch so that I can understand what it represents before selecting it.

Acceptance criteria

- Hovering, focusing, or touching a choice reveals its summary in a fixed centred caption region.
- The explanation never extends outside the mobile viewport.
- The node label remains short while the caption carries the detail.

- Moving away or losing focus restores the neutral interaction hint.

US 15 Follow one branch

User story As a person exploring an alternative, I want the selected branch to become the next decision point so that I can follow its consequences.

Acceptance criteria

- On selection, unselected siblings shrink, blur, move outward, and fade instead of vanishing abruptly.
- The chosen node changes into the current node without being replaced by a new visual object.
- The camera pans and scales to centre the selected world position.
- Existing connective geometry remains coherent throughout the shift.
- Input is temporarily locked during the transition to prevent duplicate selection.

US 16 Continue into nearby consequences

User story As a person following a path, I want its next credible options ready together so that local AI latency does not break the flow.

Acceptance criteria

- The system prefetches expansions for up to three nearby branches after the current level is received.
- Selecting a prefetched branch uses the cached expansion rather than launching a duplicate request.
- The next level presents up to three compact child labels for smooth mobile exploration.
- If expansion is still running, the selected-node transition provides enough cinematic time to mask ordinary latency.
- If expansion fails, the current tree remains intact and the person receives a retryable message.

US 17 Fit larger forks

User story As a person whose decision has many credible alternatives, I want the graph to adapt so that choices remain readable and tappable.

Acceptance criteria

- For four branches, world-space spacing increases and the camera zooms out modestly.
- For five or more branches, spacing and camera scale increase again.
- Labels are not compressed into unreadable text to preserve the default camera framing.
- Node hit areas remain at least 44 by 44 CSS pixels at the active zoom.

7 Epic E Reverse and trust the exploration

US 18 Undo one decision

User story As a person who wants to compare another route, I want to undo one branch selection so that exploration never feels like commitment.

Acceptance criteria

- Undo becomes visible only after at least one branch has been followed.
- Activating Undo removes only the current child level and restores the previous alternatives.
- The previous current node, branch paths, caption state, and camera coordinates are restored seamlessly.
- Undo does not refresh the page, restart analysis, or reconstruct the entire graph.
- Undo hides again when history becomes empty.

US 19 Know what the AI knows

User story As a person making a meaningful choice, I want facts, evidence, assumptions, and human unknowns kept distinct so that I do not mistake generated possibilities for truth.

Acceptance criteria

- Every factor and node is classified as user fact, evidence, assumption, or human unknown.
- The product does not display invented probabilities or imply certainty.

- Assumptions and human unknowns are editable in a future slice without changing the graph contract.
- The product language describes paths as plausible and exploratory, not predicted outcomes.

US 20 Use the journey accessibly

User story As a person using touch, keyboard, screen reader, or reduced motion, I want equivalent access so that the experience does not depend on animation alone.

Acceptance criteria

- Every branch is exposed as an operable button with an accessible label containing its short label and summary.
- Enter and Space select a focused branch.
- Scene changes and errors are announced politely without repeatedly interrupting the user.
- Reduced motion shortens staged animations while preserving the order and meaning of each state change.
- Text, paths, controls, and focus indicators meet mobile contrast and visibility requirements.

8 AI and data contract

The backend returns meaning; the frontend owns choreography. Provider output is normalised and validated before rendering.

Object	Required behavior	Constraint
Input	Natural-language situation and locale	12 to 6000 trimmed characters
Keywords	Specific concepts grounded in the input	1 to 8 items; 48 characters each
Factors	Facts, evidence, assumptions, and unknowns	At least one factor; editable by default
Root node	Distilled decision question and user context	One root referenced by rootNodeId
Choice node	Compact path label with concise summary	Label up to 48; summary up to 320
Expansion	Children of a selected path	1 to 6 contractually; UI normalises first nearby set

8.1 Grounding model

Grounding kind	Meaning	Product treatment
user_fact	Directly supplied by the person	Treat as current context; allow correction
evidence	Obtained from a named source	Show provenance when evidence retrieval is added
assumption	Modelled possibility	Keep editable and never present as fact
human_unknown	A value or missing answer only the person can supply	Return the question to the person

8.2 Provider behavior

- Ollama and LM Studio adapters must return the shared structured schema.
- Direct either-or input is normalised into the exact named alternatives.
- General decisions are capped at a small set of distinct root branches.
- Expanded labels are compacted to approximately three words and 22 characters for the mobile graph.

- Analysis and expansion requests are cached per decision and node during the active journey.

9 Motion and spatial acceptance

Moment	Required motion	Failure to avoid
Keyword arrival	Rise, overshoot, settle, pause	Random floating or simultaneous popping
Keyword exit	Sequential lift, growth, blur, fade	Abrupt disappearance
Passage exit	Slow fade and slight rise	Immediate logo collision
Logo to seed	Pinned dot expands in place	Dot moving between coordinate systems
Branch reveal	Path draws before node arrives	Nodes popping without connection
Selection	Rejected siblings dissolve; chosen node persists	Whole scene replacement
Camera	Pan and zoom the shared SVG viewBox	Moving nodes separately from paths
Undo	Reverse camera and restore prior fork	Refresh or graph reconstruction

9.1 Timing guidance

Spatial movement uses cubic-bezier(.22, 1, .36, 1). Timings may be tuned through usability testing, but the relative order is mandatory: explain, transform, reveal, then enable interaction. The interface must never enable a branch before its node is visible and stable.

10 Failure and edge cases

Condition	Expected response
Empty or very short input	Keep the invitation active and ask for enough context without starting analysis.
Unsupported speech recognition	Explain the limitation and preserve the fully functional text path.
Microphone permission denied	Show a specific permission message and leave text input available.
Analysis service unavailable	Return to invitation with a calm retry message; do not fake a graph.
Provider returns malformed JSON	Reject it during schema validation and handle as analysis failure.
No meaningful branches	Use a deterministic local fallback or ask for clarification; never render an empty graph.
Slow expansion	Use prefetch and transition time; keep the selected node and existing graph stable.
Expansion failure	Unlock input, retain the current tree, and show a retryable path error.
Rapid repeated taps	Ignore additional choices while the transition lock is active.
Viewport is narrow	Keep the phone canvas clipped and move detail into the fixed caption area.

11 Definition of done for MVP

- A person can complete the journey using either voice or text.
- The rendered keywords are specific to the submitted story.
- Direct comparisons produce the exact named first branches.
- The cinematic passage, logo, centred-dot growth, and decision seed occur in the intended order.
- The graph supports a variable number of branches without overlap or viewport escape.
- Branch details remain concise and contained in the fixed caption region.
- Selecting a path preserves one continuous spatial tree and expands the next level.
- Undo restores the previous fork without a page refresh or re-analysis.
- AI output is validated and grounded using the shared contract.
- Keyboard, screen-reader, touch, and reduced-motion paths are testable.
- All primary error states preserve a route to retry or use text input.

11.1 Product acceptance scenarios

Scenario	Input or condition	Expected outcome
Career relocation	A better job in Bangalore means leaving my family. Should I go?	Specific keywords; root Move to Bangalore; credible Go, Stay, Negotiate paths.
Direct platform choice	Android or iOS?	Keywords Android and iOS; root Android or iOS; branches Android and iOS.
Uncertain action	Should I launch now or learn more first?	Named alternatives preserved; expanded path offers small reversible next steps.
Voice unavailable	Browser without speech recognition	Actionable fallback message; full typed journey remains available.
Large fork	AI returns five distinct options	Wider world positions and zoomed-out camera; labels and hit areas remain usable.

11.2 Release boundaries

The MVP is complete when the journey is coherent and reversible. It is not required to recommend one optimal choice, assign probabilities, store decisions across devices, retrieve external evidence, or generate a dashboard. Those capabilities must not be simulated with unsupported claims.

12 Story traceability

Epic	Stories	Primary verification area
Capture	US 01 to US 04	Invitation, voice, text, errors, reset
Interpretation	US 05 to US 09	Listening, keywords, structured response, direct alternatives
Transformation	US 10 to US 12	Passage, logo, centred dot, decision seed
Exploration	US 13 to US 17	Variable branches, detail, selection, expansion, camera
Trust and recovery	US 18 to US 20	Undo, grounding, accessibility