

# I. Highlighting content

## Note.

*The environments presented in this section <sup>a</sup> add a short title indicating the type of information provided. This short text will always be translated into the language indicated when the `tutodoc` package is loaded.*

<sup>a</sup>The formatting comes from the `keytheorems` package.

## 1. Content in the reading flow

### Important.

*All the environments presented in this section share the same counter.*

### i. Examples

Numbered examples, if required, are indicated via `\begin{tdocexa} ... \end{tdocexa}`, which offers an optional argument for adding a mini-title. Here are two possible uses.

```
\begin{tdocexa}
  An example...
```

```
\end{tdocexa}
```

```
\begin{tdocexa}[Mini title]
```

```
  Useful?
```

```
\end{tdocexa}
```

**Example 1.** *An example...*

**Example 2** (Mini title). *Useful?*

### Important.

*The numbering of the examples is reset to zero as soon as a section with a level at least equal to a `\subsubsection` is opened.*

### Tip.

*It can sometimes be useful to return to the line at the start of the content. The code below shows how to proceed (this trick also applies to the `tdocrem` environment presented next). Note in passing that the numbering follows that of the previous example as desired.*

```
\begin{tdocexa}
  \leavevmode
  \begin{enumerate}
    \item Point 1.

    \item Point 2.
  \end{enumerate}
\end{tdocexa}
```

**Example 3.**

*1. Point 1.*

*2. Point 2.*