

# I. Use cases in L<sup>A</sup>T<sub>E</sub>X

Documenting a package or class is best done through use cases showing both the code and the corresponding result.<sup>1</sup>

## Caution.

Version 3 of `minted` cannot be used at the moment, as it contains bugs: see <https://github.com/gpoore/minted/issues/401>. We therefore force the use of version 2 of `minted`.

## 1. “*Inline*” codes

The `\tdocinlatex` macro<sup>2</sup> can be used to type inline code in a similar way to `\verb` or like a standard macro (see brace management in the last case below). Here are some examples.

|   |                 |   |
|---|-----------------|---|
| 1: <code>\tdocinlatex \$a^b = c\$ </code>               | <code>\\</code> | 1: $a^b = c$                              |
| 2: <code>\tdocinlatex+\tdocinlatex \$a^b = c\$ +</code> | <code>\\</code> | 2: <code>\tdocinlatex \$a^b = c\$ </code> |
| 3: <code>\tdocinlatex{\tdocinlatex{\$a^b = c\$}}</code> |                 | 3: <code>\tdocinlatex{\$a^b = c\$}</code> |

## Note.

The `\tdocinlatex` macro can be used in a footnote: see below.<sup>a</sup> In addition, a background color is deliberately used to subtly highlight the codes `LaTeX`.

<sup>a</sup> `$minted = TOP$` has been typed `\tdocinlatex+$minted = TOP$+` in this footnote...

## 2. Directly typed codes

**Example I.1** (Side by side). Using `\begin{tdoclatex}[sbs] ... \end{tdoclatex}`, we can display a code and its rendering side by side. Consider the following code.

```
\begin{tdoclatex}[sbs]
  $A = B + C$
\end{tdoclatex}
```

This will produce the following.

|             |             |
|-------------|-------------|
| $A = B + C$ | $A = B + C$ |
|-------------|-------------|

**Example I.2** (Following). `\begin{tdoclatex} ... \end{tdoclatex}` produces the following result, which corresponds to the default option `std`.<sup>3</sup>

|             |
|-------------|
| $A = B + C$ |
| $A = B + C$ |

**Example I.3** (Just the code). Via `\begin{tdoclatex}[code] ... \end{tdoclatex}`, we'll just get the code as shown below.

|             |
|-------------|
| $A = B + C$ |
|-------------|

<sup>1</sup>Code is formatted using the `minted` package.

<sup>2</sup>The name of the macro `\tdocinlatex` comes from “*in-line* L<sup>A</sup>T<sub>E</sub>X”.

<sup>3</sup>`std` refers to the “*standard*” behaviour of `tcolorbox` in relation to the `minted` library.

⚠ Warning.

With default formatting, if the code begins with an opening bracket, the default option must be explicitly indicated. Consider the following code.

```
\begin{tdoclatex}[std]
  [Strange... Or not!]
\end{tdoclatex}
```

This will produce the following.

[Strange... Or not!]

[Strange... Or not!]

Another method is to use the `\string` primitive. Consider the following code.

```
\begin{tdoclatex}
  \string[Strange... Or not!]
\end{tdoclatex}
```

This will produce the following.

[Strange... Or not!]

[Strange... Or not!]