

$O(1) < O(\log n) < O(n) < O(n \log n) < \dots < O(2^n n) < O(n!)$

Operation	Linked List	Array	Time Trade Offs
-----------	-------------	-------	-----------------

Insertion	$O(1)$	$O(n)$	
-----------	--------	--------	--

Deletion	$O(1)$	$O(n)$	
----------	--------	--------	--

Lookup	$O(n)$	$O(1)$	
--------	--------	--------	--

```
for (int i = 1; i < n; i++) {
    for (int j = i; j >= 0; j--) {
        System.out.println("Hello World!");
    }
}
```

$O(f(n)) = O(n^2)$ ;  $T(n) = (n(n+1)/2 - 1$

```
public static Node max(Node list) {
    if (list == null) {
        throw new IllegalArgumentException("Cannot
            find max of empty list.");
    }
    Node maxNode = null;
    Node curr = list;
    int val, max = curr.data;
    while (curr != null) {
        val = curr.data;
        if (val > max) {
            max = val;
            maxNode = curr;
        }
        curr = curr.next;
    }
    return maxNode;
}
```

```
public static Node maxify(Node list) {
    if (list == null) {
        return null;
    }
    Node maxNode = max(list);
    Node curr = list;
    Node holder = curr;
    while (curr.next != maxNode) {
        curr = curr.next;
    }
    curr.next = curr.next.next;
    maxNode.next = holder;
    return maxNode;
}
```

```
// Data fields
private Node<E> head;
private int size;

// Constructor
SingleLL() {
    head=null;
    size=0;
}

// Methods
public boolean isEmpty() {
    return size==0;
}

public void addFirst(E item) {
    head = new Node<E>(item,head);
    size++;
}

public void addLast(E item) {
    if (head==null) {
        this.addFirst(item);
    } else {
        Node<E> current = head;

        while (current.next!=null) {
            current=current.next;
        }

        current.next = new Node<E>(item,
            current.next);
        size++;
    }
}

public E get(int index) {
    if (index<0 || index>size-1) {
        throw new IllegalArgumentException
            ("Index out of bounds");
    }
    Node<E> current = head;

    for(int i=0; i<index; i++) {
        current = current.next;
    }

    return current.data;
}
```

```
// Data fields
private Node<E> head;
private int size;

// Constructor
SingleLL() {
    head=null;
    size=0;
}

// Methods
public boolean isEmpty() {
    return size==0;
}

public void addFirst(E item) {
    head = new Node<E>(item,head);
    size++;
}

public void addLast(E item) {
    if (head==null) {
        this.addFirst(item);
    } else {
        Node<E> current = head;

        while (current.next!=null) {
            current=current.next;
        }

        current.next = new Node<E>(item,
            current.next);
        size++;
    }
}

public E get(int index) {
    if (index<0 || index>size-1) {
        throw new IllegalArgumentException
            ("Index out of bounds");
    }
    Node<E> current = head;

    for(int i=0; i<index; i++) {
        current = current.next;
    }

    return current.data;
}

public static ArrayList<Integer> toBinary(int i) {
    ArrayList<Integer> result = new ArrayList<Integer>();
    StackLL<Integer> binaryStack = new StackLL<Integer>();

    if (i==0) {
        result.add(0);
        return result;
    }

    while(i>0) {
        binaryStack.push(i%2);
        i=i/2;
    }

    int size = binaryStack.size();
    for (int j =0; j<size; j++) {
        result.add(binaryStack.pop());
    }

    return result;
}
```

```
private void fillStack() {
    for (int i=0; i<inputString.length(); i++) {
        charStack.push(inputString.charAt(i));
    }
}

private String buildReverse() {
    StringBuilder s = new StringBuilder();

    while (!charStack.empty()) {
        s.append(charStack.pop());
    }

    return s.toString();
}

public boolean isPalindrome() {
    return inputString.replaceAll("\\s+", "").equalsIgnoreCase
        (this.buildReverse().replaceAll("\\s+", ""));
}
```

that increments in one unit the priority of every node whose current priority is lower\_bound or more. Note that the list is not sorted in any way. What is the time complexity of your implementation?

that increments in one unit the priority of every node whose current priority is lower\_bound or more. Note that the list is not sorted in any way. What is the time complexity of your implementation?

```
public int top_priority() {
    NodeP<E> current = this;
    int max = current.priority;

    while(current != null) {
        max = Math.max(max, current.top_priority());
        current = current.next;
    }

    return max;
}

public void bump_if(int lower_bound) {
    NodeP<E> current = this;

    while(current != null) {
        if (current.priority > lower_bound) {
            current.priority++;
        }
        current = current.next;
    }
}
```

```
public E removeFirst() {
    if (head==null) {
        throw new IllegalStateException();
    }
    E temp = head.data;
    head = head.next;
    size--;
    return temp;
}

public E removeLast() {
    if (size==0) { // empty list
        throw new IllegalStateException();
    }
    if (size==1) { // singleton list
        return this.removeFirst();
    }
    // list has two or more elements
    Node<E> current=head;

    while(current.next.next!=null) {
        current=current.next;
    }
    E temp = current.next.data;
    size--;
    current.next = null;
    return temp;
}
```

```
public E remove(int index) {
    if (index<0 || index>size-1) {
        throw new IllegalArgumentException();
    }
    if (size==1) {
        return this.removeFirst();
    } else {
        Node<E> current=head;
        Node<E> previous=head;

        for (int i=0; i<index; i++) {
            previous = current;
            current = current.next;
        }
        E temp = current.data;
        size--;
        previous.next = current.next;
        return temp;
    }
}
```

```
public E push(E item) {
    stack = new Node<E>(item,stack);
    ;
    item;
}

peek() {
    if (size==0) {
        throw new EmptyStackException();
    }
    return stack.data;
}

public E pop() {
    if (size==0) {
        throw new EmptyStackException();
    }
    E temp = stack.data;
    stack = stack.next;
    size--;
    return temp;
}

public boolean empty() {
    return size==0;
}

//Complete
StackLL<Character> s = new StackLL<Character>();
int i = 0;
boolean balanced = true;

while (i<expression.length() && balanced) {
    if (isOpen(expression.charAt(i))) {
        // opening delimiter
        s.push(expression.charAt(i));
    } else {
        //closing delimiter
        balanced = !s.empty() && OPEN.indexOf(s.pop()) == CLOSE.indexOf(expression.charAt(i));
    }
    i++;
}
return balanced && s.empty();
}

private static boolean isOpen(char ch) {
    return OPEN.indexOf(ch) > -1;
}

private static boolean isClose(char ch) {
    return CLOSE.indexOf(ch) > -1;
}
```

```
public boolean member(E item) {
    Node<E> current=head;

    while (current!=null && !current.data.equals(item)) {
        current = current.next;
    }

    return current!=null;
}

public SingleLL<E> take(int n) {
    SingleLL<E> l = new SingleLL<E>();
    int i = 0;
    Node<E> current = head;

    while (current!=null && i<n) {
        l.addLast(current.data);
        current = current.next;
        i++;
    }

    return l;
}

public SingleLL<E> take2(int n) {
    SingleLL<E> l = new SingleLL<E>();
    int i = 0;
    Node<E> current = head;
    Node<E> last = new Node<E>();
    Node<E> newHead = last;

    while (current!=null && i<n) {
        last.next = new Node<E>(current.data);
        last = last.next;
        current = current.next;
        i++;
    }
    l.head = newHead.next;
    l.size = i;
    return l;
}

public boolean hasRepetitions() {
    Node<E> current=head;

    while (current!=null
        && !member(current.next,current.data)) {
        current=current.next;
    }

    return current!=null;
}

public void stutter() {
    Node<E> current = head;

    while (current!=null) {
        current.next = new
            Node<E>(current.data,current.next);
        current = current.next.next;
    }
}
```