
Physical Data Diagram (Sprint 5)

3-05-2024 by DbSchema.com - Wise Coders



Physical Data Diagram (Sprint 5)

Table	Table dss_access_request_status				
ldx	Name	Data Type	Description		
A potential status for a user access request (e.g. Requested, Approved, or Denied)					
* Pk	access_request_status_cd	varchar(25)	System-consistent code for the request status		
*	access_request_status_nm	varchar(250)	Business term for the request status		
Indexe	es				
Туре	Name	On	Description		
Pk	dss_access_request_status_pk	access_request_status_cd			

	e dss_email_message	D. C. T.	D 14
ldx	Name	Data Type	Description
	sage that is sent to one or more re	•	
* Pk	email_message_id	bigint GENERATED ALWAYS AS IDENTITY	Unique generated key
k	email_message_type	varchar(50)	Foreign key
k	message_delivery_dtm	timestamptz	A timestamp indicating when the message delivery was initiated
	message_template_dsc	varchar(4000)	The full text or template for the message that is sent
ŧ	is_submitter_cc_required	boolean	Indicates whether the user initiating the message should receive a copy of the email
	is_host_contacted_externally	boolean	Indicates whether the the property host has already been contacted by external means
	lg_phone_no	varchar(30)	A phone number associated with a Local Government contact
	unreported_listing_no	varchar(50)	The platform issued identification number for the listing (if not included in a rental listing report)
	host_email_address_dsc	varchar(320)	E-mail address of a short term rental host (directly entered by the user as a message recipient)
	lg_email_address_dsc	varchar(320)	E-mail address of a local government contact (directly entered by the user as a message recipient)
	cc_email_address_dsc	varchar(4000)	E-mail address of a secondary message recipient (directly entered by the user)
	unreported_listing_url	varchar(4000)	User-provided URL for a short-term rental platform listing that is the subject of the message
	lg_str_bylaw_url	varchar(4000)	User-provided URL for a local government bylaw that is the subject the message
	concerned_with_rental_listing_id	bigint	Foreign key
	initiating_user_identity_id	bigint	Foreign key
	affected_by_user_identity_id	bigint	Foreign key
	involved_in_organization_id	bigint	Foreign key
	batching_email_message_id	bigint	Foreign key
	requesting_organization_id	bigint	Foreign key
	message_reason_id	bigint	Foreign key
	external_message_no	varchar(50)	External identifier for tracking the message delivery progress
	upd_dtm	timestamptz	Trigger-updated timestamp of last change
	upd_user_guid	uuid	The globally unique identifier (assigned by the identity provider) for the most recent user to record a change
ndexe	es		
Гуре	Name	On	Description
⊃k	dss_email_message_pk	email_message_id	
Foreig	n Keys		
Гуре	Name	On	Description

Table (Table dss_email_message				
ir	lss_email_message_fk_initiated_ nitiating_user_identity_id) ref dss ıser_identity_id)	by(_user_identity(
а	lss_email_message_fk_affecting iffected_by_user_identity_id) ref iser_identity_id)	(dss_user_identity (
ir	lss_email_message_fk_involving nvolved_in_organization_id)ref c organization_id)	(lss_organization (
е	lss_email_message_fk_communi email_message_type) ref dss_em email_message_type)				
	lss_email_message_fk_justified_l ef dss_message_reason(messa				
b	lss_email_message_fk_batched_ patching_email_message_id) ref email_message_id)				
re	lss_email_message_fk_requested equesting_organization_id) ref ds organization_id)				
С	lss_email_message_fk_included_ concerned_with_rental_listing_id) ental_listing_id)	in(ref dss_rental_listing(
Triggers	3				
N	Name	Definition	Description		

Table dss_email_	_message_type	

EXECUTE FUNCTION dss.dss_update_audit_columns()

dss_email_message_br_iu_tr

ldx	Name	Data Type	Description
	type or purpose of a system gener ess Granted Notification, Access De		f Takedown, Takedown Request, Delisting Warning, Delisting Request,

CREATE TRIGGER dss_email_message_br_iu_tr BEFORE INSERT OR UPDATE ON dss.dss_email_message FOR EACH ROW

* Pk email_message_type varchar(50)

System-consistent code for the type or purpose of the message (e.g. Notice of Takedown, Takedown Request, Delisting Warning, Delisting Request, Access Granted Notification, Access Denied Notification)

* email_message_type_nm varchar(250)

Business term for the type or purpose of the message (e.g. Notice of

email_message_type_nm varchar(250) Business term for the type or purpose of the message (e.g. Notice of Takedown, Takedown Request, Delisting Warning, Delisting Request, Access Granted Notification, Access Denied Notification)

Indexes

Type Name On Description

Pk dss_email_message_type_pk email_message_type

Table	Table dss_message_reason			
ldx	Name	Data Type	Description	
A des	cription of the justification for initiati	ng a message		
* Pk	message_reason_id	bigint GENERATED ALWAYS AS IDENTITY	Unique generated key	
*	email_message_type	varchar(50)	Foreign key	
*	message_reason_dsc	varchar(250)	A description of the justification for initiating a message	
Index	es			
Туре	Name	On	Description	
Pk	dss_message_reason_pk	message_reason_id		
Foreign Keys				
Туре	Name	On	Description	
	dss message reason fk justifying (email message type)			

dss_message_reason_fk_justifying (email_message_type) ref dss_email_message_type (email_message_type)

CREATE TRIGGER dss_organization_br_iu_tr BEFORE INSERT OR UPDATE ON dss.dss_organization FOR EACH ROW EXECUTE FUNCTION dss.dss_update_audit_columns()

dss_organization_br_iu_tr

Table	Table dss_organization_contact_person				
ldx	Name	Data Type	Description		
A pers	son who has been identified as a no	table contact for a particular	organization		
* Pk	organization_contact_person_id	bigint GENERATED ALWAYS AS IDENTITY	Unique generated key		
	is_primary	boolean	Indicates whether the contact should receive all communications directed at the organization		
	given_nm	varchar(25)	A name given to a person so that they can easily be identified among their family members (in some cultures, this is often the first name)		
	family_nm	varchar(25)	A name that is often shared amongst members of the same family (commonly known as a surname within some cultures)		
	phone_no	varchar(30)	Phone number given for the contact by the organization (contains only digits)		
*	email_address_dsc	varchar(320)	E-mail address given for the contact by the organization		
*	contacted_through_organization_i d	bigint	Foreign key		
*	upd_dtm	timestamptz	Trigger-updated timestamp of last change		
	upd_user_guid	uuid	The globally unique identifier (assigned by the identity provider) for the most recent user to record a change		
	email_message_type	varchar(50)	Foreign key		
Indexe	es				
Type	Name	On	Description		
Pk	dss_organization_contact_person _pk	organization_contact_pers on_id			
Foreig	Foreign Keys				

Table	Table dss_organization_contact_person			
Туре	Name	On	Description	
	<pre>dss_organization_contact_person_fk_contacted_for (contacted_through_organization_id) ref dss_organization (organization_id)</pre>			
	dss_organization_contact_person_fk_subscribed_to (email_message_type) ref dss_email_message_type (email_message_type)			
Triage	Triggore			

Triggers

Name	Definition	Description	
dss_organization_conta _br_iu_tr	ct_person		

 $\label{local_contact_person_br_iu_tr} CREATE\ TRIGGER\ dss_organization_contact_person_br_iu_tr\ BEFORE\ INSERT\ OR\ UPDATE\ ON\ dss.dss_organization_contact_person\ FOR\ EACH\ ROW\ EXECUTE\ FUNCTION\ dss.dss_update_audit_columns()$

Tabl	Table dss_organization_type				
ldx	Name	Data Type	Description		
A level of government or business category					
* Pk	organization_type	varchar(25)	System-consistent code for a level of government or business category		
*	organization_type_nm	varchar(250)	Business term for a level of government or business category		
Indexes					
Туре	Name	On	Description		
Pk	dss_organization_type_pk	organization_type			

Tabl	Fable dss_physical_address				
ldx	Name	Data Type	Description		
A pro	perty address that includes any ver	ifiable BC attributes			
* Pk	physical_address_id	bigint GENERATED ALWAYS AS IDENTITY	Unique generated key		
*	original_address_txt	varchar(250)	The source-provided address of a short-term rental offering		
	match_result_json	json	Full JSON result of the source address matching attempt		
	match_address_txt	varchar(250)	The sanitized physical address (returned as fullAddress) that has been derived from the original		
	match_score_amt	smallint	The relative score returned from the address matching attempt		
	unit_no	varchar(50)	The unitNumber (suite) returned by the address match (e.g. 100)		
	civic_no	varchar(50)	The civicNumber (building number) returned by the address match (e.g. 1285)		
	street_nm	varchar(50)	The streetName returned by the address match (e.g. Pender)		
	street_type_dsc	varchar(50)	The streetType returned by the address match (e.g. St or Street)		
	street_direction_dsc	varchar(50)	The streetDirection returned by the address match (e.g. W or West)		
	locality_nm	varchar(50)	The localityName (community) returned by the address match (e.g. Vancouver)		
	locality_type_dsc	varchar(50)	The localityType returned by the address match (e.g. City)		
	province_cd	varchar(5)	The provinceCode returned by the address match		
	site_no	varchar(50)	The siteID returned by the address match		
	block_no	varchar(50)	The blockID returned by the address match		
	location_geometry	geometry	The computed location point of the matched address		
	is_exempt	boolean	Indicates whether the address has been identified as exempt from Short Term Rental regulations		
	containing_organization_id	bigint	Foreign key		
	replacing_physical_address_id	bigint	Foreign key		
*	upd_dtm	timestamptz	Trigger-updated timestamp of last change		

Table dss_physical_address				
	upd_user_guid	uuid	The globally unique identifier (assigned by the identity provider) for the most recent user to record a change	
Indexe	es			
Туре	Name	On	Description	
Pk	dss_physical_address_pk	physical_address_id		
Foreign Keys				
Туре	Name	On	Description	
	dss_physical_address_fk_contained_in (containing_organization_id) ref dss_organization (organization_id)			
	dss_physical_address_fk_replaced_by (replacing_physical_address_id) ref dss_physical_address (physical_address_id)			
Triggers				
	Name	Definition	Description	
	dss_physical_address_br_iu_tr			

 $\label{local_continuity} CREATE\ TRIGGER\ dss_physical_address_br_iu_tr\ BEFORE\ INSERT\ OR\ UPDATE\ ON\ dss.dss_physical_address\ FOR\ EACH\ ROW\ EXECUTE\ FUNCTION\ dss.dss_update_audit_columns()$

Name	Data Type	Description	
A rental listing snapshot that is either relevant to a specific monthly report, or is the current, master version			
rental_listing_id	bigint GENERATED ALWAYS AS IDENTITY	Unique generated key	
platform_listing_no	varchar(50)	The platform issued identification number for the listing	
platform_listing_url	varchar(4000)	URL for the short-term rental platform listing	
business_licence_no	varchar(50)	The local government issued licence number that applies to the rental offering	
bc_registry_no	varchar(50)	The Short Term Registry issued permit number	
is_current	boolean	Indicates whether the listing version is the most current one (within the same listing number for the same offering platform)	
is_taken_down	boolean	Indicates whether a current listing is no longer considered active	
is_entire_unit	boolean	Indicates whether the entire dwelling unit is offered for rental (as opposed to a single bedroom)	
available_bedrooms_qty	smallint	The number of bedrooms in the dwelling unit that are available for short term rental	
nights_booked_qty	smallint	The number of nights that short term rental accommodation services were provided during the reporting period	
separate_reservations_qty	smallint	The number of separate reservations that were taken during the reporting period	
offering_organization_id	bigint	Foreign key	
including_rental_listing_report_id	bigint	Foreign key	
derived_from_rental_listing_id	bigint	Foreign key	
locating_physical_address_id	bigint	Foreign key	
upd_dtm	timestamptz	Trigger-updated timestamp of last change	
upd_user_guid	uuid	The globally unique identifier (assigned by the identity provider) for the most recent user to record a change	
es			
Name	On	Description	
dss_rental_listing_pk	rental_listing_id		
ın Keys			
Name	On	Description	
dss_rental_listing_fk_offered_by (
	al listing snapshot that is either releated rental_listing_id platform_listing_no platform_listing_url business_licence_no bc_registry_no is_current is_taken_down is_entire_unit available_bedrooms_qty nights_booked_qty separate_reservations_qty offering_organization_id including_rental_listing_report_id derived_from_rental_listing_id locating_physical_address_id upd_dtm upd_user_guid ss Name dss_rental_listing_pk In Keys Name	al listing snapshot that is either relevant to a specific monthly re rental_listing_id bigint GENERATED ALWAYS AS IDENTITY platform_listing_no varchar(50) platform_listing_url varchar(4000) business_licence_no varchar(50) bc_registry_no varchar(50) is_current boolean is_taken_down boolean is_entire_unit boolean available_bedrooms_qty smallint nights_booked_qty smallint separate_reservations_qty smallint offering_organization_id bigint including_rental_listing_report_id bigint derived_from_rental_listing_id bigint upd_dtm timestamptz upd_user_guid uuid ass Name On dss_rental_listing_pk rental_listing_id in Keys Name On	

Table dss_rental_listing

rental_listing_id)

```
dss_rental_listing_fk_included_in ( including_rental_listing_report_id ) ref
dss_rental_listing_report ( rental_listing_report_id )
dss_rental_listing_fk_located_at (
locating_physical_address_id ) ref dss_physical_address ( physical_address_id )
dss_rental_listing_fk_generating ( derived_from_rental_listing_id ) ref dss_rental_listing (
```

Triggers

Definition Name Description

dss_rental_listing_br_iu_tr

CREATE TRIGGER dss_rental_listing_br_iu_tr BEFORE INSERT OR UPDATE ON dss.dss_rental_listing FOR EACH ROW EXECUTE FUNCTION dss.dss_update_audit_columns()

ldx	Name	Data Type	Description
A person who has been identified as a notable contact for a particular rental listing			
* Pk	rental_listing_contact_id	bigint GENERATED ALWAYS AS IDENTITY	Unique generated key
*	is_property_owner	boolean	Indicates a person with the legal right to the unit being short-term rental
	listing_contact_nbr	smallint	Indicates which of the five possible supplier hosts is represented by this contact
	supplier_host_no	varchar(50)	The platform identifier for the supplier host
	full_nm	varchar(50)	The full name of the contact person as inluded in the listing
	phone_no	varchar(30)	Phone number given for the contact
	fax_no	varchar(30)	Facsimile numbrer given for the contact
	full_address_txt	varchar(250)	Mailing address given for the contact
	email_address_dsc	varchar(320)	E-mail address given for the contact
*	contacted_through_rental_listing_ id	bigint	Foreign key
k	upd_dtm	timestamptz	Trigger-updated timestamp of last change
	upd_user_guid	uuid	The globally unique identifier (assigned by the identity provider) for the most recent user to record a change
Index	es		
Туре	Name	On	Description
Pk	dss_rental_listing_contact_pk	rental_listing_contact_id	
Forei	gn Keys		
Туре	Name	On	Description
	dss_rental_listing_contact_fk_concontacted_through_rental_listing_rental_listing_id)	tacted_for(id)ref dss_rental_listing(
Trigge	ers		
	Name	Definition	Description
	dss_rental_listing_contact_br_iu_t		

CREATE TRIGGER dss_rental_listing_contact_br_iu_tr BEFORE INSERT OR UPDATE ON dss.dss_rental_listing_contact FOR EACH ROW EXECUTE FUNCTION dss.dss_update_audit_columns()

Table dss_rental_listing_report

Description ldx Name Data Type

A platform-specific collection of rental listing information that is relevant to a specific month

Unique generated key

* Pk rental_listing_report_id bigint GENERATED ALWAYS AS IDENTITY

Table	Table dss_rental_listing_report			
*	report_period_ym	date	The month to which the listing information is relevant (always set to the first day of the month)	
*	is_current	boolean	Indicates whether the rental listing version is the most recent one reported by the platform	
*	providing_organization_id	bigint	Foreign key	
*	upd_dtm	timestamptz	Trigger-updated timestamp of last change	
	upd_user_guid	uuid	The globally unique identifier (assigned by the identity provider) for the most recent user to record a change	
Indexes				
Type	Name	On	Description	
Pk	dss_rental_listing_report_pk	rental_listing_report_id		
Foreig	gn Keys			
Type	Name	On	Description	
	dss_rental_listing_report_fk_providing_organization_id) ref dss organization_id)	ded_by(s_organization(
Triggers				
	Name	Definition	Description	
	dss_rental_listing_report_br_iu_tr			

 $\label{listing_report_br_iu_tr} \begin{tabular}{l} CREATE TRIGGER dss_rental_listing_report_br_iu_tr BEFORE INSERT OR UPDATE ON dss.dss_rental_listing_report FOR EACH ROW EXECUTE FUNCTION dss.dss_update_audit_columns() \\ \end{tabular}$

	e dss_upload_delivery		
ldx	Name	Data Type	Description
A deli	very of uploaded information that	is relevant to a specific month	
* Pk	upload_delivery_id	bigint GENERATED ALWAYS AS IDENTITY	Unique generated key
*	upload_delivery_type	varchar(25)	Identifies the treatment applied to ingesting the uploaded information
	report_period_ym	date	The month to which the delivery batch is relevant (always set to the first day of the month)
*	source_hash_dsc	varchar(256)	The hash value of the information that was uploaded
	source_bin	bytea	The binary image of the information that was uploaded
*	providing_organization_id	bigint	Foreign key
*	upd_dtm	timestamptz	Trigger-updated timestamp of last change
	upd_user_guid	uuid	The globally unique identifier (assigned by the identity provider) for the most recent user to record a change
Index	es		
Туре	Name	On	Description
Pk	dss_upload_delivery_pk	upload_delivery_id	
Foreig	gn Keys		
Туре	Name	On	Description
	dss_upload_delivery_fk_provide providing_organization_id) ref corganization_id)	ed_by(dss_organization(
Trigge	ers		
	Name	Definition	Description
	dss_upload_delivery_br_iu_tr		

EXECUTE FUNCTION ass.ass_update_audit_columns()		

Tab	Table dss_upload_line				
ldx	Name	Data Type	Description		

Table	e dss_upload_line		
* Pk	upload_line_id	bigint GENERATED ALWAYS AS IDENTITY	Unique generated key
*	is_validation_failure	boolean	Indicates that there has been a validation problem that prevents successful ingestion of the upload line
*	is_system_failure	boolean	Indicates that a system fault has prevented complete ingestion of the upload line
*	is_processed	boolean	Indicates that no further ingestion attempt is required for the upload line
*	source_organization_cd	varchar(25)	An immutable system code identifying the organization who created the information in the upload line (e.g. AIRBNB)
*	source_record_no	varchar(50)	The immutable identification number for the source record, such as a rental listing number
*	source_line_txt	varchar(32000)	Full text of the uploaod line
	error_txt	varchar(32000)	Freeform description of the problem found while attempting to interpret the report line
*	including_upload_delivery_id	bigint	Foreign key
Index	es		
Туре	Name	On	Description
Pk	dss_upload_line_pk	upload_line_id	
Forei	gn Keys		
Туре	Name	On	Description
	dss_upload_line_fk_included_in (including_upload_delivery_id) ref upload_delivery_id)	dss_upload_delivery (

Tabl	Table dss_user_identity				
ldx	Name	Data Type	Description		
An externally defined domain directory object representing a potential application user or group					
* Pk	user_identity_id	bigint GENERATED ALWAYS AS IDENTITY	Unique generated key		
*	user_guid	uuid	An immutable unique identifier assigned by the identity provider		
*	display_nm	varchar(250)	A human-readable full name that is assigned by the identity provider (this may include a preferred name and/or business unit name)		
*	identity_provider_nm	varchar(25)	A directory or domain that authenticates system users to allow access to the application or its API (e.g. idir, bceidbusiness)		
*	is_enabled	boolean	Indicates whether access is currently permitted using this identity		
*	access_request_status_cd	varchar(25)	The current status of the most recent access request made by the user (restricted to Requested, Approved, or Denied)		
	access_request_dtm	timestamptz	A timestamp indicating when the most recent access request was made by the user		
	access_request_justification_txt	varchar(250)	The most recent user-provided reason for requesting application access		
	given_nm	varchar(25)	A name given to a person so that they can easily be identified among their family members (in some cultures, this is often the first name)		
	family_nm	varchar(25)	A name that is often shared amongst members of the same family (commonly known as a surname within some cultures)		
	email_address_dsc	varchar(320)	E-mail address associated with the user by the identity provider		
	business_nm	varchar(250)	A human-readable organization name that is associated with the user by the identity provider		
	terms_acceptance_dtm	timestamptz	A timestamp indicating when the user most recently accepted the published Terms and Conditions of application access		
	represented_by_organization_id	bigint	Foreign key		
*	upd_dtm	timestamptz	Trigger-updated timestamp of last change		
	upd_user_guid	uuid	The globally unique identifier (assigned by the identity provider) for the most recent user to record a change		
Index	es				

Type Name On Description

Pk dss_user_identity_pk user_identity_id

Foreign Keys

Type Name On Description

dss_user_identity_fk_representing (
 represented_by_organization_id) ref dss_organization (
 organization_id)

dss_user_identity_fk_given (access_request_status_cd) ref dss_access_request_status (access_request_status_cd)

Triggers

Name Definition Description

dss_user_identity_br_iu_tr

 $\label{lem:created} \mbox{CREATE TRIGGER dss_user_identity_br_iu_tr BEFORE INSERT OR UPDATE ON dss.dss_user_identity FOR EACH ROW EXECUTE FUNCTION dss.dss_update_audit_columns()$

Table dss_user_privilege				
ldx	Name	Data Type	Description	
A granular access right or privilege within the application that may be granted to a role				
* Pk	user_privilege_cd	varchar(25)	The immutable system code that identifies the privilege	
*	user_privilege_nm	varchar(250)	The human-readable name that is given for the role	
Indexes				
Type	Name	On	Description	
Pk	dss_user_privilege_pk	user_privilege_cd		

Table	Table dss_user_role				
ldx	Name	Data Type	Description		
A set of access rights and privileges within the application that may be granted to users					
* Pk	user_role_cd	varchar(25)	The immutable system code that identifies the role		
*	user_role_nm	varchar(250)	The human-readable name that is given for the role		
Index	es				
Type	Name	On	Description		
Pk	dss_user_role_pk	user_role_cd			

Table	Table dss_user_role_assignment				
ldx	Name	Data Type	Description		
The a	ssociation of a grantee credential to	a role for the purpose of co	nveying application privileges		
* Pk	user_identity_id	bigint	Foreign key		
* Pk	user_role_cd	varchar(25)	Foreign key		
Indexes					
Type	Name	On	Description		
Pk	dss_user_role_assignment_pk	user_identity_id, user_role_cd			
Foreig	gn Keys				
Type	Name	On	Description		
	dss_user_role_assignment_fk_granted (user_role_cd) ref dss_user_role (user_role_cd)				
	dss_user_role_assignment_fk_granted_to (user_identity_id) ref dss_user_identity (user_identity_id)				

Tabl	e dss_user_role_privilege		
ldx	Name	Data Type	Description

Table dss_user_role_privilege					
The a	ssociation of a granular application	privilege to a role			
* Pk	user_privilege_cd	varchar(25)	Foreign key		
* Pk	user_role_cd	varchar(25)	Foreign key		
Indexes					
Туре	Name	On	Description		
Pk	dss_user_role_privilege_pk	user_privilege_cd, user_role_cd			
Forei	gn Keys				
Туре	Name	On	Description		
	dss_user_role_privilege_fk_confe dss_user_role (user_role_cd)	rred_by (user_role_cd) ref			
	dss_user_role_privilege_fk_conferring (user_privilege_cd) ref dss_user_privilege (user_privilege_cd)				

Schema dss

Functions

dss_update_audit_columns