
Physical Data Diagram (Sprint 3) 3-04-2024 by DbSchema.com - Wise Coders



uuid

locating_physical_address_id

upd_dtm upd_user_guid bigin**t**

uuid

timestamptz

upd_user_guid

Physical Data Diagram (Sprint 3)

Table dss_access_request_status		
ldx	Name	Data Type
* Pk	access_request_status_cd	varchar(25)
*	access_request_status_nm	varchar(250)
Indexes	3	
Туре	Name	On
Pk	dss_access_request_status_pk	access_request_status_cd

Table	able dss_email_message			
ldx	Name	Data Type	Description	
A mes	ssage that is sent to one or more re	ecipients via email		
* Pk	email_message_id	bigint GENERATED ALWAYS AS IDENTITY	Unique generated key	
*	email_message_type	varchar(50)	Business term for the type or purpose of the message (e.g. Notice of Takedown, Takedown Request, Delisting Warning, Delisting Request, Access Granted Notification, Access Denied Notification)	
*	message_delivery_dtm	timestamptz	A timestamp indicating when the message delivery was initiated	
*	message_template_dsc	varchar(4000)	The full text or template for the message that is sent	
*	is_host_contacted_externally	boolean		
*	is_submitter_cc_required	boolean		
	message_reason_id	bigint		
	lg_phone_no	varchar(13)		
	unreported_listing_no	varchar(25)		
	host_email_address_dsc	varchar(320)	E-mail address of a short term rental host (directly entered by the user as a message recipient)	
	lg_email_address_dsc	varchar(320)		
	cc_email_address_dsc	varchar(4000)	E-mail address of a secondary message recipient (directly entered by the user)	
	unreported_listing_url	varchar(4000)	User-provided URL for a short-term rental platform listing that is the subject of the message	
	lg_str_bylaw_url	varchar(4000)		
*	initiating_user_identity_id	bigint	Foreign key	
	affected_by_user_identity_id	bigint	Foreign key	
	involved_in_organization_id	bigint	Foreign key	
Indexe	es			
Туре	Name	On	Description	
Pk	dss_email_message_pk	email_message_id		
Foreig	n Keys			
Туре	Name	On	Description	
	dss_email_message_fk_initiated_initiating_user_identity_id) ref dssuser_identity_id)	_by (s_user_identity (
	dss_email_message_fk_affecting affected_by_user_identity_id) ref user_identity_id)	dss_user_identity (
	dss_email_message_fk_involving involved_in_organization_id) ref organization_id)			
	dss_email_message_fk_communicating (email_message_type) ref dss_email_message_type (email_message_type)			
	dss_email_message_fk_justified_ ref dss_message_reason (messa			

Table (Table dss_email_message_type		
ldx	Name	Data Type	
* Pk	email_message_type	varchar(50)	
*	email_message_type_nm	varchar(250)	
Indexes			
Туре	Name	On	
Pk	dss_email_message_type_pk	email_message_type	

Table	Table dss_listing_line_error			
ldx	Name	Data Type	Description	
A rent	al listing report line that could not b	e interpreted as a valid listing	g	
* Pk	listing_line_error_id	bigint GENERATED ALWAYS AS IDENTITY	Unique generated key	
*	error_txt	varchar(4000)	Freeform description of the problem found while attempting to interpret the report line	
*	source_line_txt	varchar(32000)	Full text of the report line that could not be interpreted	
	platform_listing_no	varchar(25)	The platform issued identification number for the listing	
*	including_rental_listing_report_id	bigint	Foreign key	
Indexe	es			
Type	Name	On	Description	
Pk	dss_listing_line_error_pk	listing_line_error_id		
Foreig	n Keys			
Type	Name	On	Description	
	dss_listing_line_error_fk_included_in (including_rental_listing_report_id) ref dss_rental_listing_report (rental_listing_report_id)			

Table	Table dss_message_reason			
ldx	Name	Data Type	Description	
A des	cription of the justification for initiati	ng a message		
* Pk	message_reason_id	bigint GENERATED ALWAYS AS IDENTITY		
*	email_message_type	varchar(50)		
*	message_reason_dsc	varchar(250)	A description of the justification for initiating a message	
Index	es			
Type	Name	On	Description	
Pk	dss_message_reason_pk	message_reason_id		
Foreig	Foreign Keys			
Type	Name	On	Description	
	dss_message_reason_fk_justifying (email_message_type) ref dss_email_message_type (email_message_type)			

Tabl	Table dss_organization			
ldx	Name	Data Type	Description	
A priv	vate company or governing body that	at plays a role in short term re	ental reporting or enforcement	
* Pk	organization_id	bigint GENERATED ALWAYS AS IDENTITY	Unique generated key	
*	organization_type	varchar(25)	a level of government or business category	
*	organization_cd	varchar(25)	An immutable system code that identifies the organization (e.g. CEU, AIRBNB)	
*	organization_nm	varchar(250)	A human-readable name that identifies the organization (e.g. Corporate Enforecement Unit, City of Victoria)	
	local_government_geometry	geometry	the shape identifying the boundaries of a local government	

Table	Table dss_organization			
	managing_organization_id	bigint	Self-referential hierarchical foreign key	
*	upd_dtm	timestamptz	Trigger-updated timestamp of last change	
	upd_user_guid	uuid	The globally unique identifier (assigned by the identity provider) for the most recent user to record a change	
Index	Indexes			
Туре	Name	On	Description	
Pk	dss_organization_pk	organization_id		
Foreig	gn Keys			
Туре	Name	On	Description	
	dss_organization_fk_managed_by (managing_organization_id) ref dss_organization (organization_id)			
	dss_organization_fk_treated_as (organization_type) ref dss_organization_type (organization_type)			
Trigge	Triggers			

Iriggers

Definition Name Description dss_organization_br_iu_tr

 $\label{local_control_control} \textbf{CREATE TRIGGER dss_organization_br_iu_tr BEFORE INSERT OR UPDATE ON dss.dss_organization FOR EACH ROW EXECUTE FUNCTION dss.dss_update_audit_columns()$

ldx	Name	Data Type	Description
A pers	son who has been identified as a no	table contact for a particular	organization
* Pk	organization_contact_person_id	bigint GENERATED ALWAYS AS IDENTITY	Unique generated key
*	is_primary	boolean	Indicates whether the contact should receive all communications directed at the organization
*	given_nm	varchar(25)	A name given to a person so that they can easily be identified amon their family members (in some cultures, this is often the first name)
*	family_nm	varchar(25)	A name that is often shared amongst members of the same family (commonly known as a surname within some cultures)
*	phone_no	varchar(13)	Phone number given for the contact by the organization (contains only digits)
*	email_address_dsc	varchar(320)	E-mail address given for the contact by the organization
*	contacted_through_organization_i	bigint	Foreign key
*	upd_dtm	timestamptz	Trigger-updated timestamp of last change
	upd_user_guid	uuid	The globally unique identifier (assigned by the identity provider) for the most recent user to record a change
Index	es		
Туре	Name	On	Description
Pk	dss_organization_contact_person _pk	organization_contact_pers on_id	
Foreig	gn Keys		
Туре	Name	On	Description
	dss_organization_contact_person_contacted_through_organization_id)	_fk_contacted_for (d) ref dss_organization (
Trigge	ers		
	Name	Definition	Description
	dss_organization_contact_person _br_iu_tr		

 $\label{lem:contact_person_br_iu_tr} CREATE\ TRIGGER\ dss_organization_contact_person_br_iu_tr\ BEFORE\ INSERT\ OR\ UPDATE\ ON\ dss.dss_organization_contact_person\ FOR\ EACH\ ROW\ EXECUTE\ FUNCTION\ dss.dss_update_audit_columns()$

Table dss_organization_type		
ldx	Name	Data Type
* Pk	organization_type	varchar(25)
*	organization_type_nm	varchar(250)
Indexes		
Туре	Name	On
Pk	dss_organization_type_pk	organization_type

Table	Table dss_physical_address			
ldx	Name	Data Type	Description	
A prop	perty address that includes any veri	fiable BC attributes		
* Pk	physical_address_id	bigint GENERATED ALWAYS AS IDENTITY	Unique generated key	
*	original_address_txt	varchar(250)	The source-provided address of a short-term rental offering	
	match_result_json	json	Full JSON result of the source address matching attempt	
	match_address_txt	varchar(250)	The sanitized physical address that has been derived from the original	
	match_score_amt	smallint	The relative score returned from the address matching attempt	
	site_no	varchar(50)	The siteID returned by the address match	
	block_no	varchar(50)	The blockID returned by the address match	
	location_geometry	geometry	The computed location point of the matched address	
	is_exempt	boolean	Indicates whether the address has been identified as exempt from Short Term Rental regulations	
	containing_organization_id	bigint	Foreign key	
*	upd_dtm	timestamptz	Trigger-updated timestamp of last change	
	upd_user_guid	uuid	The globally unique identifier (assigned by the identity provider) for the most recent user to record a change	
Indexe	es			
Туре	Name	On	Description	
Pk	dss_physical_address_pk	physical_address_id		
Foreig	n Keys			
Туре	Name	On	Description	
	dss_physical_address_fk_contain containing_organization_id) ref ds organization_id)	ed_in(ss_organization(
Trigge	ors			
	Name	Definition	Description	
	dss_physical_address_br_iu_tr			

CREATE TRIGGER dss_physical_address_br_iu_tr BEFORE INSERT OR UPDATE ON dss.dss_physical_address FOR EACH ROW EXECUTE FUNCTION dss.dss_update_audit_columns()

Tabl	Fable dss_rental_listing			
ldx	Name	Data Type	Description	
A ren	tal listing snapshot that is relevant t	o a specific month		
* Pk	rental_listing_id	bigint GENERATED ALWAYS AS IDENTITY	Unique generated key	
*	platform_listing_no	varchar(25)	The platform issued identification number for the listing	
	platform_listing_url	varchar(4000)	URL for the short-term rental platform listing	
	business_licence_no	varchar(25)	The local government issued licence number that applies to the rental offering	
	bc_registry_no	varchar(25)	The Short Term Registry issued permit number	
	is_entire_unit	boolean	Indicates whether the entire dwelling unit is offered for rental (as opposed to a single bedroom)	

Table	Table dss_rental_listing				
	available_bedrooms_qty	smallint	The number of bedrooms in the dwelling unit that are available for short term rental		
	nights_booked_qty	smallint	The number of nights that short term rental accommodation services were provided during the reporting period		
	separate_reservations_qty	smallint	The number of separate reservations that were taken during the reporting period		
*	including_rental_listing_report_id	bigint	Foreign key		
*	offering_organization_id	bigint	Foreign key		
	locating_physical_address_id	bigint	Foreign key		
*	upd_dtm	timestamptz	Trigger-updated timestamp of last change		
	upd_user_guid	uuid	The globally unique identifier (assigned by the identity provider) for the most recent user to record a change		
Indexe	es				
Туре	Name	On	Description		
Pk	dss_rental_listing_pk	rental_listing_id			
Foreig	n Keys				
Туре	Name	On	Description		
	dss_rental_listing_fk_offered_by (ref dss_organization (organization				
	dss_rental_listing_fk_included_in including_rental_listing_report_id dss_rental_listing_report (rental_l	ref			
	dss_rental_listing_fk_located_at (locating_physical_address_id) ref physical_address_id)	dss_physical_address (
Trigge	ers				
	Name	Definition	Description		
	dss_rental_listing_br_iu_tr				

 $\label{listing_br_iu_tr} \mbox{CREATE TRIGGER dss_rental_listing_br_iu_tr BEFORE INSERT OR UPDATE ON dss.dss_rental_listing FOR EACH ROW EXECUTE FUNCTION dss.dss_update_audit_columns()$

Table	e dss_rental_listing_contact		
ldx	Name	Data Type	Description
A pers	son who has been identified as a no	table contact for a particular	rental listing
* Pk	rental_listing_contact_id	bigint GENERATED ALWAYS AS IDENTITY	Unique generated key
*	is_property_owner	boolean	Indicates a person with the legal right to the unit being short-term rental
	listing_contact_nbr	smallint	Indicates which of the five possible supplier hosts is represented by this contact
	supplier_host_no	varchar(25)	The platform identifier for the supplier host
	full_nm	varchar(50)	The full name of the contact person as inluded in the listing
	phone_no	varchar(13)	Phone number given for the contact
	fax_no	varchar(13)	Facsimile numbrer given for the contact
	full_address_txt	varchar(250)	Mailing address given for the contact
	email_address_dsc	varchar(320)	E-mail address given for the contact
*	contacted_through_rental_listing_ id	bigint	Foreign key
*	upd_dtm	timestamptz	Trigger-updated timestamp of last change
	upd_user_guid	uuid	The globally unique identifier (assigned by the identity provider) for the most recent user to record a change
Index	98		
Туре	Name	On	Description
Pk	dss_rental_listing_contact_pk	rental_listing_contact_id	

Table dss_rental_listing_contact Foreign Keys Type Name On Description dss_rental_listing_contact_fk_contacted_for (contacted_through_rental_listing_id) ref dss_rental_listing (rental_listing_id) Triggers Name Definition Description dss_rental_listing_contact_br_iu_t

CREATE TRIGGER dss_rental_listing_contact_br_iu_tr BEFORE INSERT OR UPDATE ON dss.dss_rental_listing_contact FOR EACH ROW EXECUTE FUNCTION dss.dss_update_audit_columns()

Tabl	a dee vental listing veneut		
labi	e dss_rental_listing_report		
ldx	Name	Data Type	Description
A deli	very of rental listing information tha	t is relevant to a specific mor	nth
* Pk	rental_listing_report_id	bigint GENERATED ALWAYS AS IDENTITY	Unique generated key
*	report_period_ym	date	The month to which the listing information is relevant (always set to the first day of the month)
	source_bin	bytea	The binary image of the information that was uploaded
*	providing_organization_id	bigint	Foreign key
*	upd_dtm	timestamptz	Trigger-updated timestamp of last change
	upd_user_guid	uuid	The globally unique identifier (assigned by the identity provider) for the most recent user to record a change
Index	es		
Туре	Name	On	Description
Pk	dss_rental_listing_report_pk	rental_listing_report_id	
Foreig	gn Keys		
Туре	Name	On	Description
	dss_rental_listing_report_fk_provi providing_organization_id) ref dss organization_id)	ded_by(s_organization(
Trigge	ers		
	Name	Definition	Description
	dss_rental_listing_report_br_iu_tr		

CREATE TRIGGER dss_rental_listing_report_br_iu_tr BEFORE INSERT OR UPDATE ON dss.dss_rental_listing_report FOR EACH ROW EXECUTE FUNCTION dss.dss_update_audit_columns()

Tabl	e dss_user_identity		
ldx	Name	Data Type	Description
An ex	ternally defined domain directory ol	bject representing a potentia	I application user or group
* Pk	user_identity_id	bigint GENERATED ALWAYS AS IDENTITY	Unique generated key
*	user_guid	uuid	An immutable unique identifier assigned by the identity provider
*	display_nm	varchar(250)	A human-readable full name that is assigned by the identity provider (this may include a preferred name and/or business unit name)
*	identity_provider_nm	varchar(25)	A directory or domain that authenticates system users to allow access to the application or its API (e.g. idir, bceidbusiness)
*	is_enabled	boolean	Indicates whether access is currently permitted using this identity
*	access_request_status_cd	varchar(25)	The current status of the most recent access request made by the user (restricted to Requested, Approved, or Denied)
	access_request_dtm	timestamptz	A timestamp indicating when the most recent access request was made by the user
	access_request_justification_txt	varchar(250)	The most recent user-provided reason for requesting application access

Table	e dss_user_identity		
	given_nm	varchar(25)	A name given to a person so that they can easily be identified among their family members (in some cultures, this is often the first name)
	family_nm	varchar(25)	A name that is often shared amongst members of the same family (commonly known as a surname within some cultures)
	email_address_dsc	varchar(320)	E-mail address associated with the user by the identity provider
	business_nm	varchar(250)	A human-readable organization name that is associated with the user by the identity provider
	terms_acceptance_dtm	timestamptz	A timestamp indicating when the user most recently accepted the published Terms and Conditions of application access
	represented_by_organization_id	bigint	Foreign key
*	upd_dtm	timestamptz	Trigger-updated timestamp of last change
	upd_user_guid	uuid	The globally unique identifier (assigned by the identity provider) for the most recent user to record a change
Indexe	es		
Туре	Name	On	Description
Pk	dss_user_identity_pk	user_identity_id	
Foreig	n Keys		
Type	Name	On	Description
	dss_user_identity_fk_representing represented_by_organization_id) organization_id)		
	dss_user_identity_fk_given (accedss_access_request_status (acceds_access_request_status)		

Triggers

Name Definition Description

dss_user_identity_br_iu_tr

 $\label{lem:created} \textbf{CREATE TRIGGER dss_user_identity_br_iu_tr BEFORE INSERT OR UPDATE ON dss.dss_user_identity FOR EACH ROW EXECUTE FUNCTION dss.dss_update_audit_columns()$

Tabl	e dss_user_privilege		
ldx	Name	Data Type	Description
A gra	nular access right or privilege withir	the application that may be	granted to a role
* Pk	user_privilege_cd	varchar(25)	The immutable system code that identifies the privilege
*	user_privilege_nm	varchar(250)	The human-readable name that is given for the role
Index	es		
Туре	Name	On	Description
Pk	dss_user_privilege_pk	user_privilege_cd	

Table	e dss_user_role		
ldx	Name	Data Type	Description
A set	of access rights and privileges with	in the application that may be	e granted to users
* Pk	user_role_cd	varchar(25)	The immutable system code that identifies the role
*	user_role_nm	varchar(250)	The human-readable name that is given for the role
Index	es		
Туре	Name	On	Description
Pk	dss user role pk	user role cd	

Tabl	e dss_user_role_assignment		
ldx	Name	Data Type	Description
The a	association of a grantee credential to	o a role for the purpose of co	onveying application privileges
* Pk	user_identity_id	bigint	Foreign key
* Pk	user_role_cd	varchar(25)	Foreign key

Table	e dss_user_role_assignment		
Index	es		
Туре	Name	On	Description
Pk	dss_user_role_assignment_pk	user_identity_id, user_role_cd	
Foreig	gn Keys		
Туре	Name	On	Description
	dss_user_role_assignment_fk_gradss_user_role (user_role_cd)	anted (user_role_cd) ref	
	dss_user_role_assignment_fk_graref dss_user_identity (user_identi	anted_to (user_identity_id) ity_id)	

Table	e dss_user_role_privilege		
ldx	Name	Data Type	Description
The a	ssociation of a granular application	privilege to a role	
* Pk	user_privilege_cd	varchar(25)	Foreign key
* Pk	user_role_cd	varchar(25)	Foreign key
Index	es		
Туре	Name	On	Description
Pk	dss_user_role_privilege_pk	user_privilege_cd, user_role_cd	
Foreig	n Keys		
Туре	Name	On	Description
	dss_user_role_privilege_fk_confedss_user_role (user_role_cd)	rred_by (user_role_cd) ref	
	dss_user_role_privilege_fk_conferef dss_user_privilege (user_privi	rring (user_privilege_cd) lege_cd)	

Schema dss

Functions

dss_update_audit_columns