

Enrollment App Deployment Runbook (Operations Edition)

Repository: nr-brmb-agristability-powerapps/enrollment app

Last updated: 2026-06-18

This version is optimized for release windows: quick checklist first, copy/paste commands second, deep detail last.

Release Window Quick Start

1) Pipeline

Action: Release app/solution to target stage (Test or Prod).

Success Pipeline stage completed and artifacts deployed.

2) Config + Bindings

Action: Update stage config file and run post-deploy script.

Watch Any `replace-with-*` value will fail script execution.

3) Push

Action: Script runs `npx power-apps push .`

Success Push exits with code 0 and app is reachable.

4) Validation

Action: Smoke test dashboard, deep links, and enrolment pages.

Blocker If dashboard or deep links fail, verify core config row immediately.

Roles and Handoffs

Stage	Primary Role	Output
Pipeline release	Release manager / DevOps	Target environment artifact deployment complete
Post-deploy bindings	App operator	Data sources rebound to target environment connections
Config verification	Business app admin	Active core config row validated
Smoke testing	QA / app operator	Go/no-go outcome

Prerequisites

- pac installed and authenticated to target environment.
- Node.js + npm installed.
- Repo checked out locally with dependencies installed.
- Access to target connector `connectionId` values.
- Permission to add/rebind Power Apps data sources.

Command Pack (Copy/Paste)

Open repo root

```
cd "c:\agristability\nr-brmb-agristability-powerapps\enrollment app"
```

Optional: sync stage config from power.config.json

```
.\scripts\sync-deploy-config-from-powerconfig.ps1 -Stage test -
PowerConfigPath .\power.config.json -DeployConfigPath
.\scripts\powerapps-deploy.config.json -AllowOverwrite
```

Run full post-deploy (Test)

```
.\scripts\post-deploy-powerapps.ps1 -Stage test -ConfigPath
.\scripts\powerapps-deploy.config.json
```

Run full post-deploy (Prod)

```
.\scripts\post-deploy-powerapps.ps1 -Stage prod -ConfigPath
.\scripts\powerapps-deploy.config.json
```

Skip build if already validated in pipeline

```
.\scripts\post-deploy-powerapps.ps1 -Stage prod -ConfigPath
.\scripts\powerapps-deploy.config.json -SkipBuild
```

Required Core Configuration Fields (Dataverse)

Table: `vsi_armsconfiguration`. One row should be active
(`vsi_activeconfiguration = Yes`).

Field	Mandatory	Used by app	Failure symptom if missing
<code>vsi_activeconfiguration</code>	Yes	Select active row	Wrong row used, inconsistent behavior
<code>vsi_coreenvironmentid</code>	Yes	Deep-link URL environment segment	Deep-link launch error
<code>vsi_tenantid</code>	Yes	Deep-link tenant and Power BI embed context	Portal link or dashboard embed failure
<code>vsi_powerbiereportgroupid</code>	Yes	Dashboard workspace/group	Dashboard page error
<code>vsi_powerbiendashboardreportid</code>	Yes	Dashboard report id	Dashboard page error
<code>vsi_enrolmententfeevariancethreshold</code>	Recommended	Variance highlight threshold	Unexpected variance flagging
<code>vsi_coreenvironmenturl</code>	Recommended	Core record navigation links	Record links incorrect or unavailable

What the Post-Deploy Script Does

- `pac code init -n <appName> -env <environmentId>`
- For each data source in stage config: `pac code add-data-source -a <apiId> -c <connectionId>`
- `npm.cmd run build` (unless `-SkipBuild`)

4. `npx.cmd power-apps push`

Validation Checklist (Go/No-Go)

- Dashboard page loads with embedded report.
 - Deep links open target app and route correctly.
 - Enrolment list loads and variance flags appear correctly.
 - Core links open expected records (if configured).
 - No placeholder values remain in target stage config.
-

Common Failures and Fast Fixes

Script fails with placeholder value

Update `scripts/powerapps-deploy.config.json` for the target stage. Replace all `replace-with-*` values.

Logic Flows/Power BI connection IDs not auto-synced

Expected in some environments if `sharedConnectionId` is not present in `power.config.json`. Enter those IDs manually in stage config.

Deep links fail after successful push

Verify active core config has valid `vsi_coreenvironmentid` and `vsi_tenantid`.

Schema file shows old environment ID

Do not manually edit schema files. Re-run target environment binding/post-deploy steps.

Files Used During Operations

- `scripts/powerapps-deploy.config.json`
- `scripts/sync-deploy-config-from-powerconfig.ps1`
- `scripts/post-deploy-powerapps.ps1`
- `docs/deployment-runbook.html` (full detailed version)