

When, and to what, does human-machine coadaptation converge?

Benjamin Chasnov, Lillian J. Ratliff, Samuel A. Burden
{bchasnov, ratliff1, sburden}@uw.edu



Department of Electrical and
Computer Engineering
University of Washington, Seattle, USA



Introduction and motivation

Machines are designed to optimize a performance metric.

A recent trend: machines run an optimization scheme in the loop **with other adaptive components**.

Example: *human-in-the-loop optimization* of assistive devices. The optimizer tries to improve the human's gait or metabolic usage by actuating their limbs.

Challenges

- the machine does not consider the human's adaptation
- the human's response is not stationary (it depends on what the machine is doing)
- un-modeled strategic components lead to sub-optimal performance (slow convergence or cycling)

Mathematical model

We consider a game played by two strategic agents – a human and a machine. Agents iteratively descend cost functions and make small adjustments to their strategy by using gradients.


Cost functions	$C_H, C_M,$
Decision variables	$(H, M) \in \mathcal{H} \times \mathcal{M}.$
Learning rates	α, β

Human (agent 1): $\frac{\partial}{\partial t} H = -\alpha \frac{\partial C_H}{\partial H}(H, M),$

Machine (agent 2): $\frac{\partial}{\partial t} M = -\beta \frac{\partial C_M}{\partial M}(H, M),$


Coadaptive closed-loop system

The human-machine adaptation is closed-loop dynamical system.



Dynamics of gradient-based learners


The **learning dynamics** explain the rich set of agent behaviors:



Cost landscape


In the neighborhood of a *local equilibrium*, the cost landscape can be approximated by quadratic costs. Agents seek *stationary points* that are *minimizers* of their individual costs.

Agents can choose only their own strategy, but other strategies will affect their cost. This is the central challenge of studying adaptation in games.



Experimental setup

Each player chooses a scalar/vector valued action H, M . The interaction is determined by the game *vector field*.




Machine: gradient descent with fixed step size

Human: move cursor to decrease cost

Cost display: prescribed through the interface


Modeling others...



Conclusion: The *steady-state performance* (i.e. when and what) is determined by the characteristics of the *equilibrium* of the game.

Response maps

If agents have quadratic costs, then their *best responses* are linear. This abstraction allows us to use geometry to analyze agent convergence.



References

- Basar and Olsder. *Dynamic noncooperative game theory*. Society for Industrial and Applied Mathematics, 1998.
- Ratliff, Burden, and Sastry. "Characterization and computation of local Nash equilibria in continuous games." In *Allerton*. IEEE, 2013.
- Fiez, Chasnov, and Ratliff. "Implicit learning dynamics in Stackelberg games: Equilibria characterization, convergence analysis, and empirical study." In *ICML*. PMLR, 2020.
- Madduri, Burden, and Orsborn. "A Game-Theoretic Model for Co-Adaptive Brain-Machine Interfaces." *bioRxiv*:2020.12.11.421800, 2020.
- S. J. Gershman, E. J. Horvitz, and J. B. Tenenbaum, "Computational rationality: A converging paradigm for intelligence in brains, minds, and machines," *Science*, vol. 349, no. 6245, pp. 273–278, 2015
- C. Papadimitriou and G. Piliouras, "Game dynamics as the meaning of a game," *ACM SIGecom Exchanges*, vol. 16, no. 2, pp. 53–63, 2019.