



(<https://www.bigdatauniversity.com>)

Lab: Connect to Db2 database on Cloud using Python

Introduction

This notebook illustrates how to access a DB2 database on Cloud using Python by following the steps below:

1. Import the `ibm_db` Python library
2. Enter the database connection credentials
3. Create the database connection
4. Close the database connection

Note: Please follow the instructions given in the first Lab of this course to Create a database service instance of Db2 on Cloud and retrieve your database Service Credentials.

Import the `ibm_db` Python library

The `ibm_db` [API \(https://pypi.python.org/pypi/ibm_db/\)](https://pypi.python.org/pypi/ibm_db/) provides a variety of useful Python functions for accessing and manipulating data in an IBM® data server database, including functions for connecting to a database, preparing and issuing SQL statements, fetching rows from result sets, calling stored procedures, committing and rolling back transactions, handling errors, and retrieving metadata.

We first import the `ibm_db` library into our Python Application

Execute the following cell by clicking within it and then press `Shift` and `Enter` keys simultaneously

In [1]:

```
import ibm_db
```

When the command above completes, the `ibm_db` library is loaded in your notebook.

Identify the database connection credentials

Connecting to dashDB or DB2 database requires the following information:

- Driver Name
- Database name
- Host DNS name or IP address
- Host port
- Connection protocol
- User ID (or username)
- User Password

Notice: To obtain credentials please refer to the instructions given in the first Lab of this course

Now enter your database credentials below and execute the cell with `Shift + Enter`

In [2]:

```
#Replace the placeholder values with your actual Db2 hostname, us  
ername, and password:  
dsn_hostname = "dashdb-txn-sbox-yp-dal09-08.services.dal.ibm.com" # e.g.: "dashdb-txn-sbox-yp-dal09-04.services.dal.ibm.com"  
dsn_uid = "xhm56168" # e.g. "abc12345"  
dsn_pwd = "5k245j6lt@b43vqk" # e.g. "7dBZ3wWt9XN6$o0J"  
  
dsn_driver = "{IBM DB2 ODBC DRIVER}"  
dsn_database = "BLUDB" # e.g. "BLUDB"  
dsn_port = "50000" # e.g. "50000"  
dsn_protocol = "TCPIP" # i.e. "TCPIP"
```

Create the DB2 database connection

Ibm_db API uses the IBM Data Server Driver for ODBC and CLI APIs to connect to IBM DB2 and Informix.

Lets build the dsn connection string using the credentials you entered above

In [3]:

```
#DO NOT MODIFY THIS CELL. Just RUN it with Shift + Enter  
#Create the dsn connection string  
dsn = (  
    "DRIVER={0};"  
    "DATABASE={1};"  
    "HOSTNAME={2};"  
    "PORT={3};"  
    "PROTOCOL={4};"  
    "UID={5};"  
    "PWD={6};").format(dsn_driver, dsn_database, dsn_hostname, ds  
n_port, dsn_protocol, dsn_uid, dsn_pwd)  
  
#print the connection string to check correct values are specifie  
d  
print(dsn)
```

```
DRIVER={IBM DB2 ODBC DRIVER};DATABASE=BLUDB;HOSTNAME  
=dashdb-txn-sbox-yp-dal09-08.services.dal.bluemix.ne  
t;PORT=50000;PROTOCOL=TCPIP;UID=xhm56168;PWD=5k245j6  
1t@b43vqk;
```

Now establish the connection to the database

In [4]:

```
#DO NOT MODIFY THIS CELL. Just RUN it with Shift + Enter  
#Create database connection  
  
try:  
    conn = ibm_db.connect(dsn, "", "")  
    print ("Connected to database: ", dsn_database, "as user: ",  
dsn_uid, "on host: ", dsn_hostname)  
  
except:  
    print ("Unable to connect: ", ibm_db.conn_errormsg() )
```

Connected to database: BLUDB as user: xhm56168 on
host: dashdb-txn-sbox-yp-dal09-08.services.dal.blue
mix.net

Congratulations if you were able to connect successfully. Otherwise check the error and try again.

In [5]:

```
#Retrieve Metadata for the Database Server  
server = ibm_db.server_info(conn)  
  
print ("DBMS_NAME: ", server.DBMS_NAME)  
print ("DBMS_VER:  ", server.DBMS_VER)  
print ("DB_NAME:    ", server.DB_NAME)
```

DBMS_NAME: DB2/LINUX8664
DBMS_VER: 11.01.0404
DB_NAME: BLUDB

In [6]:

```
#Retrieve Metadata for the Database Client / Driver
client = ibm_db.client_info(conn)

print ("DRIVER_NAME:           ", client.DRIVER_NAME)
print ("DRIVER_VER:             ", client.DRIVER_VER)
print ("DATA_SOURCE_NAME:         ", client.DATA_SOURCE_NAME)
print ("DRIVER_ODBC_VER:          ", client.DRIVER_ODBC_VER)
print ("ODBC_VER:                  ", client.ODBC_VER)
print ("ODBC_SQL_CONFORMANCE:     ", client.ODBC_SQL_CONFORMANCE)
print ("APPL_CODEPAGE:            ", client.APPL_CODEPAGE)
print ("CONN_CODEPAGE:            ", client.CONN_CODEPAGE)
```

```
DRIVER_NAME:           libdb2.a
DRIVER_VER:            11.01.0405
DATA_SOURCE_NAME:      BLUDB
DRIVER_ODBC_VER:       03.51
ODBC_VER:              03.01.0000
ODBC_SQL_CONFORMANCE: EXTENDED
APPL_CODEPAGE:         1208
CONN_CODEPAGE:         1208
```

Close the Connection

We free all resources by closing the connection. Remember that it is always important to close connections so that we can avoid unused connections taking up resources.

In [7]:

```
ibm_db.close(conn)
```

Out[7]:

True

Summary

In this tutorial you established a connection to a DB2 database on Cloud database from a Python notebook using ibm_db API.

Copyright © 2017 [cognitiveclass.ai](https://cognitiveclass.ai?utm_source=bducopyrightlink&utm_medium=dswb&utm_campaign=bdu) (cognitiveclass.ai?utm_source=bducopyrightlink&utm_medium=dswb&utm_campaign=bdu). This notebook and its source code are released under the terms of the [MIT License](https://bigdatauniversity.com/mit-license/) (<https://bigdatauniversity.com/mit-license/>).