

JAVASCRIPT QUICKSTART :)

```
<html>
</html>
```

Empty html tags above.

```
<html>
<script>
</script>
<body>
</body>
</html>
```

Again does nothing.

```
<html>
<script>
</script>
<body>
```

SOMETHING

```
</body>
</html>
```

Does "SOMETHING".

```
<html>
<script>
</script>
<body>
```

```
<div id="divtop">SOMETHING</div>
```

```
<div id="divbottom" style="position: absolute; bottom: 0px">SOMETHING
ELSE</div>
```

```
</body>
</html>
```

Use <div> tags to divide up parts of the screen and give each "div" a name using the "id" property. (See bottom of the screen.)

```
<html>
```

```
<script>
</script>
<body>

<div id="divtop">SOMETHING</div>

<div id="divbottom" style="position: absolute; bottom: 0px;
background: white; color: black; border: 1px solid red">SOMETHING
ELSE</div>

</body>
</html>
```

Use “style” to change things up.

```
<html>
<script>

window.onload=function(){
    alert("stuff");
}

</script>
<body>

<div id="divtop">SOMETHING</div>

<div id="divbottom" style="position: absolute; bottom: 0px;
background: white; color: black; border: 1px solid red">SOMETHING
ELSE</div>

</body>
</html>
```

Use the JavaScript function “alert” in the “script” tags to have an annoying pop up.

```
<html>
<script>

window.onload=function(){
    alert(1+2+3+4+5);
}

</script>
<body>
```

```

<div id="divtop">SOMETHING</div>

<div id="divbottom" style="position: absolute; bottom: 0px;
background: white; color: black; border: 1px solid red">SOMETHING
ELSE</div>

</body>
</html>

```

Use the JavaScript function “alert” in the “script” tags to have math in an annoying pop up.

```

<html>
<script>

window.onload=function(){
    document.getElementById("divbottom").innerHTML="Bottom Bottom
Something";
}

</script>
<body>

<div id="divtop">SOMETHING</div>

<div id="divbottom" style="position: absolute; bottom: 0px;
background: white; color: black; border: 1px solid red">SOMETHING
ELSE</div>

</body>
</html>

```

Use the JavaScript language in the “script” tags to change the “innerHTML” of the “divbottom” tag after the page loads.

```

<html>
<script>

function clickresp(){
    alert("You Clicked?");
}

window.onload=function(){
    document.getElementById("divbottom").style.bottom="200px";
    document.getElementById("divbottom").style.right="20px";
}

```

```
        document.getElementById("divbottom").onclick=clickresp;
    }

</script>
<body>

<div id="divtop">SOMETHING</div>

<div id="divbottom" style="position: absolute; bottom: 0px;
background: white; color: black; border: 1px solid red">SOMETHING
ELSE</div>

</body>
</html>
```

Use the JavaScript language in the “script” tags to change lots of things about “divbottom” after the page loads.

HTML / JavaScript includes pre-canned objects like CANVAS, IMG, A (links), VIDEO, AUDIO, EMBED and more (voice synthesis, midi stuff).