

Questions

4. The Codeunit Temp Blob can be found in which app? * (1 Point)

- ☐ Base Application
- ☐ System
- ☐ Business Foundation
- ☐ System Application ✓

5. Which Code analyzer(s) are required for appSource development? * (1 Point)

- ☒ AppSourceCop ✓
- ☐ CodeCop
- ☐ PerTenantExtensionCop
- ☐ UICop

6. To enable the code analysis in VSCode: (Put the steps in the correct order.) * (1 Point)

- Select **Alt+ A, Alt+L** to create a new project.
- Open the Command Palette **Ctrl+Shift+P** and choose either **User Settings** or **Workspace Settings**.
- Under **Extensions**, go to **AI Language extension configuration**. When you scroll down, you'll find Code Analyzers section, choose **Edit in settings.json**.
- Set the **al.enableCodeAnalysis** in the settings file to **true**. "al.enableCodeAnalysis": true
- In the **al.codeanalyzers** setting, use **Ctrl+Space** to pick from the available code analyzers. Separate the list of code analyzers with **commas**.

Last 2 are interchangeable



7. The **version** setting is a part of the which .json file? * (1 Point) 

- ☒ app.json ✓
- ☐ launch.json
- ☐ migration.json
- ☐ settings.json



8. Where can you set the **resource exposure policy** setting? * (1 Point) 

- ☒ app.json ✓
- ☐ launch.json
- ☐ migration.json
- ☐ settings.json



10. Which of the following statements are true? * (1 Point) 

- ☐ In order to meet the requirements for the AppSource technical validation, you must have a three letters affix registered for your extension publisher, and you must use the affix in your extension. ✓
- ☐ Per-tenant extensions aren't required to use a prefix or suffix, but we strongly recommend that you do so. You can use pte as prefix or suffix to avoid conflicts with AppSource apps or base objects. ✓
- ☐ Use the AppSourceCop tool to find all missing prefixes and/or suffixes. ✓
- ☐ Affixes aren't case-sensitive, which means that for example "ABC", "abc", and "AbC" are treated as the same affix. ✓
- ☐ If your per-tenant extension causes a conflict with a new object in the base application or an updated AppSource app, then the per-tenant extension will be required to make the change. ✓



11. When you create a new AL project in Visual Studio Code, you need to perform a number of steps. Please sort the steps in the correct order. * (1 Point)

Open Visual Studio Code

Use View > Command Palette and select AL: Go!

Specify the location of your project

Specify the AL language version

Select your environment (Sandbox or Local Server)

Set the correct launch.json settings

Download symbols



12. Which property must be set to 'Install' in a codeunit where you write installation logic? * (1 Point)

☐ IsInstall

☒ SubType ✓

☐ Type

☐ Purpose



13. Which of the following triggers can you use in an installation codeunit? * (1 Point)

☒ OnInstallAppPerCompany ✓

☒ OnInstallAppPerDatabase ✓

☐ OnCheckPreconditionsPerCompany

☐ OnCheckPreconditionsPerDatabase

☐ All of the above

☐ None of the above

14. Which of the following triggers can you use in an upgrade codeunit? * (1 Point)

- ☐ OnUpgradePerCompany
- ☐ OnUpgradePerDatabase
- ☐ OnCheckPreconditionsPerCompany
- ☐ OnCheckPreconditionsPerDatabase
- ☐ OnValidateUpgradePerCompany
- ☐ OnValidateUpgradePerDatabase
- ☐ All of the above ✓
- ☐ None of the above

15. What type of codeunit is used for handling data modifications between different versions of an extension? * (1 Point)

- ☐ Install
- ☒ Upgrade ✓
- ☐ Modify
- ☐ Update

16. What is a limitation when adding custom logic to a Role Center page? * (1 Point)

- ☐ Custom logic can only be added to the navigation area
- ☐ Custom logic must follow a specific syntax
- ☐ Custom logic cannot be directly added to the Role Center page code ✓
- ☐ Custom logic can only be added to Headlines and cues

17. Which of the following page types is typically used for displaying confirmative or exceptional dialogs in Dynamics 365 Business Central? * (1 Point)

- ☐ RoleCenter
- ☐ StandardDialog ✓
- ☐ List
- ☐ CardPart

18. Which page type in Dynamics 365 Business Central is suitable for line-based data entry tasks such as journals and inquiries? * (1 Point)

- ☐ RoleCenter
- ☐ List
- ☐ Worksheet ✓
- ☐ Card
- ☐ ListPlus

19. What is a key characteristic of ListPlus page layouts in Dynamics 365 Business Central? * (1 Point)

- ☐ They primarily support overviewing and managing master and reference data.
- ☐ They must contain a single Repeater group and can embed CardParts.
- ☐ They are optimized for line-based data entry tasks.
- ☐ They provide options for viewing or filtering data related to a specific entity context. ✓

20. What is the purpose of defining table relationships in a database? * (1 Point)

- ☐ To perform lookup functions in other tables
- ☐ To validate data entries
- ☐ To propagate changes automatically from one table to other tables
- ☐ All of the above ✓

21. What is the Extensible Property used for in Dynamics 365 Business Central tables? * (1 Point)

- ☐ It specifies the maximum record size of the table.
- ☐ It allows the table to be extended by extension objects. ✓
- ☐ It defines the primary key for the table.
- ☐ It indicates the type of data the table can store.

22. What are the four main sections that make up the structure of a table in Dynamics 365 Business Central? * (1 Point)

- ☒ Metadata, Fields, Keys, Triggers ✓
- ☐ Fields, Keys, Triggers, System Fields
- ☐ Metadata, Fields, Keys, Code
- ☐ Keys, Fields, Code, System Fields

23. What FlowField type indicates whether any records exist in a specified set in a table? * (1 Point)

- ☐ Sum
- ☐ Average
- ☒ Exists ✓
- ☐ LookUp
- ☐ Count

24. Which property can be set on a page object to indicate that the source table is a temporary table? (Select all that apply) * (1 Point)

- ☒ SourceTableTemporary ✓
- ☐ UseTemporary
- ☐ TemporaryTable
- ☐ SourceTable

Save
Save
Open
Copy
Send
Micro

25. What are the advantages of using a temporary table in Dynamics 365 Business Central? (Select all that apply) * (1 Point)

- ☐ Reduced network performance
- ☐ Reduced load on the SQL database server ✓
- ☐ Faster operations due to in-memory processing ✓
- ☐ Persistence of data even after closing the table

26. Which property is used to include field captions in a report dataset? * (1 Point)

- ☒ IncludeCaption ✓
- ☐ CaptionInclude
- ☐ FieldCaption
- ☐ CaptionField

FieldCaption is a method not a property like IncludeCaption

27. What is the purpose of the AllowScheduling property in a report object? * (1 Point)

- ☒ Allows users to schedule report generation ✓
- ☐ Sets a schedule for data extraction
- ☐ Enables real-time data updates in reports
- ☐ Limits the number of scheduled reports

28. Which property in a report object defines the caption for the request page tab related to a report's data item or an XMLport's table element? * (1 Point)

- ☒ RequestFilterHeading ✓
- ☐ AboutTitle
- ☐ ContextSensitiveHelpPage
- ☐ SaveValues
- ☐ None of the above

29. Which property defines the help article to show when the user presses Help in the UI on a request page? * (1 Point)

- ☐ RequestFilterHeading
- ☐ AboutText
- ☒ ContextSensitiveHelpPage ✓
- ☐ SaveValues

30. When is the OnPostReport trigger called in the processing of data items of a report? * (1 Point)

- ☐ After the last record of each data item
- ☒ After all records are processed ✓
- ☐ Before any records are processed
- ☐ Before the last record of each data item

31. How can you substitute a report? * (1 Point)

- ☒ To substitute a report, you create a method and subscribe it to the OnAfterSubstituteReport event in codeunit ReportManagement. ✓
- ☐ To substitute a report, you create a method and subscribe it to the OnAfterReplaceReport event in codeunit ReportManagement.
- ☐ To substitute a report, you create a method and subscribe it to the OnSubstituteReport event in codeunit ReportManagement.
- ☐ You can not substitute reports in Business Central

32. Select the value for the SqlJoinType property so the resulting dataset contains every record from the upper data item table, even if a record does not have a matching value in the lower data item for fields that are linked by the DataltemLink property: * (1 Point)

- ☒ LeftOuterJoin ✓
- ☐ InnerJoin
- ☐ RightOuterJoin
- ☐ FullOuterJoin
- ☐ CrossJoin



33. Put the following report triggers in order of execution: * (1 Point)



OnInitReport

OnPreReport

OnPreDataItem

OnAfterGetRecord

OnPostDataItem

OnPostReport

34. Which of the following methods exits from a loop or a trigger in a data item trigger of a report or XmlPort. * (1 Point)



☒ Break ✓

☐ Quit

☐ Skip

☐ Exit

35. Which property specifies whether an XMLport can handle import, export, or both operations? * (1 Point)

- ☐ DefaultFieldsValidation
- ☐ UseRequestPage
- ☒ Direction ✓
- ☐ FileName
- ☐ Type

On the example there are several questions like this to replace XXX

36. When you design XMLports, you must set the value of the Format property and the Direction property. The **XXX** property indicates the type of file that you want to import or export and the Direction property value indicates whether the XMLport will be used for import or export.

* (1 Point)

Enter your answer

Correct answers:

37. Which function in AL runs a query object and generates a dataset for reading? * (1 Point)

- ☐ Close
- ☐ SaveAsXML
- ☐ Read
- ☒ Open ✓

...

38. What are the possible file formats that can be used to save query results in Dynamics 365 Business Central? * (1 Point)

☐ JSON and YAML

☒ CSV and XML ✓

☐ Binary and hexadecimal

☐ PDF and DOCX

JSON is possible but not YAML!

...

39. Access modifiers are used to set accessibility of tables, table fields, codeunits, and queries, which controls whether the object can be used from other code in your module or other modules. Access modifiers in AL are designed to create solid APIs, by limiting the symbols that dependent modules can take a reference on. Limiting the API surface can hide implementation details and allow for later refactoring of code without breaking external code.

The access modifiers that are available in AL are:

* (1 Point)

☒ internal ✓

☒ local ✓

☒ protected ✓

☒ public ✓

☐ global

☐ var

...

40. Access modifiers are only taken into consideration at compile time. For example, at compile time, a table with Access = Internal can't be used from other modules that don't have access to the internals of the module where the table is defined, but at runtime, any module can access the table by using reflection-based mechanisms such as RecordRef, or TransferFields. And the OnRun trigger can be run on internal codeunits by using [Codeunit.Run](#). Setting the object accessibility level as Access = Internal; *cannot* be used as a security boundary. * (1 Point)

☒ True ✓

☐ False

41. Views offer the following possibilities: * (1 Point)

- ☐ Filtering on multiple table fields on the source table defined for the page. ✓
- ☐ Sorting of the data on multiple table fields, but only in one direction; either ascending or descending. ✓
- ☐ Layout changes, modifying page columns, moving them, etc. ✓
- ☐ Modifying actions in Cue groups.

42. Select the correct option: * (1 Point)

- ☐ The page customization object in Business Central allows you to add changes to the layout and actions on page that are accessible for a profile. ✓
- ☐ The page extension object in Business Central allows you to add changes to the layout and actions on page that are accessible for a profile.
- ☐ The view object in Business Central allows you to add changes to the layout and actions on page that are accessible for a profile.
- ☐ The Control add-in object in Business Central allows you to add changes to the layout and actions on page that are accessible for a profile.

43. True or False: A single page customization can be used with multiple profiles within the same extension. * (1 Point)

- ☐ True ✓
- ☐ False

44. When should you use the IsEmpty function in AL? * (1 Point)

- ☐ To retrieve the first record in a dataset.
- ☐ To check if a record exists without retrieving it. ✓
- ☐ To set filters on a query variable.
- ☐ To retrieve all records in a dataset.

45. Which AL function is optimized for reading the complete set of records in a specified filter and range? * (1 Point)

- ☐ Record.Find
- ☐ Record.FindFirst
- ☒ Record.FindSet ✓
- ☐ [Record.Next](#)

46. In AL, what does the '@' sign in a SetFilter specify? * (1 Point)

- ☐ Case-sensitive filtering
- ☒ Case-insensitive filtering ✓
- ☐ Logical "or" condition
- ☐ Logical "and" condition

47. How can you check if any records match your filters in AL? * (1 Point)

- ☐ By using the SetCurrentKey function.
- ☒ By calling the IsEmpty function after setting filters. ✓
- ☐ By using the Next statement.
- ☐ By using the SetFilter function.

48. What does the ReadUncommitted isolation level in AL allow? * (1 Point)

- ☐ Reads on committed data only.
- ☒ Dirty reads, allowing reading modified rows not yet committed. ✓
- ☐ Stable reads by holding shared locks for the entire transaction.
- ☐ Disallowing others to read with the same intent.

49. What is the purpose of controlling the database isolation level in AL? * (1 Point)

- ☐ To increase the number of database locks.
- ☒ To improve performance by limiting database locks to what's necessary. ✓
- ☐ To prevent concurrent transactions from accessing the database.
- ☐ To automatically determine the isolation levels used in transactions.

50. In AL, what does the UpdLock isolation level do? * (1 Point)

- ☐ Allows dirty reads.
- ☐ Ensures all reads are stable by holding shared locks for the lifetime of the transaction.
- ☒ Disallows others to read with the same intent. ✓
- ☐ Allows reads on committed data only.

51. How can you ensure that specific FlowFields are calculated during the implementation of your AL code? *

- ☒ By using the SetAutoCalcFields function. ✓
- ☐ By using the CalcSums function.
- ☐ By using the Validate function.
- ☐ By using the TestField function.

52. What does the TestField function do in AL? * (1 Point)

- ☒ Checks if a field has a value or if it's blank. ✓
- ☐ Calculates a total for a specific field based on dataset filters.
- ☐ Stops code implementation and creates an error message for a specific field.
- ☐ Initializes all fields on the record with default values.

53. DataTransfer uses a builder design pattern that, in general, requires that you complete the following steps: (put in correct order) * (1 Point)

Specify the source and destination tables by calling the SetTables.

Specify which fields to transfer or constant values by calling the AddFieldValue. Or you can set a constant value for fields in the destination using AddConstantValue, respectively.

Define the relationship between the source and destination tables by calling AddJoin. In most cases, this method is required for copying fields.

Add constraints on the data to transfer by calling AddSourceFilter.

Invoke the query for transferring data by calling CopyFields or CopyRows.

54. True or False: The DataTransfer object can only be used in upgrade code and it'll throw a runtime error if used outside of upgrade codeunits. * (1 Point)

- ☒ True ✓
- ☐ False

55. What is the primary role of the Redirect URI in OAuth2 authentication for Business Central? * (1 Point)

- ☐ To store user credentials securely.
- ☒ To specify the endpoint where the authorization server sends the user after authentication. ✓
- ☐ To manage user sessions within the application.
- ☐ To encrypt the access token for secure transmission.

56. What is the recommended field to use as ODataKeyFields in an API page? * (1 Point)

- ☐ EntityName
- ☐ EntitySetName
- ☒ SystemId ✓
- ☐ APIPublisher

SystemId

57. Which property indicates the field used as a key when requesting a specific record from the API? * (1 Point)

- ☐ APIVersion
- ☐ APIGroup
- ☒ ODataKeyFields ✓
- ☐ EntitySetName

58. How should the value of the primary key be specified in the OData request for a specific record? * (1 Point)

- ☐ Without quotation marks
- ☒ Within single quotation marks ✓
- ☐ Within double quotation marks
- ☐ Within square brackets

59. What is included in the base URL for an OData request to retrieve all customer records? * (1 Point)

- ☐ API version and table name
- ☒ Tenant ID and company name ✓
- ☐ Secondary key value of the record
- ☐ Sandbox environment specification

60. Which filter expression is used to filter the result set based on specific conditions? * (1 Point)

- ☐ \$orderby filter expression
- ☐ \$select filter expression
- ☒ \$filter filter expression ✓
- ☐ \$top filter expression

62. Which type of table contains transactional information of a functional domain? * (1 Point)

- ☐ Journal table
- ☐ Document history table
- ☒ Ledger table ✓
- ☐ Subsidiary table

63. What type of table is used for configuration data in a solution? * (1 Point)

- ☐ Register table
- ☐ Ledger table
- ☐ Master table
- ☒ Setup table ✓

64. What is the primary key field type used in setup tables? * (1 Point)

- ☐ Integer
- ☒ Code ✓
- ☐ Text
- ☐ Date

65. Which codeunit is typically used in the OnRun trigger of the Company-Initialize codeunit to initialize setup tables? * (1 Point)

- ☐ SalesSetup codeunit
- ☒ NoSeriesManagement codeunit ✓
- ☐ SetupManagement codeunit
- ☐ CompanySetup codeunit
- ☐ None of the above



66. What is the primary purpose of the InitSeries function in Business Central? * (1 Point)

- ☐ To initialize a new record in the database.
- ☒ To generate a unique number based on a specified number series. ✓
- ☐ To validate user inputs in a form.
- ☐ To delete existing records from a table.



67. What is the purpose of the Provider property in a FactBox area? * (1 Point)

- ☐ To link the FactBox with the header table
- ☒ To link the FactBox with another part on the document page ✓
- ☐ To filter records in the FactBox
- ☐ To display additional information about records



68. Which data type can be used to read bytes from a stream object in AL? * (1 Point)

- ☐ InBlob
- ☒ InStream ✓
- ☐ OutBlob
- ☐ OutStream
- ☐ Media

7

69. What is the purpose of the OutStream data type in AL? * (1 Point) 

- ☐ To read bytes from a stream object
- ☒ To write bytes to a stream object ✓ 
- ☐ To manage temporary data in memory
- ☐ To create XMLports for data exchange

70. Which AL functions are used to specify the source and destination for data import/export in XMLports? * (1 Point) 

- ☐ SetInput and SetOutput
- ☒ SetSource and SetDestination ✓ 
- ☐ ImportData and ExportData
- ☐ ImportXML and ExportXML
- ☐ GetSource and GetDestination
- ☐ GetInput and GetOutput

71. What are some best practices recommended for designing application tests in Business Central? * (1 Point) 

- ☐ Keep test code separate from production code
- ☐ Include positive and negative tests
- ☐ Use hardcoded values only when necessary 
- ☒ All of the above ✓

72. Which feature in Business Central helps you integrate test reports with a test management system? * (1 Point)

- ☐ Test Codeunits
- ☐ Test Pages
- ☒ Test Runner Codeunits ✓
- ☐ UI Handlers

73. Which AL objects are recommended for use instead of XML format for permission sets and permissions? * (1 Point)

- ☐ EntitlementSet and PermissionSet
- ☒ PermissionSet and PermissionSetExtension ✓
- ☐ EntitlementObject and PermissionSetExtension
- ☐ EntitlementObject and PermissionSet

74. What can developers grant permissions to using the InherentPermissions attribute? * (1 Point)

- ☐ Only users
- ☐ Only permission sets
- ☒ Methods, events, and objects ✓
- ☐ Only tables

75. What is the precedence rule when using included and excluded permission sets on the same level? * (1 Point)

- ☒ Excluded permissions take precedence over included permissions ✓
- ☐ Included permissions take precedence over excluded permissions
- ☐ Direct permissions always override indirect permissions
- ☐ Permission sets are applied randomly

76. What property is used to remove permissions defined in other permission sets from a composite permission set? * (1 Point)

- ☐ IncludedPermissionSets
- ☐ Permissions
- ☒ ExcludedPermissionSets ✓
- ☐ Assignable

77. Which method is used to serialize and write the JSON data of a JsonToken variable to a text or stream? * (1 Point)

- ☐ WriteValue
- ☐ SerializeData
- ☒ WriteTo ✓
- ☐ SerializeJson

78. What is the purpose of the ReadFrom method in the JsonToken class? * (1 Point)

- ☐ Retrieves data from a JSON file
- ☒ Reads the JSON data from a text or stream into a JsonToken variable ✓
- ☐ Reads the JSON data and converts it into AL code
- ☐ Reads the JSON data and writes it to a text or stream

79. What is the purpose of the HttpClient in Business Central when working with external REST services? * (1 Point)

- ☐ To define JSON structures
- ☐ To parse JSON documents
- ☒ To handle HTTP requests and responses ✓
- ☐ To convert JSON data to text format

80. How can you send an HTTP request using the HttpRequestMessage class in Business Central? * (1 Point)

- ☐ Using the SetRequestUri method
- ☐ Using the Method method
- ☒ Using the Send method of the HttpClient class ✓
- ☐ Using the GetHeaders method

81. What naming convention should be followed for fields in an API page? * (1 Point)

- ☐ PascalCase
- ☒ camelCase ✓
- ☐ kebab-case
- ☐ snake_case

82. What is the correct URL structure for accessing an API endpoint in Business Central Online (SaaS)? * (1 Point)

- ☐ https://<base URL>:<port>/<serverInstance>/api/<API version>/<API publisher>/<API group>/<entity>
- ☒ <https://api.businesscentral.dynamics.com/v2.0/<environment name>/api/<API publisher>/<API group>/<API version>/<entity>> ✓
- ☐ <https://api.businesscentral.dynamics.com/<API version>/<API publisher>/<API group>/<entity>>
- ☐ https://<base URL>/api/<API publisher>/<API group>/<API version>/<entity>

83. What is the primary difference between a while statement and a repeat-until statement? * (1 Point)

- ☐ A while statement checks the condition after each iteration, while a repeat-until statement checks it before.
- ☐ A while statement always runs at least once, while a repeat-until statement may not run at all.
- ☐ A while statement is used for counting iterations, while a repeat-until statement is used for indefinite loops.
- ☐ A while statement can only run one statement, while a repeat-until statement can run multiple statements.
- ☐ None of the above ✓

While check conditions in the beginning

84. How can extension publishers enable telemetry for their apps/extensions? * (1 Point)

- ☐ By setting a telemetry flag in the Azure portal
- ☐ By adding a telemetry section in the app's code
- ☐ By setting an Azure Application Insights connection string in the app's manifest ✓
- ☐ By installing a telemetry plugin

85. Which Azure service is used to gather telemetry data for analysis and presentation? * (1 Point)

- ☐ Azure Data Lake
- ☐ Azure Application Insights ✓
- ☐ Azure Monitor
- ☐ Azure Data Factory

86. How can telemetry be enabled for online environments in Business Central? * (1 Point)

- ☐ By setting the Application Insights Key in the Environment page
- ☐ By using PowerShell commands to configure the Application Insights Connection String
- ☐ By accessing the admin center and enabling telemetry for the environment
- ☐ All of the above ✓

87. How can you limit the result rows in a KQL query while developing it? * (1 Point)

- ☐ By using the summarize operator
- ☐ By adding a take operator after the where operator ✓
- ☐ By using the extend operator
- ☐ By filtering data using the where operator

88. What language is used to query data in Azure Application Insights? * (1 Point)

- ☐ SQL
- ☐ Python
- ☐ Kusto Query Language (KQL) ✓
- ☐ JavaScript
- ☐ English