

LogEpi: Logistic curves applied to Covid-19

Beatriz Cuyabano and Gabriel Rovere

April 6, 2020

This vignette offers a brief explanation on how the logistic curve is used to model epidemiological events, and provides a set of examples of analysis using the R package LogEpi¹.

A logistic curve can be used to fit a counting process that starts at zero and ends at a determined number. Such curve has been widely used to describe the growth of a population, the growth of cases in a disease outbreak, or the growth of deaths in a such outbreak. The general logistic function is described as:

$$y = f(x | a, b, c) = \frac{a}{1 + \exp [(b - x)/c]}. \quad (1)$$

The value of y represents the cumulative counts of the event to be described, x represents the days passed after the first occurrence of this event, and a , b , and c are the parameters of the event. To simplify the description, $x = 1$ at the day of the first occurrence.

- a is the total number of occurrences at the stabilization of the event,
- b is the day in which we will observe the maximum new occurrences of the event,
- c is the speed of the process.

The parameters are obtained by minimizing the mean square error (MSE) of the model:

$$\text{MSE} = \frac{1}{n} \sum_{i=1}^n \left(y_i - \frac{a}{1 + \exp [(b - x_i)/c]} \right)^2, \quad (2)$$

$$\hat{a}, \hat{b}, \hat{c} = \text{argmin MSE}, \quad (3)$$

constraining their values to $a \geq \max(y_i)$, $b \geq 1$, and $c > 0$.

Note that this curve does not take into account any demographic or social information. The adjustment is based on the observed numbers provided. If the outbreak is still in its initial stage, projections will be necessary to model the entire outbreak. This will be detailed with examples

¹LogEpi is in its initial versions. Please help us improve our work in this package by reporting any bugs, errors, or suggestions to bia.cdc@gmail.com.

throughout this document. The latest Covid-19 data used for the examples was downloaded directly into R using the LogEpi package, and is provided by Johns Hopkins University (<https://systems.jhu.edu/research/public-health/ncov/>). The datasets are available at the repository <https://github.com/CSSEGISandData/COVID-19>. This data contains the historical numbers of confirmed cases, deaths, and recovery, both globally and detailed for all the states of the United States. The examples are based on the data downloaded April 6, 2020.

We will start by loading the package and defining the folder and filenames template to download the Covid-19 data.

```
# load LogEpi package
library(LogEpi)

# define folder and filenames template for the Covid-19 data
tmp.folder <- "Covid19_folder"
tmp.filename <- "Covid19_JHdata"
```

Function `load_JH_db()` downloads the datasets into the folder defined in object `tmp.folder`, using the object `tmp.filename` as the filenames template.

```
# download the data from the JHU repository
# https://github.com/CSSEGISandData/COVID-19
loc <- load_JH_db(folder=tmp.folder, filename=tmp.filename)
```

As of today (April 6, 2020), the recovery data is not available specifically for the US states, only for the country as a whole, therefore the warning message below is expected.

```
# Warning messages:
# 1: In download.file(info.url,paste0(folder,"/",filename,"_",data.type, : cannot open
#   URL 'https://raw.githubusercontent.com/CSSEGISandData/COVID-19/master/csse_covid_
#   19_data/csse_covid_19_time_series/time_series_covid19_recovered_US.csv': HTTP sta
#   tus was '404 Not Found'
# 2: In download.file(info.url,paste0(folder,"/",filename,"_",data.type, : cannot open
#   URL 'https://raw.githubusercontent.com/CSSEGISandData/COVID-19/master/csse_covid_
#   19_data/csse_covid_19_time_series/time_series_covid19_recovered_US.csv': HTTP sta
#   tus was '404 Not Found'
```

The output of `load_JH_db()` is a list with two objects: `countries` and `US_states`. These are the lists of places for which the data is available.

```
head(loc$countries)

## [1] "Afghanistan"      "Albania"          "Algeria"
## [4] "Andorra"          "Angola"            "Antigua and Barbuda"

head(loc$US_states)

## [1] "Alabama"      "Alaska"      "American Samoa" "Arizona"
## [5] "Arkansas"     "California"
```

To extract the Covid-19 data from a location of interest, function `extract_covid19_data()` will be used. If the interest is in the data from a country, set argument `data="global"`. If the interest is in the data from a US state, set argument `data="US"`. The output will be a list with three objects: `confirmed`, `deaths`, and `recovered`. For data on states of the US, `recovered` will be `NULL`. Each object has a first column with the name of a province/state/administration within the location, and the subsequent columns are the cumulative reported numbers on the dates indicated as the column's name. If no information is available for sublocations, the first column will be empty and only one row of data will be output. We offer three examples to illustrate.

China

```
dataCovid <- extract_covid19_data("China", "global", folder=tmp.folder, filename=tmp.filename)
```

```
head(dataCovid$confirmed[,1:8],7)
```

##	Province/State	1/22/20	1/23/20	1/24/20	1/25/20	1/26/20	1/27/20	1/28/20
## 1	Anhui	1	9	15	39	60	70	106
## 2	Beijing	14	22	36	41	68	80	91
## 3	Chongqing	6	9	27	57	75	110	132
## 4	Fujian	1	5	10	18	35	59	80
## 5	Gansu	0	2	2	4	7	14	19
## 6	Guangdong	26	32	53	78	111	151	207
## 7	Guangxi	2	5	23	23	36	46	51

```
head(dataCovid$deaths[,1:8],7)
```

##	Province/State	1/22/20	1/23/20	1/24/20	1/25/20	1/26/20	1/27/20	1/28/20
## 1	Anhui	0	0	0	0	0	0	0
## 2	Beijing	0	0	0	0	0	1	1
## 3	Chongqing	0	0	0	0	0	0	0
## 4	Fujian	0	0	0	0	0	0	0
## 5	Gansu	0	0	0	0	0	0	0
## 6	Guangdong	0	0	0	0	0	0	0
## 7	Guangxi	0	0	0	0	0	0	0

```
head(dataCovid$recovered[,1:8],7)
```

##	Province/State	1/22/20	1/23/20	1/24/20	1/25/20	1/26/20	1/27/20	1/28/20
## 1	Anhui	0	0	0	0	0	0	0
## 2	Beijing	0	0	1	2	2	2	4
## 3	Chongqing	0	0	0	0	0	0	0
## 4	Fujian	0	0	0	0	0	0	0
## 5	Gansu	0	0	0	0	0	0	0
## 6	Guangdong	0	2	2	2	2	4	4
## 7	Guangxi	0	0	0	0	0	0	2

Italy

```
dataCovId <- extract_covid19_data("Italy","global",folder=tmp.folder,filename=tmp.filename)
dataCovId$confirmed[,1:8]

## Province/State 1/22/20 1/23/20 1/24/20 1/25/20 1/26/20 1/27/20 1/28/20
## 1                0        0        0        0        0        0        0

dataCovId$deaths[,1:8]

## Province/State 1/22/20 1/23/20 1/24/20 1/25/20 1/26/20 1/27/20 1/28/20
## 1                0        0        0        0        0        0        0

dataCovId$recovered[,1:8]

## Province/State 1/22/20 1/23/20 1/24/20 1/25/20 1/26/20 1/27/20 1/28/20
## 1                0        0        0        0        0        0        0
```

Michigan (US state)

```
dataCovId <- extract_covid19_data("Michigan","US",folder=tmp.folder,filename=tmp.filename)
head(dataCovId$confirmed[,1:8])

## Admin2 1/22/20 1/23/20 1/24/20 1/25/20 1/26/20 1/27/20 1/28/20
## 1 Alcona      0        0        0        0        0        0        0
## 2 Alger       0        0        0        0        0        0        0
## 3 Allegan     0        0        0        0        0        0        0
## 4 Alpena      0        0        0        0        0        0        0
## 5 Antrim       0        0        0        0        0        0        0
## 6 Arenac      0        0        0        0        0        0        0

head(dataCovId$deaths[,1:8])

## Admin2 1/22/20 1/23/20 1/24/20 1/25/20 1/26/20 1/27/20 1/28/20
## 1 Alcona      0        0        0        0        0        0        0
## 2 Alger       0        0        0        0        0        0        0
## 3 Allegan     0        0        0        0        0        0        0
## 4 Alpena      0        0        0        0        0        0        0
## 5 Antrim       0        0        0        0        0        0        0
## 6 Arenac      0        0        0        0        0        0        0

head(dataCovId$recovered[,1:8])

## NULL
```

Now, we want to build epidemic tables, with the data displayed in columns. This will be done using function `mkEpiTable()`. By default, the output is a table with cumulative the cumulative numbers of confirmed cases, deaths and recovered, as well as the number of active cases on the dates. Setting `daily=TRUE` will change the output to a table with the numbers reported in each day. The number of active cases is reported equally for both `daily=TRUE` and `daily=FALSE`, as this number is neither

cumulative nor new occurrences. For locations with detailed data by province/state/administration, data can be narrowed to a specific sublocation, or a set of sublocations. We offer a few examples on two different locations to illustrate.

China

```
dataCovId <- extract_covid19_data("China", "global", folder=tmp.folder, filename=tmp.filename)
tbCovId <- mkEpiTable(dataCovId)
head(tbCovId)
```

```
##           date confirmed deaths recovered active
## 1 2020-01-22      548      17         28    503
## 2 2020-01-23      643      18         30    595
## 3 2020-01-24      920      26         36    858
## 4 2020-01-25     1406      42         39   1325
## 5 2020-01-26     2075      56         49   1970
## 6 2020-01-27     2877      82         58   2737
```

```
tbCovId <- mkEpiTable(dataCovId, daily=TRUE)
head(tbCovId)
```

```
##           date confirmed deaths recovered active
## 1 2020-01-22      548      17         28    503
## 2 2020-01-23       95       1          2    595
## 3 2020-01-24      277       8          6    858
## 4 2020-01-25      486      16          3   1325
## 5 2020-01-26      669      14         10   1970
## 6 2020-01-27      802      26          9   2737
```

```
tbCovId <- mkEpiTable(dataCovId, specific="Hubei")
head(tbCovId)
```

```
##           date confirmed deaths recovered active
## 1 2020-01-22      444      17         28    399
## 2 2020-01-23      444      17         28    399
## 3 2020-01-24      549      24         31    494
## 4 2020-01-25      761      40         32    689
## 5 2020-01-26     1058      52         42    964
## 6 2020-01-27     1423      76         45   1302
```

```
tbCovId <- mkEpiTable(dataCovId, specific=c("Hubei", "Guangdong"))
head(tbCovId)
```

```
##           date confirmed deaths recovered active
## 1 2020-01-22      470      17         28    425
## 2 2020-01-23      476      17         30    429
## 3 2020-01-24      602      24         33    545
## 4 2020-01-25      839      40         34    765
## 5 2020-01-26     1169      52         44   1073
## 6 2020-01-27     1574      76         49   1449
```

Michigan (US state)

```
dataCovid <- extract_covid19_data("Michigan","US",folder=tmp.folder,filename=tmp.filename)
tbCovid <- mkEpiTable(dataCovid)
head(tbCovid)

##           date confirmed deaths recovered active
## 1 2020-01-22          0         0          NA     NA
## 2 2020-01-23          0         0          NA     NA
## 3 2020-01-24          0         0          NA     NA
## 4 2020-01-25          0         0          NA     NA
## 5 2020-01-26          0         0          NA     NA
## 6 2020-01-27          0         0          NA     NA

head(tbCovid[tbCovid$confirmed > 0,])

##           date confirmed deaths recovered active
## 50 2020-03-11          2         0          NA     NA
## 51 2020-03-12          2         0          NA     NA
## 52 2020-03-13         16         0          NA     NA
## 53 2020-03-14         25         0          NA     NA
## 54 2020-03-15         32         0          NA     NA
## 55 2020-03-16         54         0          NA     NA

tbCovid <- mkEpiTable(dataCovid,specific="Ingham")
head(tbCovid)

##           date confirmed deaths recovered active
## 1 2020-01-22          0         0          NA     NA
## 2 2020-01-23          0         0          NA     NA
## 3 2020-01-24          0         0          NA     NA
## 4 2020-01-25          0         0          NA     NA
## 5 2020-01-26          0         0          NA     NA
## 6 2020-01-27          0         0          NA     NA


head(tbCovid[tbCovid$confirmed > 0,])

##           date confirmed deaths recovered active
## 52 2020-03-13          1         0          NA     NA
## 53 2020-03-14          1         0          NA     NA
## 54 2020-03-15          1         0          NA     NA
## 55 2020-03-16          1         0          NA     NA
## 56 2020-03-17          3         0          NA     NA
## 57 2020-03-18          5         0          NA     NA
```

The next step is to use these tables generated by `mkEpiTable()` to model the logistic curves of the epidemic in the location of interest. We will now use the function `mkEpiCurves()`.

China

```
dataCovId <- extract_covid19_data("China", "global", folder=tmp.folder, filename=tmp.filename)
tbCovId <- mkEpiTable(dataCovId)
fitCovId <- mkEpiCurves(tbCovId, plot.title="China")
```



```
# print the parameters of the curves
```

```
fitCovId$par
```

```
##          a          b          c
## confirmed 82602 19.03933 4.719325
## deaths    3333 25.85590 6.917347
## recovered 79269 39.81607 7.792875
```

```
# print the dates in which the first observation of the epidemic events occurred
```

```
fitCovId$day1
```

```
## confirmed deaths recovered
## "2020-01-22" "2020-01-22" "2020-01-22"
```

```
# print the key dates of the of this epidemic
```

```
fitCovId$key_dates
```


```
## start_critical    inflection most_critical    end_critical
## "2020-02-01"     "2020-02-09"  "2020-02-19"  "2020-02-27"

# rates with which the epidemic event develops
head(fitCovid$rates)

##          date confirmed  deaths recovered
## 1 2020-01-22  0.000000 0.000000 0.000000
## 2 2020-01-23  1.173358 1.058824 1.071429
## 3 2020-01-24  1.430793 1.444444 1.200000
## 4 2020-01-25  1.528261 1.615385 1.083333
## 5 2020-01-26  1.475818 1.333333 1.256410
## 6 2020-01-27  1.386506 1.464286 1.183673
```


The rates in `fitCovid$rates` are the percentage with which the events develop. For example, if in a day the total number reported of the epidemic event is 100, and 120 on the next day, the rate observed in this next day is $120/100 = 1.2$, an increase of 20%.

```
# plot the rates
xrange <- c(1,nrow(fitCovid$rates))
yrange <- range(fitCovid$rates[, -1])
plot(NA,xlim=xrange,ylim=yrange,xlab="days after first record",ylab="rates")
lines(1:nrow(fitCovid$rates),fitCovid$rates$confirmed,lwd=1.5,col=4)
lines(1:nrow(fitCovid$rates),fitCovid$rates$deaths,lwd=1.5,col=2)
lines(1:nrow(fitCovid$rates),fitCovid$rates$recovered,lwd=1.5,col=3)
abline(v=which(fitCovid$rates$date == today()))
legend("topright",lwd=2,col=c(4,2,3),legend=names(fitCovid$rates)[-1])
```



Italy

```
dataCovid <- extract_covid19_data("Italy","global",folder=tmp.folder,filename=tmp.filename)
tbCovid <- mkEpiTable(dataCovid)
fitCovid <- mkEpiCurves(tbCovid,plot.title="Italy")
```



```
# print the parameters of the curves
fitCovid$par

##           a           b           c
## confirmed 142543.43  54.36203  5.812610
## deaths    18915.67  36.29729  5.462303
## recovered 123627.76  57.30615  9.270946

# print the dates in which the first observation of the epidemic events occurred
fitCovid$day1

## confirmed      deaths      recovered
## "2020-01-31" "2020-02-21" "2020-02-22"


# print the key dates of the of this epidemic
fitCovid$key_dates
```

```
## start_critical      inflection most_critical end_critical
## "2020-03-14"      "2020-03-24"  "2020-04-06"  "2020-04-16"
```

```
# rates with which the epidemic event develops
head(fitCovid$rates)
```


```
##          date confirmed deaths recovered
## 1 2020-01-31          0          0          0
## 2 2020-02-01          1          0          0
## 3 2020-02-02          1          0          0
## 4 2020-02-03          1          0          0
## 5 2020-02-04          1          0          0
## 6 2020-02-05          1          0          0
```

```
# plot the rates
xrange <- c(1,nrow(fitCovid$rates))
yrange <- range(fitCovid$rates[, -1])
plot(NA,xlim=xrange,ylim=yrange,xlab="days after first record",ylab="rates")
lines(1:nrow(fitCovid$rates),fitCovid$rates$confirmed,lwd=1.5,col=4)
lines(1:nrow(fitCovid$rates),fitCovid$rates$deaths,lwd=1.5,col=2)
lines(1:nrow(fitCovid$rates),fitCovid$rates$recovered,lwd=1.5,col=3)
abline(v=which(fitCovid$rates$date == today()))
legend("topright",lwd=2,col=c(4,2,3),legend=names(fitCovid$rates)[-1])
```



Michigan (US state)

```
dataCovid <- extract_covid19_data("Michigan","US",folder=tmp.folder,filename=tmp.filename)
tbCovid <- mkEpiTable(dataCovid)
fitCovid <- mkEpiCurves(tbCovid,plot.title="Michigan")
```



```
# print the parameters of the curves
```

```
fitCovid$par
```

```
##           a           b           c
## confirmed 24361.5974 23.75432 3.763596
## deaths    808.0161 15.98536 2.644672
## recovered 23553.5813 24.000000 4.308768
```

```
# print the dates in which the first observation of the epidemic events occurred
```

```
fitCovid$day1
```

```
## confirmed deaths recovered
## "2020-03-11" "2020-03-18" "2020-03-25"
```

```
# print the key dates of the of this epidemic
```


```
fitCovid$key_dates
```

```
## start_critical      inflection most_critical end_critical
## "2020-03-27"      "2020-04-03"  "2020-04-11"  "2020-04-18"
```

```
# rates with which the epidemic event develops
head(fitCovid$rates)
```


```
##          date confirmed deaths recovered
## 1 2020-03-11    0.0000      0          0
## 2 2020-03-12    1.0000      0          0
## 3 2020-03-13    8.0000      0          0
## 4 2020-03-14    1.5625      0          0
## 5 2020-03-15    1.2800      0          0
## 6 2020-03-16    1.6875      0          0
```

```
# plot the rates
xrange <- c(1,nrow(fitCovid$rates))
yrange <- range(fitCovid$rates[, -1])
plot(NA,xlim=xrange,ylim=yrange,xlab="days after first record",ylab="rates")
lines(1:nrow(fitCovid$rates),fitCovid$rates$confirmed,lwd=1.5,col=4)
lines(1:nrow(fitCovid$rates),fitCovid$rates$deaths,lwd=1.5,col=2)
lines(1:nrow(fitCovid$rates),fitCovid$rates$recovered,lwd=1.5,col=3)
abline(v=which(fitCovid$rates$date == today()))
legend("topright",lwd=2,col=c(4,2,3),legend=names(fitCovid$rates)[-1])
```



United States

```
dataCovid <- extract_covid19_data("US", "global", folder=tmp.folder, filename=tmp.filename)
tbCovid <- mkEpiTable(dataCovid)
fitCovid <- mkEpiCurves(tbCovid, plot.title="USA")
```




```
# print the parameters of the curves
```

```
fitCovid$par
```

```
##           a           b           c
## confirmed 1927360.74  79.57167 1.000000
## deaths    89075.85 164.48998 1.758284
## recovered 1838284.89  75.87678 4.088403
```

The figure generated indicates a poor convergence of the model on the current data. This is an indicator that the current state of the epidemic in the US is still not providing sufficient data to model the epidemic. We will work with projections to better understand the situation in the US. In this case, we will generate scenarios for this projection.

```
# project 7 days ahead of developing the epidemic in the current rates
fitCovid <- mkEpiCurves(tbCovid,plot.title="USA",project=7)
```



```
# print the parameters of the curves
fitCovid$par

##           a           b           c
## confirmed 2611806.5 88.10044 6.842560
## deaths    313561.8 54.86306 5.176168
## recovered 2298244.7 88.00000 6.421118

# print the key dates of the of this epidemic
fitCovid$key_dates

## start_critical  inflection  most_critical  end_critical
## "2020-04-06"    "2020-04-18"  "2020-05-02"  "2020-05-14"

# print the rates of the projection
unlist(fitCovid$rates_proj)

## confirmed  deaths
## 1.123794  1.200066
```