

Lecture 5

Functions. Conditional Expressions & Operators.

Senior Lecturer: Sholpan Saimassayeva

Overview

- **Mathematical functions and operators**
- **String functions and operators**
- **Condition expressions and operators**

Mathematical functions and operators

Mathematical Functions

Function	Return Type	Description	Example	Result
<code>abs(x)</code>	(same as input)	absolute value	<code>abs(-17.4)</code>	17.4
<code>cbrt(dp)</code>	dp	cube root	<code>cbrt(27.0)</code>	3
<code>ceil(dp or numeric)</code>	(same as input)	nearest integer greater than or equal to argument	<code>ceil(-42.8)</code>	-42
<code>ceiling(dp or numeric)</code>	(same as input)	nearest integer greater than or equal to argument (same as <code>ceil</code>)	<code>ceiling(-95.3)</code>	-95
<code>degrees(dp)</code>	dp	radians to degrees	<code>degrees(0.5)</code>	28.6478897565412
<code>div(y numeric, x numeric)</code>	numeric	integer quotient of y/x	<code>div(9,4)</code>	2
<code>exp(dp or numeric)</code>	(same as input)	exponential	<code>exp(1.0)</code>	2.71828182845905
<code>floor(dp or numeric)</code>	(same as input)	nearest integer less than or equal to argument	<code>floor(-42.8)</code>	-43
<code>ln(dp or numeric)</code>	(same as input)	natural logarithm	<code>ln(2.0)</code>	0.693147180559945
<code>log(dp or numeric)</code>	(same as input)	base 10 logarithm	<code>log(100.0)</code>	2
<code>log(b numeric, x numeric)</code>	numeric	logarithm to base b	<code>log(2.0, 64.0)</code>	6.0000000000
<code>mod(y, x)</code>	(same as argument types)	remainder of y/x	<code>mod(9,4)</code>	1

Mathematical Functions

<code>pi()</code>	dp	"n" constant	<code>pi()</code>	3.14159265358979
<code>power(a dp, b dp)</code>	dp	<i>a</i> raised to the power of <i>b</i>	<code>power(9.0, 3.0)</code>	729
<code>power(a numeric, b numeric)</code>	numeric	<i>a</i> raised to the power of <i>b</i>	<code>power(9.0, 3.0)</code>	729
<code>radians(dp)</code>	dp	degrees to radians	<code>radians(45.0)</code>	0.785398163397448
<code>round(dp or numeric)</code>	(same as input)	round to nearest integer	<code>round(42.4)</code>	42
<code>round(v numeric, s int)</code>	numeric	round to <i>s</i> decimal places	<code>round(42.4382, 2)</code>	42.44
<code>scale(numeric)</code>	integer	scale of the argument (the number of decimal digits in the fractional part)	<code>scale(8.41)</code>	2
<code>sign(dp or numeric)</code>	(same as input)	sign of the argument (-1, 0, +1)	<code>sign(-8.4)</code>	-1
<code>sqrt(dp or numeric)</code>	(same as input)	square root	<code>sqrt(2.0)</code>	1.4142135623731
<code>trunc(dp or numeric)</code>	(same as input)	truncate toward zero	<code>trunc(42.8)</code>	42
<code>trunc(v numeric, s int)</code>	numeric	truncate to <i>s</i> decimal places	<code>trunc(42.4382, 2)</code>	42.43

Mathematical Functions

<code>width_bucket(operand dp, b1 dp, b2 dp, count int)</code>	int	return the bucket number to which <i>operand</i> would be assigned in a histogram having <i>count</i> equal-width buckets spanning the range <i>b1</i> to <i>b2</i> ; returns 0 or <i>count</i> +1 for an input outside the range	<code>width_bucket(5.35, 0.024, 10.06, 5)</code>	3
<code>width_bucket(operand numeric, b1 numeric, b2 numeric, count int)</code>	int	return the bucket number to which <i>operand</i> would be assigned in a histogram having <i>count</i> equal-width buckets spanning the range <i>b1</i> to <i>b2</i> ; returns 0 or <i>count</i> +1 for an input outside the range	<code>width_bucket(5.35, 0.024, 10.06, 5)</code>	3
<code>width_bucket(operand anyelement, thresholds anyarray)</code>	int	return the bucket number to which <i>operand</i> would be assigned given an array listing the lower bounds of the buckets; returns 0 for an input less than the first lower bound; the <i>thresholds</i> array must be sorted , smallest first, or unexpected results will be obtained	<code>width_bucket(now(), array['yesterday', 'today', 'tomorrow']::timestampz[])</code>	2

Random Functions

Function	Return Type	Description
<code>random()</code>	<code>dp</code>	random value in the range $0.0 \leq x < 1.0$
<code>setseed(dp)</code>	<code>void</code>	set seed for subsequent <code>random()</code> calls (value between -1.0 and 1.0, inclusive)

Trigonometric Functions

Function (radians)	Function (degrees)	Description
<code>acos(x)</code>	<code>acosd(x)</code>	inverse cosine
<code>asin(x)</code>	<code>asind(x)</code>	inverse sine
<code>atan(x)</code>	<code>atand(x)</code>	inverse tangent
<code>atan2(y, x)</code>	<code>atan2d(y, x)</code>	inverse tangent of y/x
<code>cos(x)</code>	<code>cosd(x)</code>	cosine
<code>cot(x)</code>	<code>cotd(x)</code>	cotangent
<code>sin(x)</code>	<code>sind(x)</code>	sine
<code>tan(x)</code>	<code>tand(x)</code>	tangent

String functions and operators

PostgreSQL FORMAT Function

PostgreSQL **FORMAT()** function formats arguments based on a format string.

The syntax of the PostgreSQL **FORMAT()** function is as follows:

```
FORMAT(format_string [, format_arg [, ...] ])
```

String Functions and Operators

Function	Return Type	Description	Example	Result
<code>string string</code>	text	String concatenation	<code>'Post' 'greSQL'</code>	PostgreSQL
<code>string non-string or non-string string</code>	text	String concatenation with one non-string input	<code>'Value: ' 42</code>	Value: 42
<code>bit_length(string)</code>	int	Number of bits in string	<code>bit_length('jose')</code>	32
<code>char_length(string)</code> or <code>character_length(string)</code>	int	Number of characters in string	<code>char_length('jose')</code>	4
<code>lower(string)</code>	text	Convert string to lower case	<code>lower('TOM')</code>	tom
<code>octet_length(string)</code>	int	Number of bytes in string	<code>octet_length('jose')</code>	4
<code>overlay(string placing string from int [for int])</code>	text	Replace substring	<code>overlay('Txxxxas' placing 'hom' from 2 for 4)</code>	Thomas
<code>position(substring in string)</code>	int	Location of specified substring	<code>position('om' in 'Thomas')</code>	3
<code>substring(string [from int] [for int])</code>	text	Extract substring	<code>substring('Thomas' from 2 for 3)</code>	hom
<code>substring(string from pattern)</code>	text	Extract substring matching POSIX regular expression. See Section 9.7 for more information on pattern matching.	<code>substring('Thomas' from '...\$')</code>	mas
<code>substring(string from pattern for escape)</code>	text	Extract substring matching SQL regular expression. See Section 9.7 for more information on pattern matching.	<code>substring('Thomas' from '%#\"o_a#\"_' for '#')</code>	oma
<code>trim([leading trailing both] [characters] from string)</code>	text	Remove the longest string containing only characters from <i>characters</i> (a space by default) from the start, end, or both ends (both is the default) of <i>string</i>	<code>trim(both 'xyz' from 'yxTomxx')</code>	Tom
<code>trim([leading trailing both] [from] string [, characters])</code>	text	Non-standard syntax for <code>trim()</code>	<code>trim(both from 'yxTomxx', 'xyz')</code>	Tom
<code>upper(string)</code>	text	Convert string to upper case	<code>upper('tom')</code>	TOM

Examples

```
SELECT FORMAT('Hello, %s', 'PostgreSQL');
```

Data Output		Explain	Message
	format text		
1	Hello, PostgreSQL		

```
SELECT  
FORMAT('%s, %s', last_name, first_name) full_name FROM  
passengers  
ORDER BY full_name;
```

Data Output		Explain	Mes
	full_name text		
1	Abethell, Adele		
2	Adan, Lyndy		
3	Addekin, Hermon		
4	Aglione, Honor		
5	Akam, Creight		
6	Albone, Randy		
7	Aldcorn, Bess		
8	Alliston, Alexander		

PostgreSQL Letter Case Functions

- PostgreSQL **LOWER** function
- PostgreSQL **UPPER** function
- PostgreSQL **INITCAP** function

Examples

--LOWER() FUNCTION

```
SELECT LOWER(last_name)
FROM
passengers ORDER BY last_name;
```

Data Output Explain

	lower text	lock
1	abethell	
2	adan	
3	addekin	
4	aglione	

--UPPER() FUNCTION


```
SELECT UPPER(last_name)
FROM
passengers ORDER BY last_name;
```

Data Output Explain

	upper text	
1	ABETHELL	
2	ADAN	
3	ADDEKIN	
4	AGLIONE	


Examples

```
SELECT INITCAP('hello world') as example;
```

Data Output		Expl
	example text	
1	Hello World	

```
--INITCAP() FUNCTION
```

```
SELECT INITCAP(CONCAT (first_name, ' ', last_name))  
FROM  
passengers ORDER BY first_name;
```

	initcap text	
1	Abbie Gatland	
2	Abner Philippet	
3	Adamo Biggs	
4	Adele Abethell	
5	Ailene Nuzzi	
6	Aldo Arnison	

PostgreSQL LEFT Function

The PostgreSQL **LEFT()** function returns the first n characters in the string.

The following illustrates the syntax of the PostgreSQL **LEFT()** function:

```
LEFT(string, n)
```


Examples

```
SELECT LEFT('ABC',1);--A
```

```
SELECT LEFT('ABC',2);--AB
```

PostgreSQL RIGHT Function

The PostgreSQL **RIGHT()** function returns the last n characters in a string.

The following shows the syntax of the PostgreSQL **RIGHT()** function:

```
RIGHT(string, n)
```

Examples

```
SELECT RIGHT('XYZ', 2);--YZ
```

```
SELECT RIGHT('XYZ', 1);--Z
```

```
SELECT last_name FROM passengers  
WHERE RIGHT(last_name,3) = 'son';
```

Data Output		Explain	M
	last_name character varying (50)		
1	Davison		
2	Dotson		
3	Imason		
4	Arnison		
5	Edison		
6	Kristoffersson		
7	Utterson		

PostgreSQL TRIM Function

- The **LTRIM()** function removes all characters, spaces by default, from the beginning of a string.
- The **RTRIM()** function removes all characters, spaces by default, from the end of a string.
- The **BTRIM()** function is the combination of the **LTRIM()** and **RTRIM()** functions.

Examples

SELECT

LTRIM('enterprise', 'e');--nterprise

SELECT

RTRIM('enterprise', 'e');--enterpris

SELECT

BTRIM('enterprise', 'e');--nterpris

PostgreSQL POSITION Function

The PostgreSQL **POSITION()** function returns the location of a substring in a string.

The following illustrates the syntax of the PostgreSQL **POSITION()** function:

POSITION(substring in string)

Example

```
SELECT POSITION('example' IN 'PostgreSQL example');--12
```

```
SELECT POSITION('example' IN 'PostgreSQL Example');--0
```

PostgreSQL REPLACE Function

To search and replace all occurrences of a string with a new one, you use the **REPLACE()** function.

The following illustrates the syntax of the PostgreSQL **REPLACE()** function:

```
REPLACE(source, old_text, new_text );
```


Examples

SELECT

REPLACE ('ABC AA', 'A', 'Z'); --ZBC ZZ

UPDATE

customer

SET

email = REPLACE (email, 'test.com',
'example.com')

PostgreSQL Substring Function

The **substring** function returns a part of string. The following illustrates the syntax of the **substring** function:

```
SUBSTRING ( string ,start_position , length )
```

Examples

```
SELECT  
SUBSTRING ('PostgreSQL', 1, 8); -- PostgreS
```

```
SELECT  
SUBSTRING ('PostgreSQL', 8); -- SQL
```

```
SELECT  
SUBSTRING ('PostgreSQL' FROM 1 FOR 8); -- PostgreS
```

Conditional expressions and operators

Conditional expressions

- Allow you to execute different logic based on conditions.
- The most used conditional expressions are **CASE**, **COALESCE**, **NULLIF**, and conditional operators like **GREATEST** and **LEAST**.





CASE

- The SQL CASE expression is a generic conditional expression, similar to if/else statements in other programming languages:

```
CASE WHEN condition THEN result
      [WHEN ...]
      [ELSE result]
END
```

CASE

```
SELECT
  booking_id,
  price,
  CASE
    WHEN price > 5000 THEN 'High'
    WHEN price BETWEEN 3000 AND 5000 THEN 'Medium'
    ELSE 'Low'
  END AS PriceLevel
FROM booking;
```

	Data Output	Explain	Messages	Notifications
	 booking_id [PK] integer 		price numeric (7,2) 	pricelevel text 
1	1		7462.13	High
2	2		4216.60	Medium
3	3		5782.37	High
4	4		102.96	Low
5	5		6711.04	High
6	6		7813.55	High
7	7		1346.71	Low
8	8		5711.67	High
9	9		7015.82	High
10	10		1668.38	Low

COALESCE

- The COALESCE function returns the first of its arguments that is not null. Null is returned only if all arguments are null.

```
COALESCE(value [, ...])
```

```
SELECT COALESCE(description, short_description, '(none)') ...
```


Example

```
1 SELECT
2     passenger_id,
3     COALESCE(passport_number, 'No number') AS passport_of_passenger
4 FROM passengers order by passenger_id;
```

Data Output Explain Messages Notifications

	passenger_id [PK] integer 	passport_of_passenger character varying 	
1	1	176443701-2	
2	2	229690188-3	
3	3	595940366-8	
4	4	604001503-9	
5	5	No number	
6	6	865501891-0	
7	7	670764566-8	
8	8	951717035-1	
9	9	482708473-4	

NULLIF

- The `NULLIF` function returns a null value if *value1* equals *value2*; otherwise it returns *value1*. This can be used to perform the inverse operation of the `COALESCE` example given above:

```
NULLIF(value1, value2)
```

```
SELECT NULLIF(value, '(none)') ...
```

Example

```
SELECT
    booking_id,
    NULLIF(price, 0) as price
FROM booking ORDER BY booking_id;
```

Output Explain Messages Notifications

booking_id [PK] integer	price numeric (7,2)	
1	8101.06	
2	7947.11	
3	[null]	
4	9247.57	
5	5765.23	
6	1447.67	
7	2624.79	

GREATEST & LEAST

- The `GREATEST` and `LEAST` functions select the largest or smallest value from a list of any number of expressions.

```
GREATEST(value [, ...])
```

```
LEAST(value [, ...])
```

Example

```
SELECT
    booking_id,
    GREATEST(10000, price, 5000) AS Max,
    LEAST(10000, price, 5000) AS Min
FROM booking;
```

[Output](#) [Explain](#) [Messages](#) [Notifications](#)

	booking_id [PK] integer	max numeric	min numeric	
	4	10000	5000	
	5	10000	5000	
	6	10000	1447.67	
	7	10000	2624.79	
	8	10000	5000	
	9	10000	1204.56	
	10	10000	2365.17	
	11	10000	2236.74	
	12	10000	2753.61	

