

PRACTICAL : WEEK 7

Task - 1:

Write a program that prints the addresses of code, global, static, heap, and stack variables. Analyze the Linux process address space layout and explain each memory segment.

CODE:

```
#include <stdio.h>
#include <stdlib.h>

int global_var = 10;
static int static_var = 20;

void code_function()
{
    printf("Code address    : %p\n", (void *)code_function);
}

int main()
{
    int stack_var = 30;
    int *heap_var = (int *)malloc(sizeof(int));

    *heap_var = 40;

    printf("Memory Addresses:\n");

    code_function();

    printf("Global address : %p\n", (void *)&global_var);
    printf("Static address : %p\n", (void *)&static_var);
    printf("Heap address   : %p\n", (void *)heap_var);
    printf("Stack address  : %p\n", (void *)&stack_var);

    free(heap_var);

    return 0;
}
```

OUTPUT:

```
[b.deepak@BDeepaks-MacBook-Air ~ % nano memory.c
[b.deepak@BDeepaks-MacBook-Air ~ % gcc memory.c -o memory
[b.deepak@BDeepaks-MacBook-Air ~ % ./memory
Memory Addresses:
Code address      : 0x1044a04f8
Global address    : 0x1044a8000
Static address    : 0x1044a8004
Heap address      : 0x1044d5050
Stack address     : 0x16b95f138
b.deepak@BDeepaks-MacBook-Air ~ % █
```

Task - 2:

Make use of the /proc//maps file and memory analysis tools to study the memory organization of a running process. Prepare a report explaining virtual memory mappings.

CODE:

```
#include <stdio.h>
#include <unistd.h>
#include <stdlib.h>

int global_var = 100;
static int static_var = 200;

int main()
{
    int stack_var = 300;
    int *heap_var = malloc(sizeof(int));

    *heap_var = 400;

    printf("Process is running...\n");
    printf("PID: %d\n", getpid());

    printf("Global variable address: %p\n", (void *)&global_var);
    printf("Static variable address: %p\n", (void *)&static_var);
    printf("Heap variable address: %p\n", (void *)heap_var);
    printf("Stack variable address: %p\n", (void *)&stack_var);

    printf("\nProcess will remain active for 60 seconds.\n");

    sleep(60);

    free(heap_var);

    return 0;
} █
```

OUTPUT:

```
[b.deepak@BDeepaks-MacBook-Air ~ % nano memorymap.c
[b.deepak@BDeepaks-MacBook-Air ~ % gcc memorymap.c -o memory
[b.deepak@BDeepaks-MacBook-Air ~ % ./memorymap
zsh: no such file or directory: ./memorymap
[b.deepak@BDeepaks-MacBook-Air ~ % gcc memory.c -o memorymap
[b.deepak@BDeepaks-MacBook-Air ~ % ./memorymap
Memory Addresses:
Code address   : 0x1003ac4f8
Global address : 0x1003b4000
Static address : 0x1003b4004
Heap address   : 0x100aa1050
Stack address   : 0x16fa53138
b.deepak@BDeepaks-MacBook-Air ~ % █
```