


DIMENSIONS

All dimensions are approximate. Dimensions may vary with bucket and tire choice. Refer to operating specifications.



NO.	DESCRIPTION	UNIT	DATE
A	Overall Height – Bucket Raised	mm	5323
B	Bucket Pin Height at Max. Lift	mm	4163
C	Dump Clearance at Max. Lift (45°)	mm	3080
D	Reach at Max. Lift and 45° Dump	mm	1256
E	Rack Back Angle at Carry	°	49.3
F	Rack Back Angle at Ground	°	46
G	Digging Depth	mm	50
H	Rack Back Angle at Max. Lift	°	58.3
I	Dump Angle at Max. Lift	°	45
J	Carry Height	mm	400
K	Ground Clearance	mm	409
L	Center Line of Front Axle to Hitch	mm	1615
M	Wheel Base	mm	3230
N	Overall Length	mm	8100
O	Departure Angle	°	30
P	Height to Top of Cab	mm	3380
Q	Overall Width over Bucket	mm	3010
R	Min. Turning Radius over Bucket	mm	7240
S	Min. Turning Radius over Tires	mm	6650
T	Steering Angle – Left/Right	°	35
U	Width at Tread Center	mm	2240
V	Overall Width over Tires	mm	2835

TECHNICAL PARAMETERS

BASIC	Bucket Capacity	3.0m³
	Rated Payload	5000kg
	Operating Weight	17300±300kg
	Traction Force	155±3kN
	Breakout Force	170±3kN
	L×W×H	8100×3010×3380mm
ENGINE	Maker/Model	6CTAA8.3-C215
	Rated Power	160kW/2200rpm
	Maximum Torque	904N·m/1400rpm
	Bore x Stroke	114×135mm
	No. of Cylinders /Displacement	6/8.3L
	Air Cleaner	Dry, Double Elements
	Alternator	70Amp
	Battery	2-24V/120Ah
DRIVE TRAIN	Starting Motor	24V/7.8kW
	Transmission Type	Planetary Powershift
	Shift Type	Mechanical Powershift Control
	Pressure of Transmission	1.1-1.5MPa
	Torque Converter Type	Single-stage, Duo-turbine, 4-element
	Axles	Rigid (Front)&Oscillating (Rear)
	Rear Axle Oscillation	±10°
	Differential	Conventional
	Main Reducer	Spiral Bevel, 1-stage Reduction
	Final Reducer	Planetary Reduction
BRAKE SYSTEM	Tire	23.5-25 L-3 16PR TT
	Travel Speed-Forward	11.5/36 km/h
	Travel Speed-Reverse	16 km/h
	Service Brake	Single Circuit Caliper, Dry Brake
STEERING SYSTEM	Setting Pressure	0.70-0.78MPa
	Parking Brake	Air Actuated Caliper Brake
	Emergency Brake	Air Actuated Caliper Brake
	Type	Hydraulic Load Sensing System
HYDRAULIC SYSTEM	Pump	176L/min-2200rpm
	System Pressure	15MPa
	Cylinder Type	Double Acting
	Steering Angle	±35°
SERVICE REFILL CAPACITY	Type	Joystick Control (Single-lever)
	Pump	220L/min-2200rpm
	Control Valve	2 Spool
	System Pressure	16MPa
	Cycle Time (Sec)	11
SERVICE REFILL CAPACITY	Fuel Tank	285L
	Hydraulic Tank	270/275(3rd Spool)L
	Crankshaft	20L
	Transmission	46L
SERVICE REFILL CAPACITY	Front Axle/Rear Axle	28L/28L

CONFIGURATION

Cummins Engine (DCEC)
LONKING Transmission
Mechanical Powershift Control
LONKING Axles (Dry type)
Joystick Working Control (Single-lever)
Air Actuated Caliper Brake
ROPS&FOPS Cabin
Combination Instrument
Air Conditioner

OPTIONAL

High Dump
Oil-bath Air Filter
Cold Starting(-35°C)
Radial Tires
3rd Spool for Auxiliary Function
Sliding Cabin Window
Electric Heating Rear Window
Lockable Oil Tank Cap
Rear View Camera
Bucket(3 Piece Cutting Edges)
Rock Bucket(3.0m³)
Enlarged Bucket(3.5m³)
Coal Bucket(4.2m³)
Log Grapple
Grass Grapple
Marble Fork
Log Fork
Quick Hitch Coupler
Quick Hitch Bucket(3.0m³)
4in1 Bucket(Quick Hitch Only)
Snow Blade(Quick Hitch Only)

LONKING 龙工

Basic Code: 10805611720

CDM856
WHEEL LOADER
Efficiency Rules the Future



For more information on Lonking products,
Please contact our local agent:

The following blank can be used for notes or comments.

Lonking, Lonking CDM Series and their respective logos, as well as corporate identity in this leaflet are trademarks of Lonking Holdings Ltd., and may not be used without written permission.
2020/03

Specifications and design are subject to change without prior notice.
Machines shown may not include optional accessories.

LONKING (FU JIAN) INTERNATIONAL TRADE CO., LTD.
LONKING HOLDINGS LIMITED
Add:26 Minyi Road, Xinqiao, Songjiang Industrial Zone, Shanghai
Tel: +86-21-3760 2242 E-mail: export@lonking.cn
http://www.lonkinggroup.com

- RATED POWER: 160kW/2200rpm
- BUCKET CAPACITY: 3m³
- RATED PAYLOAD: 5000kg
- OPERATING WEIGHT: 17300kg