

palsr: Projected Actor Locations for spatial modeling of dyadic interactions between moving actors

Bruce A. Desmarais¹, Sangyeon Kim², and Howard Liu³

¹ Department of Political Science, Pennsylvania State University, USA ² Pennsylvania State University, USA ³ University of Southern Denmark, Denmark

DOI: [XX.XXXXX/joss.0XXXX](https://doi.org/XX.XXXXX/joss.0XXXX)

Software

- [Review](#) ↗
- [Repository](#) ↗
- [Archive](#) ↗

Submitted: 13 June 2026

Published: 13 June 2026

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

Many actors studied in the social sciences have no fixed geographic location. Armed groups roam across a theater of conflict, firms relocate, diplomats and international organizations shift their operational focus, and migrating populations move in response to events. For such *moving actors*, the location at which two of them interact is itself a meaningful, modelable outcome, but standard spatial-interaction tools assume actors sit at fixed points and so cannot be applied directly. The Projected Actor Location (PALS) method, introduced by Kim et al. (2023), fills this gap by estimating where a mobile actor effectively “is” at any point in time from the spatiotemporal history of its past interactions, and using these projected locations to model the distance between — and the probability of interaction among — pairs of actors.

`palsr` is an R package (R Core Team 2024) that implements the complete PALS workflow: constructing and validating dyadic event data, estimating the smoothing parameters by minimizing great-circle prediction error, projecting actor locations at arbitrary times, building the dyadic distance covariates used in downstream interaction models, and quantifying uncertainty through a nonparametric bootstrap with multiple-imputation (Rubin’s Rules) pooling. Performance-critical kernels — the Haversine distance and the projection smoother — are implemented in C++ through `Rcpp` (Eddelbuettel 2013), so that parameter estimation, which repeatedly re-projects every actor across a grid of times, runs quickly even on data sets with thousands of events.

Statement of need

The empirical study of geopolitical interaction — alliances, conflict, cooperation, trade — is overwhelmingly *dyadic*: the unit of analysis is a pair of actors, and a central predictor of whether and how two actors interact is the distance between them (Gleditsch and Ward 2001; Ward et al. 2007). When actors are states with fixed capitals or centroids, this distance is trivial to compute. But a large and growing share of substantively important actors — rebel groups, militias, terrorist organizations, peacekeeping deployments, non-governmental organizations — are mobile. The fine-grained, geocoded event data that now document them, such as the Armed Conflict Location and Event Data project (Raleigh et al. 2010), record *where each interaction happened* but assign actors no persistent coordinates. Treating these actors as fixed-location entities discards exactly the spatial dynamics that drive their interactions.

Existing spatial software for R does not fill this gap. General geospatial toolkits such as `sf` (Pebesma 2018) and spatial point-process libraries such as `spatstat` (Baddeley and Turner 2005) are powerful, but they operate on objects with given coordinates; they provide no way to *infer* a moving actor’s effective location, let alone one tuned to predict future interactions. Conversely, dyadic interaction models in political science and economics

typically take inter-actor distance as an exogenous input. Prior to PALS there was thus no general, estimable method for assigning time-varying locations to mobile actors in a way that is optimized for predicting their interactions.

PALS addresses this need, and the original article (Kim et al. 2023) demonstrates that PALS-based distances substantially improve the prediction of subnational conflict relative to naive location measures. However, that contribution was accompanied only by replication scripts specific to a single application. `palsr` turns the method into reusable, documented, and tested research software. It lets applied researchers in political science, conflict studies, economics, and geography apply PALS to their own dyadic event data without re-deriving the estimator, provides a principled bootstrap procedure for propagating estimation uncertainty into downstream models, and supplies a simulated example data set so that the full workflow can be learned and reproduced without access to restricted conflict data. To our knowledge it is the first general-purpose software implementation of projected-location modeling for moving actors.

Method

For a focal actor i at prediction time t , PALS forms a recency-weighted mean of the locations of i 's own past events (the *focal* component) and a recency-weighted mean of the locations of events involving i 's past interaction partners, or *alters* (the *alter* component). The projected location is a convex combination of the two,

$$g_i(t) = (1 - \pi) \sum_e W_i(e) g(e) + \pi \sum_e W_k(e) g(e), \quad \pi = \text{logistic}(\gamma + \eta v),$$

where event weights decay with age in the manner of exponential smoothing (Gardner Jr. 2006) — governed by α for the focal actor and β for the alters — and the mixing weight π depends through γ and η on the focal actor's activity relative to its alters, summarized by the event-count statistic v . The four parameters are estimated by “marching forward” through time: every event is predicted using only events strictly preceding it, and parameters are chosen to minimize the mean Haversine distance between predicted and observed interaction locations. The package also exposes a parsimonious one-parameter variant that fixes $\pi = 0$ and estimates only α , which is fast and frequently competitive.

Because the projected location is recomputed as time advances, each actor traces a *trajectory* through space rather than occupying a fixed point. Figure 1 illustrates this for four actors in the bundled simulated data: PALS projects each actor's location at yearly intervals, and the resulting paths drift through the cloud of observed events.




Figure 1: Projected locations of four actors in the simulated `nigeria_sim` data, fit with the one-parameter model and projected at yearly intervals from 2005 to 2016. Grey points are the observed dyadic events; coloured paths trace each actor's PALS-projected trajectory (arrows point forward in time).

Key features

- **Validated data container** (`pal_events()`) for dyadic, time-stamped, georeferenced events.
- **Parameter estimation** (`estimate_pals()`) for both the full four-parameter and the reduced one-parameter models, via Haversine-error minimization with a compiled objective.
- **Projection** (`project_pal()`, `project_pals()`) of actor locations at any set of times.
- **Prediction and covariate construction** (`predict_event_locations()`, `pal_distance()`) for interaction locations and dyadic distances, including a log transform for conflict-style specifications.
- **Uncertainty quantification** (`bootstrap_pals()`, `pool_rubin()`) via a nonparametric event bootstrap and Rubin's Rules (Rubin 1987).
- **Reproducible example data** (`nigeria_sim`, `simulate_conflict_events()`), a vignette, and a full `testthat` suite that also checks the C++ kernels against pure-R reference implementations.

Example

```
library(palsr)
data(nigeria_sim) # 1,500 dyadic events, 25 mobile actors

fit <- estimate_pals(nigeria_sim, model = "one") # estimate alpha
coef(fit)

# Project where each actor is on a given date.
project_pals(nigeria_sim, predict_time = as.Date("2015-01-01"), params = fit)

# Build the dyadic distance covariate for an interaction model.
```

```
dyads <- data.frame(actor1 = "G01", actor2 = "G02", time = as.Date("2014-06-01"))
pal_distance(nigeria_sim, dyads, fit, transform = "log")
```

```
# Bootstrap uncertainty in the smoothing parameter.
summary(bootstrap_pals(nigeria_sim, R = 10, model = "one", seed = 1))
```

Availability and quality control

`palsr` is developed openly on GitHub. The package ships with documentation for every exported function, an introductory vignette that walks through the full workflow on `nigeria_sim`, and a `testthat` suite covering data validation, estimation, projection, distance construction, and uncertainty quantification. The tests additionally verify the compiled C++ kernels against independent pure-R reference implementations, and continuous integration runs `R CMD check` across Linux, macOS, and Windows on every change.

Acknowledgements

We thank the editors and reviewers of *Political Science Research and Methods* for feedback on the method, and the developers of `Rcpp` (Eddelbuettel 2013) for the tooling that underpins the package’s performance.

References

- Baddeley, Adrian, and Rolf Turner. 2005. “Spatstat: An R Package for Analyzing Spatial Point Patterns.” *Journal of Statistical Software* 12 (6): 1–42. <https://doi.org/10.18637/jss.v012.i06>.
- Eddelbuettel, Dirk. 2013. *Seamless R and C++ Integration with Rcpp*. Springer. <https://doi.org/10.1007/978-1-4614-6868-4>.
- Gardner Jr., Everette S. 2006. “Exponential Smoothing: The State of the Art—Part II.” *International Journal of Forecasting* 22 (4): 637–66. <https://doi.org/10.1016/j.ijforecast.2006.03.005>.
- Gleditsch, Kristian S., and Michael D. Ward. 2001. “Measuring Space: A Minimum-Distance Database and Applications to International Studies.” *Journal of Peace Research* 38 (6): 739–58. <https://doi.org/10.1177/0022343301038006006>.
- Kim, Sangyeon, Howard Liu, and Bruce A. Desmarais. 2023. “Spatial Modeling of Dyadic Geopolitical Interactions Between Moving Actors.” *Political Science Research and Methods* 11 (3): 617–35. <https://doi.org/10.1017/psrm.2022.6>.
- Pebesma, Edzer. 2018. “Simple Features for R: Standardized Support for Spatial Vector Data.” *The R Journal* 10 (1): 439–46. <https://doi.org/10.32614/RJ-2018-009>.
- R Core Team. 2024. *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing. <https://www.R-project.org/>.
- Raleigh, Clionadh, Andrew Linke, Håvard Hegre, and Joakim Karlsen. 2010. “Introducing ACLED: An Armed Conflict Location and Event Dataset.” *Journal of Peace Research* 47 (5): 651–60. <https://doi.org/10.1177/0022343310378914>.
- Rubin, Donald B. 1987. *Multiple Imputation for Nonresponse in Surveys*. Wiley. <https://doi.org/10.1080/01621459.1987.10501564>.

[//doi.org/10.1002/9780470316696](https://doi.org/10.1002/9780470316696).

Ward, Michael D., Randolph M. Siverson, and Xun Cao. 2007. "Disputes, Democracies, and Dependencies: A Reexamination of the Kantian Peace." *American Journal of Political Science* 51 (3): 583–601. <https://doi.org/10.1111/j.1540-5907.2007.00269.x>.