Network Analysis - Blerd

Version
alpha

Data Set Up

```
# 1.
library(bipartite)
```

```
Warning: package 'bipartite' was built under R version 4.4.3
```

```
Attaching package: 'bipartite'
```

```
The following objects are masked from 'package:igraph':

    components, get.adjacency, get.incidence, project, version
```

```
# 2.
library(igraph)
library(network)
```

```
This is network 1.0.
For quickstart and vignettes, please see github.com/statnet/gallery/#statnet.
```

```
library(RColorBrewer)
```

```
Warning: package 'RColorBrewer' was built under R version 4.4.3
```

```
# 3.
dataPlantPollinatorBinaryMatrix<-as.matrix(dataPlantPollinatorBinary)

# 4. Load your data
dataCat <- read.csv("Blerd.csv")
dataCatMeg = read.csv("Blerd_Long.csv")

# Convert categorical variables to factors
dataCat$Plant = as.factor(dataCat$Plant)
dataCat$Treatment = as.factor(dataCat$Treatment)
dataCatMeg$Plant = as.factor(dataCatMeg$Plant)
dataCatMeg$Treatment = as.factor(dataCatMeg$Treatment)
dataPlantPollinator = dataCat[,-c(1,2)]
dataPlantPollinator <- as.numeric(dataPlantPollinator)

Warning: NAs introduced by coercion
```

```
dataPlantPollinator = as.numeric(dataPlantPollinator)
dataPlantPollinator <- as.matrix(dataPlantPollinator)
```

```
Warning: NAs introduced by coercion
```

```
dataPlantPollinator = as.numeric(dataPlantPollinator)
dataPlantPollinator <- as.matrix(dataPlantPollinator)
dataPlantPollinator = as.numeric(dataPlantPollinator)
dataPlantPollinator <- as.matrix(dataPlantPollinator)
dataPlantPollinator = as.numeric(dataPlantPollinator)
dataPlantPollinator <- as.matrix(dataPlantPollinator)

# 5. Select data to store as no dead individuals included
dataCat <- dataCat %>%
  filter(Plant != "Dead", Plant != "NOT_Blerd")%>%

# 6. Take out one of the blank cells that cause problems when graphing
dataCat <- dataCat %>%
  filter(Pheidole.flavens != "", Pheidole.flavens != "Dead",
         Pheidole.flavens != "Dead ", Pheidole.flavens != "",
         Pheidole.flavens != "Dead ", Pheidole.flavens != "",
         Pheidole.flavens != "", Pheidole.flavens != "Dead ")
dataCatTreatment <- as.factor(dataCat$Treatment)

data_final = dataCat
```

Correlation Matrix

```
# Define your variables
cor_vars <- c("Pheidole.flavens", "Pheidole.sp1", "Pheidole.sp2", "Pheidole.sp3", "Pheidole.sp4", "Pheidole.sp5", "Pheidole.sp6", "Pheidole.sp7", "Pheidole.sp8", "Pheidole.sp9", "Pheidole.sp10", "Pheidole.sp11", "Pheidole.sp12", "Pheidole.sp13", "Pheidole.sp14", "Pheidole.sp15", "Pheidole.sp16", "Pheidole.sp17", "Pheidole.sp18", "Pheidole.sp19", "Pheidole.sp20", "Pheidole.sp21", "Pheidole.sp22", "Pheidole.sp23", "Pheidole.sp24", "Pheidole.sp25", "Pheidole.sp26", "Pheidole.sp27", "Pheidole.sp28", "Pheidole.sp29", "Pheidole.sp30", "Pheidole.sp31", "Pheidole.sp32", "Pheidole.sp33", "Pheidole.sp34", "Pheidole.sp35", "Pheidole.sp36", "Pheidole.sp37", "Pheidole.sp38", "Pheidole.sp39", "Pheidole.sp40",
```

```
|                                                
```