

Excavation and Trenching Permit

REQUIRED FOR ALL EXCAVATIONS/ TRENCHES GREATER THAN 6-INCHES IN DEPTH				Permit No. _____							
1. Project Name		2. Company Name		3. Location of Excavation							
4. Originated By		Date Initiated	Date Expired	5. Change Notice (Date/Jacobs Signature)							
6. Drawings Required (identification No.)				7. Other Affected Drawings or Documents (if any)							
8. Description of Work (attach composite drawing of excavation location and all known interferences)											
9. Special Instructions or Comments											
Daily inspection form required for each day excavation/trench remains open.											
Pre-excavation scan(s) required?		Note: Pothole if within 5 feet of buried utility									
☐ No	☐ Yes	Identify utility locations with #####									
10. List Facilities, Services, Structures, and Utilities Affected by Excavation (Must indicate "NONE" if no utilities)											
Note: Refer to utility as-built drawing that must be attached to permit.											
Contractor Approvals											
11. Utilities cleared/marked at work task location: (Superintendent must review execution approach and sign if utilities identified)											
Print Name & Company		Signature		Date	Validated by Jacobs Supt. Signature Date						
Jacobs Reviews											
12. Civil Superintendent/Building Superintendent*				Date:							
13. Utilities Piping Superintendent /Building Superintendent*				Date:							
14. Mechanical Piping Superintendent*				Date:							
15. Electrical Superintendent/Building Superintendent*				Date:							
16. Contractor HSE				Date:							
Severity Level:		Minor		Moderate		Major		Critical		Catastrophic	
Task Review:											
Contractor Supervisor		Date		Contractor HSE		Date		Jacobs Superintendent/CM		Date	
17. Other Permits supporting this work:											
18. New utility added to as-built:											
Print Name & Company			Signature				Date				
NOTE: * WORK INSIDE BUILDING FOOTPRINT AS-BUILT REVIEW SITE CIVIL CONTRACTOR ONLY IDENTIFIES UTILITIES LOCATED EXTERIOR TO A BUILDING. UTILITIES INTERIOR TO A BUILDING MUST BE IDENTIFIED BY THE PERMITTEE IN CONSULTATION WITH THE APPLICABLE JACOBS BUILDING SUPERINTENDENT USING PROJECT AS-BUILT DRAWINGS.											

EXCAVATION AND TRENCHING SAFETY CHECKLIST (Prework and Daily Inspection) PREWORK		
Excavation Permit No.: _____		
	<u>Verified By</u>	<u>Date</u>
Excavation permit is completed, dated, all required signatures obtained, all attachments/scans/etc. are complete as required.	Jacobs Supt:	
Competent Person(s) has been designated/assigned; designation form is complete/current (within 1 year).	Jacobs Supt:	
Initial (pre-excavation) call to (811) "U DIG" has been made.	Jacobs Supt:	
Date: _____ Time: _____		
Walkdown of proposed excavation performed.	Jacobs Supt:	
Walkdown to ensure:		
- Ground markings identifying underground obstructions are present and applied. - Evaluation of the work area for potential hazards that have not been addressed by scanning existing drawing research efforts and/or other pre-task planning activities	Competent Person:	
Excavation work is released to begin	Jacobs Supt:	

EXCAVATION AND TRENCHING CHECKLIST

Y	N	N/A		Y	N	N/A	
☐	☐	☐	Checked for previously disturbed ground	☐	☐	☐	Is excavation a confined space (> 4 feet deep)?
☐	☐	☐	Excavation is close to utilities, buildings, footings or pilings, and sources of vibration	☐	☐	☐	If YES, atmospheric testing required: ☐ O2 (%) ☐ LEL (%) ☐ Toxic (CO, H2S, PID)
☐	☐	☐	Underground utilities located marked and protected before digging?	☐	☐	☐	Atmospheric testing results: O2 LEL Toxic
☐	☐	☐	Change in vehicular and machinery operation patterns communicated? How? Comment below	☐	☐	☐	Excavation > 4 feet deep?
☐	☐	☐	Soil Classification: ☐ Stable Rock ☐ Type A ☐ Type B ☐ Type C	☐	☐	☐	Protection method selected (<i>circle as needed</i>): ☐ Sloping Vert ¾:1 1:1 1-1/2:1 ☐ Benching Vert ¾:1 1:1 1-1/2:1 ☐ Shields 18" above slope? Laterally stable? ☐ Shoring Instructions must be on site ☐ Engineered Plans must be on site ☐ Other Describe in Comments below
☐	☐	☐	Site of Excavation: Depth Width Length				
☐	☐	☐	Entrance and Exit to Excavation every 25 feet: ☐ Stairway ☐ Ladders ☐ Ramp	☐	☐	☐	Adequacy and availability of all equipment, including personal protective gear, shoring material, signs, barricades, and machinery
☐	☐	☐	Water removal equipment and operation discussed in writing in JHA?	☐	☐	☐	
☐	☐	☐	Physical barricades around excavation planned, available, properly set up and / or in good condition. Jersey barriers for vehicle protection.	☐	☐	☐	Trench boxes or trench shields still in good shape (as work progresses)
☐	☐	☐	Overhead hazards (power lines, trees, etc)?	☐	☐	☐	Sloping and / or benching still in good shape (as work progresses)
☐	☐	☐	Excavated materials at least 2 feet from edge?	☐	☐	☐	

☐ ☐ ☐	Excavation safe for employees to enter?
--	---

Comments

Note: All items must be evaluated before start of work.

DAILY INSPECTION FORM – Permit #:			
Location:		Date:	Weather:
Depth:		Length:	Soil Type:
		Width:	Protective System:
YES	NO	N/A	EXCAVATION
☐	☐	☐	Excavations and Protective Systems, including sloping and benching, inspected, accepted, and approved by Competent Person daily, before start of work on each shift.
☐	☐	☐	Competent Person has authority to remove workers from excavation immediately.
☐	☐	☐	Surface encumbrances supported or removed.
☐	☐	☐	Employees protected from loose rock or soil.
☐	☐	☐	Spoils, materials, and equipment set back a minimum of 2' from edge of excavation.
☐	☐	☐	Barriers provided at all remote excavations, wells, pits, shafts, etc.
☐	☐	☐	Walkways and bridges over excavations 6' or more in depth equipped with guardrails.
☐	☐	☐	Employees prohibited from working or walking under suspended loads.
☐	☐	☐	Employees prohibited from working on faces of sloped or benched excavations above other employees.
☐	☐	☐	Warning system established and used when mobile equipment is operating near edge of excavation.
YES	NO	N/A	UTILITIES
☐	☐	☐	Utility companies contacted and/or utilities located.
☐	☐	☐	Exact location of utilities marked when near excavation.
☐	☐	☐	Underground installations protected, supported, or removed when excavation is open.
YES	NO	N/A	WET CONDITIONS
☐	☐	☐	Precautions taken to protect employees from accumulation of water.
☐	☐	☐	Water removal equipment monitored by Competent Person.
☐	☐	☐	Surface encumbrances supported or removed.
☐	☐	☐	Employees protected from loose rock or soil.
YES	NO	N/A	HAZARDOUS ATMOSPHERE
☐	☐	☐	Atmosphere tested when there is a possibility of oxygen deficiency or build-up of hazardous gases.
☐	☐	☐	Oxygen content is between 19.5% and 21%.
☐	☐	☐	Ventilation provided to prevent flammable gas build-up to 10% of lower limit of the gas.
☐	☐	☐	Testing conducted to ensure that atmosphere remains safe.
☐	☐	☐	Emergency Response Equipment readily available where a hazardous atmosphere could or does exist.
☐	☐	☐	Employees trained in the use of Personal Protective and Emergency Response Equipment.
☐	☐	☐	Safety harness and lifeline individually attended when employees enter deep confined excavation.

Deficiencies Corrected

Signature of Competent Person: _____ Date: _____