

Confined Space Entry Assessment and Permit

Date	Confined Space Name/Location			
Confined Space Entry Supervisor	Describe Tasks Involved			
SECTION I — Assessment				
Hazards Identified	Y	N	NA	Detail of Hazard and Appropriate Control
Access to Space				
Access points to space protected with barrier tape, barricades, or fencing				
Access points to space labeled "Danger, Permit-Required Confined Space, Do Not Enter"				
Isolation Hazards				
Lines and tanks flushed, purged, and clean				
Blanks installed				
Electrical lock-out/tag-out installed and tested				
Mechanical lock-out/tag-out installed and tested				
Radioactive source removed or shielded				
Atmospheric/Chemical Hazards				
Chemicals generated due to work processes				
Hazardous materials in surface coating (lead, etc.)				
Identify and measure all chemical hazards in the confined space				
Possibility of toxic/ inert gases leaking/sinking in				
Mechanical ventilation required				
Respiratory Protection required				
Supplied air or self-contained air required				
Burning, cutting, welding controlled				
Asbestos disturbed				
Potential IDLH				
Continuous Atmospheric Monitoring required	Y			
Physical Hazards				
Walking and working areas dry and clean				
Minimum illumination of 5 foot-candles				
Continuous audio or visual communication				
High pressure				
High temperature or heat stress				
Ladders, scaffolds, work platforms safeguarded				
Fall protection required				
Electrical Hazards				
Equipment bonded, grounded and tested				
GFCIs for all electrical equipment				
All equipment explosion proof/ intrinsically safe				
Work Activities				
Permits required: Hot Work, Excavation, etc.				
Hazardous work activities in surrounding areas				
Other hazards not listed above				
PPE (Describe all required PPE including retrieval equipment and harnesses.)				
Eye Protection				
Protective Clothing				
Hand and Foot Protection				
Respiratory Protection				
Fall Protection				

Jacobs FDBN Project

Confined Space Entry Assessment and Permit

SECTION II — Permit			
This confined space permit is valid only for the work, location, and time listed. If changes occur, the confined space must be re-evaluated and the permit re-issued. All hazards listed in the Assessment and Permit Section must be addressed in the SSOW			
			Note initial readings below:
Oxygen 20.8% (19.5 - 23.5%) If oxygen is < or > 20.8%, determine why	Yes	No	
Combustible gas concentration < 1 % LEL	Yes	No	
Carbon monoxide < 25 ppm	Yes	No	
Carbon dioxide < 1,000 ppm	Yes	No	
Hydrogen sulfide < 10 ppm	Yes	No	
List other Chemicals	Monitoring Levels and Action Levels		Exposure Limits (PEL, TLV, etc.)
Note: Record atmospheric readings every 15 minutes in the monitoring log!			
For continuous atmospheric testing required, list monitoring instruments and calibration dates.			
Monitoring Equipment:		Calibration Date:	
Has rescue plan been assembled and attached?	Yes	No	
Has Jacobs HSE Been Notified of Entry?	Yes	No	
Printed Names of Trained Entrants		Printed Names of Trained Attendants	
Printed Name of Subcontractor Entry Supervisor			
Subcontractor Entry Supervisor's Signature		Date	Time
Jacobs Superintendent (or Area Owner) Signature		Date	Time
Jacobs HSE Signature		Date	Time
SECTION III — Closure			
After confined space entry is complete, the supervisor shall record in this space any incidents and actions taken and any lessons learned.			
Subcontractor Supervisor Closure Signature		Date and Time of Permit Closure	
Return completed permit to Jacobs HSE department			



Client:	Project:	Location:	Date:
Name/Description of Confined Space:		Entry Supervisor:	
Standby Attendant 1 Name (printed):		Standby Attendant 2 Name (printed):	

Confined Space Authorized Entrants Sign-In and Sign-Out Log

<u>Entrant's Name Printed</u>	<u>Entrant's Signature</u>	<u>Enter Time In and Out</u>											
		In	Out	In	Out	In	Out	In	Out	In	Out	In	Out



Permit Required Confined Space Entry
ATMOSPHERIC MONITORING LOG

Attendant Name: _____

(Print Name)

Atmospheric Sampling Equipment Used:

Type

Calibrated

Continuous Monitoring - Document Results Every 15 Minutes!

Hour #	Time	%Oxygen	%LEL	H2S	CO	Other _____	Initials
	(am or pm)	(19.5%-23.5%)	(max 10%)	(max 10ppm)	(max 25ppm)		
1.	_____	_____	_____	_____	_____	_____	_____
	_____	_____	_____	_____	_____	_____	_____
	_____	_____	_____	_____	_____	_____	_____
	_____	_____	_____	_____	_____	_____	_____
2.	_____	_____	_____	_____	_____	_____	_____
	_____	_____	_____	_____	_____	_____	_____
	_____	_____	_____	_____	_____	_____	_____
	_____	_____	_____	_____	_____	_____	_____
3.	_____	_____	_____	_____	_____	_____	_____
	_____	_____	_____	_____	_____	_____	_____
	_____	_____	_____	_____	_____	_____	_____
4.	_____	_____	_____	_____	_____	_____	_____
	_____	_____	_____	_____	_____	_____	_____
	_____	_____	_____	_____	_____	_____	_____
	_____	_____	_____	_____	_____	_____	_____
5.	_____	_____	_____	_____	_____	_____	_____
	_____	_____	_____	_____	_____	_____	_____
	_____	_____	_____	_____	_____	_____	_____
	_____	_____	_____	_____	_____	_____	_____

KEEP THIS LOG AT WORKSITE DURING THE OPERATION. RETURN TO HSE TO BE MAINTAINED. ATTACH ADDITIONAL PAGES IF NEEDED.