

Fast Track to Scala

Josh Suereth

Typesafe

2012-03-05



Agenda

Why Scala?

Setting up the development environment

First steps

Basic OO features

Testing in Scala

Collections and functional programming

For-expressions and for-loops

Inheritance and traits

Pattern matching

XML support



Agenda

Why Scala?

Setting up the development environment

First steps

Basic OO features

Testing in Scala

Collections and functional programming

For-expressions and for-loops

Inheritance and traits

Pattern matching

XML support




Scala is mature

- ▶ 1996 - 1997: Pizza
- ▶ 1998 - 2000: GJ, Java generics, javac
- ▶ 2001: Scala design begins
- ▶ 2003: First experimental release
- ▶ 2005: Scala 2.0 written in Scala
- ▶ 2006: Industrial adoption starts
- ▶ 2007: First release of the Lift web framework
- ▶ 2008: First Scala LiftOff unconference, Twitter adopts Scala
- ▶ 2009: Big increase in adoption, IDEs mature
- ▶ 2010: Scala 2.8 released, first ScalaDays conference
- ▶ 2011: Scala 2.9 released, Typesafe Inc. founded



Scala is a unifier



Scala is concise

```
1 class Time(val hours: Int, val minutes: Int)
```

```
1 public class Time {                                // Java
2     private final int hours;
3     private final int minutes;
4     public Time(int hours, int minutes) {
5         this.hours = hours;
6         this.minutes = minutes;
7     }
8     public int getHours() {
9         return hours;
10    }
11    public int getMinutes() {
12        return minutes;
13    }
14 }
```



Scala is expressive

```
1 scala> val numbers = 1 to 10
2 ... = Range(1, 2, 3, 4, 5, 6, 7, 8, 9, 10)
3
4 scala> numbers filter { _ > 5 }
5 ... = Vector(6, 7, 8, 9, 10)
```



Scala is fully interoperable with Java

```
1 scala> import org.slf4j.LoggerFactory
2 import org.slf4j.LoggerFactory
3
4 scala> val logger = LoggerFactory.getLogger("logger")
5 logger: org.slf4j.Logger = Logger[logger]
6
7 scala> logger.info("Hello!")
8 09:25:11.393 [Thread-7] INFO logger - Hello!
```



Agenda

Why Scala?

Setting up the development environment

First steps

Basic OO features

Testing in Scala

Collections and functional programming

For-expressions and for-loops

Inheritance and traits

Pattern matching

XML support



Scala distribution



Exercise: Install the Scala distribution

- ▶ Download the latest stable release 2.9.1 as an archive for your platform from www.scala-lang.org/downloads
- ▶ Unpack the archive to a suitable location, e.g. `~/tools/scala/`
- ▶ Add the `bin/` directory to your path
- ▶ Verify the installation by opening a terminal and entering `scala -version`:

```
1 tmp$ scala -version
2 Scala code runner version 2.9.1.final ...
```

- ▶ Also download the Scala API documentation, unpack and browse it



Exercise: "Hello World!" on the command line

- Create the file *Hello.scala*¹ using an arbitrary text editor:


```
1 object Hello {  
2   def main(args: Array[String]) {  
3     println("Hello World!")  
4   }  
5 }
```

- Compile and run it:


```
1 tmp$ scalac Hello.scala  
2 tmp$ scala Hello  
3 Hello World!
```



There are plugins for all major IDEs



Scala IDE for Eclipse



- ▶ We, the trainer(s), will use Eclipse for this course
- ▶ Feel free to use another IDE or none at all, but we will only be able to offer limited support



Exercise: Install Eclipse and the Scala IDE for Eclipse

- ▶ Download and install Eclipse Helios (3.6) or Indigo (3.7) Classic (!) for your platform from www.eclipse.org/downloads
- ▶ Install the Scala plugin via the menu *“Help > Install New Software ...”* using the update site <http://download.scala-ide.org/releases-29/stable/site>
- ▶ Verify the installation by opening a fresh workspace, e.g. `~/workspaces/training-scala/`, and switching to the Scala perspective



Exercise: "Hello World!" in Eclipse

- ▶ Create a *"New > Scala Project"* with name *hello*
- ▶ Create a *"New > Scala Object"* with name *Hello*
- ▶ Copy the code from the previous exercise
- ▶ Select *"Run As > Scala Application"* from the context menu of the editor or package explorer
- ▶ In order to avoid conflicts with other future projects we suggest you now close or delete this project



Simple Build Tool (sbt)

```
tmp$ cd scalatrain
scalatrain$ sbt
[info] Set current project to default (in build file:/Users/hseeberger/.sbt/plugins/)
[info] Set current project to default (in build file:/Users/hseeberger/tmp/scalatrain/)
> compile
[success] Total time: 0 s, completed May 24, 2011 1:14:42 PM
```

- ▶ THE build tool for Scala
- ▶ Written in Scala and specifically for Scala
- ▶ Used by most real-world projects



Exercise: Install sbt

- ▶ Download the launcher:
<http://repo.typesafe.com/typesafe/ivy-releases/org.scala-tools.sbt/sbt-launch/0.11.2/sbt-launch.jar>
- ▶ Create the following file as a start script for sbt:

- ▶ *sbt* on Mac/Linux:

```
1 java -Xmx512M -jar <LAUNCHER-JAR> "$@"
```

- ▶ *sbt.bat* on Windows:

```
1 java -Xmx512M -jar <LAUNCHER-JAR> %*
```



Exercise: Create a sbt project

- ▶ Create a fresh project directory, e.g. `~/projects/training-scala/`, and `cd` into it
- ▶ **Attention: Do not create this in your Eclipse workspace!**
- ▶ Starting sbt will take you to an interactive session
- ▶ Execute the following three commands at the sbt prompt:

```
1 > set name := "scalatraining"
2 ...
3 > set scalaVersion := "2.9.1"
4 ...
5 > session save
6 ...
```

- ▶ Take a look at the new file *build.sbt* in the project directory *training-scala/*
- ▶ Keep the sbt session running!



sbt commands - quick overview

- ▶ General commands:
 - ▶ *exit* ends the current session
 - ▶ *help* lists available commands
- ▶ Build commands:
 - ▶ *compile* compiles main sources
 - ▶ *test:compile* compiles test sources
 - ▶ *test* runs tests
 - ▶ *console* starts the REPL
 - ▶ *run* looks for a main class and runs it
 - ▶ Triggered execution: Prefix a command with ~
- ▶ Other commands:
 - ▶ *clean* deletes all output in the *target/* directory
 - ▶ *reload* reloads the build



Exercise: Install the sbt-Eclipse integration

- ▶ The **sbteclipse** plugin let's you create Eclipse project files from an sbt project
- ▶ In the project directory (*training-scala/*), create the subdirectory *project/* and there the file *plugins.sbt* with the following contents:

```
addSbtPlugin("com.typesafe.sbteclipse" %  
             "sbteclipse-plugin" % "2.0.0")
```

- ▶ Attention:
 - ▶ Copy and paste is your friend, but sometimes the quotes are not copied correctly!
 - ▶ Also, use only one line!



Exercise: Create Eclipse project files

- ▶ In the sbt session execute the commands *reload* and the now available *eclipse*

```
1 > reload
2 ...
3 > eclipse
4 ...
5 [info] Successfully created Eclipse project files ...
```

- ▶ Import the new Eclipse project using “*Import...*” > “*Existing Projects into Workspace*”
- ▶ Verify the import by inspecting the project, e.g. the source directories *src/main/scala/* etc.



Agenda

Why Scala?

Setting up the development environment

First steps

Basic OO features

Testing in Scala

Collections and functional programming

For-expressions and for-loops

Inheritance and traits

Pattern matching

XML support



Interactive programming in the REPL

- ▶ In a terminal window enter *scala* to start the REPL
- ▶ Alternatively, in a sbt session enter the command *console*

```
1 tmp$ scala
2 Welcome to Scala version 2.9.1.final ...
3 Type in expressions to have them evaluated.
4 Type :help for more information.
```

- ▶ The REPL will evaluate Scala code:

```
1 scala> "Hello " + "World!"
2 res0: java.lang.String = Hello World!
```

- ▶ Enter *:quit* or *:q* to exit the REPL:

```
1 scala> :q
```



Immutable variables

- ▶ Scala encourages us to use immutable objects:
 - ▶ Code free of side-effects is easier to reason about
 - ▶ Pure functions can be tested easily
 - ▶ Immutable objects won't lead to concurrency issues
- ▶ An immutable variable is defined with *val*:

```
1 scala> val message = "Hello " + "World!"  
2 message: java.lang.String = Hello World!
```

- ▶ An immutable variable is ... immutable:

```
1 scala> message = "Won't compile!"  
2 <console>:8: error: reassignment to val  
3     message = "Won't compile!"
```



Type inference

- ▶ Why does this code compile?

```
1 val message = "Hello " + "World!"
```

- ▶ Because in most cases the compiler is able to infer the types
- ▶ Of course we can be explicit and use a type annotation:

```
1 val message: String = "Hello " + "World!"
```

- ▶ And of course Scala is statically typed:

```
1 scala> val message: Int = "Hello " + "World!"  
2 <console>:7: error: type mismatch;  
3   found   : java.lang.String("Hello World!")  
4   required: Int
```



Mutable variables

- ▶ Sometimes we really need mutable state
 - ▶ This holds true less often than OO programmers might believe
 - ▶ As a proof watch out how often we will use mutable state ...
- ▶ A mutable variable is defined with *var*:

```
1 scala> var year = 2011  
2 year: Int = 2011
```

- ▶ A mutable variable can be ... mutated:

```
1 scala> year = 2012  
2 year: Int = 2012
```



Everything has a value

- The last expression of a code block determines its value:

```
1 scala> val block = {  
2     |   val x = 1  
3     |   val y = 2  
4     |   x + y  
5     | }  
6 block: Int = 3
```

- *if-else* has a value²:

```
1 scala> :type if (1 == 2) "weird" else "correct"  
2 java.lang.String
```



- ▶ A method is defined with *def*.

```
1 scala> def add(x: Int, y: Int) = x + y
2 add: (x: Int,y: Int)Int
```

- ▶ The type should be given for public or non-trivial methods:

```
1 scala> def add(x: Int, y: Int): Int = x + y
2 add: (x: Int,y: Int)Int
```



Procedures aka *Unit*-Methods

- ▶ The type *Unit* means that the method's value doesn't matter:

```
1 scala> def sayHello(): Unit = println("Hello!")
2 sayHello: ()Unit
3
4 scala> sayHello
5 Hello!
```

- ▶ There is a special syntax for procedures³:

```
1 scala> def sayHello() {
2     |   println("Hello!")
3     | }
4 sayHello: ()Unit
```

³Actually Martin Odersky thinks, that this special case for procedures was a mistake; therefore we recommend you better don't use it.



Uniform access principle

- ▶ A method without parameters can be written without parens:

```
1 scala> def message = "Hello World!"  
2 message: java.lang.String
```

- ▶ Convention: No-parens style only for side-effect-free methods
- ▶ Then there is no distinction for the client between a field (stored value) and a method (computed value)



Operators are methods

- ▶ In Scala everything is an object!
- ▶ Operators are methods with one parameter used in (dot-less) operator notation:

```
1 scala> "a,b,c" split ","  
2 res0: Array[java.lang.String] = Array(a, b, c)
```

- ▶ Almost all characters are allowed for (method) identifiers:

```
1 scala> def *?!(s: String) = s.reverse  
2 $times$qmark$bang: (s: String)String
```

- ▶ Therefore the following is the call of the method `+` on the object `1` with the argument `2`:

```
1 1 + 2
```



A first glance at functions

Just to see where we will be going to:

```
1 scala> val numbers = List(1, 2, 3)
2 numbers: List[Int] = List(1, 2, 3)
3
4 scala> numbers map (x => x + 1)
5 res0: List[Int] = List(2, 3, 4)
6
7 scala> numbers sortWith ((x, y) => x > y)
8 res1: List[Int] = List(3, 2, 1)
9
10 scala> numbers map (_ + 1) sortWith (_ > _)
11 res2: List[Int] = List(4, 3, 2)
```



Agenda

Why Scala?

Setting up the development environment

First steps

Basic OO features

Testing in Scala

Collections and functional programming

For-expressions and for-loops

Inheritance and traits

Pattern matching

XML support



- ▶ Classes are blueprints for objects
- ▶ Use the keyword *class* to define a class:

```
1 class Train
```

- ▶ This is valid Scala code:
 - ▶ No semicolon thanks to semicolon inference
 - ▶ No access modifier, because public visibility is default
 - ▶ No curly braces, since *Train* has no body yet
- ▶ Classes have public visibility by default



Creating class instances

- Use the keyword *new* and the name of a class to create an instance:

```
1 new Train
```

- Actually you are calling the primary constructor which results from the class definition
- This is valid Scala code: No parens needed for an arity-0⁴ constructor



Exercise: Create the class *Train*

- ▶ Use the directory *src/main/scala/*
- ▶ Use the file name *Train.scala*
- ▶ When done, create an instance in the REPL:

```
1 scala> val train = new Train
2 train: Train = Train@77aa89eb
```



Class parameters

- ▶ Use parens after the class name to define class parameters:
 - ▶ A single parameter is defined by its name, followed by a colon and its type
 - ▶ Multiple parameters are separated by comma

```
1 class Train(number: String)
```

- ▶ Class parameters result in parameters of the primary constructor⁵ and are not visible from the outside



Exercise: Add a class parameter to *Train*

- ▶ Parameter name: *number*
- ▶ Parameter type: *String*
- ▶ Try to create a *Train* like before:

```
1 scala> :replay
2 Replaying: new Train
3 <console>:8: error: not enough arguments for
   constructor Train: (number: String)Train.
4 Unspecified value parameter number.
```

- ▶ Try to create a *Train* giving a *number*:

```
1 scala> val train = new Train("Nighttrain")
2 train: Train = Train@72d53ac7
```



Auxiliary constructors

- Use the keywords *def* and *this* to define auxiliary constructors:

```
1 class Train(number: String) {  
2   def this() = this("Default")  
3   def this(n1: String, n2: String) = this(n1 + n2)  
4 }
```

- An auxiliary constructor must immediately call another constructor of the class using *this*
- Tip: In many cases named and default arguments⁶ are preferable



Immutable fields

- Use the keyword `val` to define an immutable field:

```
1 class Train(number: String) {  
2   val kind = "ICE"  
3 }
```

- Fields have public visibility by default:

```
1 scala> val train = new Train("Nighttrain")  
2 train: Train = Train@76d88b7b  
3  
4 scala> train.kind  
5 res0: java.lang.String = ICE
```



Mutable fields

- Use the keyword *var* to define a mutable field:

```
1 class Train(number: String) {  
2   var kind = "ICE"  
3 }
```

- Of course you can change the value of a mutable field:

```
1 scala> val train = new Train  
2 train: Train = Train@64dff6e3  
3  
4 scala> train.kind = "CHANGED"  
5  
6 scala> train.kind  
7 res0: java.lang.String = CHANGED
```



Make fields out of class parameters

- ▶ Also use *val* (or *var*) to make a field out of a class parameter:

```
1 class Train(val kind: String, val number: String)
```

- ▶ Now you can access the “converted” class parameters:

```
1 scala> val train = new Train("ICE", "722")
2 train: Train = Train@3b1674f0
3
4 scala> train.kind
5 res0: String = ICE
6
7 scala> train.number
8 res1: String = 722
```



Exercise: Add fields to *Train*

- ▶ Add (prepend) the class parameter *kind* of type *String* to *Train*
- ▶ Make immutable fields out of both class parameters
- ▶ Create a *Train* and access the fields



Exercise: Create the class *Time*

- ▶ Add the class parameter *hours* of type *Int*
- ▶ Add the class parameter *minutes* of type *Int*
- ▶ Make immutable fields out of both class parameters
- ▶ Add a TODO comment to the class body that we still have to check the preconditions (valid values for hours and minutes)
- ▶ Create a *Time* and access the fields



Methods

- Use the keyword *def* to define a method:

```
1 class Time(val hours: Int, val minutes: Int) {  
2   def minus(that: Time): Int = ...  
3 }
```

- Like fields, methods have public visibility by default:

```
1 scala> val time = new Time(12, 30)  
2 time: Time = Time@32dc51c8  
3  
4 scala> time.minus(new Time(1, 30))  
5 res0: Int = 0
```



Exercise: Implement the method *Time.minus*

- ▶ Calculate the difference between the two *Times* in minutes
- ▶ Don't use any helper members yet
- ▶ Create a *Time* and verify that the new method is working:

```
1 scala> val time = new Time(12, 30)
2 time: Time = Time@113ee167
3
4 scala> time.minus(new Time(1, 30))
5 res0: Int = 660
```



Lazy vals

- ▶ Use the keyword *lazy* to define an immutable field/variable that is only evaluated on first access:

```
1 lazy val asMinutes: Int = ... // Heavy computation
```

- ▶ Why should you use lazy?
 - ▶ To reduce initial instantiation time
 - ▶ To reduce initial memory footprint
 - ▶ To resolve initialization order issues
 - ▶ In this course: For didactic reasons ;-)
- ▶ But consider the overhead:
 - ▶ Guard field
 - ▶ Synchronization



Exercise: Improve *Time.minus* using a lazy immutable field

- ▶ Add the lazy immutable field *asMinutes* to *Time*
- ▶ Use this to simplify the implementation of *minus*
- ▶ Verify that *asMinutes* is initialized correctly and *minus* still works:

```
1 scala> val time = new Time(12, 30)
2 time: Time = Time@71f08b14
3
4 scala> time.asMinutes
5 res0: Int = 750
6
7 scala> time.minus(new Time(1, 30))
8 res1: Int = 660
```



Operators and operator notation

- Operators are just methods with zero or one parameters:

```
1 scala> x.+(y) // x == 1 and y == 2
2 res0: Int = 3
3
4 scala> true.unary_!
5 res1: Boolean = false
```

- You can omit dot and parens, i.e. use operator notation:

```
1 scala> x + y
2 res0: Int = 3
3
4 scala> !true
5 res1: Boolean = false
```



Conventions for operator notation

```
1 scala> "Hello " + "World" split " " size  
2 res0: Int = 2
```

- ▶ Always use infix notation for symbolic methods (operators)
- ▶ Only use infix notation
 - ▶ if the method is free of side-effects
 - ▶ or if the method takes functions as arguments⁷
- ▶ Only use postfix notation
 - ▶ if the method is the last operation in a chain of infix calls
 - ▶ or for domain specific languages



Exercise: Add the operator - to *Time*

- ▶ Make it an alias of *minus*, i.e. delegate to *minus*
- ▶ Verify that the new operator is working as expected:

```
1 scala> val time = new Time(12, 30)
2 time: Time = Time@3513126e
3
4 scala> time - new Time(1, 30)
5 res0: Int = 660
```



Named and default arguments

- ▶ You can assign default values to parameters⁸:

```
1 class Time(val hours: Int = 0, val minutes: Int = 0)
```

- ▶ Now you can omit trailing arguments:

```
1 scala> val time = new Time(12)
2 time: Time = Time@2ce628d8
```

- ▶ But how can you omit leading arguments? Just use named arguments:

```
1 scala> val time = new Time(minutes = 30)
2 time: Time = Time@2ce628d8
```



Exercise: Add defaults to *Time*'s parameters

- ▶ Add the default value *0* to *hours* and *minutes*
- ▶ Try out various combinations of omitting and/or naming arguments for creating a *Time*:

```
1 scala> val time = new Time()  
2 time: Time = Time@3a3c6542  
3  
4 ...
```



Packages

- ▶ Use the keyword *package* to declare a package:

```
1 package org.scalatrain
```

- ▶ Looks like Java, but there are differences:
 - ▶ Packages truly nest: Members of enclosing packages are visible
 - ▶ Package structure and directory structure may differ⁹



Chained package clauses

- ▶ A single package clause brings only the last (nested) package into scope:

```
1 package org.scalatrain  
2 class Foo
```

- ▶ Use chained package clauses to bring several last (nested) packages into scope; here *Foo* becomes visible without import:

```
1 package org.scalatrain  
2 package util  
3 class Bar extends Foo
```

- ▶ Tip: Start with a root package named according to your project and use chained package clauses for your sub-packages



Exercise: Add package clauses

- ▶ Add the package clauses to *Train* and *Time*
- ▶ Use the “usual” notation
- ▶ Use the package name *org.scalatrain*
- ▶ Move the files to the directory *src/main/scala/org/scalatrain/*



Imports

- Use the keyword *import* to import a member of a package:

```
1 import org.scalatrain.Train
```

- Use the underscore to import all members of a package:

```
1 import org.scalatrain._
```

- Use selector clauses to pick multiple or rename members:

```
1 import org.scalatrain.{ Time, Train }  
2 import java.sql.{ Date => SqlDate }
```

- You can import members from any “stable identifier”, i.e. packages, singleton objects and *vals*

```
1 val time = new Time(12)  
2 import time._  
3 println(hours)
```



Exercise: Use import clauses

- ▶ Try to use *Train* like before introducing packages
- ▶ Add a wildcard import clause (use wildcards in the REPL, avoid them in “real” code)
- ▶ Try out renaming *Train* with an import selector clause



Access modifiers

- Use the keyword *protected* to make a member only visible inside its enclosing entity as well as its subtypes:

```
1 class Foo {  
2   protected val bar = "Bar"  
3 }
```

- Use the keyword *private* to make a member only visible inside its enclosing entity:

```
1 class Foo {  
2   private val bar = "Bar"  
3 }
```



Access modifiers

- Use a qualifier to relax access up to the given entity:

```
1 package foo
2 class Foo {
3     private[foo] val bar = "Bar"
4 }
```

- Use the qualifier *[this]* to restrict access to the instance only:

```
1 class Foo {
2     private[this] val bar = "Bar"
3 }
```



Singleton Objects

- ▶ A singleton object is like a class and its sole instance
- ▶ Use the keyword *object* to define a singleton object:

```
1 object Foo {  
2   val bar = "Bar"  
3 }
```

- ▶ You can access a singleton object by its name:

```
1 scala> Foo.bar  
2 res0: java.lang.String = Bar
```

- ▶ Singleton objects can be used to replace *static* from Java, but are “real” objects, e.g. can inherit and be passed as arguments



Companion objects

- ▶ If a singleton object and a class or trait¹⁰ share the same name, package and file, they are called companions:

```
1 object Time {  
2   def fromMinutes(minutes: Int): Time = ...  
3 }  
4  
5 class Time(...
```

- ▶ From a class or trait you can even access private members of the companion object, e.g. constants or “static” methods
- ▶ Except for this, there is no relation at all, especially no “is a”



Exercise: Create the companion object for *Time*

- ▶ Place it inside the same file like the class *Time*
- ▶ Add the method *fromMinutes* taking an *Int* value which creates a *Time* initialized with the given minutes
- ▶ “Normalize” the created *Time*:

```
1 scala> val time = Time.fromMinutes(100)
2 time: ...Time = org.scalatrain.Time@a51c603
3
4 scala> time.hours
5 res0: Int = 1
6
7 scala> time.minutes
8 res1: Int = 40
```



- ▶ The Scala standard library contains the singleton object *Predef*
- ▶ Its members are always “silently” imported
- ▶ E.g. use the method *require* to check preconditions:

```
1 scala> require(1 == 2, "This must obviously fail!")
2 java.lang.IllegalArgumentException: requirement
   failed: This must obviously fail.
```



Exercise: Check hours precondition for *Time*

- Use *require* to check that a *Time* cannot be created with invalid hours, i.e. only with hours greater or equal 0 and less than 24:

```
1 scala> new Time(-1, 0)
2 java.lang.IllegalArgumentException: requirement
   failed: hours must be within 0 to 23!
3   ...
4
5 scala> new Time(24, 0)
6 java.lang.IllegalArgumentException: requirement
   failed: hours must be within 0 to 23!
7   ...
```

- Keep the TODO comment for the precondition check for minutes!



Case classes

- Use the keyword *case* to define a case class:

```
1 case class Person(name: String)
```

- Now you can create new instances without *new*:

```
1 scala> val person = Person("Joe")  
2 person: Person = Person(Joe)  
3  
4 scala> val person2 = Person.apply("Joe")  
5 person2: Person = Person(Joe)
```

- Look, there is a nice *toString* implementation!



Case class benefits

- And even better, there are nice implementations for *equals* and *hashCode* based on all class parameters:

```
1 scala> person == person2
2 res0: Boolean = true
```

- All class parameters are turned into immutable fields automatically:

```
1 scala> person.name
2 res1: String = Joe
```

- There is an easy to use *copy* method using named and default parameters:

```
1 scala> person.copy(name = "Tim")
2 res2: Person = Person(Tim)
```



Why are not all classes case classes?

- ▶ Sometimes you don't want the overhead
- ▶ You cannot (should not) inherit a case class from another one
- ▶ Tip: Case classes are perfect “value objects” but in most cases not suitable for “service objects”



Exercise: Case classes

- ▶ Turn *Train* and *Time* into case classes
- ▶ Remove the *vals*, even if they don't hurt
- ▶ Also remove *new* in *Time.fromMinutes*, even if it doesn't hurt
- ▶ Try out the various case class features:

```
1 scala> Train("ICE", "722")
2 res0: org.scalatrain.Train = Train(ICE,722)
3
4 scala> Time()
5 res1: org.scalatrain.Time = Time(0,0)
6
7 scala> Time(1, 2)
8 res2: org.scalatrain.Time = Time(1,2)
9
10 scala> Time(1, 2) == Time(1, 3)
11 res3: Boolean = false
```



Agenda

Why Scala?

Setting up the development environment

First steps

Basic OO features

Testing in Scala

Collections and functional programming

For-expressions and for-loops

Inheritance and traits

Pattern matching

XML support



Testing with specs2

- ▶ You could use a Java framework like JUnit or TestNG
- ▶ But there are also advanced Scala frameworks
- ▶ We choose **specs2**, because it is very well designed, has deep features and is perfectly maintained



Writing a specification in unit test style

- ▶ Extend¹¹ *org.specs2.mutable.Specification*
- ▶ Describe a system under specification followed by *should* and a code block
- ▶ Describe an example followed by *in* and a code block returning a *Result*
- ▶ Use *todo* to declare a not yet implemented example:

```
1 class TimeSpec extends Specification {  
2  
3   "Calling Time.minus" should {  
4     "return the correct time difference" in {  
5       todo  
6     }  
7     ...  
8   }  
9 }
```



Writing a specification in acceptance test style

- ▶ Extend *org.specs2.Specification* and implement the method *is*
- ▶ Chain fragments using the operator `^`
- ▶ A fragment can be either text or an example
- ▶ An example has a description and a *Result*, separated by the operator `!`

```
1 class TrainSpec extends Specification { def is =  
2  
3   "Calling Time.minus" ^  
4     "should return the correct time diff." ! minus ^  
5     ...  
6   end  
7  
8   def minus = todo  
9   ...  
10 }
```



Running specs2 in Eclipse

- ▶ Add a *@RunWith* annotation to the specification
- ▶ Use the *org.specs2.runner.JUnitRunner*

```
1 import org.junit.runner.RunWith
2 import org.specs2.mutable.Specification
3 import org.specs2.runner.JUnitRunner
4
5 @RunWith(classOf[JUnitRunner])
6 class TimeSpec extends Specification {
7     ...
}
```



Exercise: Add specs2 as library dependency

- ▶ Add the following lines to the build configuration file *build.sbt* in the project directory *training-scala/*:

```
1  
2 libraryDependencies += Seq(  
3   "org.specs2" %% "specs2" % "1.8.2" % "test",  
4   "junit" % "junit" % "4.7" % "test"  
5 )
```

- ▶ Attention: Empty lines between settings are important!
- ▶ Run the *reload* command in sbt
- ▶ Run the *eclipse* command to recreate the Eclipse project files with, then refresh the Eclipse workspace



Exercise: Create the class *TimeSpec*

- ▶ For the time being use *todo* to implement the preliminary tests
- ▶ Use the directory *src/test/scala/*
- ▶ Tests:
 - ▶ Preconditions: *hours* and *minutes* must be within 0..23/59
 - ▶ Verify the defaults for the class parameters
 - ▶ Verify that *Time.minus* works as expected
 - ▶ Verify that *Time.asMinutes* is initialized correctly
- ▶ Run the tests in sbt with the command *test*
- ▶ Run the tests in Eclipse using a JUnit run configuration



Matchers

- Use matchers to define expressive *Results*, e.g.:

```
1 import java.lang.{ IllegalArgumentException => IAE }  
2  
3 Time(-1, 0) must throwAn[IAE]  
4  
5 Time() must equalTo(Time(0, 0))
```

- There are many more, please see the specs2 matchers guide



Exercise: Finalize the tests for *Time*

- ▶ Replace the *todos* with matcher based implementations¹²
- ▶ Run the tests and see them fail partially
- ▶ Implement the missing precondition (TODO comment) for *Time* until all the tests are passing

¹²Use explicit sample values. The ScalaCheck framework provides test data generation but will not be covered here.



Agenda

Why Scala?

Setting up the development environment

First steps

Basic OO features

Testing in Scala

Collections and functional programming

For-expressions and for-loops

Inheritance and traits

Pattern matching

XML support




Collections overview

- ▶ Scala has a comprehensive collection library
- ▶ We will only cover the basics, for details see the very good [online documentation](#)



Collection hierarchy



Creating collection instances

- Use the “class name” of the collection and append a comma-separated list of items in parens:

```
1 scala> List(1, 2, 3)
2 res0: List[Int] = List(1, 2, 3)
3
4 scala> Seq(1, 2, 3)
5 res1: Seq[Int] = List(1, 2, 3)
6
7 scala> IndexedSeq(1, 2, 3)
8 res2: IndexedSeq[Int] = Vector(1, 2, 3)
9
10 scala> List(1, 2, "z")
11 res3: List[Any] = List(1, 2, z)
```



How is that working?

- ▶ For each collection type there is a companion object with a factory method *apply*
- ▶ Whenever we try to “invoke” an object, the compiler will transform this into calling *apply*:

```
1 scala> List(1, 2, 3)
2 res0: List[Int] = List(1, 2, 3)
3
4 scala> List.apply(1, 2, 3)
5 res1: List[Int] = List(1, 2, 3)
```

- ▶ Therefore “invoking” an object is just syntactic sugar for ordinary OO method application¹³

¹³This applies in general, not only for collections.



Type parameters

- ▶ There are no raw types, all collections are parameterized
- ▶ Use square brackets to denote a type parameter¹⁴:

```
1 case class Parameterized[A](a: A)
```

- ▶ Type arguments can be inferred or may be given:

```
1 scala> Parameterized(1)
2 res0: Parameterized[Int] = Parameterized(1)
3
4 scala> Parameterized[Int](1)
5 res1: Parameterized[Int] = Parameterized(1)
```

¹⁴This applies not only to classes, but also to traits and methods.



Tuples

- ▶ Tuples aren't collections, but important, e.g. to create *Maps*
- ▶ Tuples combine a number of objects, each of arbitrary type
- ▶ Again, there is syntactic sugar to ease creating Tuples:

```
1 scala> (1, "a")
2 res0: (Int, java.lang.String) = (1,a)
3
4 scala> Tuple2(1, "a")
5 res1: (Int, java.lang.String) = (1,a)
```

- ▶ Use `_1`, `_2`, etc. to access the first, second, etc. field:

```
1 scala> res0._1
2 res2: Int = 1
```



Tuples and *Maps*

- There is an even easier way to create pairs (*Tuple2s*)¹⁵:

```
1 scala> 1 -> "a"  
2 res0: (Int, java.lang.String) = (1,a)
```

- Use a list of pairs to create a *Map*:

```
1 scala> Map(1 -> "a", 2 -> "b")  
2 res0: ...Map[Int,...String] = Map(1 -> a, 2 -> b)
```

¹⁵This is made possible by implicit conversions which we won't cover in this course.



Immutable and mutable collections

- ▶ There are three main packages for collections:
 - ▶ *scala.collection*: Abstract base, specialized by the following
 - ▶ *scala.collection.immutable*
 - ▶ *scala.collection.mutable*
- ▶ What does immutability mean?

```
1 scala> val numbers = Vector(1, 2, 3)
2 numbers: ...immutable.Vector[Int] = Vector(1, 2, 3)
3
4 scala> numbers :+ 4
5 res0: ...immutable.Vector[Int] = Vector(1, 2, 3, 4)
6
7 scala> numbers
8 res1: ...immutable.Vector[Int] = Vector(1, 2, 3)
```

- ▶ Immutable collections aren't mutated in place, but a new instance is returned



Immutable collections by default

- ▶ Many collection types can be used without import clauses
- ▶ Then the immutable ones are used¹⁶
- ▶ This is enabled by type aliases in the singleton object *Predef* and the package object¹⁷ *scala*

¹⁶Except for *Seq* where the base one is used.

¹⁷We won't cover type aliases or package objects in this course.



Some important collection methods

- ▶ *++* appends two collections
- ▶ *toSeq*, *toSet*, etc. turns a collection into a specific one
- ▶ *isEmpty* and *size* for information regarding size
- ▶ *contains* tests whether a collection contains an element
- ▶ *head* for the first element, *last* for the last
- ▶ *tail* for everything except for the first element, *init* for everything except for the last
- ▶ *take* gets the first n elements, *drop* gets all elements except for the first n
- ▶ *groupBy* partitions a collection into a *Map* of collections according to some discriminator function



Some more important collection methods

- ▶ For *Seqs*: $+:^{18}$ prepends an element, $:+$ appends one
- ▶ For *Lists*: $::^{19}$ (“Cons”) prepends an element
- ▶ For *Maps*: *getOrElse* returns the value for the given key or the given default

¹⁸Operators ending with $:$ are right-associative, i.e. $1 +: Seq(2, 3)$ results in $Seq(1, 2, 3)$.

¹⁹The singleton object *Nil* is the empty *List*, hence $1 :: 2 :: Nil$ results in $List(1, 2, 3)$.



Exercise: Add schedule to *Train*

- ▶ Create the case class *Station* with the class parameter *name* of type *String* in the file *Train.scala*
- ▶ Add the class parameter *schedule* of type *Seq[Station]* to *Train*
- ▶ Add a precondition check ensuring that the *schedule* must contain at least two *Stations* (Tip: Use the collection method *size*)
- ▶ Create the class *TrainSpec* and add a test for the above precondition



Functional collections

- ▶ Collections have a lot of higher order functions²⁰
- ▶ These take another function as argument or return a function
- ▶ Example:

```
1 scala> val numbers = List(1, 2, 3)
2 numbers: List[Int] = List(1, 2, 3)
3
4 scala> numbers map (x => x + 1)
5 res0: List[Int] = List(2, 3, 4)
```

- ▶ Function literals can also be given in curly braces²¹

²⁰Actually collections have methods, but we will use the term higher order functions nevertheless.

²¹We can give any single argument in curly braces.



Function literals

- ▶ Just like there are literals for *Int*, *String*, etc. there is also a way to write down anonymous functions
- ▶ The compiler will create a function value as an instance of a function type²²
- ▶ Syntax alternatives:

```
1 scala> numbers map (x => x + 1)
2 res0: List[Int] = List(2, 3, 4)
3
4 scala> numbers map ((x: Int) => x + 1)
5 res1: List[Int] = List(2, 3, 4)
6
7 scala> numbers map (_ + 1)
8 res2: List[Int] = List(2, 3, 4)
```



Function values

- ▶ Scala has first-class functions, i.e. functions are objects
- ▶ Therefore functions can be assigned to variables and passed as arguments:

```
1 scala> val addOne = (x: Int) => x + 1
2 addOne: (Int) => Int = <function1>
3
4 scala> numbers map addOne
5 res3: List[Int] = List(2, 3, 4)
```



Function types

- ▶ If functions are objects, which are their types?
- ▶ `Int => Int` is syntactic sugar for `Function1[Int, Int]`²³

```
1 scala> val addOne: Int => Int = x => x + 1
2 addOne: (Int) => Int = <function1>
```

- ▶ All function types define the method `apply`:

```
1 scala> addOne(2)
2 res0: Int = 3
3
4 scala> addOne.apply(2)
5 res1: Int = 3
```

²³There are also `Function0` to `Function22`.



Turning methods into functions

- ▶ Methods aren't objects, they are just members
- ▶ Use the underscore to turn a method into a function²⁴:

```
1 scala> def addOne(x: Int) = x + 1
2 addOne: (x: Int)Int
3
4 scala> val f = addOne _
5 f: (Int) => Int = <function1>
```

- ▶ If the signatures of the expected function and the given method match, the compiler can convert it implicitly:

```
1 scala> numbers map addOne // addOne is a method!
2 res8: List[Int] = List(2, 3, 4)
```

²⁴Actually this is called partial application of functions, but this advanced topic won't be covered.



Important collection methods: *map*

- *map* transforms a collection into a new one²⁵:

```
1 trait Traversable[A] {  
2   def map[B](f: A => B): Traversable[B]  
3   ...
```

- The type of the collection's elements may change:

```
1 scala> val languages = List("Scala", "JRuby", "Java")  
2 languages: List[...]String] = List(Scala, JRuby, Java)  
3  
4 scala> languages map (_.toLowerCase)  
5 res0: List[...]String] = List(scala, jruby, java)  
6  
7 scala> languages map (_.length)  
8 res1: List[Int] = List(5, 5, 4)
```



Exercise: Add departure times to *Train.schedule*

- ▶ Change the type of *Train.schedule* to a sequence of tuples:
Seq[(Time, Station)]
- ▶ Add a TODO comment for the precondition that the schedule must be monotonically increasing in time
- ▶ Adjust the test specification (make it compile again)



Exercise: Add the field *stations* to *Train*

- ▶ Use *schedule* as a starting point
- ▶ Transform its value into a *Seq[Station]* using the collection method *map*
- ▶ Add a test verifying that *stations* is initialized correctly



Important collection methods: *flatMap*

- ▶ Like *map*, *flatMap* transforms a collection into a new one
- ▶ The function argument maps each element to a collection, each of which is expanded into the resulting collection:

```
1 trait Traversable[A] {  
2   def flatMap[B](f: A => Traversable[B]):  
    Traversable[B]  
3   ...
```

- ▶ Comparison to *map*:

```
1 scala> languages map (_.toLowerCase)  
2 res0: List[...]String] = List(scala, java)  
3  
4 scala> languages flatMap (_.toLowerCase)  
5 res1: List[Char] = List(s, c, a, l, a, j, r, u, ...)
```



Exercise: Create the class *JourneyPlanner*

- ▶ Add the class parameter *trains* of type *Set[Train]*
- ▶ Add the field *stations* to *JourneyPlanner*
- ▶ The new field shall contain all *Stations* of all *trains*
- ▶ What happens if we use the collection method *map* again?
- ▶ Add a test verifying that *stations* is initialized correctly



Important collection methods: *filter*

- ▶ *filter* copies selected elements into the resulting collection
- ▶ The function argument returns a *Boolean* for each element
- ▶ Only elements for which this predicate is *true* are retained:

```
1 trait Traversable[A] {  
2   def filter(f: A => Boolean): Traversable[A]  
3   ...
```



Exercise: Add the method *trainsAt* to *JourneyPlanner*

- ▶ This new method shall have a parameter of type *Station* and determine all *Trains* that contain that *Station* in their schedule
- ▶ Add a test verifying that the correct results are returned for various *Stations*



Agenda

Why Scala?

Setting up the development environment

First steps

Basic OO features

Testing in Scala

Collections and functional programming

For-expressions and for-loops

Inheritance and traits

Pattern matching

XML support



For expressions

- ▶ For-expressions are for iteration, but they aren't loops, they yield a collection²⁶
- ▶ General syntax:

```
1 for (seq) yield expr
```

- ▶ *seq* contains generators, definitions and filters
- ▶ *expr* creates an element of the resulting collection

²⁶We will see shortly that they work for other data structures, too.



Generators

- ▶ Generators drive the iteration
- ▶ Common form:

```
1 x <- coll
```

- ▶ *coll* is the collection to be iterated²⁷
- ▶ *x* is a variable bound to the current element of the iteration²⁸
- ▶ The (first) generator determines the type of the result:

```
1 scala> for (i <- List(1, 2, 3)) yield i + 1
2 res0: List[Int] = List(2, 3, 4)
3
4 scala> for (i <- Set(1, 2, 3)) yield i + 1
5 res1: ...Set[Int] = Set(2, 3, 4)
```

²⁷As already mentioned, other data structures can be used, too.

²⁸This can be generalized to any pattern, see the upcoming chapter about pattern matching.



Multiple generators

- ▶ Either separate multiple generators by semicolon
- ▶ Or better use curly braces and new lines:

```
1 scala> for {  
2     |   i <- 1 to 3  
3     |   j <- 1 to i  
4     | } yield i * j  
5 res0: ...IndexedSeq[Int] = Vector(1, 2, 4, 3, 6, 9)
```

- ▶ The inner generators “oscillate” more frequently than the outer ones
- ▶ Note: *to* isn't a keyword, but a method²⁹

²⁹While *to* isn't a member of *Int*, it is made available by implicit conversions, which we won't cover in this course.



Filters

- ▶ Filters control the iteration
- ▶ Common form:

```
1 if expr
```

- ▶ *expr* must evaluate to a *Boolean*
- ▶ Filters can follow generators without semicolon or new line:

```
1 scala> for {  
2   |   i <- 1 to 3 if i % 2 == 1  
3   |   j <- 1 to i  
4   | } yield i * j  
5 res0: ...IndexedSeq[Int] = Vector(1, 3, 6, 9)
```

- ▶ Filter conditions can be written without parens



Definitions

- ▶ Definitions are like local *val* definitions
- ▶ Common form:

```
1 x = expr
```

- ▶ Definitions can also be directly followed by a filter:

```
1 scala> for {  
2   |   time <- times  
3   |   hours = time.hours if hours > 12  
4   | } yield (hours - 12) + "pm"  
5 res0: List[String] = List(1pm, 2pm)
```



Exercise: Add the method *stopsAt* to *JourneyPlanner*

- ▶ This new method shall have a parameter of type *Station* and determine a *(Time, Train)* for each train that contains the given *Station* in its schedule
- ▶ Hint: Use a for-expression with two generators and one filter
- ▶ Add a test verifying that the correct results are returned for various *Stations*



Translation of for-expressions

- The compiler translates for-expressions into nested calls of *flatMap*, *map* and *withFilter* (almost like *filter*)

```
1 for (i <- 1 to 3) yield i + 1
2 1 to 3 map (i => i + 1)
3
4 for (i <- 1 to 3; j <- 1 to i) yield i * j
5 1 to 3 flatMap (i => 1 to i map (j => i * j))
6
7 trains flatMap (train =>
8   train.schedule withFilter (timeAndStation =>
9     timeAndStation._2 == station
10   ) map (timeAndStation =>
11     timeAndStation._1 -> train
12   )
13 )
```



For loops

- ▶ For-loops return *Unit*, are executed for their side-effects only
- ▶ General syntax:

```
1 for (seq) body
```

- ▶ *seq* contains generators, definitions and filters
- ▶ *body* may execute a side-effect, its result is omitted

```
1 scala> for (i <- 1 to 3) println(i)
2 1
3 2
4 3
```



Translation of for-loops

- The compiler translates for-loops into nested calls of *foreach* and *withFilter*

```
1 for (i <- 1 to 3) println(i)
2 1 to 3 foreach (i => println(i))
```



Group exercise: Phone mnemonics

- ▶ Task: Given a mapping from phone keys to mnemonics and a dictionary, write a program that translates a phone number into all possible phrases made up from words in the dictionary
- ▶ Example: 7225276257 should be translated to “Scala rocks”
- ▶ Taken from Lutz Prechelt, “An Empirical Comparison of Seven Programming Languages”³⁰
- ▶ Tested with Tcl, Python, Perl, Rexx, Java, C, C++
- ▶ About 100 LOC for scripting languages, 200-300 for others
- ▶ Let's see whether we can do better with Scala!



Group exercise: Phone mnemonics - outline

```
1 class PhoneMnemonics(words: Set[String]) {  
2  
3   val mnemonics = Map('2' -> "ABC", '3' -> "DEF", ...)  
4  
5   val charCode: Map[Char, Char] = Map.empty  
6  
7   def wordCode(word: String): String = ""  
8  
9   val wordsForNumber: Map[String, Set[String]] = Map.empty  
10  
11  def encode(number: String): Set[Seq[String]] = Set.empty  
12  
13  def translate(number: String): Set[String] =  
14    encode(number) map { _ mkString " " }  
15 }
```



Agenda

Why Scala?

Setting up the development environment

First steps

Basic OO features

Testing in Scala

Collections and functional programming

For-expressions and for-loops

Inheritance and traits

Pattern matching

XML support



Class inheritance

- Use the keyword *extends* to define a subclass of another class:

```
1 class Animal
2 class Bird extends Animal
```

- Omitting *extends* means *extends AnyRef*³¹



Calling the superclass constructor

- ▶ Subclasses must immediately call their superclass constructor:

```
1 class Animal(val name: String)
2 class Bird(name: String) extends Animal(name)
```

- ▶ This won't compile:

```
1 scala> class Animal(val name: String)
2 defined class Animal
3
4 scala> class Bird(name: String) extends Animal
5 <console>:8: error: not enough arguments ...
6 Unspecified value parameter name.
```



Final classes

- Use the keyword *final* to prevent a class from being subclassed:

```
1 scala> final class Animal
2 defined class Animal
3
4 scala> class Bird extends Animal
5 <console>:8: error: illegal inheritance from final
   class Animal
```



Sealed classes

- Use the keyword *sealed* to allow subclassing only within the same source file:

```
1 sealed class Animal
2 class Bird extends Animal
3 class Fish extends Animal
```

- This means, that sealed classes can only be subclassed by you, but not by others, i.e. you know all subclasses³²



Example: Enumerations

- Create a singleton object extending from *Enumeration*:

```
1 object Consumers extends Enumeration {  
2   val Herbivore = Value  
3   val Carnivore = Value  
4 }
```

- Each element of the enumeration is defined as an immutable field initialized by calling *Value*³³ with an optional name
- The enumeration's elements have an *id* and a name:

```
1 scala> Consumers.values map { value =>  
2   |   value.id -> value.toString  
3   | }  
4 res0: ... = Set((0,Herbivore), (1,Carnivore))
```

³³The values' type is path dependent: *Consumer.Value*



Exercise: Use an enumeration for *Train.kind*

- ▶ Create the enumeration *TrainKind* with three elements³⁴:
 - ▶ *Ice*³⁵ with the name “ICE”
 - ▶ *Re* with the name “RE”
 - ▶ *Brb* with the name “BRB”
- ▶ Change the type of *Train.kind* from *String* to *TrainKind.Value*
- ▶ Adjust the test cases, i.e. make the whole project compile again

³⁴ “ICE”, “RE” and “BRB” are (some) kinds of trains in Germany.

³⁵ Constants are written in upper camel case (first letter capitalized).



Overriding members

- Use the keyword *override* to override a superclass member:

```
1 class Animal {  
2     val name = "Animal"  
3 }  
4 class Bird extends Animal {  
5     override val name = "Bird"  
6 }
```

- *override* is mandatory to avoid mistakes:

```
1 class Bird extends Animal {  
2     override val nam = "Bird"  
3 }  
4  
5 <console>:9: error: value nam overrides nothing
```

- Use the keyword *final* to prevent a member from being overridden



Overriding methods with immutable variables

- You can override a parameterless method with an immutable variable:

```
1 class Animal {  
2   def name = "Animal"  
3 }  
4 class Bird extends Animal {  
5   override val name = "Bird"  
6 }
```

- The other way round is not possible!



Exercise: Override *Time.toString*

- ▶ As *Time* is a case class, the result of *toString* looks already quite nice
- ▶ But we can do better: Let's use string formatting with the format `"%02d:%02d"` to get something like `"12:55"`
- ▶ Hint: Scala adds the instance method *format* to *String*; simply apply it to the above format string: `"%02d:%02d".format(...)`
- ▶ First use a method and then switch to an immutable field
- ▶ Add a test verifying that *Time.toString* returns a correctly formatted result



Abstract classes

- ▶ Use the keyword *abstract* to define an abstract class
- ▶ Simply omit the initialization or implementation to define an abstract field or method:

```
1 abstract class Animal {  
2     val name: String  
3     def hello: String  
4 }
```

- ▶ *abstract* is mandatory to prevent you from making a class abstract by mistake



Implementing abstract members

- Initialize or implement an abstract field or method to make it concrete:

```
1 class Bird(override val name: String) extends Animal {  
2   override def hello = "Beep"  
3 }
```

- While using *override* to initialize/implement an abstract member isn't mandatory, it is recommended to prevent you from mistakes
- There is one exception: Don't use *override val* for case class parameters, because case classes should never be subclassed




Exercise: Refactor *Train* to use a sealed abstract class

- ▶ Create the sealed abstract class *TrainInfo* with the abstract def *number* of type *String*
- ▶ Add the case classes *Ice*, *Re* and *Brb* extending *TrainInfo*
- ▶ Add the class parameter *hasWifi* of type *Boolean* with default value *false* to *Ice*
- ▶ Replace *Train*'s fields *kind* and *number* with the single field *info* of type *TrainInfo*
- ▶ Delete the enumeration *TrainKind*
- ▶ Adjust the test cases, i.e. make the whole project compile again



Scala type hierarchy



Group exercise: Two-dimensional layout library

- ▶ We want to build and render two-dimensional layout elements where element represents a rectangle filled with text
- ▶ We want to create elements using factory methods
- ▶ We want to combine elements horizontally and vertically:

```
1 scala> val e1 = Element("Hello") above Element("***")
2 ...
3 scala> val e2 = Element("+++") above Element("World")
4 ...
5 scala> e1 beside e2
6 res0: layout.Element =
7 Hello +++
8 *** World
```



Traits

- ▶ Use the keyword *trait* to define a trait:

```
1 trait Swimmer {  
2   def swim = "I am swimming!"  
3 }
```

- ▶ Traits encapsulate fields and methods³⁶
- ▶ Traits are abstract and have no parameters³⁷
- ▶ Traits can explicitly inherit from a class:

```
1 class A  
2 trait B extends A
```

³⁶You can look at traits as interfaces with concrete members.

³⁷You can also look at traits as abstract classes without parameters.



The use case for traits

- As in Java, there is no multiple (class) inheritance in Scala:

```
1 abstract class Animal {  
2   val name: String  
3 }  
4 class Bird(val name: String) extends Animal {  
5   def fly = "I am flying!"  
6 }  
7 class Fish(val name: String) extends Animal {  
8   def swim = "I am swimming!"  
9 }  
10 class Duck // ??
```

- How can we avoid code duplication?



Mix-in composition

- Use the keyword *with* to mix a trait into a class that already extends another class:

```
1 class Fish(val name: String) extends Animal with Swimmer
2 class Duck(name: String) extends Bird(name) with Swimmer
```

- Use the keyword *extends* to mix a trait into a class that doesn't explicitly inherit from another class:

```
1 trait A
2 class B extends A // class B extends AnyRef with A
```

- Mix-ins are like multiple inheritance just without the issues³⁸

³⁸The Scala compiler is able to linearize all inherited classes and mixed-in traits.



Mixing-in multiple traits

- Use the keyword *with* repeatedly to mix-in multiple traits:

```
1 trait A
2 trait B
3 trait C
4 class D extends A with B with C
```

- If multiple traits define the same members, the outermost (rightmost) one “wins”



Mix-in rules

- ▶ Traits must respect the inheritance hierarchy:

```
1 scala> class A; class B; trait C extends A
2 ...
3
4 scala> class D extends B with C
5 <console>:10: error: illegal inheritance; superclass B
6   is not a subclass of the superclass A of the mixin
   trait C
```

- ▶ Concrete members must be overridden:

```
1 scala> trait A { def x = 1 }; trait B { def x = 2 }
2 ...
3
4 scala> class C extends A with B
5 <console>:9: error: overriding method x in trait A ...
6   ... needs 'override' modifier
```



Exercise: Mix *Ordered* into *Time*

- ▶ This let's you compare *Times* using $>$, $>=$, etc.
- ▶ Implement the abstract method *compare*
- ▶ Add a test verifying that *Times* are ordered correctly



Agenda

Why Scala?

Setting up the development environment

First steps

Basic OO features

Testing in Scala

Collections and functional programming

For-expressions and for-loops

Inheritance and traits

Pattern matching

XML support



Match expressions

- ▶ Match expressions look a little like Java's *switch*, but they are different and much more powerful
- ▶ General syntax:

```
1 expr match {  
2   case pattern1 => result1  
3   case pattern2 => result2  
4   ...  
5 }
```

- ▶ *expr* in front of the keyword *match* is an arbitrary expression
- ▶ The result of *expr* is matched against the various alternatives inside the body of *match*
- ▶ Matching happens from top to bottom



Match alternatives

- ▶ General syntax:

```
1 case pattern => result
```

- ▶ An alternative starts with the keyword *case*
- ▶ *pattern* is one of various pattern types³⁹
- ▶ *result* is an arbitrary expression⁴⁰
- ▶ If a pattern matches, the match expression returns *result*
- ▶ If no alternative matches, a *MatchError* is thrown

³⁹We will discuss the various pattern types shortly.

⁴⁰The expression can span multiple lines without using curly braces.



Wildcard pattern

- Use the underscore as a wildcard to match everything:

```
1 case _ => result
```

- Use the wildcard pattern as the last alternative to prevent *MatchErrors*:

```
1 def whatIsIt(any: Any) = any match {  
2   case _ => "Something unknown"  
3 }  
4  
5 scala> whatIsIt(Time())  
6 res0: java.lang.String = Something unknown
```



Constant pattern

- Use a “stable identifier” to match “something constant”:

```
1 def whatIsIt(any: Any) = any match {  
2   case "12:00" => "High noon"  
3   case _ => "Something unknown"  
4 }  
5  
6 scala> whatIsIt("12:00")  
7 res0: java.lang.String = High noon  
8  
9 scala> whatIsIt("12:01")  
10 res1: java.lang.String = Something unknown
```

- Stable identifiers are literals and *vals* or singleton objects starting with a capital letter
- Alternatively enclose such an identifier in backticks when starting with a small letter



Variable pattern

- Use a variable starting with a small letter to capture a value:

```
1 def whatIsIt(any: Any) = any match {  
2   case x => "Something: " + x  
3 }  
4  
5 scala> whatIsIt(Time())  
6 res0: java.lang.String = Something: 00:00
```

- The variable pattern used by itself will match everything



Typed pattern

- Use a type annotation to match certain types only:

```
1 def whatIsIt(any: Any) = any match {  
2   case x: String => "A String: " + x  
3   case _: Int => "An Int value"  
4   case _ => "Something unknown"  
5 }  
6  
7 scala> whatIsIt("12:01")  
8 res01: java.lang.String = A String: 12:01  
9  
10 scala> whatIsIt(1)  
11 res1: java.lang.String = An Int value
```

- The typed pattern is always combined with the wildcard or variable pattern



Tuple pattern

- Use tuple syntax to match and decompose tuples:

```
1 def whatIsIt(any: Any) = any match {  
2   case ("12:00", "12:01") => "12:00..12:01"  
3   case ("12:00", x) => "High noon and " + x  
4   case _ => "Something else"  
5 }  
6  
7 scala> whatIsIt("12:00" -> "midnight")  
8 res0: java.lang.String = High noon and midnight
```

- The tuple pattern is combined with other patterns, e.g. with the constant or variable pattern



Constructor pattern

- Use constructor syntax to match and decompose case classes:

```
1 def whatIsIt(any: Any) = any match {  
2   case Time(12, 00) => "High noon"  
3   case Time(12, minutes) => "12:%02d" format minutes  
4 }  
5  
6 scala> whatIsIt(Time(12, 01))  
7 res0: java.lang.String = 12:01
```

- The constructor pattern is combined with other pattern, e.g. with the constant or variable pattern or with deeply nested constructor patterns



Sequence pattern

- ▶ Use “sequence constructors” to match and decompose sequences:

```
1 def whatIsIt(any: Any) = any match {  
2   case Seq(1, 2) => "1, 2"  
3   case Seq(1, 2, _*) => "1, 2, ..."  
4   case Seq(Time(h, m), x) =>  
5     "%02d:%02d, %s".format(h, m, x)  
6 }
```

- ▶ `_*` wildcard matches a trailing subsequence
- ▶ The sequence pattern is also combined with other patterns



Pattern guards

- ▶ Combining patterns gives you a lot of control over matching, but sometimes that's just not enough
- ▶ Use the keyword *if* to define a pattern guard:

```
1 def whatIsIt(any: Any) = any match {  
2   case s: String if s startsWith "x" => "x..."  
3   case _: String => """"Not starting with "x"!"""  
4   case _ => "Something else"  
5 }  
6  
7 scala> whatIsIt("xyz")  
8 res0: java.lang.String = x...
```

- ▶ Pattern guards can be written without parens



Exercise: Add the method *isShortTrip* to *JourneyPlanner*

- ▶ A trip between two *Stations* is a short trip, if:
 - ▶ There exists a connection with a single train
 - ▶ There is at most one *Station* between the given two
- ▶ *isShortTrip* has the parameters *from* and *to* of type *Station*
- ▶ Implementation hint: Take a look at the collection methods *exists* and *dropWhile* and use pattern matching with the sequence pattern
- ▶ Add a test case verifying that short trips are calculated correctly



Catching exceptions

- ▶ There are no checked exceptions in Scala
- ▶ Use patterns to catch exceptions:

```
1 try {  
2   // Possibly throwing a NumberFormatException  
3 } catch {  
4   case e: NumberFormatException => ...  
5 }
```



Patterns outside of match expressions

- Use patterns in *val* definitions or generators:

```
1 scala> val (morning, highNoon) = Time(6) -> Time(12)
2 morning: org.scalatrain.Time = 06:00
3 highNoon: org.scalatrain.Time = 12:00
4
5 scala> val charAndIndexList = List('a' -> 1, 'b' -> 2)
6 charAndIndexList: ... = List((a,1), (b,2))
7
8 scala> for ((char, index) <- charAndIndexList) {
9     |   println("%s: %s".format(index, char))
10    | }
11 1: a
12 2: b
```



Exercise: Use patterns to improve readability

- ▶ Replace clumsy tuple element accessors by patterns:
- ▶ Refactor *JourneyPlanner.stopsAt*
- ▶ Refactor *PhoneMnemonics.charCode*



Agenda

Why Scala?

Setting up the development environment

First steps

Basic OO features

Testing in Scala

Collections and functional programming

For-expressions and for-loops

Inheritance and traits

Pattern matching

XML support



XML literals

- XML literals⁴¹ are baked into the language:

```
1 scala> <time hours="12" minutes="00"/>  
2 res0: ...Elem = <time minutes="00" hours="12"></time>
```

- The compiler checks whether XML literals are well-formed:

```
1 scala> <time><unclosed></time>  
2 <console>:1: error: in XML literal: expected closing  
   tag of unclosed
```



Insert Scala code into XML literals

- Use curly braces to insert Scala expressions into XML literals:

```
1 scala> <random>{ Random.nextInt }</random>
2 res0: scala.xml.Elem = <random>-1249076074</random>
```


- For text nodes any type works, but for attribute nodes you have to provide *Strings*⁴²:

```
1 scala> val time = Time(12)
2 time: org.scalatrain.Time = 12:00
3
4 scala> <time hours={ time.hours.toString }/>
5 res0: scala.xml.Elem = <time hours="12"></time>
```

⁴²Actually you have to provide a *NodeSeq* in both cases, but only for text nodes any type is converted into a *String* first.



Important types of the XML library



- ▶ *NodeSeq* is the root of all XML types
- ▶ *Elem* represents XML elements
- ▶ *Text* represents text nodes



XML objects are sequences

- Use `++` to add two *NodeSeqs*:

```
1 scala> val ab = <a/> ++ <b/>
2 ab: scala.xml.NodeSeq = NodeSeq(<a></a>, <b></b>)
```

- Use *child* to access the child nodes of an *Elem*:

```
1 scala> val xml = <a><b><c></c></b><b><c></c></b></a>
2 xml: ...Elem = <a><b><c></c></b><b><c></c></b></a>
3
4 scala> xml.child
5 res0: .. = ArrayBuffer(<b><c></c></b>, <b><c></c></b>)
6
7 scala> xml.child.head
8 res1: scala.xml.Node = <b><c></c></b>
```



XPath like queries

- Use the operator `\` to query an *Elem* for children:

```
1 scala> xml \ "b"  
2 res0: scala.xml.NodeSeq = NodeSeq(<b><c></c></b>,  
    <b><c></c></b>)
```

- Use the operator `\\` to query an *Elem* for descendants:

```
1 scala> xml \\ "c"  
2 res0: scala.xml.NodeSeq = NodeSeq(<c></c>, <c></c>)
```

- Use `@` to query for attributes:

```
1 scala> val xml = <a><b name="b1"/><c name="b2"/></a>  
2 xml: .. = <a><b name="b1"></b><c name="b2"></c></a>  
3  
4 scala> xml \\ "@name"  
5 res0: scala.xml.NodeSeq = NodeSeq(b1, b2)
```



Digression: The *Option* class

- ▶ In Java an optional result is typically expressed by *null*
- ▶ In Scala we have the abstract class *Option* that can either be *Some* wrapping a value or *None*:

```
1 scala> Option(1)
2 res0: Option[Int] = Some(1)
3
4 scala> Option(null)
5 res1: Option[Null] = None
```

- ▶ Benefits: No more forgetting *if (... == null)*
- ▶ *Option* defines *map*, *flatMap*, *withFilter*, etc., i.e. can be used in for-expressions



Exercise: Add XML serialization to *Time*

- ▶ Add the method *toXml* to *Time*:

```
1 <time hours="12" minutes="01" />
```

- ▶ Add the method *fromXml* to the companion object *Time*:
 - ▶ Add one parameter of type *Elem*
 - ▶ The result type shall be an *Option[Time]*, depending whether the given *Elem* can be “parsed”
 - ▶ Implementation hint: Use *Exception.catching* from the package *scala.util.control* to treat *NumberFormatExceptions*
- ▶ Add tests, including one “round trip” serialization/deserialization



Unless otherwise agreed, training materials may only be used for educational and reference purposes by individual named participants in a training course offered by Typesafe or a Typesafe training partner. Unauthorized reproduction, redistribution, or use of this material is prohibited.

