

Node and Express Source Export

Complete workspace source snapshot

app.js

```
let express = require('express');
let fs = require('fs');
let path = require('path');
let app = express();
const bcrypt = require('bcryptjs');

app.use(express.urlencoded({ extended: true }));
app.use(express.json());
app.set('view engine', 'ejs');
app.set('views', path.join(__dirname, 'views'));

const employeeFilePath = path.join(__dirname, 'employees.json');
const loginFilePath = path.join(__dirname, 'logins.json');

// Admin code required to register. Configure via env var `ADMIN_CODE`.
const ADMIN_CODE = process.env.ADMIN_CODE || 'letmein123';

const defaultEmployees = [
  { id: 1, name: 'Doe, John', designation: 'Software Engineer', email: 'john.doe@example.com',
    contact: '123-456-7890', department: 'Engineering', joiningDate: '2020-01-15', location: 'New
    York' },
  { id: 2, name: 'Smith, Jane', designation: 'Product Manager', email:
    'jane.smith@example.com', contact: '987-654-3210', department: 'Marketing', joiningDate: '2020-
    02-01', location: 'Los Angeles' }
];

function readJsonArray(filePath, fallbackValue) {
  try {
    const fileContent = fs.readFileSync(filePath, 'utf8').trim();
    if (!fileContent) {
      return fallbackValue;
    }

    const parsedContent = JSON.parse(fileContent);
    return Array.isArray(parsedContent) ? parsedContent : fallbackValue;
  } catch (error) {
    return fallbackValue;
  }
}

function writeJsonArray(filePath, value) {
  fs.writeFileSync(filePath, JSON.stringify(value, null, 2));
}

// http://localhost:3000/
app.get('/', (req, res) => {
  res.render("login");
});
```

```

// http://localhost:3000/signup
app.get("/signup", (req, res) => {
  let msg = "";
  res.render("signup", { msg });
});

// Backward-compatible alias for the old signup page route
app.get("/signupPage", (req, res) => {
  res.redirect("/signup");
});

// http://localhost:3000/signIn
app.post("/signIn", (req, res) => {
  let msg="";
  let login = req.body;
  let loginFs = readJsonArray(loginFilePath, []);
  const stored = loginFs.find(l => l.emailID === login.emailID);
  let passwordMatches = false;
  if (stored) {
    try {
      passwordMatches = bcrypt.compareSync(login.password, stored.password);
    } catch (e) {
      // fallback if stored.password is plain text
      passwordMatches = stored.password === login.password;
    }
  }

  if (stored && passwordMatches) {
    let emailID = stored.emailID;
    // If the stored password was plaintext and matched, upgrade it to a hashed password
    if (stored.password === login.password) {
      try {
        const newHash = bcrypt.hashSync(login.password, 10);
        stored.password = newHash;
        writeJsonArray(loginFilePath, loginFs);
      } catch (e) {
        // ignore upgrade errors
      }
    }
    msg = "Login successful. Welcome, " + emailID + "!";
    const employees = readJsonArray(employeeFilePath, defaultEmployees);
    res.render("dashboard", {
      msg,
      emailID,
      employees: sortEmployees(employees, 'id', 'asc'),
      currentSort: 'id',
      currentOrder: 'asc',
      filters: { search: '', designation: '', department: '', location: '' }
    });
  } else {
    msg = "Invalid email ID or password.";
    res.render("login",{msg});
  }
}

```

```

    }
  });

// http://localhost:3000/signup
app.post("/signup", (req, res) => {
  let msg="";
  const { emailID, password, confirmPassword, adminCode } = req.body || {};

  if (!emailID || !password) {
    msg = 'Email ID and password are required.';
    return res.render('signup', { msg });
  }

  if (password !== confirmPassword) {
    msg = 'Passwords do not match.';
    return res.render('signup', { msg });
  }

  if (adminCode !== ADMIN_CODE) {
    msg = 'Invalid admin code.';
    return res.render('signup', { msg });
  }

  let loginFs = readJsonArray(loginFilePath, []);
  let loginExists = loginFs.find(l => l.emailID === emailID);
  if (loginExists) {
    msg = 'Email ID already exists. Please use a different email ID.';
    return res.render('signup', { msg });
  }

  // Hash the password before storing
  const hashed = bcrypt.hashSync(password, 10);
  // Only store the minimal user record with hashed password
  loginFs.push({ emailID, password: hashed });
  writeJsonArray(loginFilePath, loginFs);
  msg = 'Sign up successful. Please sign in.';
  res.render('login', { msg });
});

// search employee by id with query parameter
// http://localhost:3000/api/findEmployeeByIdUsingQuery
app.get('/api/findEmployeeByIdUsingQuery', (req, res) => {
  const employees = readJsonArray(employeeFilePath, defaultEmployees);
  let id = parseInt(req.query.id);
  let employee = employees.find(emp => emp.id === id);

  if (req.query.view === 'dashboard') {
    const sortKey = req.query.sort || 'id';
    const order = req.query.order || 'asc';
    const filters = {
      search: req.query.id || '',
      designation: req.query.designation || '',
    }
  }
});

```

```

        department: req.query.department || '',
        location: req.query.location || ''
    });

    const dashboardEmployees = employee ? [employee] : [];
    return res.render('dashboard', {
        employees: sortEmployees(dashboardEmployees, sortKey, order),
        currentSort: sortKey,
        currentOrder: order,
        filters,
        msg: employee ? `Showing employee with ID ${id}` : 'Employee not found'
    });
}

if (employee) {
    res.json(employee);
} else {
    res.status(404).json({ message: 'Employee not found' });
}
});

// search employee by id with path parameter
// http://localhost:3000/api/findEmployeeByIdUsingPath/2
// app.get('/api/findEmployeeByIdUsingPath/:id', (req, res) => {
//     const employees = readJsonArray(employeeFilePath, defaultEmployees);
//     let id = parseInt(req.params.id);
//     let employee = employees.find(emp => emp.id === id);
//     if (employee) {
//         res.json(employee);
//     } else {
//         res.status(404).json({ message: 'Employee not found' });
//     }
// });

// http://localhost:3000/api/addEmployee
app.get('/api/addEmployee', (req, res) => {
    let msg = '';
    res.render('addEmployee', { msg });
});

// http://localhost:3000/api/addEmployee
app.post('/api/addEmployee', (req, res) => {
    const employees = readJsonArray(employeeFilePath, defaultEmployees);
    const newEmployee = {
        id: employees.length > 0 ? Math.max(...employees.map(emp => emp.id)) + 1 : 1,
        name: req.body.name || 'New Employee',
        designation: req.body.designation || 'Unknown',
        email: req.body.email || 'Unknown',
        contact: req.body.contact || 'Unknown',
        department: req.body.department || 'Unknown',
        joiningDate: req.body.joiningDate || 'Unknown',
        location: req.body.location || 'Unknown'
    };

```

```

    });
    employees.push(newEmployee);
    writeJsonArray(employeeFilePath, employees);
    res.redirect(`/api/dashboard?msg=${encodeURIComponent(`Employee added successfully:
${newEmployee.name}`)}`);
  });

// http://localhost:3000/api/updateEmployee/:id
app.get('/api/updateEmployee/:id', (req, res) => {
  const employees = readJsonArray(employeeFilePath, defaultEmployees);
  const id = parseInt(req.params.id);
  const employee = employees.find(emp => emp.id === id);
  let msg = '';
  if (employee) {
    res.render('updateEmployee', { employee, msg });
  } else {
    msg = 'Employee not found';
    res.render('updateEmployee', { employee: {}, msg });
  }
});

// http://localhost:3000/api/updateEmployee/:id
app.post('/api/updateEmployee/:id', (req, res) => {
  const employees = readJsonArray(employeeFilePath, defaultEmployees);
  const id = parseInt(req.params.id);
  const employeeIndex = employees.findIndex(emp => emp.id === id);
  if (employeeIndex !== -1) {
    employees[employeeIndex] = {
      id,
      name: req.body.name || employees[employeeIndex].name,
      designation: req.body.designation || employees[employeeIndex].designation,
      email: req.body.email || employees[employeeIndex].email,
      contact: req.body.contact || employees[employeeIndex].contact,
      department: req.body.department || employees[employeeIndex].department,
      joiningDate: req.body.joiningDate || employees[employeeIndex].joiningDate,
      location: req.body.location || employees[employeeIndex].location
    };
    writeJsonArray(employeeFilePath, employees);
    res.redirect(`/api/dashboard?msg=${encodeURIComponent(`Employee updated successfully:
${employees[employeeIndex].name}`)}`);
  } else {
    res.status(404).json({ message: 'Employee not found' });
  }
});

app.get('/api/dashboard', (req, res) => {
  const employees = readJsonArray(employeeFilePath, defaultEmployees);
  const filters = {
    search: req.query.search || '',
    designation: req.query.designation || '',
    department: req.query.department || '',
    location: req.query.location || ''
  };

```

```

    };
    const sortKey = req.query.sort || 'id';
    const order = req.query.order || 'asc';
    const msg = req.query.msg || '';
    const normalizedSearch = String(filters.search || '').trim();
    const searchAsId = Number(normalizedSearch);
    const searchOnlyById = normalizedSearch !== '' && Number.isInteger(searchAsId) &&
String(searchAsId) === normalizedSearch && !filters.designation && !filters.department &&
!filters.location;

    if (searchOnlyById) {
        const redirectQuery = new URLSearchParams({
            view: 'dashboard',
            id: normalizedSearch,
            sort: sortKey,
            order,
            designation: filters.designation,
            department: filters.department,
            location: filters.location
        });

        return res.redirect(`/api/findEmployeeByIdUsingQuery?${redirectQuery.toString()}`);
    }

    const filteredEmployees = matchEmployeeSegments(employees, filters);
    const sortedEmployees = sortEmployees(filteredEmployees, sortKey, order);

    res.render('dashboard', {
        employees: sortedEmployees,
        currentSort: sortKey,
        currentOrder: order,
        filters,
        msg
    });
});

// http://localhost:3000/api/deleteEmployee/:id
app.get('/api/deleteEmployee/:id', (req, res) => {
    const employees = readJsonArray(employeeFilePath, defaultEmployees);
    const id = parseInt(req.params.id);
    const employee = employees.find(emp => emp.id === id);
    let msg = '';
    if (employee) {
        res.render('deleteEmployee', { employee, msg });
    } else {
        msg = 'Employee not found';
        res.render('deleteEmployee', { employee: {}, msg });
    }
});

// http://localhost:3000/api/deleteEmployee/:id
app.post('/api/deleteEmployee/:id', (req, res) => {

```

```

const employees = readJsonArray(employeeFilePath, defaultEmployees);
const id = parseInt(req.params.id);
const employeeIndex = employees.findIndex(emp => emp.id === id);
if (employeeIndex !== -1) {
    const deletedName = employees[employeeIndex].name;
    employees.splice(employeeIndex, 1);
    writeJsonArray(employeeFilePath, employees);
    res.redirect(`/api/dashboard?msg=${encodeURIComponent(`Employee deleted successfully:
${deletedName}`)}`);
} else {
    res.status(404).json({ message: 'Employee not found' });
}
});

```

// clicking on an employee name in the dashboard should take you to a page showing that employee's details, with options to update or delete the employee

```

// http://localhost:3000/api/viewEmployee/:id
app.get('/api/viewEmployee/:id', (req, res) => {
    const employees = readJsonArray(employeeFilePath, defaultEmployees);
    const id = parseInt(req.params.id);
    const employee = employees.find(emp => emp.id === id);
    let msg = '';
    if (employee) {
        res.render('viewEmployee', { employee, msg });
    } else {
        msg = 'Employee not found';
        res.render('viewEmployee', { employee: {}, msg });
    }
});

```

```

function sortEmployees(employees, sortKey = 'id', order = 'asc') {
    const sortedEmployees = [...employees];

    sortedEmployees.sort((a, b) => {
        const firstValue = a[sortKey];
        const secondValue = b[sortKey];

        if (typeof firstValue === 'number' && typeof secondValue === 'number') {
            return order === 'desc' ? secondValue - firstValue : firstValue - secondValue;
        }

        const firstText = String(firstValue ?? '').toLowerCase();
        const secondText = String(secondValue ?? '').toLowerCase();

        if (firstText < secondText) {
            return order === 'desc' ? 1 : -1;
        }

        if (firstText > secondText) {
            return order === 'desc' ? -1 : 1;
        }
    });
}

```



```

    return 0;
  });

  return sortedEmployees;
}

function matchEmployeeSegments(employees, filters = {}) {
  const searchTerm = String(filters.search || '').trim().toLowerCase();
  const designationTerm = String(filters.designation || '').trim().toLowerCase();
  const departmentTerm = String(filters.department || '').trim().toLowerCase();
  const locationTerm = String(filters.location || '').trim().toLowerCase();

  return employees.filter(employee => {
    const name = String(employee.name || '').toLowerCase();
    const designation = String(employee.designation || '').toLowerCase();
    const department = String(employee.department || '').toLowerCase();
    const location = String(employee.location || '').toLowerCase();
    const email = String(employee.email || '').toLowerCase();

    const searchMatches =
      !searchTerm ||
      name.includes(searchTerm) ||
      designation.includes(searchTerm) ||
      department.includes(searchTerm) ||
      location.includes(searchTerm) ||
      email.includes(searchTerm);

    const designationMatches = !designationTerm || designation.includes(designationTerm);
    const departmentMatches = !departmentTerm || department.includes(departmentTerm);
    const locationMatches = !locationTerm || location.includes(locationTerm);

    return searchMatches && designationMatches && departmentMatches && locationMatches;
  });
}

app.listen(3000, () => {
  console.log('Server is running on port 3000');
});

```

package.json

```
{
  "name": "node-and-express-login-app",
  "version": "1.0.0",
  "description": "Simple Node and Express login and employee demo app",
  "main": "app.js",
  "scripts": {
    "start": "node app.js",
    "dev": "nodemon app.js"
  },
  "dependencies": {
    "bcryptjs": "^2.4.3",
    "ejs": "^3.1.10",
    "express": "^4.19.2"
  },
  "devDependencies": {
    "nodemon": "^3.1.14"
  }
}
```

employees.json

```
[
  {
    "id": 2,
    "name": "Smith, Justin",
    "designation": "Product Manager",
    "email": "residentsmith@yahoo.com",
    "contact": "987-654-3210",
    "department": "Marketing",
    "joiningDate": "2020-02-01",
    "location": "Los Angeles"
  },
  {
    "id": 3,
    "name": "Izraelov, God",
    "designation": "Trader",
    "email": "izraelov@gmail.com",
    "contact": "493 204 9846",
    "department": "Finance",
    "joiningDate": "2026-06-09",
    "location": "Israel"
  },
  {
    "id": 4,
    "name": "Squarepants, Spongebob",
    "designation": "Fry Cook",
    "email": "spongebob@gmail.com",
    "contact": "205 822 8572",
    "department": "Restaurant",
    "joiningDate": "1999-06-17",
    "location": "Bikini Bottom"
  }
]
```

logins.json

```
[
  {
    "emailID": "bdlewis619@hotmail.com",
    "password": "$2a$10$1520VSrya00/T9euHeBZS.Bie6cysj2Btvdn3gqBZfZpbDiAWKKbu"
  },
  {
    "emailID": "name@example.com",
    "password": "$2a$10$ZcF7ujTW5v4c7lmtT4txb.ACd412B4sJETAK.xW0cy1ouVRDTycQS"
  }
]
```

views\addEmployee.ejs

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Add Employee</title>
  <style>
    body {
      font-family: Arial, sans-serif;
      margin: 0;
      background: #f4f7fb;
      color: #0f172a;
    }
    .page {
      max-width: 720px;
      margin: 0 auto;
      padding: 24px;
    }
    .card {
      background: #ffffff;
      border-radius: 16px;
      padding: 24px;
      box-shadow: 0 10px 30px rgba(15, 23, 42, 0.08);
    }
    .back-link {
      display: inline-block;
      margin-bottom: 16px;
      color: #0ea5e9;
      text-decoration: none;
      font-weight: 700;
    }
    .form-grid {
      display: grid;
      gap: 14px;
    }
    label {
      display: block;
      margin-bottom: 6px;
      font-weight: 700;
    }
    input {
      width: 100%;
      box-sizing: border-box;
      padding: 10px 12px;
      border: 1px solid #cbd5e1;
      border-radius: 8px;
      font-size: 15px;
    }
    .actions {
```

```

        display: flex;
        gap: 12px;
        flex-wrap: wrap;
        margin-top: 8px;
    }
    button,
    .button-link {
        display: inline-flex;
        align-items: center;
        justify-content: center;
        padding: 10px 14px;
        border: 0;
        border-radius: 8px;
        text-decoration: none;
        font-weight: 700;
        cursor: pointer;
        font-size: 15px;
    }
    button[type="submit"] {
        background: #38bdf8;
        color: #00111f;
    }
    .button-link {
        background: #e2e8f0;
        color: #0f172a;
    }
    .notice {
        margin-bottom: 16px;
        padding: 14px 16px;
        background: #f8fafc;
        border-left: 4px solid #0ea5e9;
        border-radius: 12px;
    }
</style>
</head>
<body>
    <div class="page">
        <a class="back-link" href="/api/dashboard">Back to Dashboard</a>
        <div class="card">
            <h1 style="margin-top:0;">Add New Employee</h1>
            <% if (typeof msg !== 'undefined' && msg) { %>
                <div class="notice"><%= msg %></div>
            <% } %>

            <form class="form-grid" action="/api/addEmployee" method="POST">
                <div>
                    <label for="name">Name:</label>
                    <input type="text" id="name" name="name" placeholder="Lastname, Firstname"
required>

                </div>

                <div>

```

```
        <label for="email">Email:</label>
        <input type="email" id="email" name="email" required>
    </div>

    <div>
        <label for="designation">Designation:</label>
        <input type="text" id="designation" name="designation" required>
    </div>

    <div>
        <label for="contact">Contact:</label>
        <input type="text" id="contact" name="contact" required>
    </div>

    <div>
        <label for="department">Department:</label>
        <input type="text" id="department" name="department">
    </div>

    <div>
        <label for="joiningDate">Joining Date:</label>
        <input type="date" id="joiningDate" name="joiningDate">
    </div>

    <div>
        <label for="location">Location:</label>
        <input type="text" id="location" name="location">
    </div>

    <div class="actions">
        <button type="submit">Add Employee</button>
        <a class="button-link" href="/api/dashboard">Cancel</a>
    </div>
</form>

<% if (typeof employee !== 'undefined' && employee) { %>
    <h2>Created Employee</h2>
    <pre><%= JSON.stringify(employee, null, 2) %></pre>
    <% } %>
</div>
</div>
</body>
</html>
```

views\dashboard.ejs

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Dashboard</title>
  <style>
    body {
      font-family: Arial, sans-serif;
      margin: 0;
      background: #f4f7fb;
      color: #0f172a;
    }
    .page {
      max-width: 1200px;
      margin: 0 auto;
      padding: 24px;
    }
    .topbar {
      display: flex;
      justify-content: space-between;
      align-items: center;
      gap: 16px;
      margin-bottom: 24px;
    }
    .logout {
      text-decoration: none;
      color: #ffffff;
      background: #dc2626;
      padding: 10px 14px;
      border-radius: 8px;
      font-weight: 700;
    }
    .card {
      background: #ffffff;
      border-radius: 16px;
      padding: 20px;
      box-shadow: 0 10px 30px rgba(15, 23, 42, 0.08);
      margin-bottom: 24px;
    }
    .actions {
      display: flex;
      gap: 12px;
      margin-top: 12px;
      flex-wrap: wrap;
    }
    .actions a {
      padding: 10px 14px;
      border-radius: 8px;
```

```
        text-decoration: none;
        font-weight: 700;
        color: #00111f;
    }
    .table-wrap {
        overflow-x: auto;
    }
    table {
        width: 100%;
        border-collapse: collapse;
        min-width: 1100px;
        background: #ffffff;
    }
    th, td {
        padding: 12px 14px;
        border-bottom: 1px solid #e2e8f0;
        text-align: left;
        white-space: nowrap;
    }
    th {
        background: #0f172a;
        color: #ffffff;
    }
    th a {
        color: inherit;
        text-decoration: none;
        display: inline-flex;
        align-items: center;
        gap: 6px;
    }
    .filters {
        display: grid;
        grid-template-columns: repeat(auto-fit, minmax(180px, 1fr));
        gap: 12px;
        margin-top: 16px;
    }
    .filters input {
        width: 100%;
        box-sizing: border-box;
        padding: 10px 12px;
        border: 1px solid #cbd5e1;
        border-radius: 8px;
    }
    .filters button {
        padding: 10px 14px;
        border: 0;
        border-radius: 8px;
        background: #0ea5e9;
        color: #ffffff;
        font-weight: 700;
        font-size: 15px;
        cursor: pointer;
    }
```



```

    }
    .empty {
      padding: 18px;
      background: #f8fafc;
      border: 1px dashed #cbd5e1;
      border-radius: 12px;
    }
  </style>
</head>
<body>
  <div class="page">
    <div class="topbar">
      <h2 style="margin:0;">Welcome to the Employee Management Dashboard<%= typeof emailID
!= 'undefined' ? ', ' + emailID : '' %></h2>
      <a class="logout" href="/">Logout</a>
    </div>

    <% if (typeof msg !== 'undefined' && msg) { %>
      <section class="card" style="border-left: 4px solid #0ea5e9; margin-bottom: 18px;">
        <strong><%= msg %></strong>
      </section>
    <% } %>

    <section class="card">
      <h3 style="margin-top:0;">Employee Table</h3>

      <% const safeCurrentSort = typeof currentSort !== 'undefined' ? currentSort : 'id';
%>

      <% const safeCurrentOrder = typeof currentOrder !== 'undefined' ? currentOrder :
'asc'; %>

      <% const safeFilters = typeof filters !== 'undefined' ? filters : { search: '',
designation: '', department: '', location: '' }; %>
      <% const searchValue = safeFilters.search || ''; %>
      <% const designationValue = safeFilters.designation || ''; %>
      <% const departmentValue = safeFilters.department || ''; %>
      <% const locationValue = safeFilters.location || ''; %>
      <% const filterQuery = `search=${encodeURIComponent(searchValue ||
'' )}&designation=${encodeURIComponent(designationValue ||
'' )}&department=${encodeURIComponent(departmentValue ||
'' )}&location=${encodeURIComponent(locationValue || '' )}`; %>

      <form class="filters" method="GET" action="/api/dashboard">
        <input type="hidden" name="sort" value="<%= safeCurrentSort %>">
        <input type="hidden" name="order" value="<%= safeCurrentOrder %>">
        <input type="text" name="search" value="<%= searchValue %>" placeholder="Search
by ID or name">
        <input type="text" name="designation" value="<%= designationValue %>"
placeholder="Filter by designation">
        <input type="text" name="department" value="<%= departmentValue %>"
placeholder="Filter by department">
        <input type="text" name="location" value="<%= locationValue %>"
placeholder="Filter by location">

```

```

        <button type="submit">Apply Filters</button>
        <a href="/api/addEmployee" style="display:inline-flex; align-items:center;
justify-content:center; padding:10px 14px; border:0; border-radius:8px; background:#38f83e;
color:#ffffff; font-weight:700; text-decoration:none; cursor:pointer;">Add Employee</a>

    </form>

    <% if (typeof employees !== 'undefined' && employees.length) { %>
    <div class="table-wrap" style="margin-top:16px;">
        <table>
            <thead>
                <tr>
                    <% const nextIdOrder = safeCurrentSort === 'id' && safeCurrentOrder
=== 'asc' ? 'desc' : 'asc'; %>
                    <% const nextNameOrder = safeCurrentSort === 'name' &&
safeCurrentOrder === 'asc' ? 'desc' : 'asc'; %>
                    <th><a href="/api/dashboard?<%= filterQuery %>&sort=id&order=<%=
nextIdOrder %>">ID</a></th>
                    <th><a href="/api/dashboard?<%= filterQuery %>&sort=name&order=<%=
nextNameOrder %>">Employees</a></th>
                    <th>Designation</th>
                    <th>Email</th>
                    <th>Contact</th>
                    <th>Department</th>
                    <th>Joining Date</th>
                    <th>Location</th>
                    <th>Actions</th>
                </tr>
            </thead>
            <tbody>
                <% employees.forEach(function(employee) { %>
                <tr>
                    <td><%= employee.id %></td>
                    <td><a href="/api/viewEmployee/<%= employee.id %>" style="text-
decoration: none; color: #0f172a; font-weight: bold;"><%= employee.name %></a></td>
                    <td><%= employee.designation %></td>
                    <td><%= employee.email %></td>
                    <td><%= employee.contact %></td>
                    <td><%= employee.department %></td>
                    <td><%= employee.joiningDate %></td>
                    <td><%= employee.location %></td>
                    <td>
                        <a href="/api/updateEmployee/<%= employee.id %>"
style="background:#38bdf8; padding: 6px 10px; border-radius: 4px; text-decoration: none; color:
#00111f; font-size: 12px;">Edit</a>
                        <a href="/api/deleteEmployee/<%= employee.id %>"
style="background:#f87171; padding: 6px 10px; border-radius: 4px; text-decoration: none; color:
#00111f; font-size: 12px; margin-left: 4px;">Delete</a>
                    </td>
                </tr>
                <% }) %>
            </tbody>

```

```
        </table>
      </div>
    <% } else { %>
      <div class="empty" style="margin-top:16px;">No employee data is available yet.
    </div>
    <% } %>
  </section>
</div>
</body>
```

views\deleteEmployee.ejs

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Delete Employee</title>
  <style>
    body {
      font-family: Arial, sans-serif;
      margin: 20px;
      background: #f4f7fb;
    }
    .container {
      max-width: 600px;
      background: #ffffff;
      border-radius: 8px;
      padding: 24px;
      box-shadow: 0 2px 8px rgba(0,0,0,0.1);
    }
    h1 {
      color: #dc2626;
    }
    .employee-details {
      background: #fef2f2;
      border: 1px solid #fecaca;
      border-radius: 8px;
      padding: 16px;
      margin: 20px 0;
    }
    .detail-row {
      display: flex;
      justify-content: space-between;
      padding: 8px 0;
      border-bottom: 1px solid #fed7d7;
    }
    .detail-row:last-child {
      border-bottom: none;
    }
    .label {
      font-weight: bold;
      color: #7f1d1d;
    }
    .value {
      color: #991b1b;
    }
    .actions {
      display: flex;
      gap: 12px;
      margin-top: 24px;
    }
```

```

}
button {
    padding: 10px 16px;
    border-radius: 6px;
    border: none;
    font-weight: 600;
    cursor: pointer;
    font-size: 14px;
}
.delete-btn {
    background: #dc2626;
    color: #ffffff;
}
.cancel-btn {
    background: #e5e7eb;
    color: #1f2937;
}
.warning {
    background: #fef3c7;
    border: 1px solid #fcd34d;
    padding: 12px;
    border-radius: 6px;
    margin-bottom: 16px;
    color: #92400e;
}
</style>
</head>
<body>
    <div class="container">
        <h1>Delete Employee</h1>
        <% if (typeof msg !== 'undefined' && msg) { %>
            <p style="color: #dc2626;"><strong><%= msg %></strong></p>
        <% } %>

        <% if (typeof employee !== 'undefined' && employee && employee.id) { %>
            <div class="warning">
                â i, This action cannot be undone. Are you sure you want to delete this
employee?
            </div>

            <div class="employee-details">
                <div class="detail-row">
                    <span class="label">ID:</span>
                    <span class="value"><%= employee.id %></span>
                </div>
                <div class="detail-row">
                    <span class="label">Name:</span>
                    <span class="value"><%= employee.name %></span>
                </div>
                <div class="detail-row">
                    <span class="label">Email:</span>
                    <span class="value"><%= employee.email %></span>

```

```

    </div>
    <div class="detail-row">
        <span class="label">Designation:</span>
        <span class="value"><%= employee.designation %></span>
    </div>
    <div class="detail-row">
        <span class="label">Contact:</span>
        <span class="value"><%= employee.contact %></span>
    </div>
    <div class="detail-row">
        <span class="label">Department:</span>
        <span class="value"><%= employee.department %></span>
    </div>
    <div class="detail-row">
        <span class="label">Location:</span>
        <span class="value"><%= employee.location %></span>
    </div>
</div>

<form action="/api/deleteEmployee/<%= employee.id %>" method="POST" style="display:
inline;">
    <div class="actions">
        <button type="submit" class="delete-btn">Confirm Delete</button>
        <a href="/api/dashboard" style="text-decoration: none;">
            <button type="button" class="cancel-btn">Cancel</button>
        </a>
    </div>
</form>
<% } else { %>
    <p style="color: #dc2626;">Employee not found. <a href="/api/dashboard">Go back to
dashboard</a></p>
    <% } %>
</div>
</body>
</html>

```

views/login.ejs

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Login</title>
  <style>
    :root {
      --bg: #0f172a;
      --panel: rgba(15, 23, 42, 0.88);
      --panel-border: rgba(148, 163, 184, 0.22);
      --text: #e2e8f0;
      --muted: #94a3b8;
      --accent: #38bdf8;
      --accent-strong: #0ea5e9;
    }

    * {
      box-sizing: border-box;
    }

    body {
      margin: 0;
      min-height: 100vh;
      font-family: "Segoe UI", Tahoma, Geneva, Verdana, sans-serif;
      color: var(--text);
      background:
        radial-gradient(circle at top left, rgba(56, 189, 248, 0.28),
transparent 30%),
        radial-gradient(circle at top right, rgba(34, 197, 94, 0.18),
transparent 28%),
        linear-gradient(135deg, #020617 0%, #0f172a 45%, #111827 100%);
      display: grid;
      place-items: center;
      padding: 24px;
    }

    .card {
      width: min(100%, 960px);
      display: grid;
      grid-template-columns: 1.1fr 0.9fr;
      border: 1px solid var(--panel-border);
      border-radius: 24px;
      overflow: hidden;
      background: var(--panel);
      box-shadow: 0 24px 80px rgba(2, 6, 23, 0.45);
      backdrop-filter: blur(14px);
    }
  </style>
</head>
</html>
```

```
.hero {
  padding: 48px;
  background:
    linear-gradient(160deg, rgba(14, 165, 233, 0.16), rgba(15, 23,
42, 0.08)),
    linear-gradient(180deg, rgba(255, 255, 255, 0.04), rgba(255,
255, 255, 0));
}

.eyebrow {
  display: inline-flex;
  align-items: center;
  gap: 10px;
  padding: 8px 14px;
  border-radius: 999px;
  background: rgba(56, 189, 248, 0.12);
  color: #7dd3fc;
  font-size: 0.85rem;
  letter-spacing: 0.04em;
  text-transform: uppercase;
}

h1 {
  margin: 18px 0 12px;
  font-size: clamp(2.2rem, 5vw, 4rem);
  line-height: 1;
}

.lead {
  margin: 0;
  max-width: 34rem;
  color: var(--muted);
  font-size: 1rem;
  line-height: 1.7;
}

.quick-actions {
  margin-top: 28px;
  display: grid;
  gap: 12px;
}

.action-row {
  display: flex;
  flex-wrap: wrap;
  gap: 12px;
}

.button {
  appearance: none;
  border: 0;
  border-radius: 14px;
```



```
padding: 10px 14px;
font-weight: 700;
font-size: 0.95rem;
text-decoration: none;
cursor: pointer;
transition: transform 0.18s ease, box-shadow 0.18s ease, background
0.18s ease;

display: inline-flex;
align-items: center;
justify-content: center;
min-width: 120px;
}

.button:hover {
  transform: translateY(-1px);
}

.button-primary {
  background: linear-gradient(135deg, var(--accent), var(--accent-
strong));
  color: #00111f;
  box-shadow: 0 12px 24px rgba(14, 165, 233, 0.28);
}

.button-secondary {
  background: rgba(148, 163, 184, 0.12);
  color: var(--text);
  border: 1px solid rgba(148, 163, 184, 0.2);
}

.button-success {
  background: rgba(34, 197, 94, 0.16);
  color: #bbf7d0;
  border: 1px solid rgba(34, 197, 94, 0.22);
}

.form-panel {
  padding: 48px;
  border-left: 1px solid var(--panel-border);
  background: rgba(15, 23, 42, 0.58);
}

.form-panel h2 {
  margin: 0 0 8px;
  font-size: 1.7rem;
}

.form-panel p {
  margin: 0 0 24px;
  color: var(--muted);
  line-height: 1.6;
}
```

```
.message {
    margin: 0 0 18px;
    padding: 12px 14px;
    border-radius: 12px;
    background: rgba(59, 130, 246, 0.12);
    color: #dbeafe;
    border: 1px solid rgba(59, 130, 246, 0.18);
}

.field {
    margin-bottom: 16px;
}

label {
    display: block;
    margin-bottom: 8px;
    color: #cbd5e1;
    font-size: 0.95rem;
}

input {
    width: 100%;
    padding: 14px 16px;
    border-radius: 14px;
    border: 1px solid rgba(148, 163, 184, 0.22);
    background: rgba(15, 23, 42, 0.9);
    color: var(--text);
    outline: none;
}

input:focus {
    border-color: rgba(56, 189, 248, 0.8);
    box-shadow: 0 0 0 4px rgba(56, 189, 248, 0.12);
}

.form-actions {
    display: flex;
    gap: 12px;
    flex-wrap: wrap;
    margin-top: 22px;
}

.links {
    margin-top: 20px;
    display: flex;
    flex-wrap: wrap;
    gap: 10px 16px;
    font-size: 0.95rem;
}

.links a {
```

```

        color: #7dd3fc;
        text-decoration: none;
    }

    .links a:hover {
        text-decoration: underline;
    }

    .route-list {
        margin-top: 24px;
        padding: 16px;
        border-radius: 16px;
        border: 1px solid rgba(148, 163, 184, 0.18);
        background: rgba(2, 6, 23, 0.35);
    }

    .route-list h3 {
        margin: 0 0 12px;
        font-size: 1rem;
        color: #cbd5e1;
    }

    .route-list ul {
        margin: 0;
        padding-left: 18px;
        color: var(--muted);
        line-height: 1.8;
    }

    @media (max-width: 840px) {
        .card {
            grid-template-columns: 1fr;
        }

        .form-panel {
            border-left: 0;
            border-top: 1px solid var(--panel-border);
        }
    }

    @media (max-width: 640px) {
        .hero,
        .form-panel {
            padding: 28px;
        }

        .button {
            width: 100%;
        }
    }
}

```

</style>

</head>

```

<body>
  <main class="card">
    <section class="hero">
      <span class="eyebrow">Employee access portal</span>
      <h1>Welcome back</h1>
      <p class="lead">
        Sign in to manage employee data and view the dashboard.
      </p>

    </section>

    <section class="form-panel">
      <h2>Login</h2>
      <p>Use your email ID and password to access the dashboard.</p>

      <% if (typeof msg !== 'undefined' && msg) { %>
        <div class="message"><%= msg %></div>
      <% } %>

      <form action="/signIn" method="post">
        <div class="field">
          <label for="emailID">Email ID</label>
          <input type="email" id="emailID" name="emailID"
placeholder="name@example.com" required>
        </div>

        <div class="field">
          <label for="password">Password</label>
          <input type="password" id="password" name="password"
placeholder="Enter your password" required>
        </div>

        <div class="form-actions">
          <button class="button button-primary" type="submit">Sign
In</button>

          <a class="button button-secondary" href="/signUp">Sign
Up</a>
        </div>
      </form>

    </section>
  </main>
</body>
</html>

```

views/signup.ejs

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Sign Up</title>
  <style>
    :root {
      --bg: #07111f;
      --panel: rgba(8, 15, 28, 0.88);
      --panel-border: rgba(148, 163, 184, 0.22);
      --text: #e5eefb;
      --muted: #9aa9bd;
      --accent: #f59e0b;
      --accent-strong: #fb7185;
      --accent-soft: rgba(245, 158, 11, 0.14);
    }

    * {
      box-sizing: border-box;
    }

    body {
      margin: 0;
      min-height: 100vh;
      display: grid;
      place-items: center;
      padding: 24px;
      color: var(--text);
      font-family: "Segoe UI", Tahoma, Geneva, Verdana, sans-serif;
      background:
        radial-gradient(circle at top left, rgba(245, 158, 11, 0.24),
transparent 30%),
        radial-gradient(circle at top right, rgba(251, 113, 133, 0.16),
transparent 24%),
        linear-gradient(135deg, #020617 0%, #07111f 45%, #111827 100%);
    }

    .card {
      width: min(100%, 980px);
      display: grid;
      grid-template-columns: 1fr 1fr;
      overflow: hidden;
      border-radius: 24px;
      border: 1px solid var(--panel-border);
      background: var(--panel);
      box-shadow: 0 26px 80px rgba(2, 6, 23, 0.48);
      backdrop-filter: blur(16px);
    }
  </style>
</head>
</html>
```

```
.hero {
  padding: 48px;
  background:
    linear-gradient(155deg, rgba(245, 158, 11, 0.16), rgba(15, 23,
42, 0.04)),
    linear-gradient(180deg, rgba(255, 255, 255, 0.05), rgba(255,
255, 255, 0));
}

.eyebrow {
  display: inline-flex;
  align-items: center;
  gap: 10px;
  padding: 8px 14px;
  border-radius: 999px;
  background: rgba(245, 158, 11, 0.13);
  color: #fde68a;
  font-size: 0.84rem;
  letter-spacing: 0.04em;
  text-transform: uppercase;
}

h1 {
  margin: 18px 0 12px;
  font-size: clamp(2.2rem, 5vw, 4rem);
  line-height: 1;
}

.lead {
  margin: 0;
  max-width: 36rem;
  color: var(--muted);
  line-height: 1.7;
}

.route-grid {
  margin-top: 28px;
  display: grid;
  gap: 12px;
}

.row {
  display: flex;
  flex-wrap: wrap;
  gap: 12px;
}

.button {
  display: inline-flex;
  align-items: center;
  justify-content: center;
```

```

        min-width: 120px;
        padding: 10px 14px;
        border-radius: 14px;
        border: 0;
        text-decoration: none;
        font-weight: 700;
        font-size: 0.95rem;
        cursor: pointer;
        transition: transform 0.18s ease, box-shadow 0.18s ease, background
0.18s ease;
    }

    .button:hover {
        transform: translateY(-1px);
    }

    .button-primary {
        background: linear-gradient(135deg, var(--accent), var(--accent-
strong));
        color: #1a0f00;
        box-shadow: 0 12px 24px rgba(245, 158, 11, 0.26);
    }

    .button-secondary {
        background: rgba(148, 163, 184, 0.12);
        color: var(--text);
        border: 1px solid rgba(148, 163, 184, 0.18);
    }

    .button-dark {
        background: rgba(15, 23, 42, 0.84);
        color: #dbeafe;
        border: 1px solid rgba(148, 163, 184, 0.16);
    }

    .route-list {
        margin-top: 24px;
        padding: 16px;
        border-radius: 16px;
        border: 1px solid rgba(148, 163, 184, 0.16);
        background: rgba(2, 6, 23, 0.36);
    }

    .route-list h3 {
        margin: 0 0 12px;
        font-size: 1rem;
        color: #d6e0ef;
    }

    .route-list ul {
        margin: 0;
        padding-left: 18px;

```

```
        color: var(--muted);
        line-height: 1.8;
    }

    .form-panel {
        padding: 48px;
        border-left: 1px solid var(--panel-border);
        background: rgba(15, 23, 42, 0.56);
    }

    .form-panel h2 {
        margin: 0 0 8px;
        font-size: 1.7rem;
    }

    .form-panel p {
        margin: 0 0 22px;
        color: var(--muted);
        line-height: 1.6;
    }

    .message {
        margin: 0 0 18px;
        padding: 12px 14px;
        border-radius: 12px;
        background: rgba(245, 158, 11, 0.12);
        color: #fde68a;
        border: 1px solid rgba(245, 158, 11, 0.18);
    }

    .field {
        margin-bottom: 16px;
    }

    label {
        display: block;
        margin-bottom: 8px;
        color: #dbeafe;
        font-size: 0.95rem;
    }

    input {
        width: 100%;
        padding: 14px 16px;
        border-radius: 14px;
        border: 1px solid rgba(148, 163, 184, 0.22);
        background: rgba(15, 23, 42, 0.9);
        color: var(--text);
        outline: none;
    }

    input:focus {
```



```
        border-color: rgba(245, 158, 11, 0.8);
        box-shadow: 0 0 0 4px rgba(245, 158, 11, 0.12);
    }

    .form-actions {
        display: flex;
        gap: 8px;
        margin-top: 18px;
        align-items: center;
        flex-wrap: nowrap;
    }

    .links {
        margin-top: 20px;
        display: flex;
        flex-wrap: wrap;
        gap: 10px 16px;
        font-size: 0.95rem;
    }

    .links a {
        color: #fde68a;
        text-decoration: none;
    }

    .links a:hover {
        text-decoration: underline;
    }

    @media (max-width: 840px) {
        .card {
            grid-template-columns: 1fr;
        }

        .form-panel {
            border-left: 0;
            border-top: 1px solid var(--panel-border);
        }
    }

    @media (max-width: 640px) {
        .hero,
        .form-panel {
            padding: 28px;
        }

        .form-actions { flex-direction: column; gap: 12px; }

        .button {
            width: 100%;
        }
    }
}
```

```

</style>
</head>
<body>
  <main class="card">
    <section class="hero">
      <span class="eyebrow">Create your account</span>
      <h1>Sign up</h1>
      <p class="lead">
        Create a new login, then use the sign-in page to reach the
        dashboard.
      </p>
    </section>

    <section class="form-panel">
      <h2>Create account</h2>
      <p>Enter the details that will be saved for sign-in.</p>

      <% if (typeof msg !== 'undefined' && msg) { %>
        <div class="message"><%= msg %></div>
      <% } %>

      <form action="/signUp" method="post">
        <div class="field">
          <label for="emailID">Email ID</label>
          <input type="email" id="emailID" name="emailID"
placeholder="name@example.com" required>
        </div>

        <div class="field">
          <label for="password">Password</label>
          <input type="password" id="password" name="password"
placeholder="Create a password" required>
        </div>

        <div class="field">
          <label for="confirmPassword">Confirm Password</label>
          <input type="password" id="confirmPassword"
name="confirmPassword" placeholder="Repeat your password" required>
        </div>

        <div class="field">
          <label for="adminCode">Admin Code</label>
          <input type="text" id="adminCode" name="adminCode"
placeholder="Enter admin code" required>
        </div>

        <div class="form-actions">
          <button class="button button-primary" type="submit">Sign
Up</button>
          <a class="button button-secondary" href="/">I already
have an account</a>

```

```
                </div>
            </form>
        </section>
    </main>
</body>
</html>
```

views\updateEmployee.ejs

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Update Employee</title>
  <style>
    body {
      font-family: Arial, sans-serif;
      margin: 0;
      background: #f4f7fb;
      color: #0f172a;
    }
    .page {
      max-width: 720px;
      margin: 0 auto;
      padding: 24px;
    }
    .card {
      background: #ffffff;
      border-radius: 16px;
      padding: 24px;
      box-shadow: 0 10px 30px rgba(15, 23, 42, 0.08);
    }
    .back-link {
      display: inline-block;
      margin-bottom: 16px;
      color: #0ea5e9;
      text-decoration: none;
      font-weight: 700;
    }
    .form-grid {
      display: grid;
      gap: 14px;
    }
    label {
      display: block;
      margin-bottom: 6px;
      font-weight: 700;
    }
    input {
      width: 100%;
      box-sizing: border-box;
      padding: 10px 12px;
      border: 1px solid #cbd5e1;
      border-radius: 8px;
      font-size: 15px;
    }
    .actions {
```

```

        display: flex;
        gap: 12px;
        flex-wrap: wrap;
        margin-top: 8px;
    }
    button,
    .button-link {
        display: inline-flex;
        align-items: center;
        justify-content: center;
        padding: 10px 14px;
        border: 0;
        border-radius: 8px;
        text-decoration: none;
        font-weight: 700;
        cursor: pointer;
        font-size: 15px;
    }
    button[type="submit"] {
        background: #38bdf8;
        color: #00111f;
    }
    .button-link {
        background: #e2e8f0;
        color: #0f172a;
    }
    .notice {
        margin-bottom: 16px;
        padding: 14px 16px;
        background: #f8fafc;
        border-left: 4px solid #0ea5e9;
        border-radius: 12px;
    }
</style>
</head>
<body>
    <div class="page">
        <a class="back-link" href="/api/dashboard">Back to Dashboard</a>
        <div class="card">
            <h1 style="margin-top:0;">Update Employee Details</h1>
            <% if (typeof msg !== 'undefined' && msg) { %>
                <div class="notice"><strong><%= msg %></strong></div>
            <% } %>

            <% if (typeof employee !== 'undefined' && employee && employee.id) { %>
                <form class="form-grid" action="/api/updateEmployee/<%= employee.id %>"
method="POST">

                    <div>
                        <label for="name">Name:</label>
                        <input type="text" id="name" name="name" value="<%= employee.name %>"
placeholder="Lastname, Firstname" required>
                    </div>

```

```

        <div>
            <label for="email">Email:</label>
            <input type="email" id="email" name="email" value="<%= employee.email
%>" required>
        </div>

        <div>
            <label for="designation">Designation:</label>
            <input type="text" id="designation" name="designation" value="<%=
employee.designation %>" required>
        </div>

        <div>
            <label for="contact">Contact:</label>
            <input type="text" id="contact" name="contact" value="<%=
employee.contact %>" required>
        </div>

        <div>
            <label for="department">Department:</label>
            <input type="text" id="department" name="department" value="<%=
employee.department %>" required>
        </div>

        <div>
            <label for="joiningDate">Joining Date:</label>
            <input type="date" id="joiningDate" name="joiningDate" value="<%=
employee.joiningDate %>" required>
        </div>

        <div>
            <label for="location">Location:</label>
            <input type="text" id="location" name="location" value="<%=
employee.location %>" required>
        </div>

        <div class="actions">
            <button type="submit">Update Employee</button>
            <a class="button-link" href="/api/dashboard">Cancel</a>
        </div>
    </form>
    <% } else { %>
        <p>Employee not found. <a href="/api/dashboard">Go back to dashboard</a></p>
    <% } %>
</div>
</div>
</body>
</html>

```

views/viewEmployee.ejs

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>View Employee</title>
  <style>
    body {
      font-family: Arial, sans-serif;
      margin: 20px;
      background: #f4f7fb;
    }
    .container {
      max-width: 600px;
      background: #ffffff;
      border-radius: 8px;
      padding: 24px;
      box-shadow: 0 2px 8px rgba(0,0,0,0.1);
    }
    h1 {
      color: #0f172a;
    }
    .detail-row {
      display: flex;
      justify-content: space-between;
      padding: 12px 0;
      border-bottom: 1px solid #e2e8f0;
    }
    .label {
      font-weight: bold;
      color: #0f172a;
    }
    .value {
      color: #475569;
    }
    .actions {
      display: flex;
      gap: 12px;
      margin-top: 24px;
    }
    a {
      padding: 10px 16px;
      border-radius: 6px;
      text-decoration: none;
      font-weight: 600;
      font-size: 14px;
      display: inline-flex;
      align-items: center;
    }
  </style>
</head>
<body>
  <div class="container">
    <h1>Employee</h1>
    <div class="detail-row">
      <div class="label">Name</div>
      <div class="value">John Doe</div>
    </div>
    <div class="detail-row">
      <div class="label">Email</div>
      <div class="value">john.doe@example.com</div>
    </div>
    <div class="detail-row">
      <div class="label">Phone</div>
      <div class="value">+1 (555) 123-4567</div>
    </div>
    <div class="actions">
      <a href="#edit">Edit</a>
      <a href="#delete">Delete</a>
    </div>
  </div>
</body>
</html>
```

```

        .edit {
            background: #38bdf8;
            color: #00111f;
        }
        .delete {
            background: #f87171;
            color: #00111f;
        }
        .back {
            background: #e5e7eb;
            color: #1f2937;
        }
    </style>
</head>
<body>
    <div class="container">
        <h1>Employee Details</h1>
        <% if (typeof msg !== 'undefined' && msg) { %>
            <p style="color: #dc2626;"><strong><%= msg %></strong></p>
        <% } %>

        <% if (typeof employee !== 'undefined' && employee && employee.id) { %>
            <% const reversedName = employee.name.split(', ').reverse().join(' '); %>
            <div class="detail-row">
                <span class="label">ID:</span>
                <span class="value"><%= employee.id %></span>
            </div>
            <div class="detail-row">
                <span class="label">Name:</span>
                <span class="value"><%= reversedName %></span>
            </div>
            <div class="detail-row">
                <span class="label">Email:</span>
                <span class="value"><%= employee.email %></span>
            </div>
            <div class="detail-row">
                <span class="label">Designation:</span>
                <span class="value"><%= employee.designation %></span>
            </div>
            <div class="detail-row">
                <span class="label">Contact:</span>
                <span class="value"><%= employee.contact %></span>
            </div>
            <div class="detail-row">
                <span class="label">Department:</span>
                <span class="value"><%= employee.department %></span>
            </div>
            <div class="detail-row">
                <span class="label">Joining Date:</span>
                <span class="value"><%= employee.joiningDate %></span>
            </div>
            <div class="detail-row">

```



```
<span class="label">Location:</span>
<span class="value"><%= employee.location %></span>
</div>

<div class="actions">
  <a href="/api/updateEmployee/<%= employee.id %>" class="edit">Edit</a>
  <a href="/api/deleteEmployee/<%= employee.id %>" class="delete">Delete</a>
  <a href="/api/dashboard" class="back">Back to Dashboard</a>
</div>
<% } else { %>
  <p>Employee not found. <a href="/api/dashboard">Go back to dashboard</a></p>
<% } %>
</div>
</body>
</html>
```