## **Instructions for MISES Analysis of Case LE55**

## 1 Prerequisites

- 1. T-Blade3 executables (tblade3, techop) can be installed following the instructions in the documentation available at gtsl.ase.uc.edu/t-blade3/T-Blade3\_v1.2\_ReadMe.pdf.
- 2. MISES is not open-source. Licensing information is available at https://tlo.mit.edu/technologies/mises-software-design-and-analysis-turbomachinery-blading. The executables iset, ises, iprint, iplot are required. The steps outlined were carried out in MISES v2.57.

## 2 Geometry Generation

- 1. Run the following commands based on the location of the T-Blade3 executables:
  - \$ /path/to/executables/tblade3 3dbgbinput.3.dat
  - \$ /path/to/executables/techop blade.11.3.Case7-28-5 15
- 2. Rename the file blade.11.3.Case7-28-5 as blade.LE55.
- 3. In the file blade.LE55 replace the first line 11.3. Case7-28-5 with LE55.

## 3 MISES Analysis

This is a summary of the steps required to run MISES for this particular case. Further information about all the executables and files can be found in the documentation at web.mit.edu/drela/Public/web/mises/mises.pdf.

- 1. Place the files blade.LE55 and ises.LE55 in a separate directory.
- 2. Run iset first to generate the grid and an initial idat.LE55 file. Run the following command:
  - \$ /path/to/executables/iset LE55

This will open a XWindow instance showing the cascade and open a menu in iset. Next, in the iset menu:

- (a) Select option 2 Generate spacings and initialize grid. Hit enter without making any changes to the spacings.
- (b) Select option 3 Elliptic grid smoother.
- (c) Select option 4 Write idat.LE55.
- (d) Select option 5 *Plot grid*. This plots the generated grid in the previously opened XWindow instance and opens a sub-menu in iset. Hit enter to quit the sub-menu without making any changes.
- (e) Select option 8 Write grid parameters to gridpar.LE55.
- (f) Select option *0* to quit iset.
- 3. This has created two files: gridpar.LE55 and idat.LE55.
- 4. Next, launch ises by running the following command:
  - \$ /path/to/executables/ises LE55

The boundary conditions for this case are:

- (a) Drive inlet slope to the inlet slope value specified in ises.LE55 (S1), which can be varied to control the incidence on the blade.
- (b) Use TE Kutta condition for the current blade.
- (c) Use LE Kutta condition for the current blade.
- (d) Drive outlet Mach number to the outlet Mach number specified in ises.LE55 (M2).

ises requires the number of iterations as input. The recommended initial iteration count is 50. For higher positive and negative incidences, more iterations might be required.

- Once ises has converged, run iprint to print a summary of the forces on the blade including the loss coefficients ω̄ and ζ. This summary can be saved in a file for future reference on Linux/Unix systems by running the following command:
  \$ /path/to/executables/iprint LE55 > output\_filename
- 6. Finally, run iplot to generate blade surface and contour plots of quantities like Mach number,  $C_p$  or  $C_f$ . Run:  $\frac{path}{to}$

This opens a menu in iplot. To generate a blade surface Mach number plot:

- (a) Select option 1 Blade surface plots. This opens a sub-menu.
- (b) In the sub-menu, select option 1 Mach vs x. This will plot the Mach number distribution in a XWindow instance.
- (c) To save the current plot in a postscript file plot.ps, select option 14 Hardcopy current plot.
- (d) Select the appropriate option to plot another quantity or select option  $\theta$  to quit to the top-level iplot menu.

To generate a contour Mach number plot:

- (a) Select option 3 Contour/grid plots in the top-level iplot menu. This opens a sub-menu.
- (b) In the sub-menu, select option 3 Flow contours (MPRQCLT). This opens another sub-menu.
- (c) In the contour/grid plot option sub-menu, select option M to plot the cascade Mach number contour in a XWindow instance.
- (d) To go back to the contour/grid plot option list, select -1 or select 0 to go back to the top-level iplot menu.

To quit iplot, select 0 in the top-level iplot menu.