2-Channel Analog Output Module 0-10 V/±10V






Fig. Series 750 / Technical data see page 30 / Delivery without Mini WSB marker Series 750 / 753 marking see pages 20 ... 21 / 22 ... 23

The analog output module creates a standardized signal of 0-10 V or $\pm\,10$ V.

The output signal is electrically isolated and will be transmitted with a resolution of 12 bits.

Outputs are short circuit protected.

The internal system supply is used for the power supply of the module.

The output channels have one common ground potential.

Description		Item no.	Pack. unit
2AO 0-10V DC		750-550	10 1)
2AO ± 10V DC		750-556	10 1)
2AO 0-10V DC/S5 2)		750-550/000-200	1
2AO ±10V DC/S5 2)		750-556/000-200	1
2AO 0-10V DC (without connector)		753-550	10 1)
2AO ±10V DC (without connector)		753-556	10 ¹⁾
1) Also available inc	dividually		
2) Data format for S	5 control with FB 251		
Accessories		Item no.	Pack. unit
FEITERIN SELV	Connectors Series 753	753-110	25
	Coding elements	753-150	100
	Miniature WSB Quick marking system		
	plain	248-501	5
	with marking	see pages 214 215	
Approvals			
Approvals Series 750 and 753	3		
• •	3		
Series 750 and 753		£	
Series 750 and 753 ••••••••••••••••••••••••••••••••••••		E	
Series 750 and 753 ® UL 508 Conformity mark	ting CG	e pages 24 27	
Series 750 and 753 ® UL 508 Conformity mark Series 750	ting CG		

No. of outputs	2
Current consumption (internal)	65 mA
Voltage supply	via system voltage DC / DC
Signal voltage	0 V 10 V (750-550, 753-550)
ů ů	± 10 V (750-556, 753-556)
Load impedance	> 5 kΩ
Linearity	±10 mV
Resolution	12 bits
Conversion time	ca. 2 ms
Output filter settle time typ.	300 µs
Measuring error (25°C)	$< \pm 0.1$ % of the full scale value
Temperature coefficient	$< \pm 0.01 \%$ /K of the full scale value
Isolation	500 V system / supply
Bit width	2 x 16 bits data
	2 x 8 bits control / status (option)
Wire connection	CAGE CLAMP®
Cross sections	0.08 mm ² 2.5 mm ² / AWG 28 14
Stripped length series 750 / 753	8 9 mm / 0.33 in
	9 10 mm / 0.37 in
Width	12 mm
Weight	approx. 55 g
EMC C -Immunity to interference	acc. to EN 50082-2 (1996)
EMC C €-Emission of interference	acc. to EN 50081-1 (1993)
EMC marine applications -	
Immunity to interference	acc. to Germanischer Lloyd (1997)
EMC marine applications -	
Emission of interference	acc. to Germanischer Lloyd (1997)