

## Homework 6: Context Doesn't Always Matter

Due 9pm, Thursday, October 29, 2020

CSCI 161

Ben Dreyer

**Overview.** This week's homework concerns the equivalence of pushdown automata and context-free grammars. It also touches on parse trees (as generated by the CYK algorithm when checking whether a string is in a grammar) and context-sensitivity (using the CFL pumping lemma to prove a language is not a CFL). You are welcome to use JFLAP to generate your diagrams, but take screenshots of these diagrams and embed them in your pdf or other main submission rather than submitting jff files. For 5% extra credit, edit this tex file with your solutions and upload your source code and your compiled pdf, which should include all diagrams.

**Question 1.** The following CFG in Chomsky normal form generates strings of balanced parentheses:

$$V_1 \rightarrow V_2V_2 \mid V_4V_3 \mid V_4V_5 \mid \epsilon$$

$$V_2 \rightarrow V_2V_2 \mid V_4V_3 \mid V_4V_5$$

$$V_3 \rightarrow V_2V_5$$

$$V_4 \rightarrow ($$

$$V_5 \rightarrow )$$

1. Recall that CYK running on a grammar with  $r$  variables and an input string  $w$  of length  $n$  populates an  $n \times n \times r$  array such that  $P[\ell, s, i]$  is true if and only if variable  $R_i$  derives  $w_s \dots w_{s+\ell-1}$ , the input substring of length  $\ell$  starting at index  $s$ . For the grammar above and input  $w = (())(())$ , give a true false answer describing the contents of each of the following cells:

$$P[1, 4, 5] = \text{True}$$

$$P[1, 5, 3] = \text{False}$$


$$P[5, 2, 1] = \text{False}$$

$$P[9, 2, 3] = \text{False}$$

*Hint:* Note that you do *not* need to run the whole algorithm to infer the subproblem answers.

2. Draw the parse tree and corresponding leftmost derivation for  $((()))$ .

*Hint:* The unambiguous derivation is 11 steps.



**Solution**  $V1 \rightarrow V4V3 \rightarrow (V3 \rightarrow (V2V5 \rightarrow (V2V2V5 \rightarrow (V4V5V2V5 \rightarrow ((V5V2V5 \rightarrow ((()V2V5 \rightarrow ((()V4V5V5 \rightarrow ((()V5V5 \rightarrow ((()()V5 \rightarrow ((()())$

**Question 2.** This question explores the context-free language of valid unary addition equations. Specifically, it concerns the following language over the alphabet  $\Sigma = \{1, +, =\}$ :

$$L = \{a + b = c \mid a, b, c \in 1^*, |a| + |b| = |c|\}.$$

Note that  $|a|$  means the length of  $a$ , and since  $a$  is all 1s, this is just the numerical value of  $a$ . For example, the string  $111 + 11111 = 11111111$  is in  $L$ , whereas  $1 + 11 = 11$  is not. The value zero is represented by the empty string, since  $|\epsilon| = 0$ . So  $+ =$ ,  $11 + = 11$ , and  $+1 = 1$  are all valid strings in the language.

a) Give a CFG for  $L$ . Part b) will be easier if you have a small grammar.

$$\begin{aligned} S &\rightarrow 1S1 \mid + X \\ x &\rightarrow 1X1 \mid = \end{aligned}$$

b) Give a PDA for  $L$  with the structure of Figure 2.24 illustrating the general CFG→PDA conversion.



