pymad8 Documentation

Release 1.6.0

Royal Holloway

CONTENTS

1	Licence & Disclaimer	3			
2	Authorship	5			
3	Installation3.1 Requirements3.2 Installation	7 7 7			
4	Converting Models 4.1 Mad8 output required 4.2 Mad8Twiss2Gmad 4.3 Mad8Saveline2Gmad 4.3 Converting Models 4.4 Mad8 output required 4.5 Mad8Twiss2Gmad 4.6 Mad8Saveline2Gmad	9 9 9			
5	Data Loading	11			
6	Plotting	13			
7	Support 7.1 Feature Request	15 15			
8	Module Contents 8.1 Module contents 8.2 pymad8.Input module 8.3 pymad8.Output module 8.4 pymad8.Mad8 module 8.5 pymad8.Plot module 8.6 pymad8.Sim module 8.7 pymad8.Visualisation module	17 17 18 20 22 23 23			
9	Indices and tables	25			
Рy	ython Module Index	27			
Indev					

pymad8 is a Python package to aid in the preparation, running and validation of BDSIM models.

CONTENTS 1

2 CONTENTS

ONE

LICENCE & DISCLAIMER

pymad8 copyright (c) Royal Holloway, University of London, 2018. All rights reserved.

This software is provided "AS IS" and any express or limit warranties, including, but not limited to, implied warranties of merchantability, of satisfactory quality, and fitness for a particular purpose or use are disclaimed. In no event shall Royal Holloway, University of London be liable for any direct, indirect, incidental, special, exemplary, or consequential damages arising in any way out of the use of this software, even if advised of the possibility of such damage.

TWO

AUTHORSHIP

The following people have contributed to pymad8:

- Stewart Boogert
- Andrey Abramov
- Laurie Nevay
- Will Parker
- William Shields
- Jochem Snuverink
- Stuart Walker

CHAPTER THREE

INSTALLATION

3.1 Requirements

- pymad8 is developed exclusively for Python 2.7.
- Requires : fortranformat

3.2 Installation

To install pymad8, simply run ${\tt make}$ install from the root pymad8 directory.:

```
cd /my/path/to/repositories/
git clone http://bitbucket.org/jairhul/pymad8
cd pymad8
make install
```

 $Alternatively, run \ {\tt make} \ \ {\tt develop} \ from \ the \ same \ directory \ to \ ensure \ that \ any \ local \ changes \ are \ picked \ up.$

FOUR

CONVERTING MODELS

pymad8 provdies converters to allow BDSIM models to prepared from optical descriptions in MAD8.

4.1 Mad8 output required

To make the Twiss and Rmatrix output:

```
use, LINE twiss, beta0=LINE.B0, save, tape=twiss_LINE rtape=rmat_LINE
```

Survey:

```
use, LINE survey, tape=survey_LINE
```

4.2 Mad8Twiss2Gmad

TBC

4.3 Mad8Saveline2Gmad

TBC

CHAPTER FIVE

DATA LOADING

Utilies to load pymad8 output data.

CHAPTER SIX

PLOTTING

SEVEN

SUPPORT

All support issues can be submitted to our issue tracker

7.1 Feature Request

Feature requests or proposals can be submitted to the issue tracker - select the issue type as proposal or enhancement.

Please have a look at the existing list of proposals before submitting a new one.

EIGHT

MODULE CONTENTS

This documentation is automatically generated by scanning all the source code. Parts may be incomplete.

8.1 Module contents

pymad8 - python tools for working with MAD8 output and input.

```
Dependencies:
package - minimum version required
numpy - 1.7.1
matplotlib - 1.3.0
```

Modules:

Input -

Output -

Plot -

Sim -

Track -

Visualisation -

Copyright Royal Holloway, University of London 2019.

8.2 pymad8.Input module

```
pymad8.Input.decodeNamed(input)
pymad8.Input.decodeOctupole(input)
pymad8.Input.decodeQuadrupole(input)
pymad8.Input.decodeSbend(input)
pymad8.Input.decodeSextupole(input)
pymad8.Input.removeComments(input)
    remove comment lines
pymad8.Input.removeContinuationSymbols(input)
    remove continuation symbols from input input: list of file lines
pymad8.Input.splitKeyValue(t)
pymad8.Input.tidy(input)
    tidy input, remove EOL, remove empty lines input: list of file lines
8.3 pymad8.Output module
class pymad8.Output.Chrom
    Bases: pymad8.Output.General
    Chromaticity data structure data: numpy array of data keys: key to data
    getData(index)
class pymad8.Output.Common
    Bases: pymad8.Output.General
    containsEnergyVariation()
         Method to determine if the energy is constant in the lattice Required if there is 1) RfCavities
    getApertures (raw=True)
    getColumn (colName)
    getData(index)
    getRowByIndex (index)
    getRowByName (name)
    keys = {'blmo': {'E': 11, 'l': 0, 'note': 10}, 'drif': {'E': 11, 'aper':
    makeLocationList (elementNames=[])
class pymad8.Output.EchoValue(echoFileName)
     loadMarkedValues()
    loadValues()
class pymad8.Output.Envelope
    Bases: pymad8.Output.General
    Beam envelope data structure data: numpy array of data keys: key to data
    getData(index)
    keys = {'s11': 0, 's12': 1, 's13': 2, 's14': 3, 's15': 4, 's16': 5, 's21': 6
class pymad8.Output.General
    General list of accelerator component infomation
```

addElement (type, name, data)

```
findByName (name)
     findByType (type)
     getColumn (key)
     getIndex (name)
     getNElements()
     getNames (ind)
     getRowByIndex (index)
     getRowByName (name)
    makeArray()
    plotXY (xkey, ykey)
     subline (start, end)
class pymad8.Output.Mad8 (filename)
     readFile (filename)
class pymad8.Output.OutputReader
    Class to load different Mad8 output files Usage : o = Mad8.OutputReader() [c,
    s] = o.readFile('./survey.tape','survey') [c, r] = o.readFile('./rmat.tape','rmat') [c,
    = o.readFile('./twiss.tape','twiss') [c, c] = o.readFile('./chrom.tape','chrom') [c, e] =
    o.readFile('./envelope.tape','envel')
    c : Common data r : Rmat object t : Twiss object c : Chrom object e : Envelope object
    readChromFile (f=None)
    readEnvelopeFile (f=None)
     readFile (fileName=", type='twiss')
         read mad8 output file
     readRmatFile (f=None)
     readSurveyFile()
    readTwissFile (f=None)
class pymad8.Output.Rmat
    Bases: pymad8.Output.General
    Rmatrix data structure data: numpy array of data keys: key to data
     getData(index)
    keys = {'r11': 0, 'r12': 1, 'r13': 2, 'r14': 3, 'r15': 4, 'r16': 5, 'r21': 6
class pymad8.Output.Saveline(fileName, lineName='EBDS')
     expandLine()
     findNamedDict(name)
     findNamedIndex(name)
     findRenamedNamedDict (name)
     findRenamedNamedIndex (name)
    makeSubLines()
    parseFile()
     readFile (fileName)
```

```
removeDuplicates()
     removeReplacements()
     writeRenamed (filename)
class pymad8.Output.Survey
     Bases: pymad8.Output.General
     Survey data structure data: numpy array of data keys: key to data
     keys = {'phi': 5, 'psi': 6, 'suml': 3, 'theta': 4, 'x': 0, 'y': 1, 'z':
class pymad8.Output.Track (folderpath, filemapname, twissname)
     appendDir (folderpath)
         Loop over all mad8 track output files in the target directory and append the data to the existing data
         structure.
     readDir()
         Loop over all mad8 track output files in the target directory and build a dictionary of the data. File
         map is used to match data from track files to observation plane in the twiss file.
class pymad8.Output.Twiss
     Bases: pymad8.Output.General
     Twiss data structure data: numpy array of data keys: key to data
     keys = {'alfx': 0, 'alfy': 5, 'betx': 1, 'bety': 6, 'dpx':
                                                                                 4, 'dpy':
                                                                                                9, 'dx':
     nameFromNearestS(s)
    plotAlf()
    plotBeta()
    plotEta()
    plotEtaPrime()
    plotMu()
pymad8.Output.getValueByName (name, key, common, table)
pymad8.Output.writeContinuation (f, l)
8.4 pymad8.Mad8 module
class pymad8.Mad8.Chrom
     Bases: pymad8.Mad8.General
     Chromaticity data structure data: numpy array of data keys: key to data
     getData(index)
class pymad8.Mad8.Common
    Bases: pymad8.Mad8.General
     containsEnergyVariation()
         Method to determine if the energy is constant in the lattice Required if there is 1) RfCavities
     getApertures (raw=True)
     getColumn (colName)
     getData(index)
     getRowByIndex (index)
```

```
getRowByName (name)
    keys = {'blmo': {'E': 11, 'l': 0, 'note': 10}, 'drif': {'E': 11, 'aper': 9, 'l
    makeLocationList(elementNames=[])
class pymad8.Mad8.EchoValue(echoFileName)
     loadValues()
class pymad8.Mad8.Envelope
    Bases: pymad8.Mad8.General
    Beam envelope data structure data: numpy array of data keys: key to data
    getData (index)
    keys = {'s11': 0, 's12': 1, 's13': 2, 's14': 3, 's15': 4, 's16': 5, 's21': 6
class pymad8.Mad8.General
    General list of accelerator component infomation
     addElement (type, name, data)
     findByName (name)
     findByType (type)
    getColumn (key)
     getIndex (name)
     getNElements()
     getNames (ind)
     getRowByIndex (index)
     getRowByName (name)
    makeArray()
    plotXY (xkey, ykey)
     subline (start, end)
class pymad8.Mad8.Mad8(filename)
    readFile (filename)
class pymad8.Mad8.OutputReader
    Class to load different Mad8 output files Usage : o = Mad8.OutputReader()
    s] = o.readFile('./survey.tape','survey') [c, r] = o.readFile('./rmat.tape','rmat') [c,
                                                                                        t]
    = o.readFile('./twiss.tape','twiss') [c, c] = o.readFile('./chrom.tape','chrom') [c, e] =
    o.readFile('./envelope.tape','envel')
    c : Common data r : Rmat object t : Twiss object c : Chrom object e : Envelope object
    {\tt readChromFile}\:(f\!\!=\!\!None)
    readEnvelopeFile (f=None)
    readFile (fileName=", type='twiss')
         read mad8 output file
     readRmatFile (f=None)
     readSurveyFile()
    readTwissFile (f=None)
```

```
class pymad8.Mad8.Rmat
    Bases: pymad8.Mad8.General
    Rmatrix data structure data: numpy array of data keys: key to data
    getData(index)
    keys = {'r11': 0, 'r12': 1, 'r13': 2, 'r14': 3, 'r15': 4, 'r16': 5, 'r21': 6
class pymad8.Mad8.Survey
    Bases: pymad8.Mad8.General
    Survey data structure data: numpy array of data keys: key to data
    keys = {'phi': 5, 'psi': 6, 'suml': 3, 'theta': 4, 'x': 0, 'y': 1, 'z': 2}
class pymad8.Mad8.Twiss
    Bases: pymad8.Mad8.General
    Twiss data structure data: numpy array of data keys: key to data
    keys = { 'alfx': 0, 'alfy': 5, 'betx': 1, 'bety': 6, 'dpx': 4, 'dpy': 9, 'dx':
    nameFromNearestS(s)
    plotAlf()
    plotBeta()
    plotEta()
    plotEtaPrime()
    plotMu()
pymad8.Mad8.getValueByName (name, key, common, table)
```

8.5 pymad8.Plot module

pymad8.Plot.survey(surveyfile='ebds1')

pymad8.Plot.AddMachineLatticeToFigure (figure, mad8opt, tightLayout=True)

Add a diagram above the current graph in the figure that represents the accelerator based on a madx twiss file in tfs format.

Note you can use matplotlib's gcf() 'get current figure' as an argument.

```
pymad8.Plot.AddMachineLatticeToFigure(gcf(), 'afile.tfs')

pymad8.Plot.apertures(twissfile='ebds1', envelfile='ebds1')

pymad8.Plot.dispersion(twissfile='ebds1')

pymad8.Plot.drawMachineLattice(mad8c, mad8t)

pymad8.Plot.energy(twissfile='ebds1')

pymad8.Plot.linearOptics(twissfile='ebds1')

pymad8.Plot.phaseAdvance(twissfile='ebds1')

pymad8.Plot.setCallbacks(figure, axm, axplot, twiss)
```

8.6 pymad8.Sim module

```
class pymad8.Sim.Track(common, rmat)

generate()
    trackParticle(p)
    trackParticles(nparticle)

pymad8.Sim.testTrack(rmatFile, nparticle=10)
```

```
8.7 pymad8. Visualisation module
pymad8.Visualisation.MakeCombinedSurveyPlot (name,
                                                                QUAD=True,
                                                                               RBEN=True,
                                                                               MONI=True.
                                                        SBEN=True,
                                                        MARK=True)
     Takes a list of Survey filenames, plots them all on the same 2D plot. For branching machines or segmented
     models. Elements selectable via booleans, default to true
class pymad8.Visualisation.OneDim(common, survey, debug)
     drawBend(c, s, suml, colour=True)
     drawElement (elem, colour=True)
     drawElements (type, colour=True)
     drawHkic(c, s, suml, colour=True)
     drawInst (c, s, suml, colour=True)
     drawMark (c, s, suml, colour=True)
     drawMoni (c, s, suml, colour=True)
     drawMult (c, s, suml, colour=True)
     drawProf (c, s, suml, colour=True)
     drawQuad (c, s, suml, colour=True)
     drawSext (c, s, suml, colour=True)
     drawVkic(c, s, suml, colour=True)
     drawWire (c, s, suml, colour=True)
     plot (colour=True)
class pymad8. Visualisation. TwoDim (common, survey,
                                                              debug=False, annotate=False,
                                           fancy=False)
     drawBend(c, s, x, y, z)
     drawElement (elem)
     drawElements(type)
     drawMark(c, s, x, y, z)
     drawMoni(c, s, x, y, z)
     drawQuad(c, s, x, y, z)
     plot (event=None)
     plotUpdate(event)
```

pymad8 Documentation, Release 1.6.0

```
pymad8.Visualisation.testOneDim()
pymad8.Visualisation.testTwoDim()
pymad8.Visualisation.transformedPoly(xy, xyc, theta)
pymad8.Visualisation.transformedRect(xyc, dx, dy, theta)
```

NINE

INDICES AND TABLES

- genindex
- modindex
- search

PYTHON MODULE INDEX

p

```
pymad8,17
pymad8.Input,17
pymad8.Mad8,20
pymad8.Output,18
pymad8.Plot,22
pymad8.Sim,23
pymad8.Visualisation,23
```

INDEX

A	drawElement() (pymad8.Visualisation.OneDim
addElement() (pymad8.Mad8.General method), 21 addElement() (pymad8.Output.General method), 18	method), 23 drawElement() (pymad8.Visualisation.TwoDim method), 23
AddMachineLatticeToFigure() (in module py-mad8.Plot), 22	drawElements() (pymad8.Visualisation.OneDim method), 23
apertures() (in module pymad8.Plot), 22 appendDir() (pymad8.Output.Track method), 20	drawElements() (pymad8.Visualisation.TwoDim method), 23
C	drawHkic() (pymad8.Visualisation.OneDim method), 23
Chrom (class in pymad8.Mad8), 20 Chrom (class in pymad8.Output), 18	drawInst() (pymad8.Visualisation.OneDim method), 23
Common (class in pymad8.Mad8), 20 Common (class in pymad8.Output), 18	<pre>drawMachineLattice() (in module py- mad8.Plot), 22</pre>
contains Energy Variation () (py-mad 8. Mad 8. Common method), 20	drawMark() (pymad8.Visualisation.OneDim method), 23
containsEnergyVariation() (py-mad8.Output.Common method), 18	drawMark() (pymad8.Visualisation.TwoDim method), 23
D	drawMoni() (pymad8.Visualisation.OneDim method), 23
decodeCollimator() (in module pymad8.Input),	drawMoni() (pymad8.Visualisation.TwoDim method), 23
decodeDecapole() (in module pymad8.Input), 17 decodeDrift() (in module pymad8.Input), 17	drawMult() (pymad8.Visualisation.OneDim method), 23
decodeFileLine() (in module pymad8.Input), 17 decodeKicker() (in module pymad8.Input), 17	drawProf() (pymad8.Visualisation.OneDim method), 23
decodeLcavity() (in module pymad8.Input), 17 decodeLine() (in module pymad8.Input), 17	drawQuad() (pymad8.Visualisation.OneDim method), 23
decodeMultipole() (in module pymad8.Input),	drawQuad() (pymad8.Visualisation.TwoDim method), 23
decodeNameAndType() (in module py- mad8.Input), 17	drawSext() (pymad8.Visualisation.OneDim method), 23
decodeNamed() (in module pymad8.Input), 17 decodeOctupole() (in module pymad8.Input), 18	drawVkic() (pymad8.Visualisation.OneDim method), 23
decodeQuadrupole() (in module pymad8.Input),	drawWire() (pymad8.Visualisation.OneDim method), 23
decodeSbend() (in module pymad8.Input), 18 decodeSextupole() (in module pymad8.Input), 18 dispersion() (in module pymad8.Plot), 22 dispersionPrime() (in module pymad8.Plot), 22 drawBend() (pymad8.Visualisation.OneDim	EchoValue (class in pymad8.Mad8), 21 EchoValue (class in pymad8.Output), 18 energy() (in module pymad8.Plot), 22 Envelope (class in pymad8.Mad8), 21
method), 23 drawBend() (pymad8.Visualisation.TwoDim method), 23	Envelope (class in pymad8.Output), 18 expandLine() (pymad8.Output.Saveline method), 19

-	
	<pre>getRowByName() (pymad8.Output.General</pre>
FindByName() (pymad8.Mad8.General method), 21	method), 19
findByName() (pymad8.Output.General method),	getValueByName() (in module pymad8.Mad8), 22
18	getValueByName() (in module pymad8.Output),
findByType() (pymad8.Mad8.General method), 21	20
findByType() (<i>pymad8.Output.General method</i>),	K
19	
findNamedDict() (pymad8.Output.Saveline	keys (pymad8.Mad8.Common attribute), 21
method), 19	keys (pymad8.Mad8.Envelope attribute), 21
findNamedIndex() (pymad8.Output.Saveline	keys (pymad8.Mad8.Rmat attribute), 22
method), 19	keys (pymad8.Mad8.Survey attribute), 22
findRenamedNamedDict() (py-	keys (pymad8.Mad8.Twiss attribute), 22
mad8.Output.Saveline method), 19	keys (pymad8.Output.Common attribute), 18
FindRenamedNamedIndex() $(py-$	keys (pymad8.Output.Envelope attribute), 18
mad8.Output.Saveline method), 19	keys (pymad8.Output.Rmat attribute), 19
	keys (pymad8.Output.Survey attribute), 20
G	keys (pymad8.Output.Twiss attribute), 20
General (class in pymad8.Mad8), 21	L
General (class in pymad8.Output), 18	_
generate() (pymad8.Sim.Track method), 23	linearOptics() (in module pymad8.Plot), 22
getApertures() (pymad8.Mad8.Common	<pre>loadMarkedValues() (pymad8.Output.EchoValue</pre>
method), 20	method), 18
getApertures() (pymad8.Output.Common	<pre>loadValues() (pymad8.Mad8.EchoValue method),</pre>
method), 18	21
getColumn() (pymad8.Mad8.Common method), 20	loadValues() (pymad8.Output.EchoValue
getColumn() (pymad8.Mad8.General method), 21	method), 18
getColumn() (pymad8.Output.Common method), 18	N //
getColumn() (pymad8.Output.General method), 19	M
getData() (pymad8.Mad8.Chrom method), 20	Mad8 (class in pymad8.Mad8), 21
getData() (pymad8.Mad8.Common method), 20	Mad8 (class in pymad8.Output), 19
getData() (pymad8.Mad8.Envelope method), 21	makeArray() (pymad8.Mad8.General method), 21
getData() (pymad8.Mad8.Rmat method), 22	makeArray() (pymad8.Output.General method), 19
getData() (pymad8.Output.Chrom method), 18	MakeCombinedSurveyPlot() (in module py-
getData() (pymad8.Output.Common method), 18	mad8. Visualisation), 23
getData() (pymad8.Output.Envelope method), 18	<pre>makeLocationList() (pymad8.Mad8.Common</pre>
getData() (pymad8.Output.Rmat method), 19	method), 21
getIndex() (pymad8.Mad8.General method), 21	<pre>makeLocationList() (pymad8.Output.Common</pre>
getIndex() (pymad8.Output.General method), 19	method), 18
getNames() (pymad8.Mad8.General method), 21	<pre>makeSubLines() (pymad8.Output.Saveline</pre>
getNames() (pymad8.Output.General method), 19	method), 19
getNElements() (pymad8.Mad8.General method),	
21	N
getNElements() (pymad8.Output.General	nameFromNearestS() (pymad8.Mad8.Twiss
method), 19	method), 22
getRowByIndex() (pymad8.Mad8.Common	nameFromNearestS() (pymad8.Output.Twiss
method), 20	method), 20
getRowByIndex() (pymad8.Mad8.General	······· //
method), 21	0
getRowByIndex() (pymad8.Output.Common	OneDim (class in pymad8. Visualisation), 23
method), 18	OutputReader (class in pymad8.Mad8), 21
<pre>getRowByIndex() (pymad8.Output.General</pre>	OutputReader (class in pymad8.Output), 19
method), 19	output Neader (class in pymado.output), 17
, 12	
	P
	P
getRowByName() (pymad8.Mad8.Common	parseFile() (pymad8.Output.Saveline method), 19
getRowByName() (pymad8.Mad8.Common method), 20	<pre>parseFile() (pymad8.Output.Saveline method), 19 phaseAdvance() (in module pymad8.Plot), 22</pre>
getRowByName() (pymad8.Mad8.Common method), 20 getRowByName() (pymad8.Mad8.General method),	parseFile() (pymad8.Output.Saveline method), 19

30 Index

plotAlf() (pymad8.Mad8.Twiss method), 22	removeReplacements() (py-
plotAlf() (pymad8.Output.Twiss method), 20	mad8.Output.Saveline method), 20
plotBeta() (pymad8.Mad8.Twiss method), 22	Rmat (class in pymad8.Mad8), 21
plotBeta() (pymad8.Output.Twiss method), 20	Rmat (class in pymad8.Output), 19
plotEta() (pymad8.Mad8.Twiss method), 22	0
plotEta() (pymad8.Output.Twiss method), 20	S
plotEtaPrime()(<i>pymad8.Mad8.Twiss method</i>), 22	Saveline (class in pymad8.Output), 19
<pre>plotEtaPrime() (pymad8.Output.Twiss method),</pre>	setCallbacks() (in module pymad8.Plot), 22
20	splitKeyValue() (in module pymad8.Input), 18
plotMu() (pymad8.Mad8.Twiss method), 22	subline() (pymad8.Mad8.General method), 21
plotMu() (pymad8.Output.Twiss method), 20	subline() (pymad8.Output.General method), 19
plotUpdate() (pymad8.Visualisation.TwoDim	Survey (class in pymad8.Mad8), 22
method), 23	Survey (class in pymad8.Output), 20
plotXY() (pymad8.Mad8.General method), 21	survey() (in module pymad8.Plot), 22
plotXY() (pymad8.Output.General method), 19	-
pymad8 (module), 17	Т
pymad8.Input (module), 17	testOneDim() (in module pymad8. Visualisation).
pymad8.Mad8 (module), 20	23
pymad8.Output (module), 18	testTrack() (in module pymad8.Sim), 23
pymad8.Plot(module),22	testTwoDim() (in module pymad8. Visualisation).
pymad8.Sim (module), 23	24
pymad8.Visualisation(<i>module</i>),23	tidy() (in module pymad8.Input), 18
R	Track (class in pymad8.Output), 20
	Track (class in pymad8.Sim), 23
readChromFile() (pymad8.Mad8.OutputReader	trackParticle() (pymad8.Sim.Track method), 23
method), 21	trackParticles() (pymad8.Sim.Track method).
readChromFile() (pymad8.Output.OutputReader	23
method), 19	transformedPoly() (in module py-
readDir() (pymad8.Output.Track method), 20	mad8.Visualisation), 24
readEnvelopeFile() (py-	transformedRect() (in module py-
mad8.Mad8.OutputReader method), 21	mad8.Visualisation), 24
readEnvelopeFile() (py-	Twiss (class in pymad8.Mad8), 22
mad8.Output.OutputReader method), 19 readFile() (pymad8.Mad8.Mad8 method), 21	Twiss (class in pymad8.Output), 20
readFile() (pymad8.Mad8.OutputReader method),	TwoDim (class in pymad8. Visualisation), 23
21	W
readFile() (pymad8.Output.Mad8 method), 19	
readFile() (pymad8.Output.OutputReader	writeContinuation() (in module py-
method), 19	mad8.Output), 20
readFile() (pymad8.Output.Saveline method), 19	writeRenamed() (pymad8.Output.Saveline
readRmatFile() (pymad8.Mad8.OutputReader	method), 20
method), 21	
readRmatFile() (pymad8.Output.OutputReader	
method), 19	
readSurveyFile() (pymad8.Mad8.OutputReader	
method), 21	
readSurveyFile() (py-	
mad8.Output.OutputReader method), 19	
readTwissFile() (pymad8.Mad8.OutputReader	
method), 21	
readTwissFile() (pymad8.Output.OutputReader	
method), 19	
removeComments() (in module pymad8.Input), 18	
removeContinuationSymbols() (in module py-	
mad8.Input), 18	
removeDuplicates() (pymad8.Output.Saveline	
method). 20	

Index 31