


Taking a Hard Look at **Generalized Coloring Numbers**



@blairdsullivan
University of Utah

*Special thanks to
Felix Reidl (Birkbeck College, London)
for original artwork and collaboration
on scientific communication*



*My work in this talk was primarily supported by the Gordon & Betty Moore Foundation,
with additional funding from DARPA, ARO, and NIH..*

Part I



Sparse classes



A false dichotomy



A better model



Parameterized algorithms

Good
Bad

Classical view

$O(n^{\log n})$, $O(2^n)$, ...

Not polynomial-time

$O(n^c)$

Polynomial-time
("efficient")



Parameterized view

$O(n^{f(k)})$

Slice-wise
polynomial time

$O(f(k)n^c)$

Fixed-parameter
tractable



Choosing a class

Larger classes




Less Structure



More




Algorithmic tractability



Can We Use Sparse Structure?





treewidth t



⋮

Evidence says...




⋮


Citations Go Here

The sparse class hierarchy


Larger classes




Shallow minors & bounded expansion



Shallow minors & bounded expansion



Shallow minors & bounded expansion










$$\nabla_r(G) = \max_{H \preccurlyeq_r G} \frac{|E(H)|}{|V(H)|}$$




A graph class has bounded expansion iff it is ∇_r -bounded.


Random model sparsity

 $G(n, \frac{\mu}{n})$  $G^{\text{CL}}(D_n)$  $G^{\text{CF}}(D_n)$  $G^{\text{RIG}}(n, \alpha, \beta, \gamma)$  $G^{\text{BA}}(n, n_0, k)$  $G^{\text{SGK}}(k, \alpha, \dots, \gamma)$  $G^{\text{RMAT}}(k, m, a, b, c)$  $G^{\text{KL}}(n, p, q, \gamma)$ 

Bounded expansion



Density
of shallow
minors



ν_r

Size of r-reachable
sets in ordering



Normalized number of
traces r-neighbourhoods
leave in any subset

$\Delta^-(\vec{G}_r)$



In-degree of
r-step (d)tf-
augmentation


Number of colours
in r-treedepth
colouring

χ_r







[Neš12 Sparsity]

Applications & Algorithms



Counting Subgraphs



$$\Sigma \triangle \#$$

Aggregate

$$\# \cdot H = \frac{1}{2}(\dots \cdot \times \dots \cdot) - (\dots \cdot + 2 \cdot \dots \cdot)$$

Compute composite pattern counts

Index/Query Metagenomes



de-Bruijn
graphs



BCALM 2







contracted
DBGs




Dvořák's
Algorithm



Domset




Genome
neighbourhoods




Part II

Generalized coloring numbers




Strong coloring & bounded expansion



u is strongly r -reachable from v if there exists a path from v to u of length at most r such that all interior vertices lie right of v .


Strong coloring & bounded expansion



u is strongly r -reachable from v if there exists a path from v to u of length at most r such that all interior vertices lie right of v .

$$\text{col}_r(G) := \min_{\mathbb{G} \in \Pi(G)} \max_{v \in G} |S_{\mathbb{G}}^r(v)|$$

Strong coloring & bounded expansion




u is strongly r -reachable from v if there exists a path from v to u of length at most r such that all interior vertices lie right of v .

$$\text{col}_r(G) := \min_{\mathbb{G} \in \Pi(G)} \max_{v \in G} |S_{\mathbb{G}}^r(v)|$$




A graph class has bounded expansion iff it is col_r -bounded.

Weak coloring & bounded expansion



u is weakly r -reachable from v if there exists a path from v to u of length at most r such that u is the path's leftmost vertex.


Weak coloring & bounded expansion



u is **weakly r -reachable** from v if there exists a path from v to u of length at most r such that u is the path's leftmost vertex.

$$\text{wcol}_r(G) := \min_{\mathbb{G} \in \Pi(G)} \max_{v \in G} |W_{\mathbb{G}}^r(v)|$$

Weak coloring & bounded expansion



u is **weakly r -reachable** from v if there exists a path from v to u of length at most r such that u is the path's leftmost vertex.


$$\text{wcol}_r(G) := \min_{\mathbb{G} \in \Pi(G)} \max_{v \in G} |W_{\mathbb{G}}^r(v)|$$




A graph class has bounded expansion iff it is wcol_r -bounded.

Weak & strong coloring

\mathbb{G}



\mathbb{G}



$$\text{col}_r(\mathbb{G}) \leq \text{wcol}_r(\mathbb{G}) \leq r(\text{col}_r(\mathbb{G}) - 1)^r + 1$$

Origin story

Introduced by Kierstead & Yang, generalizing

Def. $\text{col}(\mathbb{G}, x) := |N[x] \cap \{y \leqslant_{\mathbb{G}} x\}|$

$$\text{col}(G) := \min_{\mathbb{G} \in \Pi(G)} \max_{v \in G} \text{col}(\mathbb{G}, v)$$


Origin story

Introduced by Kierstead & Yang, generalizing

Def. $\text{col}(\mathbb{G}, x) := |N[x] \cap \{y \leqslant_{\mathbb{G}} x\}|$

$$\text{col}(G) := \min_{\mathbb{G} \in \Pi(G)} \max_{v \in G} \text{col}(\mathbb{G}, v)$$

We can greedily **color** a graph with such an ordering:

$$\chi(G) \leqslant \chi^\ell(G) \leqslant \text{col}(G)$$



Origin story

Introduced by Kierstead & Yang, generalizing

Def. $\text{col}(\mathbb{G}, x) := |N[x] \cap \{y \leqslant_{\mathbb{G}} x\}|$

$$\text{col}(G) := \min_{\mathbb{G} \in \Pi(G)} \max_{v \in G} \text{col}(\mathbb{G}, v)$$

We can greedily **color** a graph with such an ordering:

$$\chi(G) \leqslant \chi^\ell(G) \leqslant \text{col}(G)$$

Further connections to colorings:

$$\text{col}_2(G) = \chi_{\text{acyclic}}(G)$$


$$\text{wcol}_2(G) = \chi_{\text{star}}(G)$$



It's all fun and games...

r-Ordering Game


- Alice & Bob play on a graph G by alternating choosing vertices (n turns)
- Creates an order \mathbb{G} , score is $\text{col}_r(\mathbb{G})$
- Alice plays first and wants to minimize score; Bob wants to maximize



It's all fun and games...

r-Ordering Game

- Alice & Bob play on a graph G by alternating choosing vertices (n turns)
- Creates an order \mathbb{G} , score is $\text{col}_r(\mathbb{G})$
- Alice plays first and wants to minimize score; Bob wants to maximize



$\text{gcol}_r(G) :=$ Lowest score Alice
can always achieve

To planarity and beyond!

A (non-comprehensive) selection of recent work

Planar graphs have $\text{wcol}_2(G) \leq 23$

[Alm22 DM]

Koebe orders of planar graphs satisfy

$$\text{wcol}_r(\mathbb{G}) = O(r^4 \ln r)$$

[Ned22 Arxiv]

Graphs of treewidth t have

$$\text{wcol}_r(G) = \Theta(r^{t-1} \log r)$$

[Jor22 Elec J Comb]



To planarity and beyond!

A (non-comprehensive) selection of recent work

Graph powers: $\text{col}_r(G^p)$ can be bounded in terms of $\text{wcol}_r(G)$ and $\Delta(G)$.

[Kie20 DM]

If G has genus g $\begin{cases} \text{col}_r(G) \leq (2g+3)(2r+1) \\ \text{wcol}_r(G) \leq (2g + \binom{2r+2}{2})(2r+1) \end{cases}$

If G excludes a minor $\begin{cases} \text{col}_r(G) \leq \binom{t-1}{2}(2r+1) \\ \text{wcol}_r(G) \leq O(r^{t-1}) \end{cases}$

[van17 EuJC]



~~One Ring to Rule Them All~~ Order

?

Do orders witnessing low col_r also have small $\text{col}_{r'}$?

Not if low/small mean optimal!

For every $r \neq r'$ $\exists G$ such that every ordering $\mathbb{G} \in \Pi(G)$ is non-optimal for col_r or $\text{col}_{r'}$.

But: known bounds use one order for all r !



~~One Ring to Rule Them All~~ Order

?

If $\text{col}_r(G) \leq c(r)$, does $\exists c^*$ such that some \mathbb{G} has $\text{col}_r(\mathbb{G}) \leq c^*(r)$ for all r ?

Thm. (van Heuvel, Kierstead)

For all G there exists $\mathbb{G} \in \Pi(G)$ with

$$\text{col}_r(\mathbb{G}) \leq (2^r + 1)(\text{col}_{2r}(G))^{4r}$$

for all r .

[vanH21 EuJC]



Twins: twice the fun, half the sleep


Twinwidth is a hot new graph parameter generalizing an invariant of permutation classes.

[Bon20 FOCS][Gui14 SODA]

Thm. (Bonnet et al.)

If $\text{tww}(G) \leq t$ and $K_{s,s} \not\subseteq G$, then there ex. f_r s.t.
for all r . $\text{col}_r(G) \leq f_r(s,t)$

[Bon21 SODA]



Twins: twice the fun, half the sleep

Twinwidth is a hot new graph parameter generalizing an invariant of permutation classes.

[Bon20 FOCS][Gui14 SODA]

Thm. (Bonnet et al.)

If $\text{tww}(G) \leq t$ and $K_{s,s} \not\subseteq G$, then there ex. f_r s.t.

$$\text{col}_r(G) \leq f_r(s, t)$$

for all r .

[Bon21 SODA]


Thm. (Dreier et al.)

There ex. G with $\text{col}_r(G) \geq (t - 4)^r s$, and


$$\underbrace{\text{tww}(G) \leq t}_{K_{s,s} \not\subseteq G} \quad f_r(s, t) \leq (t^r + 3)s$$

[Dre22 DM]

Cops & robbers



Cops & robbers




Cops & robbers


$k + 1$ cops can
catch the robber



$\text{tw}(G) = k$



Cops & robbers



Cops & robbers



Cops & robbers

$k + 1$ cops can
catch a robber with
maximum speed r



$$\text{copw}_r(G) = k$$



Cops & robbers

$k + 1$ cops can
catch a robber with
maximum speed r \iff $\text{copw}_r(G) = k$



Thm. (Toruńczyk)

$$\text{adm}_r(G) + 1 \leq \text{copw}_r(G) \leq \text{wcol}_{2r}(G) + 1$$

[Tor23 Flip-width]




A graph class has bounded
expansion iff it is copw_r -bounded.

'Limits' of coloring numbers




Degeneracy

$$\text{col}_1(G) = \text{wcol}_1(G)$$



$$\text{wcol}_{\infty}(G) = \text{td}(G)$$




$$\text{col}_{\infty}(G) = \text{tw}(G)$$

Part III


Algorithmic questions




Computing degeneracy ordering



Computing degeneracy ordering




Computing degeneracy ordering



Computing degeneracy ordering

G



No free lunch

Thm. (Breen-McKay, Lavallee, **S**)

Deciding whether $\text{wcol}_r(G) \leq k$ or $\text{col}_r(G) \leq k$ is NP-complete even for $r = 2$.

[Bre23 EuJC (in press)]*

Anything beyond degeneracy is
hard to compute exactly.

Maybe cheap lunch?


Thm. (Dvořák)

$$\text{adm}_r(\mathbb{G}) \leq k \implies$$

$$\begin{aligned}\text{col}_r(\mathbb{G}) &\leq (k-1)^r + 1 \\ \text{wcol}_r(\mathbb{G}) &\leq (r^2 k)^r\end{aligned}$$


[TODO] [TODO]

Approximation
works just fine here!
(though slower)



Estimating path-packings

Estimate pp^r by packing shortest paths!



Thm. (Breen-McKay, Lavallee, **S**)

$$\begin{aligned} \text{pps}_{\mathbb{G}}^r(v) &\leq k \\ \text{for all } v \in G \end{aligned}$$

$$\implies$$


$$\begin{aligned} \text{col}_r(\mathbb{G}) &\leq k(k-1)^{r-1} \\ \text{wcol}_r(\mathbb{G}) &\leq \frac{k^{r+1}-1}{k-1} \end{aligned}$$

Open Problems



TEXT

TEXT



TEXT

THANKS



- [Adc13 ICDM] Aaron B. Adcock, Blair D. Sullivan, and Michael W. Mahoney. "Tree-Like Structure in Large Social and Information Networks". In: *2013 IEEE 13th International Conference on Data Mining*. 2013, pp. 1–10. DOI: [10.1109/ICDM.2013.77](https://doi.org/10.1109/ICDM.2013.77).
- [Alm22 DM] Ahlam Almulhim and H.A. Kierstead. "On the weak 2-coloring number of planar graphs". In: *Discrete Mathematics* 345.1 (2022), p. 112631. ISSN: 0012-365X. DOI: <https://doi.org/10.1016/j.disc.2021.112631>.
- [Boe20 Env Planning B] Geoff Boeing. "Planarity and street network representation in urban form analysis". In: *Environment and Planning B: Urban Analytics and City Science* 47.5 (2020), pp. 855–869. DOI: [10.1177/2399808318802941](https://doi.org/10.1177/2399808318802941).
- [Bre23 EuJC in press] Michael Breen-McKay, Brian Lavallee, and Blair D. Sullivan. *Hardness of the Generalized Coloring Numbers*. In Press, European Journal of Combinatorics, March 2023. 2023. URL: <https://arxiv.org/abs/2112.10562>.
- [Bro20 Gen Bio] C. Titus Brown et al. "Exploring neighborhoods in large metagenome assembly graphs using spacegraphcats reveals hidden sequence diversity". In: *Genome Biology* 21.1 (July 2020). DOI: [10.1186/s13059-020-02066-4](https://doi.org/10.1186/s13059-020-02066-4). URL: <https://doi.org/10.1186/s13059-020-02066-4>.
- [Dem19 JCSS] Erik D. Demaine et al. "Structural sparsity of complex networks: Bounded expansion in random models and real-world graphs". In: *Journal of Computer and System Sciences* 105 (2019), pp. 199–241. ISSN: 0022-0000. DOI: <https://doi.org/10.1016/j.jcss.2019.05.004>.
- [Dre22 DM] Jan Dreier et al. "Twin-width and generalized coloring numbers". In: *Discrete Mathematics* 345.3 (2022), p. 112746. ISSN: 0012-365X. DOI: <https://doi.org/10.1016/j.disc.2021.112746>.
- [Dvo22] Zdeněk Dvořák. "On weighted sublinear separators". In: *Journal of Graph Theory* 100.2 (2022), pp. 270–280.

- [Gas21 BIBM] William Gasper et al. "Parallel Planar Approximation for Large Networks". In: *2021 IEEE International Conference on Bioinformatics and Biomedicine (BIBM)*. 2021, pp. 1948–1955. DOI: 10.1109/BIBM52615.2021.9669815.
- [Jor22 Elec J Comb] Gwenaël Joret and Piotr Micek. "Improved Bounds for Weak Coloring Numbers". In: *The Electronic Journal of Combinatorics* 29.1 (Mar. 2022). DOI: 10.37236/10274. URL: <https://doi.org/10.37236/10274>.
- [Kie03 Order] Hal A Kierstead and Daqing Yang. "Orderings on graphs and game coloring number". In: *Order* 20.3 (2003).
- [Kie20 DM] H.A. Kierstead, Daqing Yang, and Junjun Yi. "On coloring numbers of graph powers". In: *Discrete Mathematics* 343.6 (2020), p. 111712. ISSN: 0012-365X. DOI: <https://doi.org/10.1016/j.disc.2019.111712>.
- [Man19 ICDT] Silviu Maniu, Pierre Senellart, and Suraj Jog. "An Experimental Study of the Treewidth of Real-World Graph Data". In: *22nd International Conference on Database Theory (ICDT 2019)*. Ed. by Pablo Barcelo and Marco Calautti. Vol. 127. Leibniz International Proceedings in Informatics (LIPIcs). Dagstuhl, Germany, 2019, 12:1–12:18.
- [Mar22 Alg Mol Bio] Bertrand Marchand, Yann Ponty, and Laurent Bulteau. "Tree Diet: Reducing the Treewidth to Unlock FPT Algorithms in RNA Bioinformatics". In: *Algorithms for Molecular Biology* 17 (Apr. 2022). DOI: 10.1186/s13015-022-00213-z.
- [Ned22 ArXiv] Jesper Nederlof and Karol Pilipczuk Michaland Węgrzycki. *Bounding generalized coloring numbers of planar graphs using coin models*. 2022. URL: <https://arxiv.org/abs/2201.09340>.
- [Neš08 EuJC] Jaroslav Nešetřil and Patrice Ossona de Mendez. "Grad and classes with bounded expansion I. Decompositions". In: *European Journal of Combinatorics* 29.3 (2008), pp. 760–776. ISSN: 0195-6698. DOI: <https://doi.org/10.1016/j.ejc.2006.07.013>.

- [Neš12 Sparsity] Jaroslav Nešetřil and Patrice Ossona De Mendez. *Sparsity: graphs, structures, and algorithms*. Vol. 28. Springer Science & Business Media, 2012.
- [Rei22 bioRxiv] Taylor E. Reiter et al. "Meta-analysis of metagenomes via machine learning and assembly graphs reveals strain switches in Crohn's disease". In: *bioRxiv* (2022). URL: <https://www.biorxiv.org/content/early/2022/07/05/2022.06.30.498290>.
- [Tor23 ArXiv] Symon Toruńczyk. "Flip-width: Cops and Robber on dense graphs". In: arXiv:2302.00352 (Feb. 2023). arXiv:2302.00352 [cs, math]. URL: <http://arxiv.org/abs/2302.00352>.
- [van17 EuJC] Jan van den Heuvel et al. "On the generalised colouring numbers of graphs that exclude a fixed minor". In: *European Journal of Combinatorics* 66 (2017). Selected papers of EuroComb15, pp. 129–144. ISSN: 0195-6698. DOI: <https://doi.org/10.1016/j.ejc.2017.06.019>.
- [van21 EuJC] Jan van den Heuvel and H.A. Kierstead. "Uniform orderings for generalized coloring numbers". In: *European Journal of Combinatorics* 91 (2021). Colorings and structural graph theory in context (a tribute to Xuding Zhu), p. 103214. ISSN: 0195-6698. URL: <https://www.sciencedirect.com/science/article/pii/S0195669820301359>.